

SAFETY DATA SHEET

Creation Date 10-March-2010 Revision Date 25-March-2024 Revision Number 5

1. Identification

Product Name Dimethylamine, 40% w/w in water

Cat No. : 31458

Synonyms DMA; N-Methyl-Methanamine.

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific 112 Colonnade Road, Ottawa, ON K2E 7L6,

Canada

Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids

Acute oral toxicity

Acute Inhalation Toxicity

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Category 3

Target Organs Pagainters (state Control pagaint)

Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor

Harmful if swallowed or if inhaled Causes severe skin burns and eye damage May cause respiratory irritation



Precautionary Statements

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Use non-sparking tools

Take action to prevent static discharges

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER/doctor

Rinse mouth

Do NOT induce vomiting

Wash contaminated clothing before reuse

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Harmful to aquatic life with long lasting effects

3. Composition/Information on Ingredients

| Component | CAS-No | Weight % |
|---------------|-----------|----------|
| Water | 7732-18-5 | 55-74 |
| Dimethylamine | 124-40-3 | 26-45 |

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Remove and wash

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

Inhalation If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory

medical device. Call a physician immediately.

Ingestion Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an

unconscious person. Call a physician immediately.

Most important symptoms/effects Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause

symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe

damage to the delicate tissue and danger of perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical, Alcohol resistant foam. Water mist may be used to cool closed containers.

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Unsuitable Extinguishing Media Carbon dioxide (CO2), Water may be ineffective

Flash Point -18 °C / -0.4 °F

Method - No information available

Autoignition Temperature 390 °C / 734 °F

Explosion Limits

Upper 12.3 vol % **Lower** 2.6 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Nitrogen oxides (NOx).

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards330N/A

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all

sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions Should not be released into the environment. Do not flush into surface water or sanitary

sewer system.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up** Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Corrosives area. Incompatible Materials. Metals. Strong oxidizing agents. Acids. Halogens. Peroxides. Carbon dioxide (CO2).

8. Exposure controls / personal protection

Exposure Guidelines

| Component | Alberta | British | Ontario TWAEV | Quebec | ACGIH TLV | OSHA PEL | NIOSH |
|---------------|----------------------------|--------------|---------------|--------------|--------------|---------------------------|---------------------------|
| | | Columbia | | | | | |
| Dimethylamine | TWA: 5 ppm | TWA: 5 ppm | TWA: 5 ppm | TWA: 5 ppm | TWA: 5 ppm | (Vacated) TWA: | IDLH: 500 ppm |
| 1 | TWA: 9.2 mg/m ³ | STEL: 15 ppm | STEL: 15 ppm | STEL: 15 ppm | STEL: 15 ppm | 10 ppm | TWA: 10 ppm |
| | STEL: 15 ppm | | | | | (Vacated) TWA: | TWA: 18 mg/m ³ |
| | STEL: 28 mg/m ³ | | | | | 18 mg/m ³ | • |
| | | | | | | TWA: 10 ppm | |
| | | | | | | TWA: 18 mg/m ³ | |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined

areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection
Hand Protection

Goggles

Wear appropriate protective gloves and clothing to prevent skin exposure.

| Glove material | Breakthrough time | Glove thickness | Glove comments |
|----------------|-------------------|-----------------|--------------------------------|
| Nitrile rubber | < 60 minutes | 0.38 mm | Permeation rate ~2000 |
| Butyl rubber | < 30 minutes | 0.635 mm | μg/cm2/min |
| | | | As tested under EN374-3 |
| | | | Determination of Resistance to |
| | | | Permeation by Chemicals |

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** Particulates filter conforming to EN 143 or Ammonia and organic ammonia derivatives filter Type K Green

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State Liquid Appearance Colorless

OdorAmmonia-like, Fishy, StrongOdor ThresholdNo information available

12 (1%)

Melting Point/Range-37 °C / -34.6 °FBoiling Point/Range54 °C / 129.2 °FFlash Point-18 °C / -0.4 °FEvaporation RateNo information available

Flammability (solid,gas)

Not applicable

Flammability or explosive limits

 Upper
 12.3 vol %

 Lower
 2.6 vol %

Vapor Pressure287 mbar @ 25 °CVapor Density1.55

Specific Gravity0.775-0.890SolubilitySoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature390 °C / 734 °F

Decomposition TemperatureNo information availableViscosityNo information available

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

Excess heat.

Incompatible Materials Metals, Strong oxidizing agents, Acids, Halogens, Peroxides, Carbon dioxide (CO2)

Hazardous Decomposition Products Nitrogen oxides (NOx)

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Category 4. ATE = 300 - 2000 mg/kg.

Dermal LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50 Category 4. ATE = 10 - 20 mg/l.

Component Information

| Component | | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-----------|---------------|------------------------|-------------------------|------------------------------|
| | Water | - | - | - |
| | Dimethylamine | LD50 = 698 mg/kg (Rat) | LD50 = 3900 mg/kg (Rat) | LC50 = 7340 ppm (Rat) 20 min |

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes burns by all exposure routes

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Component | CAS-No | IARC | NTP | ACGIH | OSHA | Mexico |
|---------------|-----------|------------|------------|------------|------------|------------|
| Water | 7732-18-5 | Not listed |
| Dimethylamine | 124-40-3 | Not listed |

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed

tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

This product contains the following substance(s) which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|---------------|---|---|----------|--|
| Dimethylamine | EC50: = 9 mg/L, 96h (Pseudokirchneriella subcapitata) | LC50: = 396 mg/L, 96h static (Brachydanio rerio) LC50: 127 - 349 mg/L, 96h semi-static (Poecilia reticulata) LC50: = 210 mg/L, 96h static (Poecilia reticulata) | | EC50: = 88.7 mg/L, 48h (Daphnia magna Straus) |

| | LC50: = 120 mg/L, 96h static | |
|--|------------------------------|--|
| | (Oncorhynchus mykiss) | |
| | LC50: 111 - 125 mg/L, 96h | |
| | (Oncorhynchus mykiss) | |
| | | |

Persistence and Degradability Per

Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation

No information available.

Mobility

Will likely be mobile in the environment due to its volatility.

| Component | log Pow |
|---------------|---------|
| Dimethylamine | -0.274 |

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

| Component | RCRA - U Series Wastes | RCRA - P Series Wastes |
|--------------------------|------------------------|------------------------|
| Dimethylamine - 124-40-3 | U092 | - |

14. Transport information

DOT

UN-No UN1160

Proper Shipping Name DIMETHYLAMINE SOLUTION

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group ||

TDG

UN-No UN1160

Proper Shipping Name DIMETHYLAMINE SOLUTION

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group ||

<u>IATA</u>

UN-No UN1160

Proper Shipping Name DIMETHYLAMINE, AQUEOUS SOLUTION

Hazard Class 3 Subsidiary Hazard Class 8 Packing Group II

IMDG/IMO

UN-No UN1160

Proper Shipping Name DIMETHYLAMINE, AQUEOUS SOLUTION

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group ||

15. Regulatory information

International Inventories

| Component | CAS-No | DSL | NDSL | TSCA | TSCA Inventory notification - Active-Inactive | EINECS | ELINCS | NLP |
|---------------|-----------|-----|------|------|---|-----------|--------|-----|
| Water | 7732-18-5 | X | - | X | ACTIVE | 231-791-2 | ı | 1 |
| Dimethylamine | 124-40-3 | Χ | - | Х | ACTIVE | 204-697-4 | - | - |

| Component | CAS-No | IECSC | KECL | ENCS | ISHL | TCSI | AICS | NZIoC | PICCS |
|-----------|-----------|-------|----------|------|------|------|------|-------|-------|
| Water | 7732-18-5 | X | KF-35400 | X | _ | X | X | X | X |

| Dimethylamine | 124-40-3 | Х | KE-11124 | X | Х | Х | Х | X | X |
|---------------|----------|---|----------|---|---|---|---|---|---|

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

| Component | Canada - National Pollutant Release Inventory (NPRI) | Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances | Canada's Chemicals Management Plan (CEPA) |
|---------------|---|--|--|
| Dimethylamine | Part 1, Group A Substance Part 4 Substance | | |

Legend

NPRI - National Pollutant Release Inventory

Other International Regulations

Authorisation/Restrictions according to EU REACH

| Component | | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | |
|---------------|---|---|---|
| Dimethylamine | - | Use restricted. See item 75. (see link for restriction details) | - |

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

| Component | CAS-No | OECD HPV | Persistent Organic Pollutant | Ozone Depletion Potential | Restriction of Hazardous Substances (RoHS) |
|---------------|-----------|----------|---------------------------------|------------------------------|--|
| Water | 7732-18-5 | Listed | Not applicable | Not applicable | Not applicable |
| Dimethylamine | 124-40-3 | Listed | Not applicable | Not applicable | Not applicable |

| Component | CAS-No | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements | | Rotterdam Convention (PIC) | Basel Convention (Hazardous Waste) |
|---------------|-----------|---|----------------|-------------------------------|---------------------------------------|
| Water | 7732-18-5 | Not applicable | Not applicable | Not applicable | Not applicable |
| Dimethylamine | 124-40-3 | Not applicable | Not applicable | Not applicable | Not applicable |

16. Other information

Prepared By Product Safety Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

Revision Date 25-March-2024

Creation Date10-March-2010Revision Date25-March-2024Print Date25-March-2024

Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS