

SAFETY DATA SHEET

Creation Date 08-February-2010 Revision Date 24-December-2021 **Revision Number** 6

1. Identification

Product Name Formaldehyde solution 37%

Cat No.: F75F-1GAL; F75P-1GAL; F75P-4; F75P-20

Synonyms Formalin; Methanal; Methylene oxide; Oxymethane; Formic aldehyde; Methyl aldehyde

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Manufacturer Importer/Distributor

Fisher Scientific Company Fisher Scientific 112 Colonnade Road, One Reagent Lane Fair Lawn, NJ 07410 Ottawa, ON K2E 7L6. Tel: (201) 796-7100

Canada

Tel: 1-800-234-7437

Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300

CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids Category 3 Category 3 Acute oral toxicity Category 3 Acute dermal toxicity Acute Inhalation Toxicity Category 3 Skin Corrosion/Irritation Category 1 B Category 1 Serious Eye Damage/Eye Irritation Skin Sensitization Category 1 Germ Cell Mutagenicity Category 2 Carcinogenicity Category 1A Specific target organ toxicity (single exposure) Category 1 Target Organs - Respiratory system, Central nervous system (CNS), Optic nerve.

Specific target organ toxicity - (repeated exposure) Category 1

Target Organs - Kidney, Liver, Heart, spleen, Blood.

Label Elements

Signal Word

Danger

Hazard Statements

Flammable liquid and vapor

Toxic if swallowed, in contact with skin or if inhaled

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause an allergic skin reaction

Suspected of causing genetic defects

May cause cancer

May cause drowsiness and dizziness

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not get in eyes, on skin, or on clothing

Do not breathe dust/fumes/gas/mist/vapours/spray

Ground/bond container and receiving equipment

Wear protective gloves/protective clothing/eye protection/face protection

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Keep container tightly closed

Take precautionary measures against static discharges

Contaminated work clothing should not be allowed out of the workplace

Response

Immediately call a POISON CENTER/doctor

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

Rinse mouth

Do NOT induce vomiting

Wash contaminated clothing before reuse

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Water	7732-18-5	45 - 48
Formaldehyde	50-00-0	37 - 40
Methanol	67-56-1	15

4. First-aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or

inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate

medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms/effects Difficulty in breathing. Causes burns by all exposure routes. May cause allergic skin

reaction. . Symptoms of overexposure may be headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle

pain or flushing

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point 50 °C / 122 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

Upper No data available
Lower No data available

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Hydrogen. Formaldehyde.

Protective Equipment and Precautions for Firefighters

Thermal decomposition can lead to release of irritating gases and vapors. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health **Flammability** Instability Physical hazards 3 N/A 0

Accidental release measures

Personal Precautions

Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Should not be released into the environment. Do not flush into surface water or sanitary

Environmental Precautions

sewer system. See Section 12 for additional Ecological Information.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools, Take precautionary measures against static discharges.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. Strong bases. nitriles. Acids. Isocyanates. Acid anhydrides. Metals. Acid chlorides.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Formaldehyde	Ceiling: 1 ppm Ceiling: 1.3 mg/m³ TWA: 0.75 ppm TWA: 0.9 mg/m³	TWA: 0.1 ppm STEL: 0.3 ppm	TWA: 0.1 ppm STEL: 1 ppm	Ceiling: 2 ppm Ceiling: 3 mg/m³	TWA: 0.1 ppm STEL: 0.3 ppm	(Vacated) TWA: 3 ppm (Vacated) STEL: 10 ppm (Vacated) Ceiling: 5 ppm TWA: 0.75 ppm STEL: 2 ppm	TWA: 0.016 ppm
Methanol	TWA: 200 ppm TWA: 262 mg/m³ STEL: 250 ppm STEL: 328 mg/m³ Skin	TWA: 200 ppm STEL: 250 ppm Skin	TWA: 200 ppm STEL: 250 ppm Skin	TWA: 200 ppm TWA: 262 mg/m³ STEL: 250 ppm STEL: 328 mg/m³ Skin		(Vacated) TWA:	mg/m³ STEL: 250 ppm STEL: 325

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment, Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eve Protection Gogales

Hand Protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Viton (R)	> 480 minutes	0.7 mm	As tested under EN374-3
Nitrile rubber	> 360 minutes	15 - 22 mil	Determination of Resistance to
			Permeation by Chemicals

Inspect gloves before use, observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Physical and chemical properties

Physical State Liquid **Appearance** Colorless pungent Odor

Odor Threshold No information available No information available

рΗ **Melting Point/Range** 0 °C / 32 °F 101 °C / 213.8 °F **Boiling Point/Range** Flash Point 50 °C / 122 °F **Evaporation Rate** No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper No data available Lower No data available **Vapor Pressure** No information available

Vapor Density > 1.0

Specific Gravity No information available

Solubility miscible

Partition coefficient; n-octanol/water No data available

Autoignition Temperature No information available **Decomposition Temperature** No information available **Viscosity** No information available

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong bases, nitriles, Acids, Isocyanates, Acid anhydrides,

Metals. Acid chlorides

Hazardous Decomposition Products Hydrogen, Formaldehyde

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Category 3. ATE = 50 - 300 mg/kg. **Dermal LD50** Category 3. ATE = 200 - 1000 mg/kg. Category 3. ATE = 2 - 10 mg/l. Vapor LC50

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Water	-	-	-	
Formaldehyde	500 mg/kg (Rat)	LD50 = 270 mg/kg (Rabbit)	0.578 mg/L (Rat) 4 h	
Methanol	LD50 = 1187 - 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h	

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes burns by all exposure routes

Sensitization May cause sensitization by skin contact

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Water	7732-18-5	Not listed				
Formaldehyde	50-00-0	Group 1	Known	A1	X	A2
Methanol	67-56-1	Not listed				

IARC (International Agency for Research on Cancer)

NTP: (National Toxicity Program)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program) Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human

Carcinogen

ACGIH: (American Conference of Governmental Industrial

Mexico - Occupational Exposure Limits - Carcinogens

Hygienists)

A1 - Known Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen A2 - Suspected Human Carcinogen

A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

A5 - Not Suspected as a Human Carcinogen

Mutagenic effects have occurred in humans. **Mutagenic Effects**

Experiments have shown reproductive toxicity effects on laboratory animals. **Reproductive Effects**

Developmental effects have occurred in experimental animals. Component substance is **Developmental Effects**

listed on California Proposition 65 as a developmental hazard.

Teratogenic effects have occurred in experimental animals. **Teratogenicity**

STOT - single exposure Respiratory system Central nervous system (CNS) Optic nerve STOT - repeated exposure Kidney Liver Heart spleen Blood

Aspiration hazard No information available

delayed

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

Endocrine Disruptor Information No information available

The toxicological properties have not been fully investigated. Other Adverse Effects

12. Ecological information

Ecotoxicity

Do not empty into drains. The product contains following substances which are hazardous for the environment.

L	Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
I	Formaldehyde	Not listed	Leuciscus idus: LC50 = 15	Not listed	EC50 = 20 mg/L 96h
L	-		mg/L 96h		EC50 = 2 mg/L 48h
Ī	Methanol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h
1			> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min	_
L				EC50 = 43000 mg/L 5 min	

Miscible with water Persistence is unlikely based on information available. Persistence and Degradability

Bioaccumulation/ Accumulation No information available.

. Will likely be mobile in the environment due to its water solubility. **Mobility**

Component	log Pow
Formaldehyde	-0.35
Methanol	-0.74

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Formaldehyde - 50-00-0	U122	-
Methanol - 67-56-1	U154	-

14. Transport information

DOT

UN-No UN1198

Proper Shipping Name FORMALDEHYDE SOLUTIONS, FLAMMABLE

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

<u>TDG</u>

UN-No UN1198

Proper Shipping Name FORMALDEHYDE SOLUTION, FLAMMABLE

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

IATA

UN-No UN1198

Proper Shipping Name FORMALDEHYDE SOLUTION, FLAMMABLE

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

IMDG/IMO

UN-No UN1198

Proper Shipping Name FORMALDEHYDE SOLUTION, FLAMMABLE

Hazard Class 3
Subsidiary Hazard Class 8
Packing Group III

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Water	7732-18-5	X	-	Х	ACTIVE	231-791-2	-	-
Formaldehyde	50-00-0	Х	-	Х	ACTIVE	200-001-8	-	-
Methanol	67-56-1	X	-	X	ACTIVE	200-659-6	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Water	7732-18-5	X	KE-35400	X	-	X	X	Х	X
Formaldehyde	50-00-0	Х	KE-17074	Х	Х	Х	X	Х	Х
Methanol	67-56-1	Х	KE-23193	Х	Х	Х	Х	Х	Х

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Formaldehyde	Part 1, Group A Substance Part 5, Individual Substances Part 4 Substance	Schedule I	
Methanol	Part 1, Group A Substance Part 5, Individual Substances Part 4		

Substance	

Other International Regulations

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Formaldehyde	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Methanol	-	Use restricted. See item 69. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Water	7732-18-5	Listed	Not applicable	Not applicable	Not applicable
Formaldehyde	50-00-0	Listed	Not applicable	Not applicable	Not applicable
Methanol	67-56-1	Listed	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities	Seveso III Directive (2012/18/EC) - Qualifying Quantities	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
		for Major Accident Notification	for Safety Report Requirements		
Water	7732-18-5	Not applicable	Not applicable	Not applicable	Not applicable
Formaldehyde	50-00-0	5 tonne	50 tonne	Not applicable	Not applicable
Methanol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

Creation Date08-February-2010Revision Date24-December-2021Print Date24-December-2021

Revision SummaryThis document has been updated to comply with the requirements of WHMIS 2015 to align

with the Globally Harmonised System (GHS) for the Classification and Labelling of

Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS