

## SAFETY DATA SHEET

Creation Date 06-December-2010

Revision Date 24-December-2021

Revision Number 6

### 1. Identification

**Product Name** 2-Methyl-2-phenylpropylmagnesium chloride, 0.5M solution in diethyl ether

**Cat No. :** AC438750000; AC438751000; AC438758000

**Synonyms** No information available

**Recommended Use** Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

#### Details of the supplier of the safety data sheet

##### Company

**Importer/Distributor**  
Fisher Scientific  
112 Colonnade Road,  
Ottawa, ON K2E 7L6,  
Canada  
Tel: 1-800-234-7437

Acros Organics  
One Reagent Lane  
Fair Lawn, NJ 07410

**Manufacturer**  
Fisher Scientific Company  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

**Emergency Telephone Number** For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

### 2. Hazard(s) identification

#### Classification

**WHMIS 2015 Classification** Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

<b>Flammable liquids</b>	Category 1
<b>Acute oral toxicity</b>	Category 4
<b>Skin Corrosion/Irritation</b>	Category 1 B
<b>Serious Eye Damage/Eye Irritation</b>	Category 1
<b>Specific target organ toxicity (single exposure)</b>	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
<b>Physical Hazards Not Otherwise Classified</b>	Category 1
Reacts violently with water	
May form explosive peroxides	
<b>Health Hazards Not Otherwise Classified</b>	Category 1
Prolonged or repeated contact may dry skin and cause irritation or cracking	

#### Label Elements

**Signal Word**

Danger

**Hazard Statements**

Extremely flammable liquid and vapor  
Harmful if swallowed  
Causes severe skin burns and eye damage  
May cause respiratory irritation  
May cause drowsiness and dizziness  
Reacts violently with water  
May form explosive peroxides  
Prolonged or repeated contact may dry skin and cause irritation or cracking



**Precautionary Statements**

**Prevention**

Do not allow contact with water  
Keep container tightly closed  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Ground/bond container and receiving equipment  
Use only non-sparking tools  
Take precautionary measures against static discharges  
Do not breathe dust/fumes/gas/mist/vapours/spray  
Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Wear protective gloves/protective clothing/eye protection/face protection

**Response**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER/doctor  
Rinse mouth  
Do NOT induce vomiting  
Wash contaminated clothing before reuse  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

**Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Disposal**

Dispose of contents/container to an approved waste disposal plant

### 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Ethyl ether	60-29-7	87-88
Magnesium, chloro(2-methyl-2-phenylpropyl)-	35293-35-7	12-13

#### 4. First-aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
<b>Inhalation</b>	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
<b>Most important symptoms/effects</b>	Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
<b>Notes to Physician</b>	Treat symptomatically

#### 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	CO <sub>2</sub> , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
<b>Unsuitable Extinguishing Media</b>	No information available
<b>Flash Point</b>	-28 °C / -18.4 °F
<b>Method -</b>	No information available
<b>Autoignition Temperature</b>	No information available
<b>Explosion Limits</b>	
<b>Upper</b>	No data available
<b>Lower</b>	No data available
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

##### Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

##### Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

##### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

##### NFPA

**Health**  
3

**Flammability**  
4

**Instability**  
0

**Physical hazards**  
N/A W

## 6. Accidental release measures

<b>Personal Precautions</b>	Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.
<b>Environmental Precautions</b>	Should not be released into the environment. See Section 12 for additional Ecological Information.
<b>Methods for Containment and Clean Up</b>	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

<b>Handling</b>	Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
<b>Storage.</b>	Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Flammables area. Keep away from heat, sparks and flame. Store indoors. Store contents under argon. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from water or moist air. Incompatible Materials. Strong oxidizing agents.

## 8. Exposure controls / personal protection

### Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWA/EV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl ether	TWA: 400 ppm TWA: 1210 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1520 mg/m <sup>3</sup>	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm TWA: 1210 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1520 mg/m <sup>3</sup>	TWA: 400 ppm STEL: 500 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 1200 mg/m <sup>3</sup> (Vacated) STEL: 500 ppm (Vacated) STEL: 1500 mg/m <sup>3</sup> TWA: 400 ppm TWA: 1200 mg/m <sup>3</sup>	IDLH: 1900 ppm

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

### Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to

control hazardous materials at source

### Personal protective equipment

**Eye Protection** Goggles  
**Hand Protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber Viton (R)	See manufacturers recommendations	-	Splash protection only

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

### **Respiratory Protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371

When RPE is used a face piece Fit Test should be conducted

### Environmental exposure controls

No information available.

### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	No information available
<b>Odor</b>	No information available
<b>Odor Threshold</b>	No information available
<b>pH</b>	No information available
<b>Melting Point/Range</b>	No data available
<b>Boiling Point/Range</b>	34 °C / 93.2 °F @ 760mmHg
<b>Flash Point</b>	-28 °C / -18.4 °F
<b>Evaporation Rate</b>	No information available
<b>Flammability (solid,gas)</b>	Not applicable
<b>Flammability or explosive limits</b>	
<b>Upper</b>	No data available
<b>Lower</b>	No data available
<b>Vapor Pressure</b>	No information available
<b>Vapor Density</b>	No information available
<b>Specific Gravity</b>	0.76
<b>Solubility</b>	No information available
<b>Partition coefficient; n-octanol/water</b>	No data available
<b>Autoignition Temperature</b>	No information available
<b>Decomposition Temperature</b>	No information available
<b>Viscosity</b>	No information available
<b>Molecular Formula</b>	C10 H13 Cl Mg
<b>Molecular Weight</b>	192.97

## 10. Stability and reactivity

<b>Reactive Hazard</b>	Yes
<b>Stability</b>	Moisture sensitive. Reacts violently with water. Air sensitive.
<b>Conditions to Avoid</b>	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water. Exposure to air. Exposure to moisture.
<b>Incompatible Materials</b>	Strong oxidizing agents
<b>Hazardous Decomposition Products</b>	Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> )
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	None under normal processing. Reacts violently with water.

## 11. Toxicological information

### Acute Toxicity

#### Product Information

##### Oral LD50

Category 4. ATE = 300 - 2000 mg/kg.

##### Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

##### Vapor LC50

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

#### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm ( Rat ) 4 h

**Toxicologically Synergistic Products** No information available

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Irritation** No information available

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl ether	60-29-7	Not listed	Not listed	Not listed	Not listed	Not listed
Magnesium, chloro(2-methyl-2-phenylpropyl)-	35293-35-7	Not listed	Not listed	Not listed	Not listed	Not listed

**Mutagenic Effects** No information available

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

**STOT - single exposure** Respiratory system Central nervous system (CNS)

**STOT - repeated exposure** None known

**Aspiration hazard** No information available

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be

investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** The toxicological properties have not been fully investigated.

## 12. Ecological information

### Ecotoxicity

Do not empty into drains. .

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl ether	Not listed	LC50: > 10000 mg/L, 96h static (Lepomis macrochirus) LC50: = 2560 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 5600 mg/L 15 min	EC50 = 165 mg/L/24h

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl ether	0.82

## 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Ethyl ether - 60-29-7	U117	-

## 14. Transport information

<b>DOT</b>	Not regulated
<b>Proper Shipping Name</b>	consumer commodity
<b>Technical Name</b>	Magnesium, chloro(2-methyl-2-phenylpropyl)-
<b>TDG</b>	Not regulated
<b>IATA</b>	
<b>UN-No</b>	UN2924
<b>Proper Shipping Name</b>	Flammable liquid, corrosive, n.o.s.
<b>Hazard Class</b>	3
<b>Subsidiary Hazard Class</b>	8
<b>Packing Group</b>	I
<b>IMDG/IMO</b>	
<b>UN-No</b>	UN2924
<b>Proper Shipping Name</b>	Flammable liquid, corrosive, n.o.s.
<b>Hazard Class</b>	3
<b>Subsidiary Hazard Class</b>	8
<b>Packing Group</b>	I

## 15. Regulatory information

### International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory	EINECS	ELINCS	NLP
-----------	--------	-----	------	------	----------------	--------	--------	-----

					notification - Active-Inactive			
Ethyl ether	60-29-7	X	-	X	ACTIVE	200-467-2	-	-
Magnesium, chloro(2-methyl-2-phenylpropyl)-	35293-35-7	-	X	X	ACTIVE	252-492-3	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Ethyl ether	60-29-7	X	KE-27690	X	X	X	X	X	X
Magnesium, chloro(2-methyl-2-phenylpropyl)-	35293-35-7	-	-	-	X	X	-	-	-

**Legend:**

X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**Canada**

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Ethyl ether	Part 4 Substance		

**Legend**

NPRI - National Pollutant Release Inventory

**Other International Regulations**

**Authorisation/Restrictions according to EU REACH**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable
Magnesium, chloro(2-methyl-2-phenylprop yl)-	35293-35-7	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl ether	60-29-7	Not applicable	Not applicable	Not applicable	Annex I - Y40 Annex I - Y42
Magnesium, chloro(2-methyl-2-phenylprop yl)-	35293-35-7	Not applicable	Not applicable	Not applicable	Not applicable



---

## 16. Other information

<b>Prepared By</b>	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
<b>Creation Date</b>	06-December-2010
<b>Revision Date</b>	24-December-2021
<b>Print Date</b>	24-December-2021
<b>Revision Summary</b>	This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**