

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihalan Produk:

Product Description:

Cat No. :

Base 4 Oxidizer
Base 4 Oxidizer

BP3140; NC6127707; NC9219159

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

Company

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888

 CHEMTREC Malaysia **1-800-815-308** (Malay)

 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Acute oral toxicity	Category 4 (H302)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Carcinogenicity	Category 2 (H351)
Specific target organ toxicity - (single exposure)	Category 3 (H335) (H336)
Chronic aquatic toxicity	Category 3 (H412)

Label Elements


Signal Word

Danger

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

Hazard Statements

H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P280 - Wear eye protection/ face protection
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 - Ground and bond container and receiving equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area

Response

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308 + P313 - IF exposed or concerned: Get medical advice/attention
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P330 - Rinse mouth
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Toxic to terrestrial vertebrates
Contains a known or suspected endocrine disruptor
Contains a substance on the National Authorities Endocrine Disruptor Lists

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Tetrahydrofuran	109-99-9	76 - 79
Pyridine	110-86-1	19.5
Water	7732-18-5	2.0 - 2.5
Iodine	7553-56-2	2.0 - 2.5
2,6-Di-tert-butyl-p-cresol	128-37-0	< 1.0

SECTION 4: FIRST AID MEASURES

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Protect from light. Flammables area. Shelf life 12 months. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat, sparks and flame.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Tetrahydrofuran		TWA: 50 ppm STEL: 100 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 590 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 735 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³
Pyridine		TWA: 1 ppm	(Vacated) TWA: 5 ppm (Vacated) TWA: 15 mg/m ³ TWA: 5 ppm TWA: 15 mg/m ³
Iodine		TWA: 0.001 ppm Skin	Ceiling: 0.1 ppm Ceiling: 1 mg/m ³ (Vacated) Ceiling: 0.1 ppm (Vacated) Ceiling: 1 mg/m ³
2,6-Di-tert-butyl-p-cresol		TWA: 2 mg/m ³	(Vacated) TWA: 10 mg/m ³

Component	European Union	The United Kingdom	Germany
Tetrahydrofuran	TWA: 50 ppm (8h) TWA: 150 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 300 mg/m ³ (15min) Skin	STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr Skin	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 150 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 20 ppm (8 Stunden). MAK TWA: 60 mg/m ³ (8 Stunden). MAK

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

			Höhepunkt: 40 ppm Höhepunkt: 120 mg/m ³ Haut
Pyridine		STEL: 10 ppm 15 min STEL: 33 mg/m ³ 15 min TWA: 5 ppm 8 hr TWA: 16 mg/m ³ 8 hr	Haut
Iodine		STEL: 0.1 ppm; 1.1mg/m ³	TWA: 0.1 ppm TWA: 1.1 mg/m ³ skin absorber
2,6-Di-tert-butyl-p-cresol		STEL: 30 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr	TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 4 TWA: 10 mg/m ³ (8 Stunden). MAK can occur as vapor and aerosol at the same time Höhepunkt: 40 mg/m ³

Exposure Controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system Local authorities should be advised if significant spillages cannot be contained

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Colorless

Physical State

Liquid

Odor

sweet

Odor Threshold

No data available

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

pH	No information available	
Melting Point/Range	-65 °C / -85 °F	
Softening Point	No data available	
Boiling Point/Range	65.4 °C / 149.7 °F	
Flash Point	-14.4 -12.2 °C / 6.1 - 10 °F	Method - No information available
Evaporation Rate	> 1 (Butyl Acetate = 1.0)	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	160 mmHg @ 25 °C	
Vapor Density	2.5 (Air = 1.0)	(Air = 1.0)
Specific Gravity / Density	0.89	
Bulk Density	Not applicable	Liquid
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Tetrahydrofuran	0.45	
Pyridine	0.65	
Iodine	2.49	
2,6-Di-tert-butyl-p-cresol	5.1	
Autoignition Temperature	321 °C / 609.8 °F	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Yes.

Chemical Stability

May form explosive peroxides. Light sensitive. Hazardous polymerization may occur.

Possibility of Hazardous Reactions

Hazardous Polymerization	Polymerization can occur.
Hazardous Reactions	None under normal processing.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition. Protect from direct sunlight. Incompatible products.

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

Incompatible Materials

oxygen. Acids. Bases. Bromine. Oxidizing agent.

Hazardous Decomposition Products

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h
Pyridine	LD50 = 866 mg/kg (Rat)	LD50 1000 - 2000 mg/kg (Rabbit)	LC50 = 12.898 mg/L (Rat) 4 h
Water	-	-	-
Iodine	315 mg/kg (Rat)	1425 mg/kg (Rabbit)	4.588 mg/L 4h (Rat)
2,6-Di-tert-butyl-p-cresol	> 6 g/kg (Rat)	> 2 g/kg (Rat)	-

(b) skin corrosion/irritation;

Category 2

(c) serious eye damage/irritation;

Category 2

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (76 - 79)	Local Lymph Node Assay OECD Test Guideline 429	mouse	non-sensitising

(e) germ cell mutagenicity;

No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (76 - 79)	OECD Test Guideline 476 Gene cell mutation	in vivo Mammalian	negative
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative

(f) carcinogenicity;

Category 2

Limited evidence of a carcinogenic effect The table below indicates whether each agency

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B
Pyridine				Group 2B

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Tetrahydrofuran 109-99-9 (76 - 79)	OECD Test Guideline 416	Rat 2 Generation	NOAEL = 3,000 ppm

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression.

Endocrine Disrupting Properties
Assess endocrine disrupting
properties for human health

Contains a substance on the National Authorities Endocrine Disruptor Lists

Component	EU National Authorities Endocrine Disruptor Lists - Health
2,6-Di-tert-butyl-p-cresol 128-37-0 (< 1.0)	List II

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

This product contains the following substance(s) which are hazardous for the environment. The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains a substance which is: Very toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Tetrahydrofuran	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h		
Pyridine	LC50: = 4.6 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 26 mg/L, 96h semi-static (Cyprinus carpio) LC50: 63.4 - 73.6 mg/L, 96h flow-through (Pimephales promelas)			
Iodine	Oncorhynchus mykiss: LC50 = 1,7 mg/l/96 h	EC50 = 0,2 mg/l/48 h	-	-
2,6-Di-tert-butyl-p-cresol	LC50 = 0.199 mg/L 96h	EC50 >0.31 mg/L 48h	EC50 = 0.758 mg/L 96h EC50 = 6 mg/L 72 h	EC50 = 7.82 mg/L 5 min EC50 = 8.57 mg/L 15

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

				min EC50 = 8.98 mg/L 30 min
--	--	--	--	-----------------------------------

Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Tetrahydrofuran	0.45	No data available
Pyridine	0.65	No data available
Iodine	2.49	No data available
2,6-Di-tert-butyl-p-cresol	5.1	230 - 2500 dimensionless

Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Tetrahydrofuran	Group III Chemical	

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not let this chemical enter the environment Do not empty into drains

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No	UN1993
Hazard Class	3
Packing Group	II
Proper Shipping Name	Flammable liquid, n.o.s.

Road and Rail Transport

UN-No	UN1993
-------	--------

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

Hazard Class 3
Packing Group II
Proper Shipping Name Flammable liquid, n.o.s.

IATA

UN-No UN1993
Hazard Class 3
Packing Group II
Proper Shipping Name Flammable liquid, n.o.s.

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Tetrahydrofuran	203-726-8	X	X	X	X	X	X	X	KE-33454
Pyridine	203-809-9	X	X	X	X	X	X	X	KE-29929
Water	231-791-2	X	X	X	X		X	X	KE-35400
Iodine	231-442-4	X	X	X	X		X	X	KE-21023
2,6-Di-tert-butyl-p-cresol	204-881-4	X	X	X	X	X	X	X	KE-03079

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Pyridine				Annex I - Y42

National Regulations

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

SAFETY DATA SHEET

Base 4 Oxidizer

Revision Date 24-Mar-2025

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date

24-Mar-2025

Revision Summary

Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet