

SAFETY DATA SHEET

Revision Date 01-April-2024 Revision Number 5

1. Identification

Product Name Sulfur in Diesel Fuel standard solution, Specpure®, 750 µg/g (0.075%)

Cat No. : 38770

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific 112 Colonnade Road, Ottawa, ON K2E 7L6,

Canada

Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids Category 4
Carcinogenicity Category 2

Label Elements

Signal Word

Warning

Hazard Statements

Combustible liquid

Suspected of causing cancer



Precautionary Statements

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Response

IF exposed or concerned: Get medical advice/attention

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store locked up

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Fuels, diesel, no. 2	68476-34-6	99.925
Butane, 1,1-thiobis-	544-40-1	0.075

4. First-aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Most important symptoms/effects Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness,

nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Sulfur in Diesel Fuel standard solution, Specpure®, 750 µg/g (0.075%)

Flash Point 69 °C / 156.2 °F

Method - No information available

Autoignition Temperature 500 °C / 932 °F

Explosion Limits

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Combustible material. Containers may explode when heated.

Hazardous Combustion Products

None known.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health Flammability Instability Physical hazards
2 0 -

6. Accidental release measures

Personal Precautions Ensure adequate ventilation. Use personal protective equipment as required. Remove all

sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions Should not be released into the environment. See Section 12 for additional Ecological

Information. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up**Remove all sources of ignition.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not

get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open

flames, hot surfaces and sources of ignition.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks and flame.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
-		Columbia					
Fuels, diesel, no. 2	TWA: 100 mg/m³	TWA: 100 mg/m³ Skin	TWA: 100 mg/m³ Skin	TWA: 100 mg/m³	TWA: 100 mg/m³ Skin		

Leaend

ACGIH - American Conference of Governmental Industrial Hygienists

Engineering Measures Ensure that eyewash stations and safety showers are close to the workstation location.

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact,

and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Natural rubber	See manufacturers	-	Splash protection only
Nitrile rubber	recommendations		
Neoprene			
PVC			

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** Particulates filter conforming to EN 143

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State Liquid
Appearance Light brown

Odor Petroleum distillates
Odor Threshold No information available
pH No information available

Melting Point/Range No data available

Boiling Point/Range 171 - 315 °C / 339.8 - 599 °F

Flash Point 69 °C / 156.2 °F
Evaporation Rate No information available
Flammability (solid,gas) Not applicable

Flammability (solid,gas)
Not a
Flammability or explosive limits

UpperNo data availableLowerNo data availableVapor PressureNo information availableVapor DensityNo information available

Specific Gravity 0.75 g/cm3

Solubility

No information available

Partition coefficient; n-octanol/water

Autoignition Temperature

No data available

500 °C / 932 °F

Decomposition TemperatureNo information availableViscosityNo information available

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition.

Strong oxidizing agents **Incompatible Materials**

Hazardous Decomposition Products None under normal use conditions

Hazardous Polymerization Hazardous polymerization does not occur.

None under normal processing. **Hazardous Reactions**

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. **Dermal LD50** Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Vapor LC50

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation		
Fuels, diesel, no. 2	Fuels, diesel, no. 2 Not listed		LC50 = 3.6 mg/L (Rat) 4 h LC50 = 5.4 mg/L (Rat) 4 h		
Butane, 1,1-thiobis-	LD50 = 2220 mg/kg (Rat)	Not listed	Not listed		

Toxicologically Synergistic

Products

Irritation No information available Sensitization No information available

Carcinogenicity		The table below in	dicates whether ea	ach agency has list	ed any ingredient	as a carcinogen.
Component	CAS-No	IAPC	NTD	VCCIH	OSHV	Mexico

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Fuels, diesel, no. 2	68476-34-6	Not listed	Not listed	A3	Not listed	A3
Butane, 1,1-thiobis-	544-40-1	Not listed				

ACGIH: (American Conference of Governmental Industrial

Mexico - Occupational Exposure Limits - Carcinogens

Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen A2 - Suspected Human Carcinogen A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

A5 - Not Suspected as a Human Carcinogen

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Sulfur in Diesel Fuel standard solution, Specpure®, 750 µg/g (0.075%)

Teratogenicity No information available.

STOT - single exposure None known STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

delayed

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Contains a substance which is:. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Fuels, diesel, no. 2	Not listed	LC50: = 35 mg/L, 96h flow-through (Pimephales promelas)	Not listed	Not listed
Butane, 1,1-thiobis-	Not listed	LC50: = 3.58 mg/L, 96h flow-through (Pimephales promelas)	Not listed	Not listed

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

Mobility No information available.

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a

hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOTCOMBUSTIBLE LIQUID, NOT REGULATED FOR TRANSPORT IN THIS QUANTITY

According to 49 CFR §173.150(f)(1), this material should reclassified as NA1993,

Combustible Liquid, NOS if it is shipped in bulk.

UN-No NA1993

Proper Shipping Name Combustible liquid, n.o.s.

Packing Group III

TDG Not regulated Not regulated Not regulated Not regulated Not regulated Not regulated

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Fuels, diesel, no. 2	68476-34-6	X	_	X	ACTIVE	270-676-1	-	-

Sulfur in Diesel Fuel standard solution, Specpure®, 750 μ g/g (0.075%)

Butane, 1,1-thiobis-	544-40-1	Χ	-	Χ	ACT	IVE	208-870-5	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Fuels, diesel, no. 2	68476-34-6	Х	KE-17287	-	-	X	X	X	X
Butane, 1,1-thiobis-	544-40-1	Х	-	X	Х	X	X	X	Х

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Other International Regulations

Authorisation/Restrictions according to EU REACH

Component	,	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	,
Fuels, diesel, no. 2	-	Use restricted. See item 75.	-
		(see link for restriction details)	

REACH links

https://echa.europa.eu/substances-restricted-under-reach

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Fuels, diesel, no. 2	68476-34-6	Listed	Not applicable	Not applicable	Not applicable
Butane, 1,1-thiobis-	544-40-1	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Fuels, diesel, no. 2	68476-34-6	Not applicable	Not applicable	Not applicable	Not applicable
Butane, 1,1-thiobis-	544-40-1	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Product Safety Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

Revision Date 01-April-2024

Revision Date 01-April-2024

,

Print Date 01-April-2024

Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS