

## SAFETY DATA SHEET

Creation Date 17-September-2009

Revision Date 20-October-2022

Revision Number 6

### 1. Identification

**Product Name** 4-Methyl-2-pentanone

**Cat No. :** AC222170000; AC222170010; AC222170025; AC222175000

**CAS-No** 108-10-1

**Synonyms** Isobutyl methyl ketone; Isopropylacetone; MIBK; Methyl isobutyl ketone

**Recommended Use** Laboratory chemicals.

**Uses advised against** Food, drug, pesticide or biocidal product use.

#### Details of the supplier of the safety data sheet

##### Company

##### **Importer/Distributor**

Fisher Scientific  
112 Colonnade Road,  
Ottawa, ON K2E 7L6,  
Canada  
Tel: 1-800-234-7437

Acros Organics  
One Reagent Lane  
Fair Lawn, NJ 07410

##### **Manufacturer**

Fisher Scientific Company  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

##### **Emergency Telephone Number**

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99

**CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

### 2. Hazard(s) identification

#### Classification

##### **WHMIS 2015 Classification**

Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

<b>Flammable liquids</b>	Category 2
<b>Acute Inhalation Toxicity</b>	Category 4
<b>Serious Eye Damage/Eye Irritation</b>	Category 2
<b>Carcinogenicity</b>	Category 2
<b>Specific target organ toxicity (single exposure)</b>	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
<b>Health Hazards Not Otherwise Classified</b>	Category 1
Prolonged or repeated contact may dry skin and cause irritation or cracking	

#### Label Elements

##### **Signal Word**

Danger

**Hazard Statements**

Highly flammable liquid and vapor  
Causes serious eye irritation  
Harmful if inhaled  
May cause drowsiness and dizziness  
Suspected of causing cancer  
Prolonged or repeated contact may dry skin and cause irritation or cracking

**Precautionary Statements****Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Wear protective gloves/protective clothing/eye protection/face protection  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
Keep container tightly closed  
Use explosion-proof electrical/ventilating/lighting/equipment  
Ground/bond container and receiving equipment  
Use only non-sparking tools  
Use only outdoors or in a well-ventilated area  
Take precautionary measures against static discharges  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Wash face, hands and any exposed skin thoroughly after handling

**Response**

IF exposed or concerned: Get medical advice/attention  
IF INHALED: Remove person to fresh air and keep comfortable for breathing  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

**Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed

**Disposal**

Dispose of contents/container to an approved waste disposal plant

### 3. Composition/Information on Ingredients

Component	CAS-No	Weight %
2-Pentanone, 4-methyl-	108-10-1	>95

### 4. First-aid measures

**General Advice**

If symptoms persist, call a physician.

**Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water.
<b>Most important symptoms/effects</b>	None reasonably foreseeable. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
<b>Notes to Physician</b>	Treat symptomatically

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Water spray, carbon dioxide (CO <sub>2</sub> ), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
<b>Unsuitable Extinguishing Media</b>	No information available
<b>Flash Point</b>	14 °C / 57.2 °F
<b>Method -</b>	CC (closed cup)
<b>Autoignition Temperature</b>	460 °C / 860 °F
<b>Explosion Limits</b>	
<b>Upper</b>	8.0% @ 93°C
<b>Lower</b>	1.2% @ 93°C
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

### Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### NFPA

<b>Health</b>	<b>Flammability</b>	<b>Instability</b>	<b>Physical hazards</b>
2	3	0	N/A

## 6. Accidental release measures

<b>Personal Precautions</b>	Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.
<b>Environmental Precautions</b>	Should not be released into the environment.
<b>Methods for Containment and Clean Up</b>	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## 7. Handling and storage

<b>Handling</b>	Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.
-----------------	--

Take precautionary measures against static discharges.

**Storage.**

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. Peroxides.

## 8. Exposure controls / personal protection

**Exposure Guidelines**

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
2-Pentanone, 4-methyl-	TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 307 mg/m <sup>3</sup>	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	TWA: 20 ppm STEL: 75 ppm	(Vacated) TWA: 50 ppm (Vacated) TWA: 205 mg/m <sup>3</sup> (Vacated) STEL: 75 ppm (Vacated) STEL: 300 mg/m <sup>3</sup> TWA: 100 ppm TWA: 410 mg/m <sup>3</sup>	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup>

**Legend**

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

**Engineering Measures**

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

**Personal protective equipment****Eye Protection**

Goggles

**Hand Protection**

Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Laminated film (Barrier)	> 480 minutes	0.5 mm	Splash protection only

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

**Respiratory Protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls**

No information available.

**Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	Characteristic sweet
Odor Threshold	0.04 - 0.08 ppm
pH	No information available
Melting Point/Range	-84 °C / -119.2 °F
Boiling Point/Range	117.4 °C / 243.3 °F @ 760 mmHg
Flash Point	14 °C / 57.2 °F
Method -	CC (closed cup)
Evaporation Rate	1.6 (Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	8.0% @ 93°C
Lower	1.2% @ 93°C
Vapor Pressure	21.5 mbar @ 20 °C
Vapor Density	3.45 (Air = 1.0)
Specific Gravity	0.800
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	460 °C / 860 °F
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C6 H12 O
Molecular Weight	100.16

## 10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Peroxides
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> )
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

## 11. Toxicological information

### Acute Toxicity

#### Product Information

#### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
2-Pentanone, 4-methyl-	LD50 = 2080 mg/kg ( Rat )	LD50 = 3000 mg/kg ( Rabbit )	LC50 2000 - 4000 ppm ( Rat ) 4 h

Toxicologically Synergistic Products No information available

#### Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Irritation</b>	Irritating to eyes and respiratory system
<b>Sensitization</b>	No information available
<b>Carcinogenicity</b>	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
2-Pentanone, 4-methyl-	108-10-1	Group 2B	Not listed	A3	X	A3

IARC (International Agency for Research on Cancer)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Confirmed Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

A5 - Not Suspected as a Human Carcinogen

Mexico - Occupational Exposure Limits - Carcinogens

Mexico - Occupational Exposure Limits - Carcinogens

**Mutagenic Effects** No information available

**Reproductive Effects** No information available.

**Developmental Effects** No information available.

**Teratogenicity** No information available.

**STOT - single exposure** Respiratory system Central nervous system (CNS)

**STOT - repeated exposure** None known

**Aspiration hazard** Category 1

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** The toxicological properties have not been fully investigated.

## 12. Ecological information

### Ecotoxicity

Do not empty into drains. .

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
2-Pentanone, 4-methyl-	EC50: 400 mg/L/96h	LC50: 496 - 514 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 79.6 mg/L 5 min	EC50: 4280.0 mg/L/24h EC50: 170 mg/L/48h EC50: 4280.0 mg/L/24h

**Persistence and Degradability** Persistence is unlikely

**Bioaccumulation/ Accumulation** No information available.

**Mobility** . Will likely be mobile in the environment due to its water solubility.

Component	log Pow
2-Pentanone, 4-methyl-	1.9

## 13. Disposal considerations

**Waste Disposal Methods**

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
2-Pentanone, 4-methyl- - 108-10-1	U161	-

## 14. Transport information

**DOT**

UN-No UN1245  
 Proper Shipping Name METHYL ISOBUTYL KETONE  
 Hazard Class 3  
 Packing Group II

**TDG**

UN-No UN1245  
 Proper Shipping Name METHYL ISOBUTYL KETONE  
 Hazard Class 3  
 Packing Group II

**IATA**

UN-No UN1245  
 Proper Shipping Name METHYL ISOBUTYL KETONE  
 Hazard Class 3  
 Packing Group II

**IMDG/IMO**

UN-No UN1245  
 Proper Shipping Name METHYL ISOBUTYL KETONE  
 Hazard Class 3  
 Packing Group II

## 15. Regulatory information

**International Inventories**

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
2-Pentanone, 4-methyl-	108-10-1	X	-	X	ACTIVE	203-550-1	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
2-Pentanone, 4-methyl-	108-10-1	X	KE-24725	X	X	X	X	X	X

**Legend:**

X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**Canada**

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
2-Pentanone, 4-methyl-	Part 1, Group A Substance		

	Part 5, Individual Substances Part 4 Substance		
--	---	--	--

**Legend** NPRI - National Pollutant Release Inventory

#### Other International Regulations

#### Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
2-Pentanone, 4-methyl-	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

#### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
2-Pentanone, 4-methyl-	108-10-1	Listed	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
2-Pentanone, 4-methyl-	108-10-1	Not applicable	Not applicable	Not applicable	Annex I - Y42

## 16. Other information

**Prepared By** Regulatory Affairs  
Thermo Fisher Scientific  
Email: EMSDS.RA@thermofisher.com

**Creation Date** 17-September-2009

**Revision Date** 20-October-2022

**Print Date** 20-October-2022

**Revision Summary** This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**