

Page 1/8 Creation Date 09-Apr-2018 Revision Date 29-Mar-2025 Version 3

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: <u>Graphite powder, natural, briquetting grade</u>
Product Description: <u>Graphite powder, natural, briquetting grade</u>

Cat No. : 40795 CAS No 7782-42-5

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

Supplier

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture			

Label Elements

Hazard Statements

Other Hazards

No information available

This product does not contain any known or suspected endocrine disruptors

Toxic to terrestrial vertebrates

Revision Date 29-Mar-2025

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %	
Graphite	7782-42-5	<=100	

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention

immediately if symptoms occur.

Clean mouth with water and drink afterwards plenty of water. Get medical attention if Ingestion

symptoms occur.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Self-Protection of the First Aider No special precautions required.

Most important symptoms and effects, both acute and delayed

None reasonably foreseeable.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Carbon dioxide (CO₂). Powder. Water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Graphite powder, natural, briquetting grade

Revision Date 29-Mar-2025

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

Environmental precautions

Should not be released into the environment.

Methods and Material for Containment and Cleaning Up

Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Avoid contact with skin, eyes or clothing. Avoid dust formation.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL	
Graphite		TWA: 2 mg/m ³	(Vacated) TWA: 2.5 mg/m ³	
		_	(Vacated) TWA: 10 mg/m ³	
			(Vacated) TWA: 5 mg/m ³	
			TWA: 15 mg/m ³	
			TWA: 5 mg/m ³	
			TWA: 15 mppcf	

Component	European Union	The United Kingdom	Germany
Graphite		STEL: 30 mg/m ³ 15 min	TWA: 1.25 mg/m³ (8 Stunden).
		STEL: 12 mg/m ³ 15 min	AGW - exposure factor 2
		TWA: 10 mg/m ³ 8 hr	TWA: 10 mg/m³ (8 Stunden). AGW -
		TWA: 4 mg/m ³ 8 hr	exposure factor 2
			TWA: 0.3 mg/m ³ (8 Stunden). MAK
			multiplied by the material
			density;except ultrafine particles
			TWA: 4 mg/m³ (8 Stunden). MAK
			Höhepunkt: 2.4 mg/m ³

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to

Graphite powder, natural, briquetting grade

control hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Protective gloves
Skin and body protection Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: Particle filter

To protect the wearer, respiratory protective equipment must be the correct fit and be used

Revision Date 29-Mar-2025

and maintained properly

When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u> Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls No information available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Black Physical State Solid

Odor No information available
Odor Threshold No data available
pH Not applicable

Melting Point/Range> 2760 °C / 5000 °FSoftening PointNo data availableBoiling Point/RangeNo information availableFlash PointNo information available

Flash Point No information available Method - No information available

Evaporation Rate Not applicable Solid

Flammability (solid,gas)

No information available

Explosion Limits No data available

Vapor PressureNo data availableVapor DensityNot applicable

Vapor DensityNot applicableSolidSpecific Gravity / Density2 g/cm3@ 20 °C

Bulk DensityNo data availableWater SolubilityInsoluble in waterSolubility in other solventsNo information available

Graphite powder, natural, briquetting grade

Partition Coefficient (n-octanol/water)

Autoignition Temperature Decomposition Temperature Viscosity No data available No data available

Explosive Properties
Oxidizing Properties

Not applicable No information available No information available Solid

Revision Date 29-Mar-2025

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

No information available. None under normal processing.

Conditions to Avoid

None known.

Incompatible Materials

Oxidizing agent.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

OralNo data availableDermalNo data availableInhalationNo data available

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Graphite	-	-	LC50 > 2000 mg/m ³ (Rat) 4 h

(b) skin corrosion/irritation; No data available

Graphite powder, natural, briquetting grade

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; Not applicable

Solid

Symptoms / effects,both acute and No information available.

delayed

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
	LC50: > 100 mg/L, 96h semi-static (Danio rerio)			
ľ	Semi-Static (Danio Teno)			

Persistence and degradability

Persistence Insoluble in water.

<u>Bioaccumulative potential</u> May have some potential to bioaccumulate

Mobility in soil Spillage unlikely to penetrate soil. The product is insoluble and sinks in water. Is not likely

mobile in the environment due its low water solubility.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

ALFAA40795

Revision Date 29-Mar-2025

Graphite powder, natural, briquetting grade

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on

Revision Date 29-Mar-2025

waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Waste codes should be assigned by the user based on the application for which the product

was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with

local regulations

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO Not regulated

Road and Rail Transport Not regulated

IATA Not regulated

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories China X = listed Australia U.S.A. (TSCA) Canada (DSL/NDSL) Europe

(EINECS/ELINCS/NLP) Australia (AICS) Korea (KECL) China (IECSC) Japan (ENCS) Philippines (PICCS) Taiwan (TCSI) Japan (ISHL) New Zealand (NZIoC) Japan (ISHL)

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Graphite	231-955-3	Х	Х	X	-		X	X	KE-18101

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

Graphite powder, natural, briquetting grade

TSCA - United States Toxic Substances Control Act Section 8(b)

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

Revision Date 29-Mar-2025

Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances **ENCS** - Japanese Existing and New Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit TWA - Time Weighted Average

ACGIH - American Conference of Governmental Industrial Hygienists IARC - International Agency for Research on Cancer RPE - Respiratory Protective Equipment LD50 - Lethal Dose 50%

LC50 - Lethal Concentration 50%

CAS - Chemical Abstracts Service

POW - Partition coefficient Octanol:Water

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

MARPOL - International Convention for the Prevention of Pollution from

Ships

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

EC50 - Effective Concentration 50%

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Health, Safety and Environmental Department **Prepared By**

Revision Date 29-Mar-2025

SDS sections updated. **Revision Summary**

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet