

Page 1/10 Creation Date 17-Sep-2009 Revision Date 26-Mar-2025 Version 5

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: 4-Methyl-2-pentanone Product Description: 4-Methyl-2-pentanone

**Cat No. :** L12842

Synonyms Isobutyl methyl ketone; Isopropylacetone; MIBK; Methyl isobutyl ketone

CAS No 108-10-1 Molecular Formula C6 H12 O

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

**Supplier** 

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

# **SECTION 2: HAZARDS IDENTIFICATION**

### Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Carcinogenicity	Category 2 (H351)
Specific target organ toxicity - (single exposure)	Category 3 (H336)

## Label Elements



4-Methyl-2-pentanone Revision Date 26-Mar-2025

## Signal Word

**Danger** 

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H332 - Harmful if inhaled

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

## **Precautionary Statements**

#### Prevention

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection/ face protection

P280 - Wear protective gloves

### Response

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

## **Disposal**

P501 - Dispose of contents/ container to an approved waste disposal plant

#### **Other Hazards**

EUH066 - Repeated exposure may cause skin dryness or cracking

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight %	
Methylisobutyl ketone	108-10-1	>95	

# **SECTION 4: FIRST AID MEASURES**

Description of first aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

\_\_\_\_\_

4-Methyl-2-pentanone Revision Date 26-Mar-2025

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

**Ingestion** Clean mouth with water and drink afterwards plenty of water.

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. Inhalation of high vapor concentrations may cause

symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

# **SECTION 5: FIREFIGHTING MEASURES**

#### Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

## Extinguishing media which must not be used for safety reasons

No information available.

## Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO2).

#### Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

#### Environmental precautions

Should not be released into the environment.

#### Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Revision Date 26-Mar-2025

#### Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

#### Specific End Uses

Use in laboratories.

# **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control Parameters** 

Component	Malaysia	ACGIH TLV	OSHA PEL
Methylisobutyl ketone		TWA: 20 ppm	(Vacated) TWA: 50 ppm
		STEL: 75 ppm	(Vacated) TWA: 205 mg/m <sup>3</sup>
			(Vacated) STEL: 75 ppm
			(Vacated) STEL: 300 mg/m <sup>3</sup>
			TWA: 100 ppm
			TWA: 410 mg/m <sup>3</sup>

Component	European Union	The United Kingdom	Germany
Methylisobutyl ketone	TWA: 20 ppm (8h)	STEL: 100 ppm 15 min	TWA: 20 ppm (8 Stunden). AGW -
	TWA: 83 mg/m³ (8h)	STEL: 416 mg/m <sup>3</sup> 15 min	exposure factor 2
	STEL: 50 ppm (15min)	TWA: 50 ppm 8 hr	TWA: 83 mg/m³ (8 Stunden). AGW -
	STEL: 208 mg/m³ (15min)	TWA: 208 mg/m <sup>3</sup> 8 hr	exposure factor 2
		Skin	TWA: 20 ppm (8 Stunden). MAK
			TWA: 83 mg/m³ (8 Stunden). MAK
			Höhepunkt: 40 ppm
			Höhepunkt: 166 mg/m <sup>3</sup>
			Haut

## **Exposure Controls**

## **Engineering Measures**

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

**Eye Protection** Goggles

Hand Protection Protective gloves
Skin and body protection Long sleeved clothing

Inspect gloves before use.

\_\_\_\_\_

4-Methyl-2-pentanone Revision Date 26-Mar-2025

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used

@ 760 mmHg

and maintained properly

When RPE is used a face piece Fit Test should be conducted

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls No information available

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Appearance Colorless
Physical State Liquid

Odor Characteristic sweet
Odor Threshold 0.04 - 0.08 ppm

**pH** No information available

Melting Point/Range -84 °C / -119.2 °F Softening Point No data available Boiling Point/Range 117.4 °C / 243.3 °F

Flash Point 14 °C / 57.2 °F Method - CC (closed cup)

**Evaporation Rate** 1.6 (Butyl Acetate = 1.0)

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 1.4 vol% Upper 7.5 vol%

**Opper** 7:5 **V**6176

Vapor Pressure 21.5 mbar @ 20 °C

**Vapor Density** 3.45 (Air = 1.0) (Air = 1.0)

Specific Gravity / Density 0.800

Bulk Density Not applicable Liquid

Water Solubility 17 g/l (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethylisobutyl ketone1.9

Autoignition Temperature 460 °C / 860 °F DIN 51794

**Decomposition Temperature** No data available

Viscosity No data available

Explosive Properties Vapors may form explosive mixtures with air

Oxidizing Properties No information available

4-Methyl-2-pentanone Revision Date 26-Mar-2025

Molecular FormulaC6 H12 OMolecular Weight100.16

# **SECTION 10: STABILITY AND REACTIVITY**

Reactivity

None known, based on information available.

**Chemical Stability** 

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.

None under normal processing.

**Conditions to Avoid** 

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot

surfaces and sources of ignition.

Incompatible Materials

Strong oxidizing agents. Peroxides.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO2).

# **SECTION 11: TOXICOLOGICAL INFORMATION**

### Information on Toxicological Effects

### **Product Information**

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met

Dermal Based on available data, the classification criteria are not met

Catagony 4

Inhalation Category 4

	Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ī	Methylisobutyl ketone	LD50 = 2080 mg/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 2000 - 4000 ppm (Rat) 4 h
Į				

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)		
Methylisobutyl ketone	=	=	ATE = 11 mg/L (vapour)		

ECHA (RAC) - Committee for Risk Assessment - European CHemicals Agency

ATE - Acute Toxiciy Estimate

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

Revision Date 26-Mar-2025 4-Methyl-2-pentanone

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Based on available data, the classification criteria are not met Respiratory Skin Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met (e) germ cell mutagenicity;

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

L	Component	EU	UK	Germany	IARC
Ι	Methylisobutyl ketone				Group 2B

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Component	ponent Test method Test species / Duration		
Methylisobutyl ketone	OECD Test Guideline 414	Rat	NOAEL =
108-10-1 ( >95 )			4.1 mg/l
			_
		Inhalation	

(h) STOT-single exposure; Category 3

Results / Target organs Nasal Cavities, Respiratory system, Eyes, Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

**Target Organs** None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

# **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity effects** Do not empty into drains. .

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methylisobutyl ketone	LC50: 496 - 514 mg/L,	EC50: 4280.0 mg/L/24h	EC50: 400 mg/L/96h	EC50 = 79.6 mg/L 5 min
	96h flow-through	EC50: 170 mg/L/48h		_
	(Pimephales promelas)	EC50: 4280.0 mg/L/24h		

Readily biodegradable Persistence and degradability **Persistence** Persistence is unlikely.

Component		Degradability
Methylisobutyl ketone		83 % (28 d) (OECD 301F)
108-10-1 (>95)		

#### 4-Methyl-2-pentanone

ntanone Revision Date 26-Mar-2025

Bioaccumulative potential	Bioaccumulation is unlikely	
Component	log Pow	Bioconcentration factor (BCF)
Methylisobutyl ketone	1.9	No data available

Mobility in soil The product is water soluble, and may spread in water systems. . Will likely be mobile in

the environment due to its water solubility. Highly mobile in soils.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Waste codes should be assigned by the user based on the application for which the product

was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with

local regulations

## SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1245
Hazard Class 3
Packing Group II

Proper Shipping Name METHYL ISOBUTYL KETONE

Road and Rail Transport

UN-No UN1245 Hazard Class 3 Packing Group II

Proper Shipping Name METHYL ISOBUTYL KETONE

<u>IATA</u>

UN-No UN1245
Hazard Class 3
Packing Group II

Proper Shipping Name METHYL ISOBUTYL KETONE

Special Precautions for User No special precautions required

# **SECTION 15: REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

Revision Date 26-Mar-2025 4-Methyl-2-pentanone

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Methylisobutyl ketone	203-550-1	X	X	X	Х	X	X	X	KE-24725

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methylisobutyl ketone				Annex I - Y42

## National Regulations

**Persistent Organic Pollutant Ozone Depletion Potential** 

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

# **SECTION 16: OTHER INFORMATION**

#### Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List **ENCS** - Japanese Existing and New Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

TWA - Time Weighted Average

WEL - Workplace Exposure Limit **ACGIH** - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer

RPE - Respiratory Protective Equipment

LD50 - Lethal Dose 50%

LC50 - Lethal Concentration 50% POW - Partition coefficient Octanol:Water EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**Prepared By** Health, Safety and Environmental Department

**Revision Date** 26-Mar-2025

**Revision Summary** SDS sections updated.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Revision Date 26-Mar-2025

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**