

SAFETY DATA SHEET

Creation Date 14-May-2009 Revision Date 25-March-2024 Revision Number 2

1. Identification

Product Name Ethylenediamine, 99%

Cat No. : \$55547

CAS-No 107-15-3

Synonyms 1,2-Diaminoethane

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific 112 Colonnade Road, Ottawa, ON K2E 7L6,

Canada

Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids Category 3 Acute oral toxicity Category 4 Acute dermal toxicity Category 3 Acute Inhalation Toxicity Category 4 Skin Corrosion/Irritation Category 1 B Serious Eye Damage/Eye Irritation Category 1 Respiratory Sensitization Category 1 Skin Sensitization Category 1 Specific target organ toxicity (single exposure) Category 3

Target Organs - Respiratory system.

Label Elements

Signal Word

Danger

Hazard Statements

Flammable liquid and vapor

Toxic in contact with skin

Causes severe skin burns and eye damage

Harmful if swallowed or if inhaled

May cause an allergic skin reaction

May cause allergy or asthma symptoms or breathing difficulties if inhaled

May cause respiratory irritation



Precautionary Statements

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Use only outdoors or in a well-ventilated area

Contaminated work clothing should not be allowed out of the workplace

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Wear respiratory protection

Use non-sparking tools

Take action to prevent static discharges

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Rinse mouth

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Immediately call a POISON CENTER/doctor

Do NOT induce vomiting

Wash contaminated clothing before reuse

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Harmful to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Ethylenediamine	107-15-3	>95

4. First-aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh

air. Immediate medical attention is required.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms/effects Causes burns by all exposure routes. May cause allergy or asthma symptoms or breathing

difficulties if inhaled. May cause allergic skin reaction. Difficulty in breathing. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may

be headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water mist may be used to cool closed containers. CO 2, dry chemical, dry sand,

alcohol-resistant foam.

Unsuitable Extinguishing Media No information available

Flash Point 38 °C / 100.4 °F

Method - No information available

Autoignition Temperature 385 °C / 725 °F

Explosion Limits

Upper 16.6 vol % **Lower** 2.7 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrogen oxides (NOx). Thermal decomposition can lead to release of irritating gases and vapors.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health **Flammability** Instability Physical hazards N/A

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage. Do not flush into surface

water or sanitary sewer system.

Up

Methods for Containment and Clean Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Storage.

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
Ethylenediamine	TWA: 10 ppm TWA: 25 mg/m³ Skin	TWA: 10 ppm Skin	TWA: 10 ppm Skin	TWA: 10 ppm TWA: 25 mg/m³ Skin	Skin	` 10 ppm	IDLH: 1000 ppm TWA: 10 ppm TWA: 25 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof

electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control

hazardous materials at source

Personal protective equipment

Eye Protection Hand Protection Goggles

Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber	> 480 minutes	0.38 mm	

Neoprene > 480 minutes 0.45 mm As tested under EN374-3
Natural rubber Determination of Resistance to
PVC Permeation by Chemicals

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** conforming to EN14387 Organic gases and vapours filter Type A Brown

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid
Appearance Colorless
Odor Ammonia-like

Odor Threshold
pHNo information available
12.211% aq.sol

Melting Point/Range 11 °C / 51.8 °F

Boiling Point/Range117 - 118 °C / 242.6 - 244.4 °F @ 760 mmHg **Flash Point**38 °C / 100.4 °F

Flash Point 38 °C / 100.4 °F Evaporation Rate 0.91

Flammability (solid,gas)

Not applicable

Flammability or explosive limits
Upper 16.6 vol %

Lower 16.6 Vol %
2.7 Vol %

Vapor Pressure13.3 mbar @ 20 °CVapor Density2.1

Specific Gravity

Solubility

0.898
Solubility

SolubilitySoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature385 °C / 725 °F

Decomposition Temperature > 120°C

Viscosity 1.6 mPa.s @ 20 °C

Molecular FormulaC2 H8 N2Molecular Weight60.1

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions. Air sensitive.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition. Exposure to air.

Incompatible Materials Strong oxidizing agents

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO₂), Nitrogen oxides (NOx), Thermal

decomposition can lead to release of irritating gases and vapors

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

LD50 Oral VALUE 866 mg/kg **LC50 Inhalation (DUST) VALUE** >20 mg/L/4h

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylenediamine	637 mg/kg (Rat)	560 mg/kg (Rabbit)	14.7 mg/L/4h (Rat)
	866 mg/kg (Rat)		

Toxicologically Synergistic

Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes burns by all exposure routes

Sensitization May cause sensitization by skin contact

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethylenediamine	107-15-3	Not listed				

Mutagenic Effects Mutagenic effects have occured in microorganisms.

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling

delayed

of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing:

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms

of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants. Contains a substance which is:. Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component Freshwater Algae Freshwater Fish Microtox Water Flea
--

Ethylenediamine	151 mg/L EC50 = 96 h 645	180 - 560 mg/L LC50 96 h	EC50 = 20 mg/L 15 min	17 mg/L EC50 = 48 h
	mg/L EC50 = 72 h	115.7 mg/L LC50 96 h 191 -	EC50 = 29 mg/L 17 h	
		254 mg/L LC50 96 h 98.6 -	_	
		131.6 mg/L LC50 96 h		

Persistence and Degradability

Persistence is unlikely

Bioaccumulation/ Accumulation

No information available.

Mobility

. Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Ethylenediamine	-1.221

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1604

Proper Shipping Name ETHYLENEDIAMINE

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

TDG

UN-No UN1604

Proper Shipping Name ETHYLENEDIAMINE

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

<u>IATA</u>

UN-No UN1604

Proper Shipping Name Ethylenediamine

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

IMDG/IMO

UN-No UN1604

Proper Shipping Name Ethylenediamine

Hazard Class 8
Subsidiary Hazard Class 3
Packing Group ||

15. Regulatory information

International Inventories

	Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Ī	Ethylenediamine	107-15-3	X	-	X	ACTIVE	203-468-6	430-750-8	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Ethylenediamine	107-15-3	X	X	X	X	X	X	X	X

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Ethylenediamine	Part 4 Substance		

Legend

NPRI - National Pollutant Release Inventory

Other International Regulations

Authorisation/Restrictions according to EU REACH

Γ	Component	REACH (1907/2006) - Annex XIV -	REACH (1907/2006) - Annex XVII -	REACH Regulation (EC
		Substances Subject to	Restrictions on Certain Dangerous	1907/2006) article 59 - Candidate
		Authorization	Substances	List of Substances of Very High
				Concern (SVHC)
Г	Ethylenediamine	=	Use restricted. See item 75.	SVHC Candidate list - 203-468-6 -
	-		(see link for restriction details)	Respiratory sensitising properties
L				(Article 57(f) - human health)

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

REACH links

https://echa.europa.eu/authorisation-list

https://echa.europa.eu/substances-restricted-under-reach

https://echa.europa.eu/candidate-list-table

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethylenediamine	107-15-3	Listed	Not applicable	Not applicable	Not applicable
Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethylenediamine	107-15-3	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Product Safety Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

Creation Date14-May-2009Revision Date25-March-2024Print Date25-March-2024

Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS