Thermo Fisher SCIENTIFIC

SAFETY DATA SHEET

Page 1/9 Revision Date 10-Sep-2024 Version 4

ALFAA40680

Beryllium wire

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: 铍线, 0.25mm (0.01in) 直径, 退火

Product Description: Beryllium wire

 Cat No. :
 40680

 CAS No
 7440-41-7

 Molecular Formula
 Be

Supplier Avocado Research Chemicals Ltd.

(Part of Thermo Fisher Scientific)

Shore Road, Heysham Lancashire, LA3 2XY, United Kingdom

Office Tel: +44 (0) 1524 850506 Office Fax: +44 (0) 1524 850608

Emergency Telephone Number For information US call: 001-800-227-6701 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals.
Uses advised against No Information available

SECTION 2. HAZARD IDENTIFICATION

Physical StateAppearanceOdorSolidDark greyOdorless

Emergency Overview

Flammable solid. Toxic if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. Fatal if inhaled. May cause cancer by inhalation.

Classification of the substance or mixture

| Flammable solids. | Category 2 |
|--|-------------|
| Acute Oral Toxicity | Category 3 |
| Acute Inhalation Toxicity - Dusts and Mists | Category 2 |
| Skin Corrosion/Irritation | Category 2 |
| Serious Eye Damage/Eye Irritation | Category 2 |
| Skin Sensitization | Category 1 |
| Carcinogenicity | Category 1A |
| Specific target organ toxicity - (single exposure) | Category 3 |
| Specific target organ toxicity - (repeated exposure) | Category 1 |

Label Elements

Beryllium wire

Page 2/9 Revision Date 10-Sep-2024



Signal Word

Danger

Hazard Statements

- H228 Flammable solid
- H301 Toxic if swallowed
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- H372 Causes damage to organs through prolonged or repeated exposure
- H330 Fatal if inhaled
- H350i May cause cancer by inhalation

Precautionary Statements

Prevention

- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P271 Use only outdoors or in a well-ventilated area
- P272 Contaminated work clothing should not be allowed out of the workplace
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P284 Wear respiratory protection

Response

- P302 + P352 IF ON SKIN: Wash with plenty of soap and water
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 Immediately call a POISON CENTER or doctor
- P330 Rinse mouth
- P362 + P364 Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Physical and Chemical Hazards

Combustible material.

Health Hazards

Toxic if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. Fatal if inhaled. May cause cancer by inhalation.

Environmental hazards

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Is not likely mobile in the environment due its low water solubility. Spillage unlikely to penetrate soil.

This product does not contain any known or suspected endocrine disruptors.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | CAS No | Weight % |
|-----------|-----------|----------|
| Beryllium | 7440-41-7 | > 99 |

Beryllium wire

Deryman wife

Page 3/9

Revision Date 10-Sep-2024

SECTION 4. FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.

Ingestion

Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms and effects

None reasonably foreseeable. May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Notes to Physician

Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical.

Extinguishing media which must not be used for safety reasons

Carbon dioxide (CO₂).

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

Environmental Precautions

Should not be released into the environment. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

Beryllium wire

Page 4/9 Revision Date 10-Sep-2024

bei yili uli

Methods for Containment and Clean Up

Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Avoid dust formation. Use only under a chemical fume hood. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance.

Storage

Keep in a dry, cool and well-ventilated place. Keep container tightly closed.

Specific Use(s)

Use in laboratories

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

| Component | China | Taiwan | Thailand | Hong Kong |
|-----------|-------------------------------|------------------------------|----------------------------------|------------------------------|
| Beryllium | TWA: 0.0005 mg/m ³ | TWA: 0.002 mg/m ³ | Ceiling: 0.005 mg/m ³ | TWA: 0.002 mg/m ³ |
| | STEL: 0.001 mg/m ³ | _ | STEL: 0.025 mg/m ³ | STEL: 0.01 mg/m ³ |
| | Skin | | TWA: 0.002 mg/m ³ | _ |

| Component | ACGIH TLV | OSHA PEL | NIOSH | The United Kingdom | European Union |
|-----------|--------------------------------|------------------------------|-----------------------------------|----------------------------------|-------------------------------|
| Beryllium | TWA: 0.00005 mg/m ³ | (Vacated) TWA: 2 | IDLH: 4 mg/m ³ | STEL: 0.006 mg/m ³ 15 | TWA: 0.0002 mg/m ³ |
| | | μg/m³ | Ceiling: 0.0005 mg/m ³ | min | (8h) |
| | | Ceiling: 2 µg/m ³ | | TWA: 0.002 mg/m ³ 8 | TWA: 0.0006 mg/m ³ |
| | | (Vacated) STEL: 25 | | hr | (8h) |
| | | μg/m³ | | Carc. | Skin |
| | | (Vacated) Ceiling: 5 | | | |
| | | μg/m³ | | | |
| | | TWA: 0.2 μg/m ³ | | | |
| | | STEL: 2 µg/m ³ | | | |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Beryllium wire

Page 5/9 Revision Date 10-Sep-2024

 Glove material
 Breakthrough time
 Glove thickness
 EU standard
 Glove comments

 Nitrile rubber
 See manufacturers recommendations
 EN 374
 (minimum requirement)

 Neoprene PVC
 Natural rubber

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Solid

Recommended half mask:- Particle filtering: EN149:2001 When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceDark greyPhysical StateSolid

Odor Odorless

Odor Threshold No data available PH No information available

Melting Point/Range 1278 °C / 2332.4 °F
Softening Point
Boiling Point/Range 2970 °C / 5378 °F

Boiling Point/Range2970 °C / 5378 °F **Q** 5 mmHg **No information available Method - No information available**

Evaporation Rate Not applicable Solid

Flammability (solid,gas) No information available

Explosion Limits No data available

Vapor Pressure 1.85 mmHg
Vapor Density Not applicable

Specific Gravity / Density

Bulk Density

Bulk Density

1.85 @ 20°C

Water Solubility

Insoluble

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Autoignition Temperature

Decomposition Temperature

Viscosity

Not applicable

Not applicable

Viscosity Not applicable Solid

Explosive PropertiesOxidizing Properties
No information available
No information available

Page 6/9 Revision Date 10-Sep-2024

Beryllium wire

Molecular FormulaBeMolecular Weight9.01

SECTION 10. STABILITY AND REACTIVITY

Stability Stable.

Hazardous ReactionsNone under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid Incompatible products.

Materials to avoid Acids. Bases. Halogens. Metals.

Hazardous Decomposition Products Beryllium oxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Product Information

(a) acute toxicity;

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory No data available Skin Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

| Component | EU | UK | Germany | IARC |
|-----------|--------------|----|---------|---------|
| Bervllium | Carc Cat. 1B | | Cat. 1 | Group 1 |

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system

(i) STOT-repeated exposure; Category 1

Route of exposure Inhalation Target Organs Lungs.

(j) aspiration hazard; Not applicable

Solid

Page 7/9 Revision Date 10-Sep-2024

Beryllium wire

delaved

Symptoms / effects, both acute and Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects May cause long-term adverse effects in the environment. Do not allow material to

contaminate ground water system.

Persistence and Degradability Product contains heavy metals. Discharge into the environment must be avoided. Special

pre-treatment is necessary Insoluble in water, May persist.

Persistence Degradability

Degradation in sewage

treatment plant

Not relevant for inorganic substances.

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

Bioaccumulative Potential May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

Mobility in soil Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water

solubility

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from Residues/Unused

Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not empty into drains.

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport

IMDG/IMO Not regulated

IATA Not regulated

No special precautions required **Special Precautions for User**

SECTION 15. REGULATORY INFORMATION

International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan

Page 8/9 Revision Date 10-Sep-2024

Beryllium wire

(ISHL), Australia (AICS), Korea (KECL).

| Component | The | List of | TCSI | IECSC | EINECS | TSCA | DSL | PICCS | ENCS | ISHL | AICS | KECL |
|-----------|---|---------|------|-------|-----------|------|-----|-------|-------------|------|------|----------|
| | Inventory of Hazardous Chemicals (2015 Edition) | • | | | | | | | | | | |
| Beryllium | Х | Х | Х | Х | 231-150-7 | Х | Х | Х | Х | | Χ | KE-02829 |

National Regulations

| Component | Toxic Chemical Substances Control Act |
|--------------------|---------------------------------------|
| Beryllium | Class II (95 wt%) |
| 7440-41-7 (> 99) | TRQ = 50 kg |

SECTION 16. OTHER INFORMATION

Prepared By Health, Safety and Environmental Department

Revision Date 10-Sep-2024

Revision Summary New emergency telephone response service provider.

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Legend

Inventory

Substances List

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic

ICAO/IATA - International Civil Aviation Organization/International Air **Transport Association**

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

TSCA - United States Toxic Substances Control Act Section 8(b)

ENCS - Japanese Existing and New Chemical Substances

PNEC - Predicted No Effect Concentration

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ALFAA40680

SAFETY DATA SHEET

Page 9/9 Revision Date 10-Sep-2024

Beryllium wire

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet