

Part of Thermo Fisher Scientific

SAFETY DATA SHEET

Creation Date 02-Feb-2012 Revision Date 26-Jan-2015 Revision Number 1

1. Identification

Product Name Flex 100

Cat No. : 22-046-344; 22-046-345; 22-900-650; 81-15

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Details of the supplier of the safety data sheet

CompanyEmergency Telephone NumberRichard Allan ScientificChemtrec US: (800) 424-9300

A Subsidiary of Thermo Fisher Scientific Chemtrec EU: 001 (202) 483-7616

4481 Campus Drive Kalamazoo, MI 49008 Tel: (800) 522-7270

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Acute oral toxicity	Category 3
Acute dermal toxicity	Category 3
Acute Inhalation Toxicity - Dusts and Mists	Category 3
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Central nervous system (CNS), Optic nerv	e.
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Kidney, Liver, spleen.	•

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor

Toxic if swallowed

Toxic in contact with skin

Causes serious eye irritation

Toxic if inhaled

May cause drowsiness or dizziness

Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

IF exposed: Call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Rinse mouth

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

3. Composition / information on ingredients

Component	CAS-No	Weight %		
Isopropyl alcohol	67-63-0	57 - 63		
Methyl alcohol	67-56-1	37 - 43		

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth

resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a

respiratory medical device. Immediate medical attention is required.

Ingestion Do not induce vomiting. Call a physician or Poison Control Center immediately.

Most important symptoms/effects Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO 2, dry chemical, dry sand, alcohol-resistant foam. Cool closed containers exposed to fire

with water spray.

Unsuitable Extinguishing Media Water may be ineffective

Autoignition Temperature

Explosion Limits

No information available

Upper 36.0 vol % **Lower** 2.0 vol %

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Environmental Precautions

Carbon monoxide (CO) Carbon dioxide (CO2) Formaldehyde peroxides

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
3	3	0	N/A

6. Accidental release measures

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Take precautionary

measures against static discharges. Do not get in eyes, on skin, or on clothing. Should not be released into the environment. See Section 12 for additional ecological

information.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary **Up** measures against static discharges. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling Use only under a chemical fume hood. Wear personal protective equipment. Keep away

from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Do not ingest.

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH		
Isopropyl alcohol	TWA: 200 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm		
	STEL: 400 ppm	(Vacated) TWA: 980 mg/m ³	TWA: 400 ppm		
		(Vacated) STEL: 500 ppm	TWA: 980 mg/m ³		
		(Vacated) STEL: 1225 mg/m ³	STEL: 500 ppm		
		TWA: 400 ppm STEL: 1225 mg/m ³			
		TWA: 980 mg/m ³			
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm		
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m ³	TWA: 200 ppm		
	Skin		TWA: 260 mg/m ³		
		(Vacated) STEL: 325 mg/m ³	STEL: 250 ppm		
		Skin	STEL: 325 mg/m ³		
		TWA: 200 ppm	-		
		TWA: 260 mg/m ³			

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Isopropyl alcohol	TWA: 400 ppm	TWA: 400 ppm	TWA: 200 ppm
	TWA: 985 mg/m ³	TWA: 980 mg/m ³	STEL: 400 ppm
	STEL: 500 ppm		
	STEL: 1230 mg/m ³		
Methyl alcohol	Methyl alcohol TWA: 200 ppm		TWA: 200 ppm
	TWA: 262 mg/m ³		STEL: 250 ppm
	STEL: 250 ppm		Skin
	STEL: 328 mg/m ³		
	Skin		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid

Revision Date 26-Jan-2015 **Flex 100**

Appearance Clear Colorless Alcohol-like Odor

Odor Threshold No information available

5.0 - 7.3

Melting Point/Range No data available

Boiling Point/Range 71.7 - 81 °C / 161.1 - 178 °F

Flash Point 16.6 °C / 61.9 °F **Evaporation Rate** 3.3 (Butyl Acetate = 1.0) Flammability (solid,gas) No information available

Flammability or explosive limits

Upper 36.0 vol % 2.0 vol % Lower **Vapor Pressure** 55 mmHa **Vapor Density** (Air = 1.0) 1.50.79

Relative Density

Solubility Soluble in water Partition coefficient; n-octanol/water No data available **Autoignition Temperature** No information available **Decomposition Temperature** No information available **Viscosity** No information available

10. Stability and reactivity

None known, based on information available **Reactive Hazard**

Stable under normal conditions. Stability

Conditions to Avoid Incompatible products. Heat, flames and sparks.

Strong oxidizing agents, Peroxides, Acids, Acid anhydrides, Acid chlorides, Metals **Incompatible Materials**

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Formaldehyde, peroxides

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Category 3. ATE = 50 - 300 mg/kg. Oral LD50 **Dermal LD50** Category 3. ATE = 200 - 1000 mg/kg.

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Vapor LC50

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation 72.6 mg/L (Rat) 4 h		
Isopropyl alcohol	5840 mg/kg (Rat)	13900 mg/kg (Rat) 12870 mg/kg (Rabbit)			
Methyl alcohol	ohol 6200 mg/kg (Rat) 15800 mg/kg (Rabbit)		64000 ppm (Rat) 4 h 83.2 mg/L (Rat) 4 h		

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes and skin Sensitization No information available

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

Comp	onent	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico

| Isopropyl alcohol | 67-63-0 | Not listed |
|-------------------|---------|------------|------------|------------|------------|------------|
| Methyl alcohol | 67-56-1 | Not listed |

IARC: (International Agency for Research on Cancer)

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Mutagenic Effects No information available

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental effects have occurred in experimental animals. Component substance is **Developmental Effects**

listed on California Proposition 65 as a developmental hazard.

Teratogenicity Teratogenic effects have occurred in experimental animals.

STOT - single exposure Central nervous system (CNS) Optic nerve

STOT - repeated exposure Kidney Liver spleen

No information available **Aspiration hazard**

delayed

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isopropyl alcohol	1000 mg/L EC50 > 96 h 1000 mg/L EC50 > 72 h	1400000 µg/L LC50 96 h 11130 mg/L LC50 96 h 9640 mg/L LC50 96 h	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h

Persistence and Degradability Bioaccumulation/ Accumulation No information available No information available.

Mobility

Component	log Pow
Isopropyl alcohol	0.05
Methyl alcohol	-0.74

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component		RCRA - U Series Wastes	RCRA - P Series Wastes		
	Methyl alcohol - 67-56-1	U154	-		

14. Transport information

DOT

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S.

(ISOPROPANOL, METHANOL) Proper technical name

Hazard Class 3
Packing Group ||

TDG

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S.

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group ||

IATA

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S.

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

IMDG/IMO

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S.

Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group ||

15. Regulatory information

International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Isopropyl alcohol	Х	Х	-	200-661-7	-		Χ	Χ	Χ	Х	Х
Methyl alcohol	Х	Х	-	200-659-6	-		Х	Х	Х	Х	Х

Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	57 - 63	1.0
Methyl alcohol	67-56-1	37 - 43	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

Clean Water Act Not applicable

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs	
Methyl alcohol	5000 lb	-	

California Proposition 65

This product contains the following Proposition 65 chemicals:

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Methyl alcohol	67-56-1	Developmental	-	Developmental
04.4. B'-14.4.16.	,			

State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Isopropyl alcohol	X	X	X	-	X
Methyl alcohol	X	X	X	Х	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B2 Flammable liquid

D2A Very toxic materials D1A Very toxic materials



16. Other information

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

 Creation Date
 02-Feb-2012

 Revision Date
 26-Jan-2015

 Print Date
 26-Jan-2015

Revision Summary

This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of SDS