

Page 1 / 10 Creation Date 28-Oct-2010 Revision Date 22-Mar-2025 Version 5

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: <u>Lithium isopropoxide, solution in hexanes</u>
Product Description: <u>Lithium isopropoxide, solution in hexanes</u>

Cat No. : 380200000; 380201000

Molecular Formula C3 H7 Li O

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

| Flammable liquids | Category 2 (H225) |
|--|---------------------|
| Aspiration Toxicity | Category 1 (H304) |
| Skin Corrosion/Irritation | Category 1 A (H314) |
| Serious Eye Damage/Eye Irritation | Category 1 (H318) |
| Reproductive Toxicity | Category 2 (H361f) |
| Specific target organ toxicity - (single exposure) | Category 3 (H336) |
| Specific target organ toxicity - (repeated exposure) | Category 2 (H373) |
| Chronic aquatic toxicity | Category 2 (H411) |

Label Elements



Signal Word Danger

Revision Date 22-Mar-2025

Hazard Statements

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H336 - May cause drowsiness or dizziness

H361f - Suspected of damaging fertility

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P330 - Rinse mouth

P331 - Do NOT induce vomiting

P363 - Wash contaminated clothing before reuse

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

EUH014 - Reacts violently with water

This product does not contain any known or suspected endocrine disruptors

Toxic to terrestrial vertebrates

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Component | CAS No | Weight % |
|----------------------|-----------|----------|
| Hexane | 110-54-3 | 90 |
| Lithium iso-propoxid | 2388-10-5 | 10 |

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Lithium isopropoxide, solution in hexanes

Revision Date 22-Mar-2025

Eye Contact Rinse immediately with plenty of water, also under the evelids, for at least 15 minutes.

Immediate medical attention is required.

Wash off immediately with plenty of water for at least 15 minutes. Remove and wash **Skin Contact**

contaminated clothing and gloves, including the inside, before re-use. Call a physician

immediately.

Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an Ingestion

unconscious person. Call a physician immediately. Call a physician or poison control center

immediately. If vomiting occurs naturally, have victim lean forward.

Inhalation If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

> mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by

aspiration).

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting. Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Carbon dioxide (CO₂). Dry chemical. Chemical foam. Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Water.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Lithium isopropoxide, solution in hexanes

Personal Precautions. Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Protect from moisture. Corrosives area. Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from water or moist air.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

| Component | Malaysia | ACGIH TLV | OSHA PEL |
|-----------|----------|-------------|--------------------------------------|
| Hexane | | TWA: 50 ppm | (Vacated) TWA: 50 ppm |
| | | Skin | (Vacated) TWA: 180 mg/m ³ |
| | | | TWA: 500 ppm |
| | | | TWA: 1800 mg/m ³ |

| Component | European Union | The United Kingdom | Germany |
|-----------|--|---|-------------------------------|
| Hexane | TWA: 20 ppm (8hr) TWA: 72 mg/m³ (8hr) | TWA: 72 mg/m ³ TWA: 20 ppm STEL: 60 ppm STEL: 216 mg/m ³ | TWA: 180 mg/m³ TWA: 50 ppm |

Exposure Controls

Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to

Revision Date 22-Mar-2025

Lithium isopropoxide, solution in hexanes

control hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Protective gloves

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: Inorganic gases and vapours filter Type B Grey Ammonia and organic ammonia derivatives

filter Type K Green conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u> Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls Prevent product from entering drains Do not allow material to contaminate ground water

system

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance No information available

Physical State Liquid

Odor No information available
Odor Threshold No data available
pH No information available

Melting Point/RangeNo data availableSoftening PointNo data available

Boiling Point/Range 68 - 72 °C / 154.4 - 161.6 °F @ 760 mmHg

Flash Point -27 °C / -16.6 °F Method - No information available

Evaporation Rate No data available

Flammability (solid,gas)

Not applicable

Liquid

Explosion Limits

No data available

Vapor Pressure No data available

Vapor Density No data available (Air = 1.0)

Specific Gravity / Density 0.690

Bulk Density Not applicable Liquid

Water Solubility reacts

Solubility in other solvents No information available

ACR38020

Revision Date 22-Mar-2025

Lithium isopropoxide, solution in hexanes

Partition Coefficient (n-octanol/water)

Componentlog PowHexane4.11

Autoignition Temperature Decomposition Temperature Viscosity No data available No data available No data available

Explosive Properties

Oxidizing Properties No information available

Vapors may form explosive mixtures with air

Revision Date 22-Mar-2025

Molecular Formula C3 H7 Li O
Molecular Weight 66.03

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Yes.

Chemical Stability

Moisture sensitive.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

No information available.

None under normal processing. Reacts violently with water.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

Exposure to moist air or water. Exposure to moisture.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product InformationNo acute toxicity information is available for this product

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met Dermal Based on available data, the classification criteria are not met

Lithium isopropoxide, solution in hexanes

Revision Date 22-Mar-2025

Inhalation Based on available data, the classification criteria are not met

Toxicology data for the components

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation | | |
|-----------|----------------------|----------------------------|----------------------------|--|--|
| Hexane | LD50 = 25 g/kg (Rat) | LD50 = 3000 mg/kg (Rabbit) | LC50 = 48000 ppm (Rat) 4 h | | |
| | | | | | |

(b) skin corrosion/irritation; Category 1 A

Category 1 (c) serious eye damage/irritation;

(d) respiratory or skin sensitization;

No data available Respiratory Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Category 2

Category 3 (h) STOT-single exposure;

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Central nervous system (CNS), Peripheral Nervous System (PNS). **Target Organs**

(j) aspiration hazard; Category 1

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

delayed

tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment. The product contains following substances which are hazardous for the

environment.

| Component | Freshwater Fish | Water Flea | Freshwater Algae | Microtox |
|-----------|------------------------|---------------------|------------------|----------|
| Hexane | LC50: 2.1 - 2.98 mg/L, | EC50: 3.87 mg/L/48h | | |
| | 96h flow-through | | | |

Lithium isopropoxide, solution in hexanes

Revision Date 22-Mar-2025

| (Pimephales promelas) | | |
|-----------------------|--|--|
| | | |

Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Degradation in sewage

treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

Bioaccumulative potential Bioaccumulation is unlikely

| Component | log Pow | Bioconcentration factor (BCF) |
|-----------|---------|-------------------------------|
| Hexane | 4.11 | No data available |

The product contains volatile organic compounds (VOC) which will evaporate easily from all Mobility in soil

surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Do not flush to sewer Waste codes should be assigned by the user based on the

application for which the product was used Can be landfilled or incinerated, when in

compliance with local regulations Do not empty into drains Large amounts will affect pH and

harm aquatic organisms Do not let this chemical enter the environment

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN2924 **Hazard Class** 3 **Subsidiary Hazard Class** 8 Packing Group

Proper Shipping Name

Flammable liquid, corrosive, n.o.s.

Road and Rail Transport

UN-No UN2924 **Hazard Class Subsidiary Hazard Class Packing Group**

Proper Shipping Name

Flammable liquid, corrosive, n.o.s.

Lithium isopropoxide, solution in hexanes

IATA

UN-No UN2924 **Hazard Class Subsidiary Hazard Class** 8 **Packing Group**

Proper Shipping Name Flammable liquid, corrosive, n.o.s.

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

| | Component | EINECS | TSCA | DSL | PICCS | ENCS | ISHL | IECSC | AICS | KECL |
|---|-----------|-----------|------|-----|-------|------|------|-------|------|----------|
| ı | Hexane | 203-777-6 | X | X | Х | X | X | Χ | Χ | KE-18626 |

| Component | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements | Rotterdam Convention (PIC) | Basel Convention (Hazardous Waste) |
|-----------|--|---|----------------------------|---------------------------------------|
| Hexane | | | | Annex I - Y42 |

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Revision Date 22-Mar-2025

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

TWA - Time Weighted Average

ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer LD50 - Lethal Dose 50%

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% POW - Partition coefficient Octanol:Water

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of

Dangerous Goods by Road IMO/IMDG - International Maritime Organization/International Maritime ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from Ships

Page 9/10

OECD - Organisation for Economic Co-operation and Development

ATE - Acute Toxicity Estimate

BCF - Bioconcentration factor

VOC - (Volatile Organic Compound)

Lithium isopropoxide, solution in hexanes

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date 22-Mar-2025

Revision Summary SDS sections updated.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Revision Date 22-Mar-2025