

Page 1/10 Creation Date 11-Jun-2009 Revision Date 22-Mar-2025

Version 8

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THECOMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: <u>Toluena</u> Product Description: <u>Toluene</u>

 Cat No. :
 448400000; 448401000

 Synonyms
 Tol; Methylbenzene

CAS No 108-88-3 Molecular Formula C7 H8

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd

Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square, No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,

Selangor Darul Ehsan, Malaysia. Main line: +60 3-5525 7888

Supplier

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Aspiration Toxicity	Category 1 (H304)
Skin Corrosion/Irritation	Category 2 (H315)
Reproductive Toxicity	Category 2 (H361d)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)
Chronic aquatic toxicity	Category 3 (H412)

Label Elements



Toluene Revision Date 22-Mar-2025

Signal Word Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361d - Suspected of damaging the unborn child

H373 - May cause damage to organs through prolonged or repeated exposure if inhaled

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

Prevention

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection/ face protection

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P331 - Do NOT induce vomiting

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Toluene	108-88-3	<=100

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice If symptoms persist, call a physician.

Toluene Revision Date 22-Mar-2025

Eye ContactRinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists,

call a physician.

Ingestion Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call

a physician or poison control center immediately. If vomiting occurs naturally, have victim

lean forward.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur. Risk of serious damage to the lungs (by aspiration).

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes central nervous system depression. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Smallest quantities reaching the lungs through swallowing or

subsequent vomiting may result in lung edema or pneumonia. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream.

Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO2).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Toluene Revision Date 22-Mar-2025

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Toluene		TWA: 20 ppm	(Vacated) TWA: 100 ppm
			(Vacated) TWA: 375 mg/m ³
			Ceiling: 300 ppm
			(Vacated) STEL: 150 ppm
			(Vacated) STEL: 560 mg/m ³
			TWA: 200 ppm

Component	European Union	The United Kingdom	Germany
Toluene	TWA: 50 ppm (8hr)	STEL: 100 ppm 15 min	TWA: 50 ppm (8 Stunden). AGW -
	TWA: 192 mg/m ³ (8hr)	STEL: 384 mg/m ³ 15 min	exposure factor 2
	STEL: 100 ppm (15min)	TWA: 50 ppm 8 hr	TWA: 190 mg/m³ (8 Stunden). AGW
	STEL: 384 mg/m³ (15min)	TWA: 191 mg/m ³ 8 hr	- exposure factor 2
	Skin	Skin	TWA: 50 ppm (8 Stunden). MAK
			TWA: 190 mg/m³ (8 Stunden). MAK
			Höhepunkt: 100 ppm
			Höhepunkt: 380 mg/m ³
			Haut

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles)

ACR44840 Page 4 / 10

Toluene Revision Date 22-Mar-2025

Hand Protection Protective gloves
Skin and body protection Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used

@ 760 mmHg

and maintained properly

When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u> Handle in accordance with good industrial hygiene and safety practice

system

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Colorless
Physical State Liquid
Odor aromatic
Odor Threshold 1.74 ppm

pH No information available

Melting Point/Range -95 °C / -139 °F Softening Point No data available Boiling Point/Range 111 °C / 231.8 °F

Flash Point 4 °C / 39.2 °F Method - No information available

Evaporation Rate 2.4 (Butyl acetate = 1.0)

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 1.2 vol% Upper 7 vol%

Vapor Pressure 29 mbar @ 20 °C

Vapor Density 3.1 (Air = 1.0)

Specific Gravity / Density 0.866

Bulk Density Not applicable Liquid

Water Solubility practically insoluble 0.5 g/L @ 20°C

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Component log Pow Toluene 2.73

Toluene Revision Date 22-Mar-2025

Autoignition Temperature Decomposition Temperature

Decomposition Temp Viscosity Explosive Properties

Oxidizing Properties

Ire No data available 0.6 mPa.s @ 20 °C Not explosive Not oxidising

535 °C / 995 °F

Vapors may form explosive mixtures with air

Molecular Formula Molecular Weight C7 H8 92.14

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.

None under normal processing.

Conditions to Avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials

Strong oxidizing agents. Strong acids. Strong bases. Halogenated compounds.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

OralBased on available data, the classification criteria are not metDermalBased on available data, the classification criteria are not metInhalationBased on available data, the classification criteria are not met

Component	Component LD50 Oral LD50 Dermal		LC50 Inhalation		
Toluene			26700 ppm (Rat) 1 h		
l oluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26		

Toluene Revision Date 22-Mar-2025

(b) skin corrosion/irritation; Category 2
Test method OECD 404
Test species rabbit

Observational endpoint Irritating to skin

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

RespiratoryBased on available data, the classification criteria are not met

Skin Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Category 2

Reproductive Effects Experiments have shown reproductive toxicity effects on laboratory animals.

Developmental Effects Developmental effects have occurred in experimental animals.

Teratogenicity Possible risk of harm to the unborn child.

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Target Organs Liver, Kidney, Central nervous system (CNS), Blood, spleen, Neuropsychological effects,

Eyes, Ears.

(j) aspiration hazard; Category 1

Owner towns to the state to the second course

delayed

Symptoms / effects, both acute and Causes central nervous system depression. Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects The product contains following substances which are hazardous for the environment.

Contains a substance which is:. Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Toluene	50-70 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h	EC50: = 12.5 mg/L, 72h	EC50 = 19.7 mg/L 30
	5-7 mg/L LC50 96 h	(Daphnia magna)	static	min
	15-19 mg/L LC50 96 h	EC50: 5.46 - 9.83 mg/L,	(Pseudokirchneriella	
	28 mg/L LC50 96 h	48h Static (Daphnia	subcapitata)	
	12 mg/L LC50 96 h	magna)	EC50: > 433 mg/L, 96h	
			(Pseudokirchneriella	
			subcapitata)	

Toluene Revision Date 22-Mar-2025

Persistence and degradability
Persistence
Persistence
Readily biodegradable
Persistence is unlikely.

Comp	onent	Degradability	
Toluene		86% (20d)	
108-88-3	(<=100)		

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential Bioaccumulation is unlikely

<u> </u>	2.000000		
Component	log Pow	Bioconcentration factor (BCF)	
Toluene	2.73	90	

Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all

surfaces. Spillage unlikely to penetrate soil. The product is insoluble and floats on water. Is

not likely mobile in the environment due its low water solubility.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Do not flush to sewer Waste codes should be assigned by the user based on the

application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not let this chemical enter the environment Do not

empty into drains

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1294
Hazard Class 3
Packing Group II

Proper Shipping Name TOLUENE

Road and Rail Transport

UN-No UN1294 Hazard Class 3 Packing Group II

Proper Shipping Name TOLUENE

<u>IATA</u>

UN-No UN1294

Toluene Revision Date 22-Mar-2025

Hazard Class Ш **Packing Group**

TOLUENE Proper Shipping Name

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Toluene	203-625-9	Х	Х	Х	X	X	Χ	Χ	KE-33936

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Toluene		_		Annex I - Y42

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances **IECSC** - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic

Substances List **ENCS** - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% POW - Partition coefficient Octanol:Water TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from

Ships ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Toluene Revision Date 22-Mar-2025

Revision Date 22-Mar-2025 **Revision Summary** Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet