

Australian statement of hazardous nature: Classified as hazardous according to criteria of Safe Work Australia

## Section 1 - Identification

Product Name 0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

Product Code J/8750/08, J/8750/15, J/8750/17, J/8750/24

Address ThermoFisher Scientific Australia Pty Ltd

5 Caribbean Drive, Scoresby VICTORIA 3179, Australia

Emergency Tel. CHEMTREC®

03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292

Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against

Verify requirements related to using, handling and storing these substances. This product

contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. This product does not contain any substance(s) subject to Prohibition, Authorization or

Restriction. This product does not contain any substance(s) listed on the voluntary National

Code of Practice for Chemicals of Security Concern.

# Section 2 - Hazard(s) Identification

#### Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids Category 2

**Health hazards** 

Aspiration Toxicity

Acute Oral Toxicity

Acute Dermal Toxicity

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Category 1

Reproductive Toxicity

Category 2

Category 1

Category 2

Reproductive Toxicity Category 2
Specific target organ toxicity - (single exposure) Category 3 Category 1

Specific target organ toxicity - (repeated exposure)

Category 2

**Environmental hazards** 

Chronic aquatic toxicity Category 3

Label Elements

FSUJ8750 Version 2 18-Nov-2022 Page 1/12









Flame

**Exclamation Mark** 

Health Hazard

### Signal Word

### **Danger**

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H361 - Suspected of damaging fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled

#### **Precautionary Statements**

P201 - Obtain special instructions before use

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P202 - Do not handle until all safety precautions have been read and understood

P240 - Ground and bond container and receiving equipment

P243 - Take action to prevent static discharges

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P242 - Use non-sparking tools

P271 - Use only outdoors or in a well-ventilated area

P270 - Do not eat, drink or smoke when using this product

P280 - Wear protective gloves/protective clothing/eve protection/face protection

P310 - Immediately call a POISON CENTER or doctor

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P330 - Rinse mouth

P331 - Do NOT induce vomiting

P363 - Wash contaminated clothing before reuse

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/ container to an approved waste disposal plant

#### Other information

Toxic to terrestrial vertebrates

# Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Methyl alcohol	67-56-1	17
Toluene	108-88-3	80

FSUJ8750 Version 2 18-Nov-2022 Page 2/12

1-Butanaminium, N,N,N-tributyl-, hydroxide	2052-49-5	3

# **Section 4 - First Aid Measures**

**Inhalation** Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. Risk of serious damage to the lungs (by

aspiration).

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting

occurs naturally, have victim lean forward.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In

the case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

**General Advice** Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination.

First Aid Facilities Eyewash, safety shower and washroom.

Most important symptoms and

effects

None reasonably foreseeable. Causes severe eye damage. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

# Section 5 - Fire Fighting Measures

### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

### Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

### **Hazardous Decomposition Products**

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition. Vapors may form explosive mixtures with air.

### Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

# Section 6 - Accidental Release Measures

### **Emergency procedures**

Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak.

FSUJ8750 Version 2 18-Nov-2022 Page 3/12

Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

#### **Environmental Precautions**

Do not flush into surface water or sanitary sewer system.

### Methods for Containment and Clean Up

#### Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

#### Clean-up methods - large spillage

Typically only supplied is small quantiites as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

#### **Reference to Other Sections**

Refer to protective measures listed in Sections 8 and 13.

# Section 7 - Handling and Storage

#### **Precautions for Safe Handling**

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals AS 1940-2004 - The storage and handling of flammable and combustible liquids

# Section 8 - Exposure Controls and Personal Protection

#### **Exposure limits**

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)] Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Methyl alcohol	STEL: 250 ppm STEL: 328 mg/m³ TWA: 200 ppm TWA: 262 mg/m³	TWA: 200 ppm TWA: 262 mg/m³ STEL: 250 ppm STEL: 328 mg/m³ Skin	TWA: 200 ppm STEL: 250 ppm Skin	WEL - TWA: 200 ppm TWA; 266 mg/m³ TWA WEL - STEL: 250 ppm STEL; 333 mg/m³ STEL	100 ppm TWA MAK; 130 mg/m³ TWA MAKSkin absorber
Toluene	STEL: 150 ppm STEL: 574 mg/m³ TWA: 50 ppm TWA: 191 mg/m³	TWA: 20 ppm TWA: 75 mg/m³ STEL: 100 ppm STEL: 377 mg/m³ Skin	TWA: 20 ppm	STEL: 100 ppm 15 min STEL: 384 mg/m³ 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m³ 8 hr Skin	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 190 mg/m³ (8 Stunden). AGW - exposure factor 2 TWA: 50 ppm (8 Stunden). MAK TWA: 190 mg/m³ (8 Stunden). MAK

FSUJ8750 Version 2 18-Nov-2022 Page 4/12

# 0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

## SAFETY DATA SHEET

	Höhepunkt: 100 ppm Höhepunkt: 380 mg/m³ Haut
--	--

### **Biological limit values**

**NZ** - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand	European Union	United Kingdom	Germany
Methyl alcohol		15 mg/L (urine) end of shift (Methyl alcohol)	·	-	Methanol: 15 mg/L urine
Toluene		0.03 mg/L (urine) end of exposure or end of shift (Toluene) 0.3 mg/g creatinine (urine) end of exposure or end of shift (O-Cresol)			Toluene: 600 µg/L whole blood (immediately after exposure) Toluene: 75 µg/L urine (end of shift) o-Cresol (after hydrolysis): 1.5 mg/L urine (for long-term exposures: at the end of the shift after several shifts) o-Cresol (after hydrolysis): 1.5 mg/L urine (end of shift)

# **Exposure Controls Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

Eye Protection Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial

applications)

Hand Protection Protective gloves

Γ	Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
1	Viton (R)	See manufacturers	-	AS/NZS 2161	(minimum requirement)
		recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

**Repiratory Protection** Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or

other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use

and maintenance of repiratory protective devices

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and

vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

FSUJ8750 Version 2 18-Nov-2022 Page 5/12

Vapors may form explosive mixtures with air

Recommended half mask:- Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water

vstem

# Section 9 - Physical and Chemical Properties

#### Information on basic physical and chemical properties

Appearance Colorless Physical State Liquid

**Odor** aromatic

Odor Threshold
PH
Not applicable
Melting Point/Range
Softening Point
Boiling Point/Range
No data available
No data available
No information available

Flash Point 4 °C / 39.2 °F Method - No information available

Evaporation Rate

No data available

Flammability (solid,gas) Not applicable Liquid

Explosion Limits Lower 1.2 vol% Upper 44 vol%

Vapor Pressure 128 hPa @ 20°C1

Vapor Density No information available (Air = 1.0)

Specific Gravity / Density 0.850

Bulk Density Not applicable Liquid

Water Solubility Immiscible

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowMethyl alcohol-0.74Toluene2.731-Butanaminium, N.N.N-tributyl-,1.518

hydroxide

Autoignition Temperature

Autoignition Temperature

Decomposition Temperature

Viscosity

455 °C / 851 °F

No data available

No data available

Explosive Properties

Oxidizing Properties No information available

Other information

# Section 10 - Stability and Reactivity

Reactivity None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition, Incompatible products.

Incompatible Materials Acids, Acid anhydrides, Acid chlorides, Metals, Reducing Agent.

Hazardous Decomposition Products Nitrogen oxides (NOx). Carbon monoxide (CO). Carbon dioxide (CO2).

**Hazardous Polymerization** Hazardous polymerization does not occur.

FSUJ8750 Version 2 18-Nov-2022 Page 6/12

# Section 11 - Toxicological Information

### Information on Toxicological Effects

**Product Information** 

(a) acute toxicity;

Category 4 Oral Category 4 **Dermal** Inhalation Category 4

### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 - 2769  mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L (Rat) 4 h
Toluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h
1-Butanaminium, N,N,N-tributyl-, hydroxide	500 mg/kg (Rat)		

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available No data available Skin

Component	Test method	Test species	Study result
Methyl alcohol	OECD Test Guideline 406	guinea pig	non-sensitising
67-56-1 ( 17 )	Guinea Pig Maximisation Test		

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

Category 2 (g) reproductive toxicity;

Component	Test method	Test species / Duration	Study result
Methyl alcohol	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)
67-56-1 ( 17 )			

Teratogenicity

Possible risk of harm to the unborn child **Developmental Effects** Teratogenic effects have occurred in experimental animals.

Category 1 (h) STOT-single exposure;

Category 3

Central nervous system (CNS) Results / Target organs

Optic nerve

(i) STOT-repeated exposure; Category 2

**Target Organs** Neuropsychological effects, Eyes, Ears.

Category 1 (j) aspiration hazard;

Symptoms / effects, both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

FSUJ8750 Version 2 18-Nov-2022 Page 7/12

delayed tiredness, nausea and vomiting

# Section 12 - Ecological Information

**Ecotoxicity effects** 

The product contains following substances which are hazardous for the environment.

Contains a substance which is:. Harmful to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methyl alcohol	Pimephales promelas:	EC50 > 10000 mg/L 24h		EC50 = 39000 mg/L 25
	LC50 > 10000 mg/L 96h	_		min
				EC50 = 40000 mg/L 15
				min
				EC50 = 43000 mg/L 5
				min
Toluene		EC50: = 11.5 mg/L, 48h	EC50: = 12.5 mg/L, 72h	EC50 = 19.7 mg/L 30
	5-7 mg/L LC50 96 h	(Daphnia magna)	static	min
		EC50: 5.46 - 9.83 mg/L,	(Pseudokirchneriella	
	28 mg/L LC50 96 h	48h Static (Daphnia	subcapitata)	
	12 mg/L LC50 96 h	magna)	EC50: > 433 mg/L, 96h	
			(Pseudokirchneriella	
			subcapitata)	

Persistence and Degradability

Persistence

Persistence is unlikely, Immiscible with water.

Component	Degradability
Methyl alcohol	DT50 ~ 17.2d
67-56-1 ( 17 )	>94% after 20d
Toluene	86% (20d)
108-88-3 ( 80 )	

Degradation in sewage treatment plant
Bioaccumulative Potential

Contains substances known to be hazardous to the environment or not degradable in waste

water treatment plants.

May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10 dimensionless
Toluene	2.73	90
1-Butanaminium, N,N,N-tributyl-, hydroxide	1.518	No data available

Mobility

The product is insoluble and floats on water. Spillage unlikely to penetrate soil. Is not likely mobile in the environment due its low water solubility

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

# Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

**Contaminated Packaging** 

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Do not let this chemical enter the environment.

# Section 14 - Transport Information

FSUJ8750 Version 2 18-Nov-2022 Page 8 / 12

IMDG/IMO

**UN-No** UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Technical Shipping Name Contains toluene and methanol

Hazard Class 3
Packing Group

**ADG** 

**UN-No** UN1993

Proper Shipping Name Flammable liquid, n.o.s.

Technical Shipping Name Contains toluene and methanol

Hazard Class 3
Packing Group ||

Component	Hazchem Code
Methyl alcohol	2WE
67-56-1 ( 17 )	
Toluene	3YE
108-88-3 ( 80 )	

#### IATA

**UN-No** UN1993

**Proper Shipping Name** Flammable liquid, n.o.s.

Technical Shipping Name Contains toluene and methanol

Hazard Class 3
Packing Group ||

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

# Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations Australia

See section 8 for national exposure control parameters.

#### Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons			
Methyl alcohol - 67-56-1	Schedule 5 listed - except its derivatives;in preparations except a) when included in Schedule 10, or b) in preparations containing <=2% of Methanol, or c) when Methanol is present only as a denaturant of			
	Ethanol			
	Schedule 6 listed - except its derivatives; except a) when included in Schedule 5, or b) when included in Schedule 10, or c) in preparations containing <=2% of Methanol Schedule 10 listed			
Toluene - 108-88-3	Schedule 5 listed - including Kerosene, Diesel [distillate], Mineral turpentine, White petroleum spirit, Toluene, Xylene and light mineral and paraffin oils but except their derivative; except a) Toluene and Xylene when included in Schedule 6, b) Benzene and liquid aromatic hydrocarbons when included in Schedule 7, c) food grade and pharmaceutical grade White mineral oil, d) in solid or semi-solid preparations, e) in preparations containing <=25% of designated solvents, f) in preparations packed in pressurized spray packs, g) in adhesives packed in containers each containing <=50 grams of			
	adhesive, h) in writing correction fluids and thinners for writing correction fluids packed in containers			

FSUJ8750 Version 2 18-Nov-2022 Page 9/12

	having a capacity of <=20 mL, or i) in other preparations when packed in containers with a capacity of <=2 mL
	Schedule 6 listed - except its derivatives; except in preparations containing <=50% of Toluene or Toluene and Xylene
- 2052-49-5	Schedule 5 listed - in preparations except: a) when separately specified in these Schedules, b) Dialkyl or dialkoyl quaternary ammonium compounds where the alkyl or alkoyl groups are derived from tallow or hydrogenated tallow or similar chain length [C16/C18] source, or c) in preparations containing <=5% of such Quaternary ammonium compounds  Schedule 6 listed - except: a) when separately specified in these Schedules, b) when included in Schedule 5, c) Dialkyl or Dialkoyl quaternary ammonium compounds where the Alkyl or Alkoyl groups are derived from Tallow or hydrogenated Tallow or similar chain length [C16/C18] sources, or d) in preparations containing <=5% of such Quaternary ammonium compounds

### **Australian Industrial Chemicals Introduction Scheme (AICIS)**

Component	Australian Industrial Chemicals Introduction	Additional information
	Scheme (AICIS)	
Methyl alcohol - 67-56-1	Present	•
Toluene - 108-88-3	Present	-
1-Butanaminium, N,N,N-tributyl-, hydroxide	Present	-
- 2052-49-5		

### Australian - Illicit Drug Precursors/Reagents Substance List

Verify requirements related to using, handling and storing these substances. This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list.

#### **Chemicals of Security Concern**

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

Component	Australian - Illicit Drug	Chemicals of Security Concern
	Precursors/Reagents Substance List	
Toluene - 108-88-3	Category 3	

#### Legend

Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted.

### National pollutant inventory Subject to reporting requirements

Component	National pollutant inventory
Methyl alcohol - 67-56-1	10 tonne/yr. Threshold category 1
Toluene - 108-88-3	10 tonne/yr. Threshold category 1

### Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

## **International Inventories**

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	<b>ENCS</b>	ISHL	IECSC	KECL
Methyl alcohol	Х	Х	200-659-6	-	X	Х	-	Х	Χ	Х	Х	KE-23193
Toluene	Х	X	203-625-9	-	X	Х	-	Χ	Χ	Х	Χ	KE-33936
1-Butanaminium, N,N,N-tributyl-, hydroxide	X	Х	218-147-6	-	Х	X	-	X	Х	Х	Х	KE-34029

Legend: X - Listed. '-' - Not Listed. KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

FSUJ8750 Version 2 18-Nov-2022 Page 10 / 12

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

### Basel convention on the control of transboundary movements of hazardous wastes and their dispoal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories of Wastes to Be Controlled
Toluene - 108-88-3	Annex I - Y42	Y42 except Halogenated solvents

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methyl alcohol	67-56-1	Listed	Not applicable	500 tonne	5000 tonne
Toluene	108-88-3	Listed	Not applicable	Not applicable	Not applicable
1-Butanaminium, N,N,N-tributyl-, hydroxide	2052-49-5	Not applicable	Not applicable	Not applicable	Not applicable

#### Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Toluene	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

https://echa.europa.eu/substances-restricted-under-reach

# **Section 16 - Other Information**

#### Legend

AICS - Australian Inventory of Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

ICAO/IATA - International Civil Aviation Organization/International Air

NZIoC - New Zealand Inventory of Chemicals

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japanese Existing and New Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

**ACGIH** - American Conference of Governmental Industrial Hygienists Predicted No Effect Concentration (PNEC)

FSUJ8750 Version 2 18-Nov-2022 Page 11/12

# 0.1M Tetra-n-butylammonium hydroxide in toluene/methanol

## SAFETY DATA SHEET

Transport Association IMO/IMDG - International Maritime Organization/International Maritime

Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from

Ships

NZS 5433:2012 - Transport of Dangerous Goods on Land

**LD50** - Lethal Dose 50% **EC50** - Effective Concentration 50%

WEL - Workplace Exposure Limit
DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

**OECD** - Organisation for Economic Co-operation and Development

LC50 - Lethal Concentration 50% ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment NOEC - No Observed Effect Concentration

**BCF** - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

### Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards
Health Hazards
Calculation method
Environmental hazards
Cn basis of test data
Calculation method

#### **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Revision Date 18-Nov-2022 Revision Summary Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

# **End of Safety Data Sheet**

FSUJ8750 Version 2 18-Nov-2022 Page 12 / 12