

# **SAFETY DATA SHEET**

Creation Date 16-Jan-2009 Revision Date 26-Mar-2024 Revision Number 4

### 1. Identification

Product Name Methyl formate, 97%, cont. ca 3% methanol

Cat No. : L03623

**CAS No** 107-31-3

**Synonyms** Formic acid methyl ester; Methyl methanoate

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

### Details of the supplier of the safety data sheet

### Company

Thermo Fisher Scientific Chemicals, Inc. 30 Bond Street

Ward Hill, MA 01835-8099

Tel: 800-343-0660 Fax: 800-322-4757

### **Emergency Telephone Number**

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

# 2. Hazard(s) identification

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids

Acute oral toxicity

Acute Inhalation Toxicity - Vapors

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Category 2

Specific target organ toxicity (single exposure)

Category 3

Target Organs - Respiratory system, Central nervous system (CNS), Optic nerve.

#### Label Elements

# Signal Word

Danger

### **Hazard Statements**

Extremely flammable liquid and vapor

Toxic if inhaled Harmful if swallowed Causes serious eye irritation Causes skin irritation May cause respiratory irritation



### **Precautionary Statements**

#### Prevention

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Take precautionary measures against static discharge

### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician

#### Skin

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash before reuse

If skin irritation occurs: Get medical advice/attention

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

### Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

#### **Fire**

Explosion risk in case of fire

Fight fire with normal precautions from a reasonable distance

Evacuate area

# Storage

Store in a well-ventilated place. Keep container tightly closed

Store locked up

# **Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

WARNING. Reproductive Harm - https://www.p65warnings.ca.gov/.

# 3. Composition/Information on Ingredients

Component	CAS No	Weight %
Methyl formate	107-31-3	>97
Methyl alcohol	67-56-1	<3

### 4. First-aid measures

**General Advice** If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

**Inhalation** Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If

not breathing, give artificial respiration.

**Ingestion** Do NOT induce vomiting. Get medical attention.

Most important symptoms and

effects

Notes to Physician

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting

Treat symptomatically

# 5. Fire-fighting measures

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may

be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point -32 °C / -25 °F

Method - No information available

Autoignition Temperature 440 °C / 824 °F

**Explosion Limits** 

Upper 23% Lower 4.5%

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

### **Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors. Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Methanol.

### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

HealthFlammabilityInstabilityPhysical hazards240N/A

# 6. Accidental release measures

Personal Precautions Use personal protective equipment as required. Ensure adequate ventilation. Remove all

sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions** Should not be released into the environment. Do not flush into surface water or sanitary

sewer system.

**Methods for Containment and Clean** Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. **Up** Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 7. Handling and storage

Handling

Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Flammables area. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame. Incompatible Materials. Strong oxidizing agents. .

# 8. Exposure controls / personal protection

### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Methyl formate	TWA: 50 ppm	(Vacated) TWA: 100 ppm	IDLH: 4500 ppm	TWA: 100 ppm
1	STEL: 100 ppm	(Vacated) TWA: 250 mg/m <sup>3</sup>	TWA: 100 ppm	STEL: 150 ppm
	Skin	(Vacated) STEL: 150 ppm	TWA: 250 mg/m <sup>3</sup>	
		(Vacated) STEL: 375 mg/m <sup>3</sup>	STEL: 150 ppm	
		TWA: 100 ppm	STEL: 375 mg/m <sup>3</sup>	
		TWA: 250 mg/m <sup>3</sup>	_	
Methyl alcohol	TWA: 200 ppm	(Vacated) TWA: 200 ppm	IDLH: 6000 ppm	TWA: 200 ppm
	STEL: 250 ppm	(Vacated) TWA: 260 mg/m <sup>3</sup>	TWA: 200 ppm	STEL: 250 ppm
	Skin	(Vacated) STEL: 250 ppm	TWA: 260 mg/m <sup>3</sup>	
		(Vacated) STEL: 325 mg/m <sup>3</sup>	STEL: 250 ppm	
		Skin	STEL: 325 mg/m <sup>3</sup>	
		TWA: 200 ppm		
		TWA: 260 mg/m <sup>3</sup>		

#### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

**Engineering Measures**Use only under a chemical fume hood. Ensure that eyewash stations and safety showers

are close to the workstation location. Use explosion-proof electrical/ventilating/lighting

equipment. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166. Tight sealing safety goggles. Face protection shield.

**Skin and body protection**Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if

exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: low boiling organic solvent. Type AX. Brown. conforming to EN371.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

# 9. Physical and chemical properties

Physical StateLiquidAppearanceColorlessOdorOrganic

Odor
Odor Threshold
PH
Organic
No information available
4-5 @ 20°C (20 %)

 Melting Point/Range
 -100 °C / -148 °F

 Boiling Point/Range
 31 - 33 °C / 88 - 91 °F

 Flash Point
 -32 °C / -25 °F

Evaporation Rate No information available

Flammability (solid,gas)

Not applicable
Flammability or explosive limits

Upper 23% Lower 4.5%

Vapor Pressure 644 mbar @ 20 °C

Vapor Density 2.07 Specific Gravity 0.968

SolubilitySoluble in waterPartition coefficient; n-octanol/waterNo data availableAutoignition Temperature440 °C / 824 °FDecomposition TemperatureNo information availableViscosity0.35 mPa.s at 20 °C

Molecular Formula 0.35 mFa.s. of Molecular Formula 0.35 mFa.s. of Molecular Weight 0.35 mFa.s.

# 10. Stability and reactivity

Reactive Hazard None known, based on information available

**Stability** Stable under normal conditions.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents,

Hazardous Decomposition Products Carbon monoxide (CO<sub>2</sub>), Carbon dioxide (CO<sub>2</sub>), Methanol

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions** None under normal processing.

# 11. Toxicological information

**Acute Toxicity** 

**Product Information** 

Oral LD50 Category 4. ATE = 300 - 2000 mg/kg.

**Dermal LD50** Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50 Category 3. ATE = 2 - 10 mg/l.

**Component Information** 

	Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
Methyl formate LD50 = 475 mg/kg ( Rat )		LD50 > 5 g/kg ( Rabbit )	LC50 > 21 mg/L (Rat) 4 h			
	Methyl alcohol	LD50 = 1187 - 2769 mg/kg (Rat)	LD50 = 17100 mg/kg ( Rabbit )	LC50 = 128.2 mg/L ( Rat ) 4 h		

**Toxicologically Synergistic** 

No information available

**Products** 

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin

Sensitization No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl formate	107-31-3	Not listed				
Methyl alcohol	67-56-1	Not listed				

Mutagenic Effects No information available

Reproductive Effects

No information available.

Developmental Effects

No information available.

**Teratogenicity** No information available.

STOT - single exposure Respiratory system Central nervous system (CNS) Optic nerve

No information available

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects,both acute and Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

**delayed** tiredness, nausea and vomiting

Other Adverse Effects The toxicological properties have not been fully investigated.

# 12. Ecological information

#### **Ecotoxicity**

Do not empty into drains.

**Endocrine Disruptor Information** 

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl formate	EC50: = 240 mg/L, 72h (Desmodesmus subspicatus) EC50: = 190 mg/L, 96h (Desmodesmus subspicatus)	Not listed	EC50 > 10000 mg/L 17 h	EC50: > 500 mg/L, 48h (Daphnia magna)
Methyl alcohol	Not listed		EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl formate	-0.21
Methyl alcohol	-0.74

# 13. Disposal considerations

**Waste Disposal Methods** 

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

# 14. Transport information

DOT

UN-No UN1243

Proper Shipping Name METHYL FORMATE

Hazard Class 3
Packing Group

<u>TDG</u>

UN-No UN1243

Proper Shipping Name METHYL FORMATE

Hazard Class 3
Packing Group

<u>IATA</u>

UN-No UN1243
Proper Shipping Name Methyl formate

Hazard Class
Packing Group

IMDG/IMO

UN-No UN1243
Proper Shipping Name Methyl formate

Hazard Class 3
Packing Group

# 15. Regulatory information

### **United States of America Inventory**

Component	CAS No TSCA		TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags	
Methyl formate	107-31-3	Χ	ACTIVE	-	
Methyl alcohol	67-56-1	X	ACTIVE	-	

### Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'-' - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

### **International Inventories**

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Methyl formate	107-31-3	Χ	-	203-481-7	Χ	Χ	Χ	Χ	Χ	KE-17243
Methyl alcohol	67-56-1	Х	-	200-659-6	Х	Χ	Х	Х	Х	KE-23193

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

### U.S. Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting threasholds
Methyl alcohol	67-56-1	<3	1.0 %	-

### SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)** 

Not applicable

### Clean Air Act

Component HAPS Data		Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

**OSHA** - Occupational Safety and

Health Administration

Not applicable

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Methyl alcohol	5000 lb	-	5000 lb 2270 kg

### **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Component	CAS No California Prop. 65		Prop 65 NSRL	Category
Methyl alcohol	phol 67-56-1 Developmental		-	Developmental

# U.S. State Right-to-Know

# Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl formate	X	X	X	-	X
Methyl alcohol	X	X	X	X	X

### **U.S.** Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

### U.S. Department of Homeland

This product contains the following DHS chemicals:

Security Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard		
Methyl formate	Release STQs - 10000lb		

### Other International Regulations

Mexico - Grade Severe risk, Grade 4

### Authorisation/Restrictions according to EU REACH

Component		REACH (1907/2006) - Annex XIV - Substances Subject to Authorization		REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl formate	107-31-3	-	Use restricted. See item 75.	-

		(see link for restriction details)
Methyl alcohol	67-56-1	- Use restricted. See item - 69.
		(see link for restriction details) Use restricted. See item
		75. (see link for restriction details)

#### **REACH links**

https://echa.europa.eu/substances-restricted-under-reach

### Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl formate	107-31-3	Listed	Not applicable	Not applicable	Not applicable
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)? Not applicable

### Other International Regulations

Co	mponent	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Met	nyl formate	107-31-3	Not applicable	Not applicable	Not applicable	Not applicable
Met	hyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable

	16. Other information	
Prepared By	Health, Safety and Environmental Department	

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

 Creation Date
 16-Jan-2009

 Revision Date
 26-Mar-2024

 Print Date
 26-Mar-2024

**Revision Summary** New emergency telephone response service provider.

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**