# Thermo Fisher SCIENTIFIC

# SAFETY DATA SHEET

Page 1/9 Creation Date 13-Sep-2010 Revision Date 12-Apr-2024 Version 4

ACR45166

## 3-Methyl-1-butanol

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: 3-甲基-1-丁醇 Product Description: 3-Methyl-1-butanol

Cat No.: 451660000; 451660010

Synonyms Isoamyl alcohol; Isopentyl alcohol

CAS No 123-51-3 Molecular Formula C5 H12 O

Supplier UK entity/business name

Fisher Scientific UK Bishop Meadow Road,

Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name** Thermo Fisher Scientific

Janssen Pharmaceuticalaan 3a, 2440 Geel, Belgium

Emergency Telephone Number For information US call: 001-800-227-6701 / Europe call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals.
Uses advised against No Information available

## **SECTION 2. HAZARD IDENTIFICATION**

Physical StateAppearanceOdorLiquidClearCharacteristic

## **Emergency Overview**

Flammable liquid and vapor. May be harmful in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness and dizziness. Causes damage to organs. Repeated exposure may cause skin dryness or cracking.

## Classification of the substance or mixture

Flammable liquids.	Category 3
Acute Dermal Toxicity	Category 5
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Specific target organ toxicity - (single exposure)	Category 1 Category 3

#### **Label Elements**

Page 2/9 Revision Date 12-Apr-2024

## 3-Methyl-1-butanol



#### Signal Word

## **Danger**

#### **Hazard Statements**

- H226 Flammable liquid and vapor
- H313 May be harmful in contact with skin
- H332 Harmful if inhaled
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H370 Causes damage to organs

## **Precautionary Statements**

#### Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P240 Ground and bond container and receiving equipment
- P241 Use explosion-proof electrical/ ventilating/ lighting equipment
- P242 Use non-sparking tools
- P243 Take action to prevent static discharges
- P264 Wash face, hands and any exposed skin thoroughly after handling
- P271 Use only outdoors or in a well-ventilated area
- P280 Wear protective gloves/protective clothing/eye protection/face protection

#### Response

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P312 Call a POISON CENTER or doctor if you feel unwell
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
- P362 + P364 Take off contaminated clothing and wash it before reuse

#### Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

#### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## **Physical and Chemical Hazards**

Vapors may cause flash fire or explosion. Flammable liquid.

## **Health Hazards**

Causes serious eye irritation. Causes damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness. May be harmful in contact with skin. Causes skin irritation. Harmful if inhaled.

## **Environmental hazards**

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. . Will likely be mobile in the environment due to its water solubility. The product is water soluble, and may spread in water systems.

Toxic to terrestrial vertebrates. This product does not contain any known or suspected endocrine disruptors.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS No	Weight %
Isoamyl alcohol	123-51-3	<=100

## **SECTION 4. FIRST AID MEASURES**

Page 3/9 Revision Date 12-Apr-2024

3-Methyl-1-butanol

#### **General Advice**

If symptoms persist, call a physician.

#### **Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.

#### Inhalation

Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention. If not breathing, give artificial respiration.

## Ingestion

Do NOT induce vomiting. Get medical attention.

## Most important symptoms and effects

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

#### Self-Protection of the First Aider

Use personal protective equipment as required.

#### **Notes to Physician**

Treat symptomatically. Symptoms may be delayed.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

## Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors.

## **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

## **Personal Precautions**

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

#### **Environmental Precautions**

Should not be released into the environment. See Section 12 for additional Ecological Information.

## Methods for Containment and Clean Up

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

Refer to protective measures listed in Sections 8 and 13.

Page 4/9 Revision Date 12-Apr-2024

3-Methyl-1-butanol

## **SECTION 7. HANDLING AND STORAGE**

#### Handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. Use only non-sparking tools.

#### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

## Specific Use(s)

Use in laboratories

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **Control Parameters**

Component	China	Taiwan	Thailand	Hong Kong
Isoamyl alcohol	-	TWA: 100 ppm		-
1		TWA: 361 mg/m <sup>3</sup>		

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
Isoamyl alcohol	Isoamyl alcohol TWA: 100 ppm		IDLH: 500 ppm	STEL: 125 ppm 15 min	
	STEL: 125 ppm	ppm	TWA: 100 ppm	STEL: 458 mg/m <sup>3</sup> 15	
		(Vacated) TWA: 360	TWA: 360 mg/m <sup>3</sup>	min	
		mg/m³	STEL: 125 ppm	TWA: 100 ppm 8 hr	
			STEL: 450 mg/m <sup>3</sup>	TWA: 366 mg/m <sup>3</sup> 8 hr	
		ppm			
		(Vacated) STEL: 450			
		mg/m³			
		TWA: 100 ppm			
		TWA: 360 mg/m <sup>3</sup>			

#### <u>Legend</u>

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

#### **Monitoring methods**

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

## **Exposure Controls**

#### **Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

## Personal protective equipment

**Eve Protection** Goggles (European standard - EN 166)

Hand Protection Protective gloves

Page 5/9 Revision Date 12-Apr-2024

## 3-Methyl-1-butanol

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to

EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

141

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

**Environmental exposure controls** No information available.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance Clear Physical State Liquid

**Odor Threshold** 

Odor Characteristic

**pH** 6.5 25 g/l aq.sol

No data available

Melting Point/Range -117 °C / -178.6 °F

Softening Point No data available

**Boiling Point/Range** 130 - 132 °C / 266 - 269.6 °F 760 mm HG

Flash Point 45 °C / 113 °F Method - No information available

Evaporation Rate

No data available

Flammability (solid,gas) Not applicable Liquid

 Explosion Limits
 Lower 1.0 Vol% Upper 8 Vol%

 Vapor Pressure
 4 hPa @ 20 °C

**Vapor Density** 3.04 (Air = 1.0) (Air = 1.0)

Specific Gravity / Density 0.807-0.811

Bulk Density Not applicable Liquid

Water Solubility 25 g/L (20°C)

Solubility in other solvents No information available

Partition Coefficient (n-octanol/water)

Componentlog PowIsoamyl alcohol1.35

Autoignition Temperature 365 - °C / 689 - °F

**Decomposition Temperature** 335 °C

Viscosity 4.3 mPa s at 20 °C

Page 6/9 Revision Date 12-Apr-2024

3-Methyl-1-butanol

Explosive Properties explosive air/vapour mixtures possible

Oxidizing Properties No information available

Molecular FormulaC5 H12 OMolecular Weight88.15

## **SECTION 10. STABILITY AND REACTIVITY**

**Stability** Stable under normal conditions.

Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Materials to avoid Strong oxidizing agents. Metals. Alkali metals. Halogens. Acids. Acid anhydrides. Acid

chlorides. Isocyanates.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO2).

## **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **Product Information**

(a) acute toxicity;

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation		
Isoamyl alcohol	LD50 = 5770 mg/kg (Rat)	LD50 = 3250 mg/kg (Rabbit)	LC50 > 2000 ppm (Rat) 8 h		

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

**Respiratory**Based on available data, the classification criteria are not met
Skin
Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

Page 7/9 Revision Date 12-Apr-2024

3-Methyl-1-butanol

(j) aspiration hazard; Based on available data, the classification criteria are not met

Other Adverse Effects Tumorigenic effects have been reported in experimental animals.

Symptoms / effects,both acute and Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

delayed

## **SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity effects**This product contains the following substance(s) which are hazardous for the environment..

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Isoamyl alcohol	LC50 96 h 700 mg/L (rainbow trout)	EC50: = 260 mg/L, 48h (Daphnia magna)	EC50: = 181 mg/L, 96h (Desmodesmus subspicatus) EC50: = 493 mg/L, 72h (Desmodesmus subspicatus)	EC50 = 2500 mg/L 17 h

Persistence and Degradability

**Persistence** 

Readily biodegradable

Soluble in water, Persistence is unlikely, based on information available.

Bioaccumulative Potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Isoamyl alcohol	1.35	No data available

Mobility in soil

The product is water soluble, and may spread in water systems Will likely be mobile in the

environment due to its water solubility Highly mobile in soils

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected endocrine disruptors

This product does not contain any known or suspected substance This product does not contain any known or suspected substance

## **SECTION 13. DISPOSAL CONSIDERATIONS**

Waste from Residues/Unused

**Products** 

Waste is classified as hazardous. Dispose of in accordance with the European Directives

on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

empty container away from heat and sources of ignition.

Other Information Waste codes should be assigned by the user based on the application for which the product

was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with

local regulations.

## **SECTION 14. TRANSPORT INFORMATION**

**Road and Rail Transport** 

UN-No UN1105

Proper Shipping Name PENTANOLS

Hazard Class 3
Packing Group III

Page 8/9 Revision Date 12-Apr-2024

3-Methyl-1-butanol

#### IMDG/IMO

UN1105 **UN-No PENTANOLS Proper Shipping Name** 

**Hazard Class** 3 **Packing Group** Ш

**IATA** 

**UN-No** UN1105 **Proper Shipping Name PENTANOLS** 

**Hazard Class** 3 Ш **Packing Group** 

**Special Precautions for User** No special precautions required

## **SECTION 15. REGULATORY INFORMATION**

#### International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The	List of	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	<b>ENCS</b>	ISHL	AICS	KECL
	Inventory of Hazardous Chemicals (2015 Edition)	goods GB										
Isoamyl alcohol	X	Х	Х	Х	204-633-5	Χ	Χ	Х	Х	Χ	Χ	KE-23575

#### **National Regulations**

## **SECTION 16. OTHER INFORMATION**

13-Sep-2010 **Creation Date Revision Date** 12-Apr-2024 Not applicable. **Revision Summary** 

## **Training Advice**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical incident response training.

## Legend

**CAS** - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances

**ENCS** - Japanese Existing and New Chemical Substances **AICS** - Australian Inventory of Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

Page 9/9 Revision Date 12-Apr-2024

3-Methyl-1-butanol

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration **PBT** - Persistent, Bioaccumulative, Toxic

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

PNEC - Predicted No Effect Concentration

IARC - International Agency for Research on Cancer

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**MARPOL** - International Convention for the Prevention of Pollution from Ships

niips

ATE - Acute Toxicity Estimate
VOC - (Volatile Organic Compound)

TWA - Time Weighted Average

LD50 - Lethal Dose 50%

## Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**