

SAFETY DATA SHEET

Creation Date 21-May-2012 Revision Date 25-March-2024 Revision Number 4

1. Identification

Product Name Methylmagnesium bromide, 3M in ether

Cat No.: 87324

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific 112 Colonnade Road, Ottawa, ON K2E 7L6,

Canada

Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99 **CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids Category 1

Substances/mixtures which, in contact with water, emit Category 1 Gas(es) = Methane

flammable gases

Acute oral toxicity

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific target organ toxicity (single exposure)

Category 1

Category 1

Category 3

Target Organs - Respiratory system, Central nervous system (CNS).

Physical Hazards Not Otherwise Classified Category 1

Reacts violently with water May form explosive peroxides

Label Elements

Signal Word

Danger

Hazard Statements

Extremely flammable liquid and vapor

In contact with water releases flammable gases which may ignite spontaneously

Harmful if swallowed

Causes severe skin burns and eye damage

Causes serious eye damage

May cause respiratory irritation

May cause drowsiness and dizziness

Reacts violently with water

May form explosive peroxides



Precautionary Statements

Prevention

Do not allow contact with water

Keep container tightly closed

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Ground/bond container and receiving equipment

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Use non-sparking tools

Take action to prevent static discharges

Handle and store contents under inert gas. Protect from moisture

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER/doctor

Rinse mouth

Do NOT induce vomiting

Wash contaminated clothing before reuse

Explosion risk in case of fire

Fight fire with normal precautions from a reasonable distance

Evacuate area

Storage

Store locked up

Store in a dry place

Store in a closed container

Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients Component CAS-No Weight %

Ethyl ether	60-29-7	65
Methylmagnesium bromide	75-16-1	35

4. First-aid measures

General Advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Eye ContactRinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the

substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If

not breathing, give artificial respiration.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately.

Most important symptoms/effects Causes burns by all exposure routes. Difficulty in breathing. Product is a corrosive material.

Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool

closed containers.

Unsuitable Extinguishing Media DO NOT USE WATER

Flash Point -40 °C / -40 °F

Method - (based on components)

Autoignition Temperature

Explosion Limits

No information available

Upper No data available Lower No data available

Sensitivity to Mechanical Impact No information available Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Extremely flammable. Corrosive material. Reacts violently with water. Contact with water liberates extremely flammable gases. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen halides. Magnesium oxides. Methane.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Flammability Instability Physical hazards Health W

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

Environmental Precautions

Avoid release to the environment. See Section 12 for additional Ecological Information.

Up

Methods for Containment and Clean Do not expose spill to water. Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Storage.

Store indoors. Keep away from heat, sparks and flame. Keep away from water or moist air. Store under an inert atmosphere. Flammables area. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Incompatible Materials. Acids. Bases. Water. Alcohols.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta		Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
		Columbia					
Ethyl ether	TWA: 400 ppm	(Vacated) TWA:	IDLH: 1900 ppm				
	TWA: 1210	STEL: 500 ppm	STEL: 500 ppm	TWA: 1210	STEL: 500 ppm	400 ppm	
	mg/m³			mg/m³		(Vacated) TWA:	
	STEL: 500 ppm			STEL: 500 ppm		1200 mg/m ³	
	STEL: 1520			STEL: 1520		(Vacated) STEL:	
	mg/m³			mg/m³		500 ppm	
						(Vacated) STEL:	
						1500 mg/m ³	
						TWA: 400 ppm	
						TWA: 1200	
						mg/m³	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact,

and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber	See manufacturers	-	Splash protection only
Viton (R)	recommendations		

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly **Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State Liquid Appearance Brown

Odor
Odor No information available
No information available
PH No information available
No information available
No data available
No data available
No information available

Flash Point -40 °C / -40 °F

Method - (based on components)

Evaporation Rate No information available

Flammability (solid,gas) Not applicable

Flammability or explosive limits

Upper
LowerNo data available
No data availableVapor PressureNo information availableVapor DensityNo information availableSpecific Gravity1.035

Solubility
No information available
Partition coefficient; n-octanol/water
No data available

Autoignition Temperature

Decomposition Temperature

Viscosity

No information available
No information available
No information available

Molecular Formula C H3 Br Mg Molecular Weight 119.26

10. Stability and reactivity

Reactive Hazard Yes

Reacts violently with water. Moisture sensitive. Air sensitive. May form explosive peroxides. Stability

Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or **Conditions to Avoid**

water. Exposure to air. Incompatible products.

Incompatible Materials Acids, Bases, Water, Alcohols

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO2), Hydrogen halides, Magnesium oxides,

Methane

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions Contact with water liberates extremely flammable gases.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Category 4. ATE = 300 - 2000 mg/kg.

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. **Dermal LD50** Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Vapor LC50

Component Information

Component LD50 Oral		LD50 Dermal	LC50 Inhalation	
Ethyl ether	Ethyl ether 1215 mg/kg (Rat)		32000 ppm (Rat) 4 h	

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes burns by all exposure routes

Sensitization No information available

The table below indicates whether each agency has listed any ingredient as a carcinogen. Carcinogenicity

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl ether	60-29-7	Not listed				
Methylmagnesium bromide	75-16-1	Not listed				

No information available **Mutagenic Effects**

Reproductive Effects No information available. **Developmental Effects** No information available.

Teratogenicity No information available.

Respiratory system Central nervous system (CNS) STOT - single exposure

None known STOT - repeated exposure

Aspiration hazard No information available

Symptoms / effects,both acute and Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

delayed

Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms

of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of

high vapor concentrations may cause symptoms like headache, dizziness, tiredness,

nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

This product contains the following substance(s) which are hazardous for the environment. .

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl ether	Not listed	LC50: > 10000 mg/L, 96h	EC50 = 5600 mg/L 15 min	EC50 = 165 mg/L/24h
		static (Lepomis macrochirus)	_	_
		LC50: = 2560 mg/L, 96h		
		flow-through (Pimephales		
		promelas)		
		, ,		

Persistence and Degradability

Soluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation

No information available.

Mobility

. Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Ethyl ether	0.82

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Ethyl ether - 60-29-7	U117	=

14. Transport information

DOT

UN-No UN1928

Proper Shipping Name consumer commodity METHYL MAGNESIUM BROMIDE, IN ETHYL ETHER

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group

TDG

UN-No UN1928

Proper Shipping Name METHYL MAGNESIUM BROMIDE, IN ETHYL ETHER

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group

<u>IATA</u>

UN-No UN1928

Proper Shipping Name Methyl magnesium bromide in ethyl ether (Mixture)

Hazard Class 4.3 Subsidiary Hazard Class 3 Packing Group 1

IMDG/IMO

UN-No UN1928

Proper Shipping Name Methylmagnesium bromide in ethyl ether (Mixture)

Hazard Class 4.3 Subsidiary Hazard Class 3

Packing Group

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Ethyl ether	60-29-7	X	-	X	ACTIVE	200-467-2	-	-
Methylmagnesium bromide	75-16-1	-	Х	Х	ACTIVE	200-844-1	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Ethyl ether	60-29-7	X	KE-27690	X	X	X	X	X	Х
Methylmagnesium bromide	75-16-1	-	-	X	X	X	-	X	Х

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (http://ncis.nier.go.kr/en/main.do)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Ethyl ether	Part 4 Substance		

Other International Regulations

Authorisation/Restrictions according to EU REACH

Not applicable

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable
Methylmagnesium bromide	75-16-1	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	(2012/18/EC) -	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl ether	60-29-7	Not applicable	Not applicable	Not applicable	Annex I - Y40 Annex I - Y42
Methylmagnesium bromide	75-16-1	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Product Safety Department

Email: chem.techinfo@thermofisher.com

www.thermofisher.com

 Creation Date
 21-May-2012

 Revision Date
 25-March-2024

 Print Date
 25-March-2024

Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS