



# Fisher Scientific

Part of Thermo Fisher Scientific

## SAFETY DATA SHEET

Revision Date 26-Jan-2015

Revision Number 1

### 1. Identification

**Product Name** Hematoxylin Stain 2, Fisher Pinnacle Portfolio

**Cat No. :** 22220102

**Synonyms** No information available

**Recommended Use** Laboratory chemicals.

**Uses advised against** No Information available

**Details of the supplier of the safety data sheet**

**Emergency Telephone Number**

Chemtrec US: (800) 424-9300

Chemtrec EU: 001 (202) 483-7616

### 2. Hazard(s) identification

**Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute oral toxicity

Category 4

Serious Eye Damage/Eye Irritation

Category 1

**Label Elements**

**Signal Word**

Danger

**Hazard Statements**

Harmful if swallowed

Causes serious eye damage



**Precautionary Statements**

**Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Wear protective gloves/protective clothing/eye protection/face protection

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor/physician

**Ingestion**

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

**Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

None identified

### 3. Composition / information on ingredients

Component	CAS-No	Weight %
Ethylene glycol	107-21-1	25 - 30
Aluminum sulfate	10043-01-3	5 - 8
Acetic acid	64-19-7	< 1.0
Benz[b]indeno[1,2-d]pyran-3,4,6a,9,10(6H)-pentol, 7,11b-dihydro-, cis-(+)-	517-28-2	0.4

### 4. First-aid measures

<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes.
<b>Inhalation</b>	Move to fresh air.
<b>Ingestion</b>	Do not induce vomiting.
<b>Most important symptoms/effects</b>	Causes eye burns.
<b>Notes to Physician</b>	Treat symptomatically

### 5. Fire-fighting measures

<b>Unsuitable Extinguishing Media</b>	No information available
<b>Flash Point</b>	> °C
<b>Method -</b>	No information available
<b>Autoignition Temperature</b>	No information available
<b>Explosion Limits</b>	
<b>Upper</b>	No data available
<b>Lower</b>	No data available
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

**Specific Hazards Arising from the Chemical**

Keep product and empty container away from heat and sources of ignition.

**Hazardous Combustion Products**

None known

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**NFPA**

**Health**  
2

**Flammability**  
1

**Instability**  
0

**Physical hazards**  
N/A

## 6. Accidental release measures

<b>Personal Precautions</b>	Ensure adequate ventilation. Use personal protective equipment.
<b>Environmental Precautions</b>	See Section 12 for additional ecological information.

**Methods for Containment and Clean Up** No information available.

## 7. Handling and storage

<b>Handling</b>	Ensure adequate ventilation.
<b>Storage</b>	Keep containers tightly closed in a dry, cool and well-ventilated place.

## 8. Exposure controls / personal protection

**Exposure Guidelines** This product does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylene glycol	Ceiling: 100 mg/m <sup>3</sup>	(Vacated) Ceiling: 50 ppm (Vacated) Ceiling: 125 mg/m <sup>3</sup>	
Aluminum sulfate		(Vacated) TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Acetic acid	TWA: 10 ppm STEL: 15 ppm	(Vacated) TWA: 10 ppm (Vacated) TWA: 25 mg/m <sup>3</sup> TWA: 10 ppm TWA: 25 mg/m <sup>3</sup>	IDLH: 50 ppm TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 15 ppm STEL: 37 mg/m <sup>3</sup>

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Ethylene glycol	Ceiling: 50 ppm Ceiling: 127 mg/m <sup>3</sup>	Ceiling: 100 mg/m <sup>3</sup>	CEV: 100 mg/m <sup>3</sup>
Aluminum sulfate	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	
Acetic acid	TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 15 ppm STEL: 37 mg/m <sup>3</sup>	TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 15 ppm STEL: 37 mg/m <sup>3</sup>	TWA: 10 ppm STEL: 15 ppm

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

<b>Eye/face Protection</b>	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
<b>Skin and body protection</b>	Wear appropriate protective gloves and clothing to prevent skin exposure.
<b>Respiratory Protection</b>	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
<b>Hygiene Measures</b>	Handle in accordance with good industrial hygiene and safety practice.

## 9. Physical and chemical properties

Physical State	Liquid
Appearance	Purple
Odor	sweet
Odor Threshold	No information available
pH	
Melting Point/Range	No data available
Boiling Point/Range	158.9 °C
Flash Point	> °C
Evaporation Rate	0.3 (Butyl Acetate = 1.0)
Flammability (solid,gas)	No information available
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	32 mmHg
Vapor Density	1.1 (Air = 1.0)
Relative Density	1.052 @ 21°C
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available

## 10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	None under normal use conditions
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

## 11. Toxicological information

### Acute Toxicity

Oral LD50	Category 4. ATE = 300 - 2000 mg/kg.
Dermal LD50	Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.
Vapor LC50	Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylene glycol	4000 - 10200 mg/kg ( Rat )	9530 µL/kg ( Rabbit ) 10600 mg/kg ( Rat )	Not listed
Aluminum sulfate	6207 mg/kg ( Mouse)	>5 g/kg ( Rabbit)	Not listed
Acetic acid	3310 mg/kg ( Rat )	1060 mg/kg ( Rabbit )	11.4 mg/L ( Rat ) 4 h
Benz[b]indeno[1,2-d]pyran-3,4,6a,9,10(6H)-pentol, 7,11b-dihydro-, cis-(+)-	400 mg/kg ( Rat )	Not listed	Not listed

Toxicologically Synergistic Products	No information available
--------------------------------------	--------------------------

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available
Sensitization	No information available

**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethylene glycol	107-21-1	Not listed	Not listed	Not listed	Not listed	Not listed
Aluminum sulfate	10043-01-3	Not listed	Not listed	Not listed	Not listed	Not listed
Acetic acid	64-19-7	Not listed	Not listed	Not listed	Not listed	Not listed
Benz[b]indeno[1,2-d]pyran-3,4,6a,9,10(6H)-pentol, 7,11b-dihydro-, cis-(+)-	517-28-2	Not listed	Not listed	Not listed	Not listed	Not listed

**Mutagenic Effects**

No information available

**Reproductive Effects**

No information available.

**Developmental Effects**

No information available.

**Teratogenicity**

No information available.

**STOT - single exposure**

None known

**STOT - repeated exposure**

None known

**Aspiration hazard**

No information available

**Symptoms / effects, both acute and delayed**

No information available

**Endocrine Disruptor Information**

No information available

**Other Adverse Effects**

The toxicological properties have not been fully investigated.

## 12. Ecological information

**Ecotoxicity**

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethylene glycol	6500 - 13000 mg/L EC50 96 h	16000 mg/L LC50 96 h 40000 - 60000 mg/L LC50 96 h 40761 mg/L LC50 96 h 27540 mg/L LC50 96 h 14 - 18 mL/L LC50 96 h 41000 mg/L LC50 96 h	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	46300 mg/L EC50 = 48 h
Aluminum sulfate	Not listed	37 mg/L LC50 96 h 100 mg/L LC50 96 h	Not listed	136 mg/L EC50 15 min 38.2 mg/L EC50 48h
Acetic acid	-	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	EC50 = 95 mg/L/24h

**Persistence and Degradability**

No information available

**Bioaccumulation/ Accumulation**

No information available.

**Mobility**

No information available.

Component	log Pow
Ethylene glycol	-1.93
Acetic acid	-0.2

## 13. Disposal considerations

**Waste Disposal Methods**

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

## 14. Transport information

<b>DOT</b>	Not regulated
<b>TDG</b>	Not regulated
<b>IATA</b>	Not regulated
<b>IMDG/IMO</b>	Not regulated

## 15. Regulatory information

**International Inventories**

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ethylene glycol	X	X	-	203-473-3	-		X	X	X	X	X
Aluminum sulfate	X	X	-	233-135-0	-		X	X	X	X	X
Acetic acid	X	X	-	200-580-7	-		X	X	X	X	X
Benz[b]indeno[1,2-d]pyran-3,4,6a,9,10(6H)-pentol, 7,11b-dihydro-, cis-(+)-	X	X	-	208-237-3	-		X	X	X	X	X

**Legend:**

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

**U.S. Federal Regulations**

TSCA 12(b) Not applicable

SARA 313 Not applicable

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Ethylene glycol	107-21-1	25 - 30	1.0

**SARA 311/312 Hazardous Categorization**

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act Not applicable

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Aluminum sulfate	X	5000 lb	-	-
Acetic acid	X	5000 lb	-	-

Clean Air Act Not applicable

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
-----------	-----------	-------------------------	-------------------------

Ethylene glycol	X		-
-----------------	---	--	---

**OSHA** Occupational Safety and Health Administration  
Not applicable

**CERCLA**  
Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethylene glycol	5000 lb	-
Aluminum sulfate	5000 lb	-
Acetic acid	5000 lb	-

**California Proposition 65** This product does not contain any Proposition 65 chemicals

**State Right-to-Know** Not applicable

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethylene glycol	X	X	X	X	X
Aluminum sulfate	X	X	X	-	-
Acetic acid	X	X	X	-	X

#### U.S. Department of Transportation

Reportable Quantity (RQ): N  
DOT Marine Pollutant N  
DOT Severe Marine Pollutant N

#### U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

#### Other International Regulations

**Mexico - Grade** No information available

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

**WHMIS Hazard Class** D1B Toxic materials  
E Corrosive material



## 16. Other information

**Prepared By** Regulatory Affairs  
Thermo Fisher Scientific  
Email: EMSDS.RA@thermofisher.com

**Revision Date** 26-Jan-2015  
**Print Date** 26-Jan-2015  
**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS)

#### Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the

date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of SDS**