

SAFETY DATA SHEET

Page 1/9 Revision Date 29-Mar-2023

Version 1

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Identifier

Perihalan Produk: Gram Decolorizer
Product Description: Gram Decolorizer

Cat No.: R40054, R40055, R40075

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Details of the supplier of the safety data sheet

Company Thermo Scientific Microbiology Sdn Bhd

No.6, Jalan TTC 6, Taman Teknologi Cheng,

Cheng, 75250 Melaka, Malaysia

+606 334 0975 .

Supplier Remel

12076 Santa Fe Drive Lenexa,

KS 66215 United States Telephone: 1-800-255-6730

Fax:1-800-621-8251

E-mail address mbd-sds@thermofisher.com

Emergency Telephone Number

(603) 5122 8888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Specific target organ toxicity - (single exposure)	Category 2 (H371)
	Category 3 (H336)

Label Elements



Signal Word Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H371 - May cause damage to organs

H336 - May cause drowsiness or dizziness

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P280 - Wear eye protection/ face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

Other Hazards

EUH066 - Repeated exposure may cause skin dryness or cracking

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Acetone	67-64-1	50
Ethyl alcohol	64-17-5	47.5
Methyl alcohol	67-56-1	2.5

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice If symptoms persist, call a physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get

medical attention.

Skin Contact If skin irritation persists, call a physician. Wash off immediately with plenty of water for at

least 15 minutes.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if

symptoms occur.

Self-Protection of the First Aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like

headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

None under normal use conditions.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Acetone		TWA: 250 ppm	(Vacated) TWA: 750 ppm
		STEL: 500 ppm	(Vacated) TWA: 1800 mg/m ³
			(Vacated) STEL: 2400 mg/m ³
			(Vacated) STEL: 1000 ppm
			TWA: 1000 ppm
			TWA: 2400 mg/m ³
Ethyl alcohol		STEL: 1000 ppm	(Vacated) TWA: 1000 ppm
			(Vacated) TWA: 1900 mg/m ³
			TWA: 1000 ppm
			TWA: 1900 mg/m ³
Methyl alcohol		TWA: 200 ppm	(Vacated) TWA: 200 ppm
		STEL: 250 ppm	(Vacated) TWA: 260 mg/m ³
		Skin	(Vacated) STEL: 250 ppm
			(Vacated) STEL: 325 mg/m ³
			Skin
			TWA: 200 ppm
			TWA: 260 mg/m ³

Component	European Union	The United Kingdom	Germany		
Acetone	Acetone TWA: 500 ppm (8h)		TWA: 500 ppm		
	TWA: 1210 mg/m ³ (8h)	TWA: 1210 mg/m ³	TWA: 1200 mg/m ³		
		STEL: 1500 ppm	-		
		STEL: 3620 mg/m ³			
Ethyl alcohol		TWA: 1000 ppm TWA; 1920 mg/m ³	200 ppm TWA MAK; 380 mg/m ³		
		TWA	TWA MAK		
		WEL - STEL: 3000 ppm STEL;			
		5760 mg/m ³ STEL			
Methyl alcohol	TWA: 200 ppm 8 hr	WEL - TWA: 200 ppm TWA; 266	100 ppm TWA MAK; 130 mg/m ³		
	TWA: 260 mg/m ³ 8 hr	mg/m³ TWA	TWA MAKSkin absorber		
	Skin	WEL - STEL: 250 ppm STEL; 333			
		mg/m ³ STEL			

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye ProtectionGogglesHand ProtectionProtective glovesSkin and body protectionLong sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators

To protect the wearer, respiratory protective equipment must be the correct fit and be used

Liquid

(Air = 1.0)

and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures When using do not eat, drink or smoke Provide regular cleaning of equipment, work area

and clothing

Environmental exposure controls
Do not allow material to contaminate ground water system Prevent product from entering

drain

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Clear
Physical State Liquid
Odor pungent

Odor Threshold No data available No information available

Melting Point/Range -116 °C / -176.8 °F Softening Point No data available

Boiling Point/Range No information available °C / °F

Flash Point 10 °C / 50 °F Method - No information available

Evaporation Rate No data available Flammability (solid,gas) Not applicable

Explosion Limits

No data available

Vapor Pressure
No data available
Vapor Density
No data available

Specific Gravity / Density No data available 0.77 - 0.8 @ 25°C

Bulk Density Not applicable Liquid

Water Solubility
Solubility in other solvents
No information available
No information available

Partition Coefficient (n-octanol/water)

Componentlog PowAcetone-0.24Ethyl alcohol-0.32Methyl alcohol-0.74

Autoignition Temperature
Decomposition Temperature
Viscosity

No data available
No data available
No data available

Explosive Properties

Oxidizing Properties No information available

Properties Vapors may form explosive mixtures with air

VOC Content(%) 100

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

No information available. None under normal processing.

Conditions to Avoid

Heating in air. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

None known.

Hazardous Decomposition Products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Acute Toxicity

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit)	76 mg/l, 4 h, (rat)
		> 7400 mg/kg (rat)	
Ethyl alcohol	LD50 = 7060 mg/kg (Rat)		20000 ppm/10H (Rat)
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h

Chronic Toxicity Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen Ethanol has been shown to be carcinogenic in long-term studies only when consumed and abused as an alcoholic beverage. This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans

(Group 2A) or possibly carcinogenic to humans (Group 2B)

Sensitization **Mutagenic Effects Reproductive Effects Developmental Effects** No information available No information available No information available No information available

Target Organs None known.

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting.

SECTION 12: ECOLOGICAL INFORMATION

<u>Ecotoxicity effects</u>

Contains a substance which is:. Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Acetone		EC50 = 12700 mg/L/48h EC50 = 12600 mg/L/48h	() ,	EC50 = 14500 mg/L/15 min
	Leuciscus idus: LC50 = 11300 mg/L/48h Salmo gairdneri: LC50 = 6100 mg/L/24h			
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h		EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min

Persistence and degradability No information available

reconstruction and degradability	
Component	Degradability
Acetone 67-64-1 (50)	91 % (28 d) (OECD 301 B)
Methyl alcohol	DT50 ~ 17.2d >94% after 20d

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential No information available

Component	log Pow	Bioconcentration factor (BCF)
Acetone	-0.24	0.69 dimensionless
Ethyl alcohol	-0.32	No data available
Methyl alcohol	-0.74	<10 dimensionless

Mobility in soil No information available. .

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

SAFETY DATA SHEET

Gram Decolorizer Revision Date 29-Mar-2023

Waste from Residues/Unused

Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on

waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers

retain product residue, (liquid and/or vapor), and can be dangerous Keep product and

empty container away from heat and sources of ignition

Other Information Do not flush to sewer Waste codes should be assigned by the user based on the

application for which the product was used Can be landfilled or incinerated, when in

compliance with local regulations

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1993 Hazard Class 3 Packing Group II

Proper Shipping Name Flammable liquid, n.o.s.

Road and Rail Transport Not regulated

IATA

UN-No UN1993
Hazard Class 3
Packing Group II

Proper Shipping Name Flammable liquid, n.o.s.

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Acetone	-	Х	Х	Х	X	X	Χ	Χ	KE-29367
Ethyl alcohol	=	Х	Х	Х	X	X	Χ	Χ	KE-13217
Methyl alcohol	-	Х	Х	Х	X	X	Χ	Χ	KE-23193

	Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Г	Acetone				Annex I - Y42
	Ethyl alcohol				Annex I - Y42
	Methyl alcohol	500 tonne	5000 tonne		

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b)

Revision Date 29-Mar-2023

EINECS/ELINCS - European Inventory of Existing Commercial Chemical DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances/EU List of Notified Chemical Substances

Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances **KECL** - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

TWA - Time Weighted Average

ACGIH - American Conference of Governmental Industrial Hygienists RPE - Respiratory Protective Equipment

IARC - International Agency for Research on Cancer

LC50 - Lethal Concentration 50% POW - Partition coefficient Octanol:Water LD50 - Lethal Dose 50% EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

MARPOL - International Convention for the Prevention of Pollution from Ships

OECD - Organisation for Economic Co-operation and Development

ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)

BCF - Bioconcentration factor

Key literature references and sources for data

https://echa.europa.eu/information-on-chemicals Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date 29-Mar-2023

Revision Summary SDS sections updated.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet