

Creation Date 14-Feb-2022

Revision Date 14-Feb-2022

Revision Number 1

COVER SHEET FOR KIT

Company	Thermo Fisher (Kandel) GmbH Erlenbachweg 2, 76870 Kandel, Germany Tel: +49 (0) 721 84007 280 Fax: +49 (0) 721 84007 300
Emergency Telephone Number	Swiss distributor - Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach Tel: +41 (0) 56 618 41 11 e-mail - infoch@thermofisher.com Carechem 24: +44 (0) 1235 239 670 (Multi-language emergency number) Poison Information Center Mainz www.giftinfo.uni-mainz.de Telephone: +49(0)6131/19240 Exclusively for customers in Austria: Poison Information Center (VIZ) Emergency call 0-24 clock: +43 1 406 43 43 Office hours: Monday to Friday, 8am to 4pm, tel: +43 1 406 68 98 For customers in Switzerland: Tox Info Suisse Emergency Number: 145 (24hr) Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad) Chemtrec (24h) Toll-Free: 0800 564 402 Chemtrec Local: +41-43 508 20 11 (Zurich) tech@alfa.com www.alfa.com Product safety Tel + +049 (0) 7275 988687-0
E-mail address	
Product Description: Cat No. : Recommended Use	Magnesium oxide, 2 part ceramic adhesive paste 43135 Laboratory chemicals adhesives
Description Transport information	43135-P & 43135-L Not regulated

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Magnesium oxide, 2 part ceramic adhesive paste
Cat No. : 43135

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company	Thermo Fisher (Kandel) GmbH Erlenbachweg 2, 76870 Kandel, Germany Tel: +49 (0) 721 84007 280 Fax: +49 (0) 721 84007 300 Swiss distributor - Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach Tel: +41 (0) 56 618 41 11 e-mail - infoch@thermofisher.com
E-mail address	tech@alfa.com www.alfa.com Product safety Tel + +049 (0) 7275 988687-0

1.4. Emergency telephone number

Carechem 24: **+44 (0) 1235 239 670** (Multi-language emergency number)
Poison Information Center Mainz
www.giftinfo.uni-mainz.de
Telephone: +49(0)6131/19240

Exclusively for customers in Austria:
Poison Information Center (VIZ)
Emergency call 0-24 clock: **+43 1 406 43 43**
Office hours: Monday to Friday, 8am to 4pm, tel: +43 1 406 68 98

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Specific target organ toxicity - (single exposure)	Category 3 (H335)

Environmental hazards

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

- H315 - Causes skin irritation
- H318 - Causes serious eye damage
- H335 - May cause respiratory irritation

Precautionary Statements

- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

Toxic to terrestrial vertebrates

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Water	7732-18-5	231-791-2	40 - 60	-
Sodium silicate	1344-09-8	EEC No. 215-687-4	40 - 60	Skin Irrit. 2 (H315) Eye Irrit. 1 (H318) STOT SE 3 (H335)

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 12

Switzerland - Storage of hazardous substances

Storage class - SC 10/12
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

exposure to chemical and biological agents.

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Sodium silicate 1344-09-8 (40 - 60)				DNEL = 1.59mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Sodium silicate 1344-09-8 (40 - 60)				DNEL = 5.61mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Sodium silicate 1344-09-8 (40 - 60)	PNEC = 7.5mg/L		PNEC = 7.5mg/L	PNEC = 348mg/L	

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Sodium silicate 1344-09-8 (40 - 60)	PNEC = 1mg/L				

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber Nitrile rubber Neoprene PVC	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced Recommended Filter type: Particulates filter conforming to EN 143
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Recommended half mask:- Particle filtering: EN149:2001 When RPE is used a face piece Fit Test should be conducted
Environmental exposure controls	No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Cloudy white	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	100 °C / 212 °F	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	Not applicable	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	11-11.5	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Vapor Pressure	No data available	
Density / Specific Gravity	1.3 -1.5	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

VOC Content(%)	0
-----------------------	---

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
---------------------------------	---------------------------

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

Hazardous Reactions None under normal processing.

10.4. Conditions to avoid
Incompatible products. Excess heat.

10.5. Incompatible materials
Metals. Ammonia. Strong acids.

10.6. Hazardous decomposition products
None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Based on ATE data, the classification criteria are not met
ATE = 2306 mg/kg
Dermal Based on ATE data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	-	-
Sodium silicate	1153 mg/kg (Rat) 1960 mg/kg (Rat)	LD50 = 4640 mg/kg (rabbit)	-

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;
Respiratory No data available
Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available
There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3
Results / Target organs Respiratory system.

(i) STOT-repeated exposure; No data available
Target Organs None known.

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed No information available.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Sodium silicate	LC50: = 3185 mg/L, 96h semi-static (Brachydanio rerio) LC50: 301 - 478 mg/L, 96h (Lepomis macrochirus)		

12.2. Persistence and degradability

Persistence

Miscible with water, Persistence is unlikely, based on information available.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

12.4. Mobility in soil

The product is water soluble, and may spread in water systems Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Do not flush to sewer.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

ADR

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

IATA

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

No hazards identified

14.6. Special precautions for user

No special precautions required

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
Sodium silicate	1344-09-8	215-687-4	-	-	X	X	KE-31002	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
-----------	--------	------	---	-----	------	------	-------	-------

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

Water	7732-18-5	X	ACTIVE	X	-	X	X	X
Sodium silicate	1344-09-8	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Water	7732-18-5	Not applicable	Not applicable
Sodium silicate	1344-09-8	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Sodium silicate	WGK1	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste

Revision Date 14-Feb-2022

WEL - Workplace Exposure Limit
ACGIH - American Conference of Governmental Industrial Hygienists
DNEL - Derived No Effect Level
RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%
NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
ATE - Acute Toxicity Estimate
VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By	Health, Safety and Environmental Department
Creation Date	14-Feb-2022
Revision Date	14-Feb-2022
Revision Summary	SDS sections updated.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Creation Date 02-Aug-2018

Revision Date 14-Feb-2022

Revision Number 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Magnesium oxide, 2 part ceramic adhesive paste (P)**
Cat No. : **43135-P**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address tech@alfa.com
www.alfa.com
Product safety Tel + +049 (0) 7275 988687-0

1.4. Emergency telephone number

Carechem 24: **+44 (0) 1235 239 670** (Multi-language emergency number)
Poison Information Center Mainz
www.giftinfo.uni-mainz.de
Telephone: +49(0)6131/19240

Exclusively for customers in Austria:
Poison Information Center (VIZ)
Emergency call 0-24 clock: **+43 1 406 43 43**
Office hours: Monday to Friday, 8am to 4pm, tel: +43 1 406 68 98

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Based on available data, the classification criteria are not met

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements

None required

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Magnesium oxide	1309-48-4	215-171-9	70 - 90	-
Aluminum oxide (Al ₂ O ₃)	1344-28-1	215-691-6	10 - 30	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Self-Protection of the First Aider No special precautions required.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Metal oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

6.2. Environmental precautions

Should not be released into the environment. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Avoid dust formation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 13

Switzerland - Storage of hazardous substances

Storage class - SC 11/13
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Magnesium oxide		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA / VME: 10 mg/m ³ (8 heures).	TWA: 10 mg/m ³ 8 uren	TWA / VLA-ED: 10 mg/m ³ (8 horas)
Aluminum oxide (Al ₂ O ₃)		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA / VME: 10 mg/m ³ (8 heures).	TWA: 1 mg/m ³ 8 uren	TWA / VLA-ED: 10 mg/m ³ (8 horas) TWA / VLA-ED: 1 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Magnesium oxide		TWA: 1.25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 0.3 mg/m ³ (8 Stunden). MAK multiplied by the material density TWA: 4 mg/m ³ (8 Stunden). MAK Höhepunkt: 2.4 mg/m ³	TWA: 10 mg/m ³ 8 horas		
Aluminum oxide (Al ₂ O ₃)		TWA: 1.25 mg/m ³ (8 Stunden). AGW -	TWA: 10 mg/m ³ 8 horas		

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

		exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 4 mg/m ³ (8 Stunden). MAK TWA: 1.5 mg/m ³ (8 Stunden). MAK			
--	--	---	--	--	--

Component	Austria	Denmark	Switzerland	Poland	Norway
Magnesium oxide	MAK-KZGW: 20 mg/m ³ 15 Minuten MAK-KZGW: 10 mg/m ³ 15 Minuten MAK-TMW: 5 mg/m ³ 8 Stunden MAK-TMW: 10 mg/m ³ 8 Stunden	TWA: 6 mg/m ³ 8 timer	TWA: 3 mg/m ³ 8 Stunden	TWA: 10 mg/m ³ 8 godzinach	TWA: 10 mg/m ³ 8 timer STEL: 20 mg/m ³ 15 minutter. set equal to the limit value for Nuisance dust;value calculated
Aluminum oxide (Al ₂ O ₃)	MAK-KZGW: 10 mg/m ³ 15 Minuten MAK-TMW: 5 mg/m ³ 8 Stunden	TWA: 5 mg/m ³ 8 timer TWA: 2 mg/m ³ 8 timer	STEL: 24 mg/m ³ 15 Minuten TWA: 3 mg/m ³ 8 Stunden	TWA: 2.5 mg/m ³ 8 godzinach TWA: 1.2 mg/m ³ 8 godzinach	TWA: 10 mg/m ³ 8 timer STEL: 20 mg/m ³ 15 minutter. set equal to the limit value for Nuisance dust;value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Magnesium oxide	TWA: 10.0 mg/m ³	TWA-GVI: 4 mg/m ³ 8 satima. fume; respirable dust TWA-GVI: 10 mg/m ³ 8 satima. fume; total dust, inhalable particles	TWA: 4 mg/m ³ 8 hr. respirable dust TWA: 5 mg/m ³ 8 hr. fume TWA: 10 mg/m ³ 8 hr. total inhalable dust STEL: 10 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min STEL: 30 mg/m ³ 15 min		TWA: 5 mg/m ³ 8 hodinách. fume Ceiling: 10 mg/m ³ fume
Aluminum oxide (Al ₂ O ₃)		TWA-GVI: 10 mg/m ³ 8 satima. total dust, inhalable particles TWA-GVI: 4 mg/m ³ 8 satima. respirable dust			

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Magnesium oxide			TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 6 mg/m ³ 8 óraban. AK	TWA: 6 mg/m ³ 8 klukkustundum. Mg Ceiling: 12 mg/m ³ Mg
Aluminum oxide (Al ₂ O ₃)	TWA: 10 mg/m ³ 8 tundides. total dust TWA: 4 mg/m ³ 8 tundides. respirable dust		TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³ 8 óraban. AK Al TWA: 2 mg/m ³ 8 óraban. AK Al	TWA: 10 mg/m ³ 8 klukkustundum. Al Ceiling: 20 mg/m ³ Al

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Magnesium oxide		TWA: 4 mg/m ³ IPRD			TWA: 5 mg/m ³ 8 ore STEL: 15 mg/m ³ 15 minute
Aluminum oxide (Al ₂ O ₃)	TWA: 6 mg/m ³	TWA: 5 mg/m ³ inhalable fraction IPRD Al TWA: 2 mg/m ³ respirable fraction IPRD Al			TWA: 2 mg/m ³ 8 ore TWA: 3 mg/m ³ 8 ore TWA: 1 mg/m ³ 8 ore STEL: 5 mg/m ³ 15 minute STEL: 10 mg/m ³ 15 minute STEL: 3 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Magnesium oxide	MAC: 4 mg/m ³	TWA: 10 mg/m ³ respirable fraction, dust			

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

		TWA: 4 mg/m ³ inhalable fraction, fume			
Aluminum oxide (Al ₂ O ₃)	TWA: 6 mg/m ³ 0043 in the form of disintegration aerosol TWA: 1 mg/m ³ 0045 containing up to 20% Cr ₂ O ₃ ; catalyst IM-2201 MAC: 3 mg/m ³	TWA: 4 mg/m ³ inhalable dust TWA: 1.5 mg/m ³ respirable dust		TLV: 5 mg/m ³ 8 timmar. AI NGV TLV: 2 mg/m ³ 8 timmar. AI NGV	

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Aluminum oxide (Al ₂ O ₃) 1344-28-1 (10 - 30)				DNEL = 0.84mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Aluminum oxide (Al ₂ O ₃) 1344-28-1 (10 - 30)			DNEL = 3mg/m ³ DNEL = 15.63mg/m ³	DNEL = 3mg/m ³ DNEL = 15.63mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Aluminum oxide (Al ₂ O ₃) 1344-28-1 (10 - 30)	PNEC = 0.3136µg/L		PNEC = 3.136µg/L	PNEC = 20mg/L	

8.2. Exposure controls

Engineering Measures

None under normal use conditions.

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments (minimum requirement)
Natural rubber	See manufacturers	-		

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

Nitrile rubber Neoprene PVC	recommendations	EN 374
-----------------------------------	-----------------	--------

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection No protective equipment is needed under normal use conditions.

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Particle filter

Small scale/Laboratory use Maintain adequate ventilation

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Powder Solid	
Appearance	White	
Odor	Odorless	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	3600 °C / 6512 °F	
Flammability (liquid)	Not applicable	Solid
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	Not applicable	
Decomposition Temperature	No data available	
pH	8 - 10.5	
Viscosity	Not applicable	Solid
Water Solubility	Insoluble in water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	3.0 - 3.90 g/cm3	
Vapor Density	Not applicable	Solid
Particle characteristics	No data available	

9.2. Other information

Evaporation Rate Not applicable - Solid

SECTION 10: STABILITY AND REACTIVITY

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization

No information available.

Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

Interhalogens. Oxidizing agent.

10.6. Hazardous decomposition products

Metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

No data available

Inhalation

No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Magnesium oxide	LD50 = 3990 mg/kg (Rat) LD50 = 3870 mg/kg (Rat)	-	-
Aluminum oxide (Al ₂ O ₃)	> 5000 mg/kg (Rat) (OECD Guideline 401)	-	> 2.3 mg/l 4 h (OECD Guideline 403)

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
-----------	----	----	---------	------

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

Aluminum oxide (Al ₂ O ₃)			Cat. 2 (Fibre dust)	
--	--	--	---------------------	--

(g) reproductive toxicity;	No data available
(h) STOT-single exposure;	No data available
(i) STOT-repeated exposure;	No data available
Target Organs	No information available.
(j) aspiration hazard;	Not applicable Solid
Symptoms / effects, both acute and delayed	No information available.

11.2. Information on other hazards

Endocrine Disrupting Properties	Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.
---------------------------------	---

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects	Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants.
---------------------	---

12.2. Persistence and degradability

Persistence	May persist, based on information available.
Degradability	Not relevant for inorganic substances.

<u>12.3. Bioaccumulative potential</u>	May have some potential to bioaccumulate
--	--

<u>12.4. Mobility in soil</u>	Is not likely mobile in the environment due its low water solubility.
-------------------------------	---

<u>12.5. Results of PBT and vPvB assessment</u>	No data available for assessment.
---	-----------------------------------

12.6. Endocrine disrupting properties

Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors
---------------------------------	---

12.7. Other adverse effects

Persistent Organic Pollutant	This product does not contain any known or suspected substance
Ozone Depletion Potential	This product does not contain any known or suspected substance

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.
Contaminated Packaging	Empty remaining contents. Dispose of in accordance with local regulations. Do not re-use empty containers.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Waste codes should be assigned by the user based on the application for which the product was used.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO Not regulated

14.1. UN number
14.2. UN proper shipping name
14.3. Transport hazard class(es)
14.4. Packing group

ADR Not regulated

14.1. UN number
14.2. UN proper shipping name
14.3. Transport hazard class(es)
14.4. Packing group

IATA Not regulated

14.1. UN number
14.2. UN proper shipping name
14.3. Transport hazard class(es)
14.4. Packing group

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Magnesium oxide	1309-48-4	215-171-9	-	-	X	X	KE-22728	X	X
Aluminum oxide (Al ₂ O ₃)	1344-28-1	215-691-6	-	-	X	X	KE-01012	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Magnesium oxide	1309-48-4	X	ACTIVE	X	-	X	X	X
Aluminum oxide (Al ₂ O ₃)	1344-28-1	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Magnesium oxide	1309-48-4	Not applicable	Not applicable
Aluminum oxide (Al ₂ O ₃)	1344-28-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Magnesium oxide	WGK1	
Aluminum oxide (Al ₂ O ₃)	nwg	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Magnesium oxide 1309-48-4 (70 - 90)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Prepared By Health, Safety and Environmental Department

Creation Date 02-Aug-2018

Revision Date 14-Feb-2022

Revision Summary Initial Release.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

SAFETY DATA SHEET

Magnesium oxide, 2 part ceramic adhesive paste (P)

Revision Date 14-Feb-2022

materials or in any process, unless specified in the text

End of Safety Data Sheet