

Classified as hazardous in accordance with the criteria of EPA New Zealand

Section 1 - Identification

Product Identifier

Product Name	<u>Toluene, Semiconductor Grade</u>
CAS No	108-88-3
Synonyms	Tol; Methylbenzene
Molecular Formula	C7 H8
Molecular Weight	92.14
Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

Product Code	19399
Address	Thermo Fisher Scientific New Zealand Ltd 244 Bush Road, Albany, Auckland, New Zealand
Emergency Tel.	CHEMTREC® 09 980 6780 or +64 9 980 6780
Telephone / Fax Numbers	Tel: 09 980 6700 Fax: 09 980 6788
E-mail address	<u>ANZinfo@thermofisher.com</u>

Section 2 - Hazard(s) Identification

Classification under Work Safe New Zealand

Classified as hazardous in accordance with the criteria of EPA New Zealand

HSNO Approval Number **HSR001227**

GHS Classification

Physical hazards

Flammable liquids

Category 2

Health hazards

Aspiration Toxicity	Category 1
Acute Oral Toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity - (single exposure)	Category 3
Specific target organ toxicity - (repeated exposure)	Category 2

Environmental hazards

Chronic aquatic toxicity

Category 3

Label Elements**Signal Word****Danger****Hazard Statements**

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects
H319 - Causes serious eye irritation
H302 + H332 - Harmful if swallowed or if inhaled

Precautionary Statements**Prevention**

P202 - Do not handle until all safety precautions have been read and understood
P201 - Obtain special instructions before use
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P242 - Use non-sparking tools
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P240 - Ground and bond container and receiving equipment
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
P243 - Take action to prevent static discharges
P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection/ face protection

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308 + P313 - IF exposed or concerned: Get medical advice/attention
P331 - Do NOT induce vomiting
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Toluene	108-88-3	<=100

Section 4 - First Aid Measures

Description of first aid measures

General Advice	If symptoms persist, call a physician.
New Zealand Emergency Tel.	CHEMTREC® 09 980 6780 or +64 9 980 6780
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Difficulty in breathing. Causes central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically. Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream.

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures**Emergency procedures**

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Precautions to prevent secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling**Advice on safe handling**

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

Conditions for Safe Storage, Including any Incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

Incompatible Materials

Strong oxidizing agents. Strong acids. Strong bases. Halogenated compounds.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Control parameters**Exposure limits**

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

Component	New Zealand WEL	Australia	ACGIH TLV	The United Kingdom
Toluene	TWA: 20 ppm TWA: 75 mg/m ³	STEL: 150 ppm STEL: 574 mg/m ³	TWA: 20 ppm	STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min

	STEL: 100 ppm STEL: 377 mg/m ³ Skin	TWA: 50 ppm TWA: 191 mg/m ³		TWA: 50 ppm 8 hr TWA: 191 mg/m ³ 8 hr Skin
--	--	---	--	---

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

ACGIH - American Conference of Governmental Industrial Hygienists (ACGIH) TLVs® and BEIs®- Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices. 2022 Edition

Component	New Zealand	Australia	ACGIH - Biological Exposure Indices	United Kingdom
Toluene	0.03 mg/L (urine) end of exposure or end of shift (Toluene) 0.3 mg/g creatinine (urine) end of exposure or end of shift (O-Cresol)		0.02 mg/L Medium: blood Time: prior to last shift of workweek Determinant: Toluene 0.03 mg/L Medium: urine Time: end of shift Determinant: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Determinant: o-Cresol with hydrolysis	

Appropriate engineering controls**Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Individual protection measures, such as personal protective equipment**Eye Protection**

Wear safety glasses with side shields (or goggles) (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Viton (R).	< 240 minutes	0.30 mm	AS/NZS 2161	Permeation rate 68 µg/cm ² /min As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Viton (R)	> 480 minutes	0.70 mm		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Long sleeved clothing

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.
Environmental exposure controls	Prevent product from entering drains. Do not allow material to contaminate ground water system.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	aromatic	
Odor Threshold	1.74 ppm	
pH	No information available	
Melting Point/Range	-95 °C / -139 °F	
Softening Point	No data available	
Boiling Point/Range	111 °C / 231.8 °F	@ 760 mmHg
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.2 vol% Upper 7 vol%	
Flash Point	4 °C / 39.2 °F	Method - No information available
Autoignition Temperature	535 °C / 995 °F	
Decomposition Temperature	No data available	
Viscosity	0.6 mPa.s @ 20 °C	
Water Solubility	practically insoluble 0.5 g/L @ 20°C	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Toluene	2.73	
Vapor Pressure	29 mbar @ 20 °C	
Density / Specific Gravity	0.866	
Bulk Density	Not applicable	Liquid
Vapor Density	3.1	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

Other information

Molecular Formula	C7 H8
Molecular Weight	92.14
Explosive Properties	Not explosive Vapors may form explosive mixtures with air
Oxidizing Properties	Not oxidising
Evaporation Rate	2.4 (Butyl acetate = 1.0)

Section 10 - Stability and Reactivity

Reactivity	None known, based on information available
Stability	Stable under normal conditions.
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

Conditions to Avoid Incompatible products, Excess heat, Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids, Strong bases, Halogenated compounds.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂).

Section 11 - Toxicological Information

Acute Effects

Information on likely routes of exposure

Product Information

Inhalation Irritating to respiratory system. May be harmful if inhaled. May cause drowsiness and dizziness.

Eyes Irritating to eyes.

Skin Irritating to skin. Can be absorbed through skin. May be harmful in contact with skin.

Ingestion Aspiration hazard if swallowed - can enter lungs and cause damage. May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful if swallowed. Potential for aspiration if swallowed.

Numerical measures of toxicity

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met

Dermal Based on available data, the classification criteria are not met

Inhalation Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

(b) skin corrosion/irritation;

Test method Category 2
OECD 404

Test species rabbit

Observational endpoint Irritating to skin

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met

Skin Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

Reproductive Effects Category 2
Experiments have shown reproductive toxicity effects on laboratory animals

Developmental Effects Developmental effects have occurred in experimental animals

Teratogenicity Possible risk of harm to the unborn child

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS)

(i) STOT-repeated exposure; Category 2

Target Organs Liver, Kidney, Central nervous system (CNS), Blood, spleen, Neuropsychological effects, Eyes, Ears.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed

Causes central nervous system depression. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Section 12 - Ecological Information

Ecotoxicity

Aquatic ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	EC50 = 19.7 mg/L 30 min

Terrestrial ecotoxicity

There is no data for this product

Persistence and Degradability

Readily biodegradable

Persistence

Persistence is unlikely.

Component	Degradability
Toluene 108-88-3 (<=100)	86% (20d)

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative Potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Toluene	2.73	90

Mobility

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Spillage unlikely to penetrate soil. The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility.

Other adverse effects

Endocrine Disruptor Information Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected endocrine disruptors
This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste treatment methods

Waste from Residues/Unused Products	Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
Other Information	Disposal agencies or waste contractors must comply with the New Zealand Hazardous Substances (Disposal) Regulations . Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

Section 14 - Transport Information

Component	Hazchem Code
Toluene 108-88-3 (<=100)	3YE

NZS 5433:2020

UN-No	UN1294
Proper Shipping Name	TOLUENE
Hazard Class	3
Packing Group	II

IATA

UN-No	UN1294
Proper Shipping Name	TOLUENE
Hazard Class	3
Packing Group	II

IMDG/IMO

UN-No	UN1294
Proper Shipping Name	TOLUENE
Hazard Class	3
Packing Group	II

Environmental hazards	No hazards identified
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable, packaged goods
Special Precautions	No special precautions required. Please refer to the applicable dangerous goods regulations for additional information.
Additional information	None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number	HSR001227
-----------------------------	-----------

National Regulations

Any applicable tolerable exposure limits and environmental exposure limits according to the EPA Controls for Hazardous Substances are listed below

Component	Tolerable Exposure Limit (TEL) Air	Tolerable Exposure Limit (TEL) Water	Tolerable Exposure Limit (TEL) Surface	Environmental Exposure Limits (EEL)
Toluene	400 µg/m ³	0.8 mg/L		330 µg/L (Water)

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information. Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information.

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licensing requirements when they apply.

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

International Inventories

New Zealand (NZIoC), Australia (AICS), Europe (EINECS/ELINCS/NLP), Korea (KECL), China (IECSC), Taiwan (TCSI), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	NZIoC	AICS	EINECS	ELINCS	NLP	KECL	IECSC	TCSI
Toluene	108-88-3	X	X	203-625-9	-	-	KE-33936	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	PICCS	ISHL	ENCS
Toluene	108-88-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Section 16 - Other Information

This safety data sheet complies with the requirements of the EPA Hazardous Substances (Hazard Classification) Notice 2020 and WorkSafe New Zealand Regulations**Legend**

NZIoC - New Zealand Inventory of Chemicals	AICS - Australian Inventory of Chemical Substances
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List	ENCS - Japanese Existing and New Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances	KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances	CAS - Chemical Abstracts Service
TWA - Time Weighted Average	ACGIH - American Conference of Governmental Industrial Hygienists
IARC - International Agency for Research on Cancer	PNEC - Predicted No Effect Concentration
NZS 5433:2020 - Transport of Dangerous Goods on Land	OECD - Organisation for Economic Co-operation and Development
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association	IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
MARPOL - International Convention for the Prevention of Pollution from Ships	ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail
LD50 - Lethal Dose 50%	LC50 - Lethal Concentration 50%
EC50 - Effective Concentration 50%	ATE - Acute Toxicity Estimate
WEL - Workplace Exposure Limit	RPE - Respiratory Protective Equipment
DNEL - Derived No Effect Level	NOEC - No Observed Effect Concentration
POW - Partition coefficient Octanol:Water	BCF - Bioconcentration factor
vPvB - very Persistent, very Bioaccumulative	PBT - Persistent, Bioaccumulative, Toxic
VOC - (Volatile Organic Compound)	

Key literature references and sources for data

HSNO classifications provided in the New Zealand Chemical Classification Information Database (CCID).

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

EPA Guide to classifying hazardous substances in New Zealand

EPA - Assigning a product to an existing HSNO approval guide

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Revision Date	13-Mar-2023
Revision Summary	Not applicable

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet