

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**
**Product Identifier**

Perihal Produk:

Product Description:

Cat No. :

**Petroleum Eter 60-80 °C**
**Petroleum ether 60-80°C**

 P/1800/PB17, P/1800/15, P/1800/17, P/1800/25, P/1800/27, P/1800/21RSS,  
 P/1800/24RSS, P/1800/25RSS, P/1800/34RSS, P/1800/27RSS

Synonyms

Lignoine

**Relevant identified uses of the substance or mixture and uses advised against**

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

Company

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd  
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,  
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,  
 Selangor Darul Ehsan, Malaysia.  
 Main line: +60 3-5525 7888

Supplier

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

 Tel: +03-5525 7888  
 CHEMTREC Malaysia **1-800-815-308** (Malay)  
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

**SECTION 2: HAZARDS IDENTIFICATION**
**Classification of the substance or mixture**

|                                                    |                   |
|----------------------------------------------------|-------------------|
| Flammable liquids                                  | Category 2 (H225) |
| Aspiration Toxicity                                | Category 1 (H304) |
| Skin Corrosion/Irritation                          | Category 2 (H315) |
| Specific target organ toxicity - (single exposure) | Category 3 (H336) |
| Chronic aquatic toxicity                           | Category 2 (H411) |

**Label Elements**


Signal Word

Danger

# SAFETY DATA SHEET

Petroleum ether 60-80°C

Revision Date 23-Mar-2025

## Hazard Statements

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

## Precautionary Statements

### Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P240 - Ground and bond container and receiving equipment  
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment  
P242 - Use non-sparking tools  
P243 - Take action to prevent static discharges  
P264 - Wash face, hands and any exposed skin thoroughly after handling  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves/protective clothing/eye protection/face protection

### Response

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P312 - Call a POISON CENTER or doctor if you feel unwell  
P331 - Do NOT induce vomiting  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish  
P362 + P364 - Take off contaminated clothing and wash it before reuse

### Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Other Hazards

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Component                                                         | CAS No | Weight % |
|-------------------------------------------------------------------|--------|----------|
| HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | N/A    | > 99     |

## SECTION 4: FIRST AID MEASURES

### Description of first aid measures

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.

#### Ingestion

Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

#### Inhalation

Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately

# SAFETY DATA SHEET

Petroleum ether 60-80°C

Revision Date 23-Mar-2025

if symptoms occur. Aspiration into lungs can produce severe lung damage.

**Self-Protection of the First Aider** Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**Most important symptoms and effects, both acute and delayed**

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

**Extinguishing media**

**Suitable Extinguishing Media**

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

**Extinguishing media which must not be used for safety reasons**

Do not use water jetstream. Do not use a solid water stream as it may scatter and spread fire.

**Special hazards arising from the substance or mixture**

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

**Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

**Advice for fire-fighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal Precautions, Protective Equipment and Emergency Procedures**

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation. Evacuate personnel to safe areas. Do not touch or walk through spilled material.

**Environmental precautions**

Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage.

**Methods and Material for Containment and Cleaning Up**

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

**Reference to Other Sections**

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

# SAFETY DATA SHEET

Petroleum ether 60-80°C

Revision Date 23-Mar-2025

## Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

## Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

## Specific End Uses

Use in laboratories.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

| Component                                                               | European Union                        | The United Kingdom | Germany |
|-------------------------------------------------------------------------|---------------------------------------|--------------------|---------|
| HYDROCARBONS, C6-C7,<br>n-alkanes, isoalkanes, cyclics, <5%<br>n-hexane | TWA - 8 Hrs<br>1200 mg/m <sup>3</sup> |                    |         |

### Exposure Controls

#### Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Wear safety glasses with side shields (or goggles)

#### Hand Protection

Protective gloves

#### Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

#### Recommended Filter type:

low boiling organic solvent Type AX Brown conforming to EN371

### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

### Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system Local authorities should be advised if significant spillages cannot be contained

# SAFETY DATA SHEET

Petroleum ether 60-80°C

Revision Date 23-Mar-2025

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|                                         |                                              |                                             |
|-----------------------------------------|----------------------------------------------|---------------------------------------------|
| Appearance                              | Colorless                                    |                                             |
| Physical State                          | Liquid                                       |                                             |
| Odor                                    | Petroleum distillates                        |                                             |
| Odor Threshold                          | No data available                            |                                             |
| pH                                      | No information available                     |                                             |
| Melting Point/Range                     | No data available                            |                                             |
| Softening Point                         | No data available                            |                                             |
| Boiling Point/Range                     | 60 - 80 °C / 140 - 176 °F                    |                                             |
| Flash Point                             | < 0 °C / < 32 °F                             | Method - No information available           |
| Evaporation Rate                        | 2                                            | (Ether = 1.0)                               |
| Flammability (solid,gas)                | Not applicable                               | Liquid                                      |
| Explosion Limits                        | <b>Lower</b> 0.8 vol%<br><b>Upper</b> 8 vol% |                                             |
| Vapor Pressure                          | 155 hPa                                      |                                             |
| Vapor Density                           | 3.0                                          | (Air = 1.0)                                 |
| Specific Gravity / Density              | 0.670                                        |                                             |
| Bulk Density                            | Not applicable                               | Liquid                                      |
| Water Solubility                        | Insoluble                                    |                                             |
| Solubility in other solvents            | No information available                     |                                             |
| Partition Coefficient (n-octanol/water) |                                              |                                             |
| Autoignition Temperature                | 240 °C / 464 °F                              |                                             |
| Decomposition Temperature               | No data available                            |                                             |
| Viscosity                               | 0.5 mm <sup>2</sup> /s @ 20 °C               |                                             |
| Explosive Properties                    |                                              | Vapors may form explosive mixtures with air |
| Oxidizing Properties                    | No information available                     |                                             |

## SECTION 10: STABILITY AND REACTIVITY

### Reactivity

None known, based on information available.

### Chemical Stability

Stable under normal conditions.

### Possibility of Hazardous Reactions

|                          |                                          |
|--------------------------|------------------------------------------|
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Hazardous Reactions      | None under normal processing.            |

# SAFETY DATA SHEET

Petroleum ether 60-80°C

Revision Date 23-Mar-2025

## Conditions to Avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

## Incompatible Materials

Strong oxidizing agents. Strong acids.

## Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

#### Product Information

##### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

### Toxicology data for the components

| Component                                                         | LD50 Oral               | LD50 Dermal             | LC50 Inhalation                         |
|-------------------------------------------------------------------|-------------------------|-------------------------|-----------------------------------------|
| HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | LD50 > 5840 mg/kg (rat) | LD50 > 2920 mg/kg (rat) | LC50 > 25200 mg/m <sup>3</sup> (rat) 4h |

##### (b) skin corrosion/irritation;

Category 2

##### (c) serious eye damage/irritation;

Based on available data, the classification criteria are not met

##### (d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

##### (e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

##### (f) carcinogenicity;

Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

##### (g) reproductive toxicity;

Based on available data, the classification criteria are not met

##### (h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

##### (i) STOT-repeated exposure;

Based on available data, the classification criteria are not met

Target Organs

None known.

# SAFETY DATA SHEET

Petroleum ether 60-80°C

Revision Date 23-Mar-2025

(j) aspiration hazard; Category 1

**Symptoms / effects, both acute and delayed** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

**Ecotoxicity effects** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

| Component                                                         | Freshwater Fish                                                                                                        | Water Flea                                                         | Freshwater Algae | Microtox                                                  |
|-------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|------------------|-----------------------------------------------------------|
| HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | LC50 96 hours 11.4 mg/l Onchorhynchus mykiss (Rainbow trout)<br>28 days 2.04 mg/l Onchorhynchus mykiss (Rainbow trout) | EC50 48 hours 3 mg/l Daphnia magna<br>21 days 1 mg/l Daphnia magna |                  | EC50 72 hours 30-100 mg/l Pseudokirchneriella subcapitata |

**Persistence and degradability** Readily biodegradable  
**Persistence** Persistence is unlikely, based on information available.

| Component                                                                       | Degradability |
|---------------------------------------------------------------------------------|---------------|
| HYDROCARBONS, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane<br>N/A (> 99) | 98% (28 days) |

**Degradation in sewage treatment plant** Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**Bioaccumulative potential** Bioaccumulation is unlikely

**Mobility in soil** The product is insoluble and floats on water. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**Other adverse effects** No information available

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste treatment methods**  
**Waste from Residues/Unused Products** Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

**Other Information** Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not let this chemical enter the environment Do not

# SAFETY DATA SHEET

Petroleum ether 60-80°C

Revision Date 23-Mar-2025

empty into drains

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

|                      |                               |
|----------------------|-------------------------------|
| UN-No                | UN1268                        |
| Hazard Class         | 3                             |
| Packing Group        | II                            |
| Proper Shipping Name | Petroleum distillates, n.o.s. |

### Road and Rail Transport

|                      |                               |
|----------------------|-------------------------------|
| UN-No                | UN1268                        |
| Hazard Class         | 3                             |
| Packing Group        | II                            |
| Proper Shipping Name | Petroleum distillates, n.o.s. |

### IATA

|                      |                               |
|----------------------|-------------------------------|
| UN-No                | UN1268                        |
| Hazard Class         | 3                             |
| Packing Group        | II                            |
| Proper Shipping Name | Petroleum distillates, n.o.s. |

Special Precautions for User No special precautions required

## SECTION 15: REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Note UVCB Hydrocarbons  
CAS No. 64742-49-0: TSCA, DSL, AICS, ENCS, PICCS, CHINA, KECL  
Aromatic content < 0.01%

### National Regulations

|                              |                                                                |
|------------------------------|----------------------------------------------------------------|
| Persistent Organic Pollutant | This product does not contain any known or suspected substance |
| Ozone Depletion Potential    | This product does not contain any known or suspected substance |

## SECTION 16: OTHER INFORMATION

### Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances



# SAFETY DATA SHEET

Petroleum ether 60-80°C

Revision Date 23-Mar-2025

KECL - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

## Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date

23-Mar-2025

Revision Summary

Not applicable.

**In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**