

Creation Date 01-Feb-2010

Revision Date 21-Mar-2024

Revision Number 13

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Formaldehyde solution 35-38%
Cat No. : SP/2298/21, SP/2298/24, SP/2298/25
Synonyms Formalin; Formol; Methanal
Molecular Formula C H₂ O

Unique Formula Identifier (UFI) YKUD-HWHS-AU1X-96JU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road, Loughborough,
Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Acute oral toxicity	Category 3 (H301)
Acute dermal toxicity	Category 3 (H311)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Skin Sensitization	Category 1 (H317)
Germ Cell Mutagenicity	Category 2 (H341)
Carcinogenicity	Category 1B (H350)
Specific target organ toxicity - (single exposure)	Category 1 (H370)
	Category 3 (H335)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H370 - Causes damage to organs
H335 - May cause respiratory irritation
H341 - Suspected of causing genetic defects
H350 - May cause cancer
H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled
Combustible liquid

Precautionary Statements

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

Additional EU labelling

Restricted to professional users

2.3. Other hazards

Lachrymator (substance which increases the flow of tears)
This product does not contain any known or suspected endocrine disruptors
Toxic to terrestrial vertebrates

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Formaldehyde	50-00-0	200-001-8	35-41	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) STOT SE 3 (H335) Muta. 2 (H341) Carc. 1B (H350)
Methanol	67-56-1	200-659-6	5-14	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Water	7732-18-5	231-791-2	40-46	-

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Formaldehyde	Skin Corr. 1B :: C>=25% Eye Irrit. 2 :: 5%<=C<25% Skin Irrit. 2 :: 5%<=C<25% Skin Sens. 1 :: C>=0.2% STOT SE 3 :: C>=5%	-	-
Methanol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. May cause allergic skin reaction. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Combustible material. Containers may explode when heated.

Hazardous Combustion Products

Formic acid, Oxygen from the air can oxidize formaldehyde to formic acid, especially when heated, Carbon monoxide (CO), Carbon dioxide (CO₂).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 6.1C

Switzerland - Storage of hazardous substances

Storage class - SC 6.1
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Formaldehyde	TWA: 0.37 mg/m ³ (8h) TWA: 0.3 ppm (8h) Skin STEL: 0.74 mg/m ³ (8h) STEL: 0.6 ppm (8h)	STEL: 2 ppm 15 min STEL: 2.5 mg/m ³ 15 min TWA: 2 ppm 8 hr TWA: 2.5 mg/m ³ 8 hr Carc.	TWA / VME: 0.5 ppm (8 heures). for the healthcare, funeral and embalming sectors until July 11, 2024 TWA / VME: 0.3 ppm (8	STEL: 0.3 ppm 15 minuten STEL: 0.38 mg/m ³ 15 minuten	STEL / VLA-EC: 0.6 ppm (15 minutos). STEL / VLA-EC: 0.74 mg/m ³ (15 minutos). TWA / VLA-ED: 0.3 ppm (8 horas)

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

			heures). TWA / VME: 0.37 mg/m ³ (8 heures). TWA / VME: 0.62 mg/m ³ (8 heures). for the healthcare, funeral and embalming sectors until July 11, 2024 STEL / VLCT: 0.6 ppm. restrictive limit STEL / VLCT: 0.74 mg/m ³ . restrictive limit		TWA / VLA-ED: 0.37 mg/m ³ (8 horas)
Methanol	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	WEL - TWA: 200 ppm TWA; 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL; 333 mg/m ³ STEL	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 260 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 1000 ppm. restrictive limit STEL / VLCT: 1300 mg/m ³ . restrictive limit Peau	TWA: 200 ppm 8 uren TWA: 266 mg/m ³ 8 uren STEL: 250 ppm 15 minuten STEL: 333 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 266 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
Formaldehyde	TWA: 0.37 mg/m ³ 8 ore. Time Weighted Average TWA: 0.3 ppm 8 ore. Time Weighted Average TWA: 0.62 mg/m ³ 8 ore. Time Weighted Average for the health care, funeral and embalming sectors until July 11, 2024 TWA: 0.5 ppm 8 ore. Time Weighted Average for the health care, funeral and embalming sectors until July 11, 2024 STEL: 0.74 mg/m ³ 15 minuti. Short-term STEL: 0.6 mg/m ³ 15 minuti. Short-term Pelle	TWA: 0.3 ppm (8 Stunden). AGW - exposure factor 2 TWA: 0.37 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 0.3 ppm (8 Stunden). MAK no irritation should occur during mixed exposure TWA: 0.37 mg/m ³ (8 Stunden). MAK no irritation should occur during mixed exposure Höhepunkt: 0.6 ppm Höhepunkt: 0.74 mg/m ³	STEL: 0.6 ppm 15 minutos STEL: 0.74 mg/m ³ 15 minutos Ceiling: 0.3 ppm TWA: 0.3 ppm 8 horas TWA: 0.37 mg/m ³ 8 horas TWA: 0.62 mg/m ³ 8 horas TWA: 0.5 ppm 8 horas	STEL: 0.5 mg/m ³ 15 minuten TWA: 0.15 mg/m ³ 8 uren	TWA: 0.3 ppm 8 tunteina TWA: 0.37 mg/m ³ 8 tunteina STEL: 0.6 ppm 15 minuutteina STEL: 0.74 mg/m ³ 15 minuutteina
Methanol	TWA: 200 ppm 8 ore. Time Weighted Average TWA: 260 mg/m ³ 8 ore. Time Weighted Average Pelle	100 ppm TWA MAK; 130 mg/m ³ TWA MAKSkin absorber	STEL: 250 ppm 15 minutos TWA: 200 ppm 8 horas TWA: 260 mg/m ³ 8 horas Pele	huid TWA: 133 mg/m ³ 8 uren	TWA: 200 ppm 8 tunteina TWA: 270 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 330 mg/m ³ 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Formaldehyde	MAK-KZGW: 0.6 ppm 15 Minuten MAK-KZGW: 0.74 mg/m ³ 15 Minuten MAK-TMW: 0.3 ppm 8 Stunden MAK-TMW: 0.37 mg/m ³ 8 Stunden	TWA: 0.3 ppm 8 timer TWA: 0.37 mg/m ³ 8 timer STEL: 0.74 mg/m ³ 15 minutter STEL: 0.6 ppm 15 minutter	STEL: 0.6 ppm 15 Minuten STEL: 0.74 mg/m ³ 15 Minuten TWA: 0.3 ppm 8 Stunden TWA: 0.37 mg/m ³ 8 Stunden	STEL: 0.74 mg/m ³ 15 minutach TWA: 0.37 mg/m ³ 8 godzinach	TWA: 0.37 mg/m ³ 8 timer TWA: 0.3 ppm 8 timer STEL: 0.74 mg/m ³ 15 minutter. value from the regulation STEL: 0.6 ppm 15 minutter. value from the regulation Ceiling: 1 ppm Ceiling: 1.2 mg/m ³
Methanol	Haut MAK-KZGW: 800 ppm	TWA: 200 ppm 8 timer TWA: 260 mg/m ³ 8 timer	Haut/Peau STEL: 400 ppm 15	STEL: 300 mg/m ³ 15 minutach	TWA: 100 ppm 8 timer TWA: 130 mg/m ³ 8 timer

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

	15 Minuten MAK-KZGW: 1040 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 260 mg/m ³ 8 Stunden	STEL: 400 ppm 15 minutter STEL: 520 mg/m ³ 15 minutter Hud	Minuten STEL: 520 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	TWA: 100 mg/m ³ 8 godzinach	STEL: 150 ppm 15 minutter. value calculated STEL: 162.5 mg/m ³ 15 minutter. value calculated Hud
--	--	---	--	---	---

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Formaldehyde	TWA: 0.37 mg/m ³ TWA: 0.3 ppm TWA: 0.62 mg/m ³ STEL : 0.5 ppm STEL : 0.74 mg/m ³ STEL : 0.6 ppm	TWA-GVI: 0.3 ppm 8 satima. except health, funeral and embalming sector TWA-GVI: 0.37 mg/m ³ 8 satima. except health, funeral and embalming sector TWA-GVI: 0.5 ppm 8 satima. applies to health, funeral and embalming sector applies until July 11, 2024 TWA-GVI: 0.62 mg/m ³ 8 satima. applies to health, funeral and embalming sector applies until July 11, 2024 STEL-KGVI: 0.6 ppm 15 minutama. STEL-KGVI: 0.74 mg/m ³ 15 minutama.	TWA: 0.3 ppm 8 hr. TWA: 0.5 ppm 8 hr. for the healthcare, funeral and embalming sectors until July 11, 2024 TWA: 0.37 mg/m ³ 8 hr. TWA: 0.62 mg/m ³ 8 hr. for the healthcare, funeral and embalming sectors until July 11, 2024 STEL: 0.6 ppm 15 min STEL: 0.738 mg/m ³ 15 min STEL: 0.62 mg/m ³ 15 min	STEL: 0.74 mg/m ³ STEL: 0.6 ppm TWA: 0.3 ppm TWA: 0.37 mg/m ³	TWA: 0.37 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 0.74 mg/m ³
Methanol	TWA: 200 ppm TWA: 260.0 mg/m ³ Skin notation	kože TWA-GVI: 200 ppm 8 satima. TWA-GVI: 260 mg/m ³ 8 satima.	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 250 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Formaldehyde	TWA: 0.3 ppm 8 tundides. TWA: 0.37 mg/m ³ 8 tundides. TWA: 0.62 mg/m ³ 8 tundides. in the health, funeral and embalming sectors;valid until July 10, 2024 TWA: 0.5 ppm 8 tundides. in the health, funeral and embalming sectors;valid until July 10, 2024 STEL: 0.6 ppm 15 minutites. STEL: 0.74 mg/m ³ 15 minutites.		STEL: 0.6 ppm STEL: 0.74 mg/m ³ TWA: 0.3 ppm TWA: 0.37 mg/m ³	STEL: 0.74 mg/m ³ 15 percekben. CK TWA: 0.37 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	STEL: 0.6 ppm STEL: 0.74 mg/m ³ TWA: 0.3 ppm 8 klukkustundum. TWA: 0.37 mg/m ³ 8 klukkustundum. Skin notation
Methanol	Nahk TWA: 200 ppm 8 tundides. TWA: 250 mg/m ³ 8 tundides. STEL: 250 ppm 15 minutites. STEL: 350 mg/m ³ 15 minutites.	Skin notation TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr	skin - potential for cutaneous absorption STEL: 250 ppm STEL: 325 mg/m ³ TWA: 200 ppm TWA: 260 mg/m ³	TWA: 260 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 260 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 520 mg/m ³

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Formaldehyde	STEL: 0.74 mg/m ³ STEL: 0.6 ppm TWA: 0.37 mg/m ³ TWA: 0.62 mg/m ³ TWA: 0.3 ppm TWA: 0.5 ppm	TWA: 0.3 ppm IPRD TWA: 0.37 mg/m ³ IPRD TWA: 0.62 mg/m ³ IPRD for healthcare, funeral, and embalming industries TWA: 0.5 ppm IPRD for healthcare, funeral, and embalming industries STEL: 0.74 mg/m ³ STEL: 0.6 ppm			TWA: 1 ppm 8 ore TWA: 1.2 mg/m ³ 8 ore STEL: 2 ppm 15 minute STEL: 3 mg/m ³ 15 minute
Methanol	skin - potential for cutaneous exposure TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm IPRD TWA: 260 mg/m ³ IPRD Oda	Possibility of significant uptake through the skin TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 200 ppm TWA: 260 mg/m ³	Skin notation TWA: 200 ppm 8 ore TWA: 260 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Formaldehyde	Skin notation MAC: 0.5 mg/m ³	Ceiling: 0.74 mg/m ³ TWA: 0.3 ppm TWA: 0.37 mg/m ³	TWA: 0.62 mg/m ³ 8 urah applies for health care, funeral and embalming activities until July 11, 2024 TWA: 0.5 ppm 8 urah applies for health care, funeral and embalming activities until July 11, 2024 TWA: 0.37 mg/m ³ 8 urah TWA: 0.3 ppm 8 urah Koža STEL: 0.6 ppm 15 minutah STEL: 0.74 mg/m ³ 15 minutah	Binding STEL: 0.6 ppm 15 minuter Binding STEL: 0.74 mg/m ³ 15 minuter TLV: 0.3 ppm 8 timmar. NGV TLV: 0.37 mg/m ³ 8 timmar. NGV Hud	
Methanol	TWA: 5 mg/m ³ 1250 Skin notation MAC: 15 mg/m ³	Potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm 8 urah TWA: 260 mg/m ³ 8 urah Koža STEL: 800 ppm 15 minutah STEL: 1040 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 250 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 200 ppm 8 saat TWA: 260 mg/m ³ 8 saat

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Methanol			Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine (end of shift) Methanol: 15 mg/L urine (for long-term exposures: at the end of the shift after several shifts)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methanol					Methanol: 6 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Methanol			Methanol: 30 mg/L urine end of exposure or work shift		

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

			Methanol: 30 mg/L urine after all work shifts for long-term exposure		
--	--	--	--	--	--

Monitoring methods

MDHS78 Formaldehyde in air. Laboratory method using a diffusive sampler, solvent desorption and high performance liquid chromatography

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Formaldehyde 50-00-0 (35-41)			DNEL = 37µg/cm ²	DNEL = 240mg/kg bw/day
Methanol 67-56-1 (5-14)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Formaldehyde 50-00-0 (35-41)	DNEL = 0.75mg/m ³		DNEL = 0.375mg/m ³	DNEL = 9mg/m ³
Methanol 67-56-1 (5-14)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Formaldehyde 50-00-0 (35-41)	PNEC = 0.44mg/L	PNEC = 2.3mg/kg sediment dw	PNEC = 4.44mg/L	PNEC = 0.19mg/L	PNEC = 0.2mg/kg soil dw
Methanol 67-56-1 (5-14)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Formaldehyde 50-00-0 (35-41)	PNEC = 0.44mg/L	PNEC = 2.3mg/kg sediment dw			
Methanol 67-56-1 (5-14)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	> 480 minutes	0.7 mm	EN 374	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Nitrile rubber	> 360 minutes	15 - 22 mil		
Butyl rubber	> 240 minutes	25 -35 mil		
Neoprene gloves	> 60 minutes	18 - 24 mil		

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Irritating pungent	
Odor Threshold	0.8 - 1 ppm	
Melting Point/Range	-15 °C / 5 °F	
Softening Point	No data available	
Boiling Point/Range	97 °C / 206.6 °F	@ 760 mmHg
Flammability (liquid)	Flammable Combustible liquid	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 7 vol% Upper 73 vol%	
Flash Point	63 - 75 °C / 145.4 - 167 °F	Method - No information available
Autoignition Temperature	424 °C / 795.2 °F	
Decomposition Temperature	> 150°C	
pH	3-4.2	
Viscosity	1.0 mPas @ 20°C	
Water Solubility	Miscible	

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Formaldehyde	-0.35	
Methanol	-0.74	
Vapor Pressure	2 mbar @ 20 °C	
Density / Specific Gravity	1.083	
Bulk Density	Not applicable	Liquid
Vapor Density	> 1.0	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C H ₂ O
Molecular Weight	30.02
Explosive Properties	explosive air/vapour mixtures possible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions. Stabilized with Methanol. Hazardous polymerization may occur upon depletion of inhibitor.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization may occur upon depletion of inhibitor.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Temperatures above 65°C. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Potassium permanganate. Peroxides. Perchloric acid + aniline. Strong bases. Sodium hydroxide. Ammonia. Hydroxides. Sodium bisulfite. Strong acids. Hydrogen chloride. Isocyanates. Acid anhydrides. Magnesium carbonates. Iodine.

10.6. Hazardous decomposition products

Formic acid. Oxygen from the air can oxidize formaldehyde to formic acid, especially when heated. Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;	
Oral	Category 3
Dermal	Category 3
Inhalation	Category 3

Toxicology data for the components

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Formaldehyde	500 mg/kg (Rat)	LD50 = 270 mg/kg (Rabbit)	0.578 mg/L (Rat) 4 h
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Water	-	-	-

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

Category 1

Component	Test method	Test species	Study result
Formaldehyde 50-00-0 (35-41)	Skin sensitization Test method Patch Test Respiratory sensitization in vitro	Man guinea pig	Sensitizer Sensitization
Methanol 67-56-1 (5-14)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

No information available

(e) germ cell mutagenicity; Category 2

Mutagenic effects have occurred in humans

(f) carcinogenicity; Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Formaldehyde	Carc Cat. 1B	Cat 3		Group 1

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Methanol 67-56-1 (5-14)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

(h) STOT-single exposure; Category 3

Results / Target organs

Respiratory system, Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs

None known.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Ingestion

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Formaldehyde	Leuciscus idus: LC50 = 15 mg/L 96h	EC50 = 20 mg/L 96h EC50 = 2 mg/L 48h	EC50 (72h) = 4.89 mg/L (Desmodesmus subspicatus)
Methanol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	

Component	Microtox	M-Factor
Methanol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

12.2. Persistence and degradability

Persistence

Not applicable for mixtures

Soluble in water, Persistence is unlikely, based on information available, Miscible with water.

Component	Degradability
Formaldehyde 50-00-0 (35-41)	Readily biodegradable (OECD guideline 301A, 301C and 301D) under aerobic and anaerobic conditions.
Methanol 67-56-1 (5-14)	DT50 ~ 17.2d >94% after 20d

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Formaldehyde	-0.35	No data available
Methanol	-0.74	<10 dimensionless

12.4. Mobility in soil

The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN2209
14.2. UN proper shipping name	FORMALDEHYDE SOLUTION
14.3. Transport hazard class(es)	8
14.4. Packing group	III

ADR

14.1. UN number	UN2209
14.2. UN proper shipping name	FORMALDEHYDE SOLUTION
14.3. Transport hazard class(es)	8
14.4. Packing group	III

IATA

14.1. UN number	UN2209
14.2. UN proper shipping name	FORMALDEHYDE SOLUTION
14.3. Transport hazard class(es)	8
14.4. Packing group	III

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Formaldehyde	50-00-0	200-001-8	-	-	X	X	KE-17074	X	X
Methanol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Formaldehyde	50-00-0	X	ACTIVE	X	-	X	X	X
Methanol	67-56-1	X	ACTIVE	X	-	X	X	X
Water	7732-18-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Formaldehyde	50-00-0	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Methanol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Water	7732-18-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Formaldehyde	50-00-0	5 tonne	50 tonne
Methanol	67-56-1	500 tonne	5000 tonne
Water	7732-18-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Formaldehyde	WGK 3	Krebserzeugende Stoffe - : 5 mg/m ³ (Massenkonzentration)
Methanol	WGK 2	Class I : 20 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Formaldehyde	Tableaux des maladies professionnelles (TMP) - RG 43
Methanol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Formaldehyde 50-00-0 (35-41)		Group I	
Methanol 67-56-1 (5-14)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H370 - Causes damage to organs

H335 - May cause respiratory irritation

H341 - Suspected of causing genetic defects

H350 - May cause cancer

H225 - Highly flammable liquid and vapor

Legend

SAFETY DATA SHEET

Formaldehyde solution 35-38%

Revision Date 21-Mar-2024

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 01-Feb-2010

Revision Date 21-Mar-2024

Revision Summary SDS sections updated.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet