

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihal Produk:

Nickel based steam reforming catalyst, HiFUEL® R110

Product Description:

Nickel based steam reforming catalyst, HiFUEL® R110

Cat No. :

45465

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

Company

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

Supplier

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

 Tel: +03-5525 7888
 CHEMTREC Malaysia 1-800-815-308 (Malay)
 CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Skin Sensitization	Category 1 (H317)
Carcinogenicity	Category 1A (H350i)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)
Chronic aquatic toxicity	Category 4 (H413)

Label Elements


Signal Word

Danger

Hazard Statements

H317 - May cause an allergic skin reaction

SAFETY DATA SHEET

Nickel based steam reforming catalyst, HiFUEL® R110

Revision Date 31-Mar-2025

H350i - May cause cancer by inhalation
H372 - Causes damage to organs through prolonged or repeated exposure
H413 - May cause long lasting harmful effects to aquatic life

Precautionary Statements

Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P264 - Wash face, hands and any exposed skin thoroughly after handling
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P272 - Contaminated work clothing should not be allowed out of the workplace
P270 - Do not eat, drink or smoke when using this product
P280 - Wear protective gloves

Response

P308 + P313 - IF exposed or concerned: Get medical advice/attention
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 - Store in a well-ventilated place

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Nickel oxide	1313-99-1	60
Aluminum oxide	1344-28-1	40

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Self-Protection of the First Aider

No special precautions required.

Most important symptoms and effects, both acute and delayed

May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest

SAFETY DATA SHEET

Nickel based steam reforming catalyst, HiFUEL® R110

Revision Date 31-Mar-2025

pain, muscle pain or flushing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Not combustible.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Nickel oxides, Fumes of aluminum or aluminum oxide.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Avoid dust formation. Do not get in eyes, on skin, or on clothing.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

SAFETY DATA SHEET

Nickel based steam reforming catalyst, HiFUEL® R110

Revision Date 31-Mar-2025

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Nickel oxide		TWA: 0.2 mg/m ³	(Vacated) TWA: 1 mg/m ³
Aluminum oxide		TWA: 1 mg/m ³	(Vacated) TWA: 10 mg/m ³ (Vacated) TWA: 5 mg/m ³ TWA: 15 mg/m ³ TWA: 5 mg/m ³

Component	European Union	The United Kingdom	Germany
Nickel oxide		STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr Skin	TWA: 0.03 mg/m ³ (8 Stunden). AGW - exposure factor 8
Aluminum oxide		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA: 1.25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 4 mg/m ³ (8 Stunden). MAK TWA: 1.5 mg/m ³ (8 Stunden). MAK

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles)

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Particle filter

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

No information available

SAFETY DATA SHEET

Nickel based steam reforming catalyst, HiFUEL® R110

Revision Date 31-Mar-2025

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Physical State

Solid Pellets

Odor

Odorless

Odor Threshold

No data available

pH

No information available

Melting Point/Range

No data available

Softening Point

No data available

Boiling Point/Range

No information available

Flash Point

No information available

Method - No information available

Evaporation Rate

Not applicable

Solid

Flammability (solid,gas)

No information available

Explosion Limits

No data available

Vapor Pressure

23 hPa @ 20 °C

Vapor Density

Not applicable

Solid

Specific Gravity / Density

No data available

Bulk Density

No data available

Water Solubility

Insoluble in water

Solubility in other solvents

No information available

Partition Coefficient (n-octanol/water)

Autoignition Temperature

No data available

Decomposition Temperature

No data available

Viscosity

Not applicable

Solid

Explosive Properties

No information available

Oxidizing Properties

No information available

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization

No information available.

Hazardous Reactions

None under normal processing.

Conditions to Avoid

SAFETY DATA SHEET

Nickel based steam reforming catalyst, HiFUEL® R110

Revision Date 31-Mar-2025

None known.

Incompatible Materials

Acids. Reducing Agent. Halogens. Oxidizing agent.

Hazardous Decomposition Products

Nickel oxides. Fumes of aluminum or aluminum oxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

No data available

Inhalation

No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Nickel oxide	LD50 > 5000 mg/kg (Rat)	-	LC50 > 5.08 mg/L (Rat) 4 h
Aluminum oxide	> 5000 mg/kg (Rat) (OECD Guideline 401)	-	> 2.3 mg/l 4 h (OECD Guideline 403)

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity; No data available

(f) carcinogenicity;

Category 1A

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Nickel oxide	Carc Cat. 1A		Cat. 1	Group 1
Aluminum oxide			Cat. 2 (Fibre dust)	

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

SAFETY DATA SHEET

Nickel based steam reforming catalyst, HiFUEL® R110

Revision Date 31-Mar-2025

(i) STOT-repeated exposure; Category 1

Target Organs Lungs.

(j) aspiration hazard; Not applicable
Solid

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Nickel oxide	LC50: > 100 mg/L, 96h static (Brachydanio rerio)	EC50: > 100 mg/L, 48h (Daphnia magna)	EC50: > 127.3 mg/L, 72h (Pseudokirchneriella subcapitata)	

Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Persistence Insoluble in water, May persist.
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

Mobility in soil Spillage unlikely to penetrate soil. Is not likely mobile in the environment due its low water solubility.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods
Waste from Residues/Unused Products Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

Other Information Waste codes should be assigned by the user based on the application for which the product was used Do not empty into drains

SAFETY DATA SHEET

Nickel based steam reforming catalyst, HiFUEL® R110

Revision Date 31-Mar-2025

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO	Not regulated
Road and Rail Transport	Not regulated
IATA	Not regulated
Special Precautions for User	No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Nickel oxide	215-215-7	X	X	X	X	X	X	X	KE-25858
Aluminum oxide	215-691-6	X	X	X	X	X	X	X	KE-01012

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Nickel oxide		1 tonne		

National Regulations

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

SAFETY DATA SHEET

Nickel based steam reforming catalyst, HiFUEL® R110

Revision Date 31-Mar-2025

Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor

MARPOL - International Convention for the Prevention of Pollution from Ships
ATE - Acute Toxicity Estimate
VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Prepared By	Health, Safety and Environmental Department
Revision Date	31-Mar-2025
Revision Summary	Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet