

SAFETY DATA SHEET

Creation Date 24-Nov-2010

Revision Date 23-Feb-2022

Revision Number 7

1. Identification

Product Name Lithium aluminium hydride, 15% solution in toluene/THF

Cat No. : AC385570000; AC385571000; AC385578000

Synonyms LAH; Lithium tetrahydridoaluminate

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Substances/mixtures which, in contact with water, emit flammable gases	Category 1
Skin Corrosion/Irritation	Category 1 A
Serious Eye Damage/Eye Irritation	Category 1
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Kidney, Liver, Neurological effects, Eyes, Ears.	
Aspiration Toxicity	Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
In contact with water releases flammable gases which may ignite spontaneously
May be fatal if swallowed and enters airways
Causes severe skin burns and eye damage
May cause respiratory irritation
May cause drowsiness or dizziness
Suspected of causing cancer
Suspected of damaging the unborn child
May cause damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep away from any possible contact with water, because of violent reaction and possible flash fire
Handle under inert gas. Protect from moisture
Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse
Brush off loose particles from skin. Immerse in cool water/wrap with wet bandages

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Ingestion

Do NOT induce vomiting
Rinse mouth

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Store in a dry place. Store in a closed container

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

May form explosive peroxides

WARNING. Cancer and Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Tetrahydrofuran	109-99-9	60
Toluene	108-88-3	25
Lithium aluminum hydride	16853-85-3	15

4. First-aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Most important symptoms and effects	Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	DO NOT USE WATER
Flash Point	-20 °C / -4 °F
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available

Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen. Burning produces obnoxious and toxic fumes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
3

Flammability
3

Instability
2

Physical hazards
W

6. Accidental release measures**Personal Precautions**

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage**Handling**

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Refrigerator/flammables. Corrosives area. Keep away from heat, sparks and flame. Protect from moisture. Store under an inert atmosphere. Shelf life 12 months. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Acids. Strong oxidizing agents. Alcohols. Strong reducing agents.

8. Exposure controls / personal protection**Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Tetrahydrofuran	TWA: 50 ppm STEL: 100 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 590 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 735 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³	IDLH: 2000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 250 ppm STEL: 735 mg/m ³	TWA: 200 ppm TWA: 590 mg/m ³ STEL: 250 ppm STEL: 735 mg/m ³
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 375 mg/m ³ Ceiling: 300 ppm (Vacated) STEL: 150 ppm (Vacated) STEL: 560 mg/m ³ TWA: 200 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³	TWA: 20 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment**Eye/face Protection**

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Clear
Odor	No information available
Odor Threshold	No information available
pH	No information available
Melting Point/Range	No data available
Boiling Point/Range	No information available
Flash Point	-20 °C / -4 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	0.880
Solubility	Water reactive
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available

Viscosity No information available

10. Stability and reactivity

Reactive Hazard Yes

Stability Risk of explosion by shock, friction, fire or other sources of ignition. Stable under normal conditions. Moisture sensitive. May form explosive peroxides.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Incompatible products. Exposure to moist air or water.

Incompatible Materials Acids, Strong oxidizing agents, Alcohols, Strong reducing agents

Hazardous Decomposition Products Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen, Burning produces obnoxious and toxic fumes

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information No acute toxicity information is available for this product

Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Dermal LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50 Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Causes burns by all exposure routes

Sensitization No information available

Carcinogenicity Limited evidence of a carcinogenic effect. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Tetrahydrofuran	109-99-9	Group 2B	Not listed	A3	X	A3
Toluene	108-88-3	Not listed	Not listed	Not listed	Not listed	Not listed
Lithium aluminium hydride	16853-85-3	Not listed	Not listed	Not listed	Not listed	Not listed

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects No information available

Reproductive Effects SUSPECT REPRODUCTIVE HAZARD - CONTAINS MATERIAL WHICH MAY INJURE UNBORN CHILD (CAUSE BIRTH DEFECTS) (BASED ON ANIMAL DATA).

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)
STOT - repeated exposure Kidney Liver Neurological effects Eyes Ears

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Tetrahydrofuran	Group III Chemical	Not applicable	Not applicable

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not empty into drains. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms. Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Tetrahydrofuran	Not listed	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	Not listed	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h
Toluene	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50 = 19.7 mg/L 30 min	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility . Is not likely mobile in the environment.

Component	log Pow
Tetrahydrofuran	0.45
Toluene	2.73

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Tetrahydrofuran - 109-99-9	U213	-
Toluene - 108-88-3	U220	-

14. Transport information

DOT

UN-No UN1411
 Proper Shipping Name LITHIUM ALUMINUM HYDRIDE, ETHEREAL
 Hazard Class 4.3
 Packing Group I

TDG

UN-No UN1411
 Proper Shipping Name LITHIUM ALUMINUM HYDRIDE, ETHEREAL
 Hazard Class 4.3
 Subsidiary Hazard Class 3
 Packing Group I

IATA

UN-No UN1411
 Proper Shipping Name LITHIUM ALUMINIUM HYDRIDE, ETHEREAL
 Hazard Class 4.3
 Subsidiary Hazard Class 3
 Packing Group I

IMDG/IMO

UN-No UN1411
 Proper Shipping Name LITHIUM ALUMINIUM HYDRIDE, ETHEREAL
 Hazard Class 4.3
 Subsidiary Hazard Class 3
 Packing Group I

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Tetrahydrofuran	109-99-9	X	ACTIVE	-
Toluene	108-88-3	X	ACTIVE	-
Lithium aluminum hydride	16853-85-3	X	ACTIVE	-

Legend:

TSCA - US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Component	CAS No	TSCA 12(b) - Notices of Export
Tetrahydrofuran	109-99-9	Section 4, 1 % de minimus concentration

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Tetrahydrofuran	109-99-9	X	-	203-726-8	X	X	X	X	X	KE-33454
Toluene	108-88-3	X	-	203-625-9	X	X	X	X	X	KE-33936
Lithium aluminum hydride	16853-85-3	-	X	240-877-9	X	X	X	X	X	KE-00990

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations**SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Toluene	108-88-3	25	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Toluene	X	1000 lb	X	X

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Toluene	X		-

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Tetrahydrofuran	1000 lb	-
Toluene	1000 lb 1 lb	-

California Proposition 65 This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Tetrahydrofuran	109-99-9	Carcinogen	-	Carcinogen
Toluene	108-88-3	Developmental	-	Developmental

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Tetrahydrofuran	X	X	X	-	X
Toluene	X	X	X	X	X
Lithium aluminum hydride	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High
-----------	---	---	--

			Concern (SVHC)
Tetrahydrofuran	-	Use restricted. See item 75. (see link for restriction details)	-
Toluene	-	Use restricted. See item 48. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Lithium aluminum hydride	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Tetrahydrofuran	109-99-9	Listed	Not applicable	Not applicable	Not applicable
Toluene	108-88-3	Listed	Not applicable	Not applicable	Not applicable
Lithium aluminum hydride	16853-85-3	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Tetrahydrofuran	109-99-9	Not applicable	Not applicable	Not applicable	Not applicable
Toluene	108-88-3	Not applicable	Not applicable	Not applicable	Annex I - Y42
Lithium aluminum hydride	16853-85-3	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 24-Nov-2010
Revision Date 23-Feb-2022
Print Date 23-Feb-2022
Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS