

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name n-Hexane

CAS No 110-54-3

Synonyms Hexane; Hex

Product Code H306-1; H306-4; H306-4LC; H306-SK4; H306-RS50; H306-RS200; XXH306ENTRS200; NC2669922

Address ThermoFisher Scientific Australia Pty Ltd
5 Caribbean Drive, Scoresby
VICTORIA 3179, Australia

Emergency Tel. CHEMTREC®
03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292
Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids

Category 2

Health hazards

Aspiration Toxicity

Category 1

Skin Corrosion/Irritation

Category 2

Reproductive Toxicity

Category 2

Specific target organ toxicity - (single exposure)

Category 3

Specific target organ toxicity - (repeated exposure)

Category 2

Environmental hazards

Chronic aquatic toxicity

Category 2

Label Elements



Flame



Exclamation Mark



Health Hazard



Environment

Signal Word**Danger****Hazard Statements**

H225 - Highly flammable liquid and vapor
 H304 - May be fatal if swallowed and enters airways
 H315 - Causes skin irritation
 H336 - May cause drowsiness or dizziness
 H361 - Suspected of damaging fertility or the unborn child
 H373 - May cause damage to organs through prolonged or repeated exposure
 H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P233 - Keep container tightly closed
 P240 - Ground and bond container and receiving equipment
 P242 - Use non-sparking tools
 P243 - Take action to prevent static discharges
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray
 P264 - Wash face, hands and any exposed skin thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear eye protection/ face protection
 P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
 P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P308 + P313 - IF exposed or concerned: Get medical advice/attention
 P331 - Do NOT induce vomiting
 P332 + P313 - If skin irritation occurs: Get medical advice/attention
 P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
 P362 + P364 - Take off contaminated clothing and wash it before reuse
 P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
 P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

This product does not contain any known or suspected endocrine disruptors

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Hexane	110-54-3	> 95
2-Methylpentane	107-83-5	< 2.5
3-Methylpentane	96-14-0	< 1

Section 4 - First Aid Measures

Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
General Advice	If symptoms persist, call a physician.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Hexane	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 50 ppm Skin	TWA: 72 mg/m ³ TWA: 20 ppm STEL: 60 ppm STEL: 216 mg/m ³	TWA: 180 mg/m ³ TWA: 50 ppm
2-Methylpentane			TWA: 500 ppm STEL: 1000 ppm		TWA: 500 ppm (8 Stunden). AGW - exposure factor 2 TWA: 1800 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 500 ppm (8 Stunden). MAK TWA: 1800 mg/m ³ (8 Stunden). MAK Höhepunkt: 1000 ppm Höhepunkt: 3600 mg/m ³
3-Methylpentane			TWA: 500 ppm STEL: 1000 ppm		TWA: 500 ppm (8 Stunden). AGW - exposure factor 2 TWA: 1800 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 500 ppm (8 Stunden). MAK TWA: 1800 mg/m ³ (8 Stunden). MAK

					Stunden). MAK Höhepunkt: 1000 ppm Höhepunkt: 3600 mg/m ³
--	--	--	--	--	---

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand	European Union	United Kingdom	Germany
Hexane		5 mg/L (urine) end of shift (2,5-Hexanedione)			2,5-Hexandione plus 4,5-Dihydroxy-2-hexanone (after hydrolysis): 5 mg/L urine (end of shift)

Exposure Controls**Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Wear safety glasses with side shields (or goggles) (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber	See manufacturers recommendations	-	AS/NZS 2161	(minimum requirement)
Viton (R)				

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Long sleeved clothing

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties**Appearance**

Colorless

Physical State

Liquid

Odor	Petroleum distillates	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	-95 °C / -139 °F	
Softening Point	No data available	
Boiling Point/Range	69 °C / 156.2 °F	@ 760 mmHg
Flash Point	-22 °C / -7.6 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.1 vol% Upper 7.5 vol%	
Vapor Pressure	160 mbar @ 20 °C	
Vapor Density	2.97 (Air = 1.0)	(Air = 1.0)
Specific Gravity / Density	0.659	
Bulk Density	Not applicable	Liquid
Water Solubility	Insoluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Hexane	4.11	
Autoignition Temperature	223 °C / 433.4 °F	
Decomposition Temperature	No data available	
Viscosity	0.31 mPa s at 20 °C	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	
Other information		
Molecular Formula	C6 H14	
Molecular Weight	86.18	

Section 10 - Stability and Reactivity

Reactivity	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products, Heat, flames and sparks, Exposure to light, Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Halogens.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂).
Hazardous Polymerization	No information available.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 48000 ppm (Rat) 4 h

- (b) skin corrosion/irritation; Category 2
- (c) serious eye damage/irritation; Based on available data, the classification criteria are not met
- (d) respiratory or skin sensitization;
 Respiratory Based on available data, the classification criteria are not met
 Skin Based on available data, the classification criteria are not met
- (e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Mutagenic effects have occurred in experimental animals

- (f) carcinogenicity; Based on available data, the classification criteria are not met
 There are no known carcinogenic chemicals in this product
- (g) reproductive toxicity;
 Reproductive Effects Category 2
 Developmental Effects Experiments have shown reproductive toxicity effects on laboratory animals
 Teratogenicity Developmental effects have occurred in experimental animals
 Teratogenic effects have occurred in experimental animals.
- (h) STOT-single exposure; Category 3
 Results / Target organs Central nervous system (CNS)
- (i) STOT-repeated exposure; Category 2
 Target Organs Skin, Respiratory system, Eyes, Central nervous system (CNS), Heart, Blood, Liver, Reproductive System, Peripheral Nervous System (PNS).
- (j) aspiration hazard; Category 1
- Other Adverse Effects Tumorigenic effects have been reported in experimental animals.

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effects Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Hexane	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	EC50: 3.87 mg/L/48h		

Persistence and Degradability

Persistence Persistence is unlikely, based on information available.
 Degradation in sewage Contains substances known to be hazardous to the environment or not degradable in waste
 treatment plant water treatment plants.
 Bioaccumulative Potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Hexane	4.11	No data available

Mobility The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility Disperses rapidly in air

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

Section 14 - Transport Information

IMDG/IMO

UN-No UN1208
Proper Shipping Name Hexanes
Hazard Class 3
Packing Group II

Component	IMDG Marine Pollutant
Hexane 110-54-3 (> 95)	IMDG regulated marine pollutant (Listed in the index)

ADG

UN-No UN1208
Proper Shipping Name Hexanes
Hazard Class 3
Packing Group II

IATA

UN-No UN1208
Proper Shipping Name Hexanes
Hazard Class 3
Packing Group II

Environmental hazards

Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

Special Precautions

No special precautions required

Additional information

None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

No poison schedule number allocated.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Hexane - 110-54-3	Schedule 5 listed - including Kerosene, Diesel [distillate], Mineral turpentine, White petroleum spirit, Toluene, Xylene and light mineral and paraffin oils but except their derivative; except a) Toluene and Xylene when included in Schedule 6, b) Benzene and liquid aromatic hydrocarbons when included in Schedule 7, c) food grade and pharmaceutical grade White mineral oil, d) in solid or semi-solid preparations, e) in preparations containing ≤25% of designated solvents, f) in preparations packed in pressurized spray packs, g) in adhesives packed in containers each containing ≤50 grams of adhesive, h) in writing correction fluids and thinners for writing correction fluids packed in containers having a capacity of ≤20 mL, or i) in other preparations when packed in containers with a capacity of ≤2 mL

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Hexane - 110-54-3	Present	-
2-Methylpentane - 107-83-5	Present	-
3-Methylpentane - 96-14-0	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

National pollutant inventory

Subject to reporting requirements

Component	National pollutant inventory
Hexane - 110-54-3	10 tonne/yr. Threshold category 1

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licensing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Hexane	X	X	203-777-6	438-390-3	X	X	-	X	X	X	X	KE-18626
2-Methylpentane	X	X	203-523-4	438-390-3	X	X	-	X	X	X	X	KE-24699
3-Methylpentane	X	X	202-481-4	438-390-3	X	X	-	X	X	X	X	KE-24700

Legend: X - Listed. '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)**International Regulations**

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

MARPOL - International Convention for the Prevention of Pollution from Ships

Component	IMDG Marine Pollutant
Hexane - 110-54-3	IMDG regulated marine pollutant (Listed in the index)

Basel convention on the control of transboundary movements of hazardous wastes and their disposal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories of Wastes to Be Controlled
Hexane - 110-54-3	Annex I - Y42	Y42 except Halogenated solvents

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Hexane	110-54-3	Listed	Not applicable	Not applicable	Not applicable
2-Methylpentane	107-83-5	Listed	Not applicable	Not applicable	Not applicable
3-Methylpentane	96-14-0	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Hexane	-	Use restricted. See item 75. (see link for restriction details)	-
2-Methylpentane	-	Use restricted. See item 75. (see link for restriction details)	-
3-Methylpentane	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
IECSC - Chinese Inventory of Existing Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from

NZIoC - New Zealand Inventory of Chemicals
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japanese Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
CAS - Chemical Abstracts Service
ACGIH - American Conference of Governmental Industrial Hygienists
PNEC - Predicted No Effect Concentration
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

Ships

NZS 5433:2020 - Transport of Dangerous Goods on Land

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

WEL - Workplace Exposure Limit

DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail

OECD - Organisation for Economic Co-operation and Development

LC50 - Lethal Concentration 50%

ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment

NOEC - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Revision Date

17-May-2024

Revision Summary

Update to GHS format.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet