

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Nafion® D-521 dispersion, 5% w/w in water and 1-propanol**
Cat No. : **42117**

Unique Formula Identifier (UFI) **5JCM-668Y-UX0U-TRS6**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 3 (H226)

Health hazards

Serious Eye Damage/Eye Irritation
Specific target organ toxicity - (single exposure)

Category 1 (H318)
Category 3 (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor
H318 - Causes serious eye damage
H336 - May cause drowsiness or dizziness

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280 - Wear eye protection/ face protection
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No
-----------	--------	-------	----------	---

ALFAA42117

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

				1272/2008
n-Propanol	71-23-8	EEC No. 200-746-9	48.2	Flam. Liq. 2 (H225) Eye Dam. 1 (H318) STOT SE 3 (H336)
Water	7732-18-5	231-791-2	45.2	-
Ethanesulfonic acid, 2-[1-[difluoro[(trifluoroethenyl)oxy]methyl]-1, 2,2,2-tetrafluoroethoxy]-1,1,2,2-tetrafluoro-, polymer with tetrafluoroethene	31175-20-9	680-985-7	3.6	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)
Ethyl alcohol	64-17-5	200-578-6	3	Flam. Liq. 2 (H225)

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes severe eye damage. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority.

CH

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

- The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
n-Propanol		STEL: 250 ppm 15 min STEL: 625 mg/m ³ 15 min TWA: 200 ppm 8 hr TWA: 500 mg/m ³ 8 hr Skin	TWA / VME: 200 ppm (8 heures). TWA / VME: 500 mg/m ³ (8 heures).	TWA: 100 ppm 8 uren TWA: 250 mg/m ³ 8 uren	STEL / VLA-EC: 400 ppm (15 minutos). STEL / VLA-EC: 1000 mg/m ³ (15 minutos). TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 500 mg/m ³ (8 horas) Piel
Ethyl alcohol		TWA: 1000 ppm TWA; 1920 mg/m ³ TWA WEL - STEL: 3000 ppm STEL: 5760 mg/m ³ STEL	TWA / VME: 1000 ppm (8 heures). TWA / VME: 1900 mg/m ³ (8 heures). STEL / VLCT: 5000 ppm. STEL / VLCT: 9500 mg/m ³ .	TWA: 1000 ppm 8 uren TWA: 1907 mg/m ³ 8 uren	STEL / VLA-EC: 1000 ppm (15 minutos). STEL / VLA-EC: 1910 mg/m ³ (15 minutos).

Component	Italy	Germany	Portugal	The Netherlands	Finland
n-Propanol			STEL: 400 ppm 15 minutos TWA: 200 ppm 8 horas		TWA: 200 ppm 8 tunteina TWA: 500 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 620 mg/m ³ 15 minuutteina
Ethyl alcohol		200 ppm TWA MAK; 380 mg/m ³ TWA MAK	STEL: 1000 ppm 15 minutos	huid STEL: 1900 mg/m ³ 15 minuten TWA: 260 mg/m ³ 8 uren	TWA: 1000 ppm 8 tunteina TWA: 1900 mg/m ³ 8 tunteina STEL: 1300 ppm 15 minuutteina STEL: 2500 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
n-Propanol	MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 500 mg/m ³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 500 mg/m ³ 8 timer STEL: 400 ppm 15 minutter STEL: 1000 mg/m ³ 15 minutter Hud	Haut/Peau TWA: 200 ppm 8 Stunden TWA: 500 mg/m ³ 8 Stunden	STEL: 600 mg/m ³ 15 minutach TWA: 200 mg/m ³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 245 mg/m ³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 306.25 mg/m ³ 15 minutter. value calculated Hud
Ethyl alcohol	MAK-KZGW: 2000 ppm 15 Minuten MAK-KZGW: 3800 mg/m ³ 15 Minuten MAK-TMW: 1000 ppm 8 Stunden MAK-TMW: 1900 mg/m ³ 8 Stunden	TWA: 1000 ppm 8 timer TWA: 1900 mg/m ³ 8 timer STEL: 2000 ppm 15 minutter STEL: 3800 mg/m ³ 15 minutter	STEL: 1000 ppm 15 Minuten STEL: 1920 mg/m ³ 15 Minuten TWA: 500 ppm 8 Stunden TWA: 960 mg/m ³ 8 Stunden	TWA: 1900 mg/m ³ 8 godzinach	TWA: 500 ppm 8 timer TWA: 950 mg/m ³ 8 timer STEL: 625 ppm 15 minutter. value calculated STEL: 1187.5 mg/m ³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
n-Propanol	TWA: 300.0 mg/m ³ STEL : 500.0 mg/m ³	TWA-GVI: 200 ppm 8 satima. TWA-GVI: 500 mg/m ³ 8 satima. STEL-KGVI: 250 ppm 15 minutama. STEL-KGVI: 625 mg/m ³	TWA: 100 ppm 8 hr. STEL: 300 ppm 15 min Skin		TWA: 500 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

		15 minutama.			
Ethyl alcohol	TWA: 1000 mg/m ³	TWA-GVI: 1000 ppm 8 satima. TWA-GVI: 1900 mg/m ³ 8 satima.	STEL: 1000 ppm 15 min		TWA: 1000 mg/m ³ 8 hodinách. Ceiling: 3000 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
n-Propanol			STEL: 250 ppm STEL: 625 mg/m ³ TWA: 200 ppm TWA: 500 mg/m ³		TWA: 200 ppm 8 klukkustundum. TWA: 500 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 1000 mg/m ³
Ethyl alcohol	TWA: 500 ppm 8 tundides. TWA: 1000 mg/m ³ 8 tundides. STEL: 1000 ppm 15 minutites. STEL: 1900 mg/m ³ 15 minutites.		TWA: 1000 ppm TWA: 1900 mg/m ³	STEL: 3800 mg/m ³ 15 percekben. CK TWA: 1900 mg/m ³ 8 órában. AK	TWA: 1000 ppm 8 klukkustundum. TWA: 1900 mg/m ³ 8 klukkustundum. Ceiling: 2000 ppm Ceiling: 3800 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
n-Propanol	TWA: 10 mg/m ³				TWA: 81 ppm 8 ore TWA: 200 mg/m ³ 8 ore STEL: 203 ppm 15 minute STEL: 500 mg/m ³ 15 minute
Ethyl alcohol	TWA: 1000 mg/m ³	TWA: 500 ppm IPRD TWA: 1000 mg/m ³ IPRD STEL: 1000 ppm STEL: 1900 mg/m ³			TWA: 1000 ppm 8 ore TWA: 1900 mg/m ³ 8 ore STEL: 5000 ppm 15 minute STEL: 9500 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
n-Propanol	TWA: 10 mg/m ³ 1762 MAC: 30 mg/m ³			Indicative STEL: 250 ppm 15 minuter Indicative STEL: 600 mg/m ³ 15 minuter TLV: 150 ppm 8 timmar. NGV TLV: 350 mg/m ³ 8 timmar. NGV	
Ethyl alcohol	TWA: 1000 mg/m ³ 2391 MAC: 2000 mg/m ³	Ceiling: 1920 mg/m ³ TWA: 500 ppm TWA: 960 mg/m ³	TWA: 960 mg/m ³ 8 urah TWA: 500 ppm 8 urah STEL: 1000 ppm 15 minutah STEL: 1920 mg/m ³ 15 minutah	Indicative STEL: 1000 ppm 15 minuter Indicative STEL: 1900 mg/m ³ 15 minuter TLV: 500 ppm 8 timmar. NGV TLV: 1000 mg/m ³ 8 timmar. NGV	

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
n-Propanol 71-23-8 (48.2)				DNEL = 136mg/kg bw/day
Ethyl alcohol 64-17-5 (3)				DNEL = 343mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
n-Propanol 71-23-8 (48.2)		DNEL = 1723mg/m ³		DNEL = 268mg/m ³
Ethyl alcohol 64-17-5 (3)	DNEL = 1900mg/m ³			DNEL = 950mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
n-Propanol 71-23-8 (48.2)	PNEC = 6.83mg/L	PNEC = 27.5mg/kg sediment dw	PNEC = 10mg/L	PNEC = 96mg/L	PNEC = 1.49mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
n-Propanol 71-23-8 (48.2)	PNEC = 0.683mg/L	PNEC = 2.75mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)
Nitrile rubber				
Neoprene				
PVC				

Skin and body protection

Long sleeved clothing.

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Particle filtering: EN149:2001
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid dispersion	
Appearance	Cloudy white	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	24 °C / 75.2 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
n-Propanol	0.2	
Ethyl alcohol	-0.32	
Vapor Pressure	No data available	
Density / Specific Gravity	0.98	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties explosive air/vapour mixtures possible

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization

No information available.

Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Propanol	LD50 = 1870 mg/kg (Rat)	LD50 = 4049 mg/kg (Rabbit)	LC50 > 33.8 mg/L (Rat) 4 h
Water	-	-	-
Ethyl alcohol	LD50 = 7060 mg/kg (Rat)	-	20000 ppm/10H (Rat)

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
n-Propanol	Pimephales promelas: LC50=4480 mg/L 96h	EC50: 3339 - 3977 mg/L, 48h Static (Daphnia magna) EC50: = 3642 mg/L, 48h (Daphnia magna)	
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/L/96h	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/l (Chlorella vulgaris)

Component	Microtox	M-Factor
n-Propanol	EC50 = 17700 mg/L 5 min EC50 = 45000 mg/L 5 h EC50 = 8686 mg/L 15 min EC50 = 980 mg/L 12 h	
Ethyl alcohol	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min	

12.2. Persistence and degradability No information available
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential No information available

Component	log Pow	Bioconcentration factor (BCF)
n-Propanol	0.2	No data available

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

Ethyl alcohol	-0.32	No data available
---------------	-------	-------------------

12.4. Mobility in soil No information available

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1987
14.2. UN proper shipping name ALCOHOLS, N.O.S.
Technical Shipping Name 1-propanol, ethanol
14.3. Transport hazard class(es) 3
14.4. Packing group III

ADR

14.1. UN number UN1987
14.2. UN proper shipping name ALCOHOLS, N.O.S.
Technical Shipping Name 1-propanol, ethanol
14.3. Transport hazard class(es) 3
14.4. Packing group III

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

IATA

14.1. UN number UN1987
14.2. UN proper shipping name ALCOHOLS, N.O.S.
Technical Shipping Name 1-propanol, ethanol
14.3. Transport hazard class(es) 3
14.4. Packing group III

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
n-Propanol	71-23-8	200-746-9	-	-	X	X	KE-29362	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
Ethanesulfonic acid, 2-[1-[difluoro(trifluoroethenyl)oxy]methyl]-1,2,2,2-tetrafluoroethoxy]-1,1,2,2-tetrafluoro-, polymer with tetrafluoroethene	31175-20-9	-	-	-	X	X	2009-3-41 51	X	-
Ethyl alcohol	64-17-5	200-578-6	-	-	X	X	KE-13217	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
n-Propanol	71-23-8	X	ACTIVE	X	-	X	X	X
Water	7732-18-5	X	ACTIVE	X	-	X	X	X
Ethanesulfonic acid, 2-[1-[difluoro(trifluoroethenyl)oxy]methyl]-1,2,2,2-tetrafluoroethoxy]-1,1,2,2-tetrafluoro-, polymer with tetrafluoroethene	31175-20-9	X	ACTIVE	-	X	-	-	-
Ethyl alcohol	64-17-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
n-Propanol	71-23-8	-	Use restricted. See item 75. (see link for restriction details)	-
Water	7732-18-5	-	-	-
Ethanesulfonic acid,	31175-20-9	-	-	-

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

2-[1-[difluoro(trifluoroethenyl)oxy]methyl]-1,2,2,2-tetrafluoroethoxy-1,1,2,2-tetrafluoro-, polymer with tetrafluoroethene				
Ethyl alcohol	64-17-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
n-Propanol	71-23-8	Not applicable	Not applicable
Water	7732-18-5	Not applicable	Not applicable
Ethanesulfonic acid, 2-[1-[difluoro(trifluoroethenyl)oxy]methyl]-1,2,2,2-tetrafluoroethoxy-1,1,2,2-tetrafluoro-, polymer with tetrafluoroethene	31175-20-9	Not applicable	Not applicable
Ethyl alcohol	64-17-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

See table for values

Component	OECD PFAS	US (EPA) PFAS	EU (ECHA) PFAS	UK (HSE) PFAS	Chemsec PFAS (Sin List)
Ethanesulfonic acid, 2-[1-[difluoro(trifluoroethenyl)oxy]methyl]-1,2,2,2-tetrafluoroethoxy-1,1,2,2-tetrafluoro-, polymer with tetrafluoroethene (CAS #: 31175-20-9)	Listed	-	Listed	Listed	-

PFAS Legend

Listed = Meets the PFAS definition of the named authority

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
n-Propanol	WGK1	
Ethyl alcohol	WGK1	

Component	France - INRS (Tables of occupational diseases)
n-Propanol	Tableaux des maladies professionnelles (TMP) - RG 84
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
n-Propanol 71-23-8 (48.2)		Group I	
Ethyl alcohol 64-17-5 (3)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

SAFETY DATA SHEET

Nafion® D-521 dispersion, 5% w/w in water and 1-propanol

Revision Date 19-Mar-2024

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By

Health, Safety and Environmental Department

Revision Date

19-Mar-2024

Revision Summary

New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet