

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**
**Product Identifier**

Perihal Produk:

Product Description:

Cat No. :

Synonyms

**Permout Mounting Media**
**Permout Mounting Media**

SP15-100; SP15-500

A permanent adhesive for cementing cover glass to microscope slide.

**Relevant identified uses of the substance or mixture and uses advised against**

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

**Company**

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd  
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,  
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,  
 Selangor Darul Ehsan, Malaysia.  
 Main line: +60 3-5525 7888

**E-mail address**

Enquiry.my@thermofisher.com

**Emergency Telephone Number**

 Tel: +03-5525 7888  
 CHEMTREC Malaysia **1-800-815-308** (Malay)  
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

**SECTION 2: HAZARDS IDENTIFICATION**
**Classification of the substance or mixture**

|                                                      |                    |
|------------------------------------------------------|--------------------|
| Flammable liquids                                    | Category 2 (H225)  |
| Aspiration Toxicity                                  | Category 1 (H304)  |
| Skin Corrosion/Irritation                            | Category 2 (H315)  |
| Reproductive Toxicity                                | Category 2 (H361d) |
| Specific target organ toxicity - (single exposure)   | Category 3 (H336)  |
| Specific target organ toxicity - (repeated exposure) | Category 2 (H373)  |

**Label Elements**


Signal Word

Danger

# SAFETY DATA SHEET

Permout Mounting Media

Revision Date 24-Mar-2025

## Hazard Statements

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H361d - Suspected of damaging the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure

## Precautionary Statements

### Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P240 - Ground and bond container and receiving equipment  
P242 - Use non-sparking tools  
P243 - Take action to prevent static discharges  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray  
P264 - Wash face, hands and any exposed skin thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear eye protection/ face protection

### Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308 + P313 - IF exposed or concerned: Get medical advice/attention  
P332 + P313 - If skin irritation occurs: Get medical advice/attention  
P331 - Do NOT induce vomiting  
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish  
P362 + P364 - Take off contaminated clothing and wash it before reuse

### Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Other Hazards

Toxic to terrestrial vertebrates  
This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Component                     | CAS No     | Weight % |
|-------------------------------|------------|----------|
| Toluene                       | 108-88-3   | 55       |
| Polyterpene hydrocarbon resin | 68240-09-5 | 45       |

## SECTION 4: FIRST AID MEASURES

### Description of first aid measures

#### General Advice

If symptoms persist, call a physician.

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

# SAFETY DATA SHEET

Permout Mounting Media

Revision Date 24-Mar-2025

|                                           |                                                                                                                                                                                                     |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Skin Contact</b>                       | Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.                                                                                   |
| <b>Ingestion</b>                          | Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward. |
| <b>Inhalation</b>                         | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).                                   |
| <b>Self-Protection of the First Aider</b> | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.                                                    |

## **Most important symptoms and effects, both acute and delayed**

None reasonably foreseeable. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## **Indication of any immediate medical attention and special treatment needed**

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

### **Extinguishing media**

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire.

### **Special hazards arising from the substance or mixture**

Keep product and empty container away from heat and sources of ignition. Runoff to sewer may create fire or explosion hazard. Do not allow run-off from fire-fighting to enter drains or water courses. Vapors may travel to source of ignition and flash back. Vapors may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.). Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air.

### **Hazardous Combustion Products**

Carbon oxides.

### **Advice for fire-fighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

### **Environmental precautions**

Do not flush into surface water or sanitary sewer system.

### **Methods and Material for Containment and Cleaning Up**

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use

# SAFETY DATA SHEET

Permout Mounting Media

Revision Date 24-Mar-2025

spark-proof tools and explosion-proof equipment.

## Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

### Specific End Uses

Use in laboratories.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

| Component | Malaysia | ACGIH TLV   | OSHA PEL                                                                                                                                                               |
|-----------|----------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toluene   |          | TWA: 20 ppm | (Vacated) TWA: 100 ppm<br>(Vacated) TWA: 375 mg/m <sup>3</sup><br>Ceiling: 300 ppm<br>(Vacated) STEL: 150 ppm<br>(Vacated) STEL: 560 mg/m <sup>3</sup><br>TWA: 200 ppm |

| Component | European Union                                                                                                                | The United Kingdom                                                                                                        | Germany                                                                                                                                                                                                                                                                    |
|-----------|-------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Toluene   | TWA: 50 ppm (8hr)<br>TWA: 192 mg/m <sup>3</sup> (8hr)<br>STEL: 100 ppm (15min)<br>STEL: 384 mg/m <sup>3</sup> (15min)<br>Skin | STEL: 100 ppm 15 min<br>STEL: 384 mg/m <sup>3</sup> 15 min<br>TWA: 50 ppm 8 hr<br>TWA: 191 mg/m <sup>3</sup> 8 hr<br>Skin | TWA: 50 ppm (8 Stunden). AGW -<br>exposure factor 2<br>TWA: 190 mg/m <sup>3</sup> (8 Stunden). AGW -<br>exposure factor 2<br>TWA: 50 ppm (8 Stunden). MAK<br>TWA: 190 mg/m <sup>3</sup> (8 Stunden). MAK<br>Höhepunkt: 100 ppm<br>Höhepunkt: 380 mg/m <sup>3</sup><br>Haut |

### Exposure Controls

#### Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Wear safety glasses with side shields (or goggles)

#### Hand Protection

Protective gloves Viton (R)

#### Skin and body protection

Long sleeved clothing

# SAFETY DATA SHEET

Permout Mounting Media

Revision Date 24-Mar-2025

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.  
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

## Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

## Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

## Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

## Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|                                         |                          |                                   |
|-----------------------------------------|--------------------------|-----------------------------------|
| Appearance                              | Yellow                   |                                   |
| Physical State                          | Liquid                   |                                   |
| Odor                                    | aromatic                 |                                   |
| Odor Threshold                          | No data available        |                                   |
| pH                                      | No information available |                                   |
| Melting Point/Range                     | No data available        |                                   |
| Softening Point                         | No data available        |                                   |
| Boiling Point/Range                     | 111 °C / 231.8 °F        | @ 760 mmHg                        |
| Flash Point                             | 4 °C / 39.2 °F           | Method - No information available |
| Evaporation Rate                        | No information available |                                   |
| Flammability (solid,gas)                | Not applicable           | Liquid                            |
| Explosion Limits                        | Lower 1.2<br>Upper 7.1   |                                   |
| Vapor Pressure                          | No information available |                                   |
| Vapor Density                           | 3.1                      | (Air = 1.0)                       |
| Specific Gravity / Density              | No data available        |                                   |
| Bulk Density                            | Not applicable           | Liquid                            |
| Water Solubility                        | Insoluble                |                                   |
| Solubility in other solvents            | No information available |                                   |
| Partition Coefficient (n-octanol/water) |                          |                                   |
| Component                               | log Pow                  |                                   |
| Toluene                                 | 2.73                     |                                   |
| Autoignition Temperature                | 480 °C / 896 °F          |                                   |
| Decomposition Temperature               | No data available        |                                   |
| Viscosity                               | No data available        |                                   |

# SAFETY DATA SHEET

Permout Mounting Media

Revision Date 24-Mar-2025

## Explosive Properties Oxidizing Properties

No information available

Vapors may form explosive mixtures with air

## VOC Content(%)

55%

## SECTION 10: STABILITY AND REACTIVITY

### Reactivity

No.

### Chemical Stability

Stable under normal conditions.

### Possibility of Hazardous Reactions

#### Hazardous Polymerization Hazardous Reactions

No information available.  
None under normal processing.

### Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition.

### Incompatible Materials

Strong oxidizing agents.

### Hazardous Decomposition Products

Carbon oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

#### Product Information

#### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

#### Toxicology data for the components

| Component | LD50 Oral            | LD50 Dermal                   | LC50 Inhalation       |
|-----------|----------------------|-------------------------------|-----------------------|
| Toluene   | > 5000 mg/kg ( Rat ) | LD50 = 12000 mg/kg ( Rabbit ) | 26700 ppm ( Rat ) 1 h |

#### (b) skin corrosion/irritation;

Category 2

#### (c) serious eye damage/irritation;

No data available

# SAFETY DATA SHEET

Permout Mounting Media

Revision Date 24-Mar-2025

**(d) respiratory or skin sensitization;**

Respiratory No data available  
Skin No data available

**(e) germ cell mutagenicity;** No data available

**(f) carcinogenicity;** No data available  
There are no known carcinogenic chemicals in this product

**(g) reproductive toxicity;** Category 2  
**Developmental Effects** Possible risk of harm to the unborn child.

**(h) STOT-single exposure;** Category 3  
**Results / Target organs** Central nervous system (CNS).

**(i) STOT-repeated exposure;** Category 2  
**Target Organs** Neuropsychological effects, Eyes, Ears.

**(j) aspiration hazard;** Category 1

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

**Ecotoxicity effects** The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms.

| Component | Freshwater Fish                                                                                              | Water Flea                                                                                   | Freshwater Algae                                                                                                           | Microtox                |
|-----------|--------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Toluene   | 50-70 mg/L LC50 96 h<br>5-7 mg/L LC50 96 h<br>15-19 mg/L LC50 96 h<br>28 mg/L LC50 96 h<br>12 mg/L LC50 96 h | EC50: = 11.5 mg/L, 48h (Daphnia magna)<br>EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna) | EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata)<br>EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata) | EC50 = 19.7 mg/L 30 min |

**Persistence and degradability**

**Persistence** Insoluble in water, Persistence is unlikely, based on information available.

| Component                  | Degradability |
|----------------------------|---------------|
| Toluene<br>108-88-3 ( 55 ) | 86% (20d)     |

**Degradation in sewage treatment plant** Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**Bioaccumulative potential** May have some potential to bioaccumulate

| Component | log Pow | Bioconcentration factor (BCF) |
|-----------|---------|-------------------------------|
|-----------|---------|-------------------------------|

# SAFETY DATA SHEET

Permout Mounting Media

Revision Date 24-Mar-2025

|         |      |    |
|---------|------|----|
| Toluene | 2.73 | 90 |
|---------|------|----|

**Mobility in soil** Spillage unlikely to penetrate soil. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Is not likely mobile in the environment due its low water solubility. Will likely be mobile in the environment due to its volatility.

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**Other adverse effects** No information available

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste treatment methods**  
**Waste from Residues/Unused Products** Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

**Other Information** Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations

## SECTION 14: TRANSPORT INFORMATION

**IMDG/IMO**  
UN-No UN1294  
Hazard Class 3  
Packing Group II  
Proper Shipping Name TOLUENE SOLUTION

**Road and Rail Transport**  
UN-No UN1294  
Hazard Class 3  
Packing Group II  
Proper Shipping Name TOLUENE SOLUTION

**IATA**  
UN-No UN1294  
Hazard Class 3  
Packing Group II  
Proper Shipping Name TOLUENE SOLUTION

**Special Precautions for User** No special precautions required

## SECTION 15: REGULATORY INFORMATION

**Safety, health and environmental regulations/legislation specific for the substance or mixture**



# SAFETY DATA SHEET

Permout Mounting Media

Revision Date 24-Mar-2025

International Inventories X = listed

| Component                     | EINECS    | TSCA | DSL | PICCS | ENCS | ISHL | IECSC | AICS | KECL     |
|-------------------------------|-----------|------|-----|-------|------|------|-------|------|----------|
| Toluene                       | 203-625-9 | X    | X   | X     | X    | X    | X     | X    | KE-33936 |
| Polyterpene hydrocarbon resin | -         | X    | X   | X     | -    |      | X     | X    | KE-34432 |

| Component | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements | Rotterdam Convention (PIC) | Basel Convention (Hazardous Waste) |
|-----------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|----------------------------|------------------------------------|
| Toluene   |                                                                                           |                                                                                          |                            | Annex I - Y42                      |

## National Regulations

**Persistent Organic Pollutant**  
**Ozone Depletion Potential**

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## SECTION 16: OTHER INFORMATION

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**POW** - Partition coefficient Octanol:Water

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date

24-Mar-2025

Revision Summary

Not applicable.

**In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013**

### Disclaimer

# SAFETY DATA SHEET

Permound Mounting Media

Revision Date 24-Mar-2025

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**