

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihalan Produk: **Petroleum ether, b.p. 40-65°C**
 Product Description: **Petroleum ether, b.p. 40-65°C**
 Cat No. : 444290000; 444290050
 Synonyms: Ligroine

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use: Laboratory chemicals.
 Uses advised against: No Information available

Company Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number Tel: +03-5525 7888
 CHEMTREC Malaysia **1-800-815-308** (Malay)
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Aspiration Toxicity	Category 1 (H304)
Skin Corrosion/Irritation	Category 2 (H315)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Chronic aquatic toxicity	Category 2 (H411)

Label Elements

Signal Word
Danger
Hazard Statements

H225 - Highly flammable liquid and vapor

SAFETY DATA SHEET

Petroleum ether, b.p. 40-65°C

Revision Date 22-Mar-2025

H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 - Ground and bond container and receiving equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor if you feel unwell
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Pentane	109-66-0	50
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	64742-49-0	47-50
Hexane	110-54-3	<3

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

SAFETY DATA SHEET

Petroleum ether, b.p. 40-65°C

Revision Date 22-Mar-2025

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

Self-Protection of the First Aider Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SAFETY DATA SHEET

Petroleum ether, b.p. 40-65°C

Revision Date 22-Mar-2025

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Pentane		TWA: 1000 ppm	(Vacated) TWA: 600 ppm (Vacated) TWA: 1800 mg/m ³ (Vacated) STEL: 750 ppm (Vacated) STEL: 2250 mg/m ³ TWA: 1000 ppm TWA: 2950 mg/m ³
Hexane		TWA: 50 ppm Skin	(Vacated) TWA: 50 ppm (Vacated) TWA: 180 mg/m ³ TWA: 500 ppm TWA: 1800 mg/m ³

Component	European Union	The United Kingdom	Germany
Pentane	TWA: 1000 ppm (8hr) TWA: 3000 mg/m ³ (8hr)	STEL: 1800 ppm 15 min STEL: 5400 mg/m ³ 15 min TWA: 600 ppm 8 hr TWA: 1800 mg/m ³ 8 hr	TWA: 1000 ppm (8 Stunden). AGW - exposure factor 2 TWA: 3000 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 1000 ppm (8 Stunden). MAK TWA: 3000 mg/m ³ (8 Stunden). MAK Höhepunkt: 2000 ppm Höhepunkt: 6000 mg/m ³
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)		RCP Isohexanes, TWA (8 h) 250 ppm, 1000 mg/m ³	
Hexane	TWA: 20 ppm (8hr) TWA: 72 mg/m ³ (8hr)	TWA: 72 mg/m ³ TWA: 20 ppm STEL: 60 ppm STEL: 216 mg/m ³	TWA: 180 mg/m ³ TWA: 50 ppm

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles)

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

SAFETY DATA SHEET

Petroleum ether, b.p. 40-65°C

Revision Date 22-Mar-2025

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

low boiling organic solvent Type AX Brown conforming to EN371

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear
Physical State	Liquid
Odor	Petroleum distillates
Odor Threshold	No data available
pH	No information available

Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	40 - 60 °C / 104 - 140 °F	@ 760
Flash Point	-55 °C / -67 °F	Method - No information available

Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.1 vol% Upper 7.8 vol%	

Vapor Pressure	285 mmHg @ 20°C	
Vapor Density	>1 @ 101kPa	(Air = 1.0)
Specific Gravity / Density	0.65	
Bulk Density	Not applicable	Liquid
Water Solubility	Insoluble	
Solubility in other solvents	No information available	

Partition Coefficient (n-octanol/water)

Component	log Pow
Pentane	3.45
Hexane	4.11

SAFETY DATA SHEET

Petroleum ether, b.p. 40-65°C

Revision Date 22-Mar-2025

Autoignition Temperature	>200 °C	
Decomposition Temperature	No data available	
Viscosity	0.3 mm ² /s @ 20°C	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

Conditions to Avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Pentane	LD50 > 2000 mg/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 364 g/m ³ (Rat) 4 h
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	LD50 > 5000 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit)	LC50 = 73680 ppm (Rat) 4 h
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 48000 ppm (Rat) 4 h

SAFETY DATA SHEET

Petroleum ether, b.p. 40-65°C

Revision Date 22-Mar-2025

--	--	--	--

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	Carc Cat. 1B			

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Pentane	LC50: = 9.99 mg/L, 96h (Lepomis macrochirus) LC50: = 11.59 mg/L, 96h (Pimephales promelas) LC50: = 9.87 mg/L, 96h (Oncorhynchus mykiss)	EC50: = 9.74 mg/L, 48h (Daphnia magna)		
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	LC50: = 8.41 mg/L, 96h semi-static, closed			

SAFETY DATA SHEET

Petroleum ether, b.p. 40-65°C

Revision Date 22-Mar-2025

	(Oncorhynchus mykiss)			
Hexane	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	EC50: 3.87 mg/L/48h		

Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Pentane	3.45	No data available
Hexane	4.11	No data available

Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not let this chemical enter the environment Do not empty into drains

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No

UN3295

Hazard Class

3

Packing Group

II

Proper Shipping Name

Hydrocarbons, liquid, n.o.s. Petroleum ether, boiling range 40-60°C

Road and Rail Transport

UN-No

UN3295

Hazard Class

3

Packing Group

II

Proper Shipping Name

Hydrocarbons, liquid, n.o.s. Petroleum ether, boiling range 40-60°C

SAFETY DATA SHEET

Petroleum ether, b.p. 40-65°C

Revision Date 22-Mar-2025

IATA

UN-No UN3295
Hazard Class 3
Packing Group II
Proper Shipping Name Hydrocarbons, liquid, n.o.s. Petroleum ether, boiling range 40-60°C

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Pentane	203-692-4	X	X	X	X	X	X	X	KE-27968
Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)	265-151-9	X	X	X	-		X	X	KE-25623
Hexane	203-777-6	X	X	X	X	X	X	X	KE-18626

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Hexane				Annex I - Y42

National Regulations

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

SAFETY DATA SHEET

Petroleum ether, b.p. 40-65°C

Revision Date 22-Mar-2025

OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor

ATE - Acute Toxicity Estimate
VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date 22-Mar-2025
Revision Summary Not applicable.

**In accordance with local and national regulations: Occupational Safety and Health
(Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet