

Creation Date 01-Aug-2018

Revision Date 01-Aug-2018

Revision Number 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identification

Product Description: Silver two part conductive adhesive, resin
Cat No. : 12942-resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Thermo Fisher (Kandel) GmbH
Zeppelinstr. 7b
76185 Karlsruhe / Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300
E-mail address tech@alfa.com
www.alfa.com
Product safety Tel + +049 (0) 7275 988687-0

1.4. Emergency telephone number

Carechem 24: +44 (0) 1235 239 670 (Multi-language emergency number)
Poison Information Center Mainz
www.giftinfo.uni-mainz.de Telephone: +49(0)6131/19240

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Skin Corrosion/irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Skin Sensitization	Category 1 (H317)
Germ Cell Mutagenicity	Category 2 (H341)
Carcinogenicity	Category 2 (H351)

Environmental hazards

Chronic aquatic toxicity	Category 2 (H411)
--------------------------	-------------------

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

2.2. Label elements



Signal Word

Warning

Hazard Statements

- H315 - Causes skin irritation
- H317 - May cause an allergic skin reaction
- H319 - Causes serious eye irritation
- H341 - Suspected of causing genetic defects
- H351 - Suspected of causing cancer
- H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

- P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
- P332 + P313 - If skin irritation occurs: Get medical advice/ attention
- P201 - Obtain special instructions before use
- P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection
- P308 + P313 - IF exposed or concerned: Get medical advice/ attention

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS-No	EC-No.	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Silver	7440-22-4	231-131-3	70.0	-
Bisphenol A - Epichlorohydrin polymer	25068-38-6		25.0	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)
n-Butyl glycidyl ether (BGE)	2426-08-6	EEC No. 219-376-4	5.0	Acute Tox. 4 (H302) Acute Tox. 4 (H332) Skin Sens. 1 (H317) Muta. 2 (H341) Carc. 2 (H351) STOT SE 3 (H335) Aquatic Chronic 3 (H412) Flam. Liq. 3 (H226)

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Inhalation	Move to fresh air.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Metal oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

6.3. Methods and material for containment and cleaning up

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive 2006/15/EC of 7 February 2006 establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC on the protection of the health and safety of workers from the risks related to chemical agents at work. **UK** - EH40/2005 Containing the workplace exposure limits (WELs) for use with the Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended). Updated by September 2006 official press release and October 2007 Supplement. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority.

Component	European Union	The United Kingdom	France	Belgium	Spain
Silver	TWA: 0.1 mg/m ³ 8 hr	STEL: 0.3 mg/m ³ 15 min TWA: 0.1 mg/m ³ 8 hr	TWA / VME: 0.1 mg/m ³ (8 heures). indicative limit	TWA: 0.1 mg/m ³ 8 uren	TWA / VLA-ED: 0.1 mg/m ³ (8 horas)
n-Butyl glycidyl ether (BGE)			TWA / VME: 25 ppm (8 heures). TWA / VME: 135 mg/m ³ (8 heures).	TWA: 3 ppm 8 uren TWA: 16.2 mg/m ³ 8 uren Huid	TWA / VLA-ED: 3 ppm (8 horas) TWA / VLA-ED: 16 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
Silver	TWA: 0.1 mg/m ³ 8 ore. Media Ponderata nel Tempo	TWA: 0.1 mg/m ³ (8 Stunden). AGW - exposure factor 8 TWA: 0.01 mg/m ³ (8 Stunden). AGW - exposure factor	TWA: 0.01 mg/m ³ 8 horas	TWA: 0.1 mg/m ³ 8 uren	TWA: 0.1 mg/m ³ 8 tunteina

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

		2 TWA: 0.1 mg/m ³ (8 Stunden). MAK TWA: 0.01 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.8 mg/m ³ Höhepunkt: 0.02 mg/m ³			
n-Butyl glycidyl ether (BGE)		Haut	TWA: 3 ppm 8 horas Pele		STEL: 25 ppm 15 minuutteina STEL: 140 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Silver	MAK-KZW: 0.1 mg/m ³ 15 Minuten MAK-TMW: 0.1 mg/m ³ 8 Stunden Ceiling: 0.1 mg/m ³	TWA: 0.01 mg/m ³ 8 timer	STEL: 0.8 mg/m ³ 15 Minuten STEL: 0.02 mg/m ³ 15 Minuten TWA: 0.1 mg/m ³ 8 Stunden TWA: 0.01 mg/m ³ 8 Stunden	TWA: 0.05 mg/m ³ 8 godzinach	TWA: 0.1 mg/m ³ 8 timer STEL: 0.3 mg/m ³ 15 minutter. value calculated metal dust and fume
n-Butyl glycidyl ether (BGE)	Haut	TWA: 6 ppm 8 timer TWA: 30 mg/m ³ 8 timer	Haut/Peau STEL: 50 ppm 15 Minuten STEL: 270 mg/m ³ 15 Minuten TWA: 25 ppm 8 Stunden TWA: 135 mg/m ³ 8 Stunden	STEL: 60 mg/m ³ 15 minutach TWA: 30 mg/m ³ 8 godzinach	TWA: 5 ppm 8 timer TWA: 27 mg/m ³ 8 timer STEL: 10 ppm 15 minutter. value calculated STEL: 40.5 mg/m ³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Silver	TWA: 0.1 mg/m ³	TWA-GVI: 0.1 mg/m ³ 8 satima.	TWA: 0.1 mg/m ³ 8 hr. metallic STEL: 0.3 mg/m ³ 15 min	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ 8 hodinách. Ceiling: 0.3 mg/m ³
Bisphenol A - Epichlorohydrin polymer	TWA: 1.0 mg/m ³				
n-Butyl glycidyl ether (BGE)		TWA-GVI: 25 ppm 8 satima. TWA-GVI: 135 mg/m ³ 8 satima.	TWA: 3 ppm 8 hr. STEL: 9 ppm 15 min Skin		

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Silver	TWA: 0.1 mg/m ³ 8 tundides.		TWA: 0.1 mg/m ³	STEL: 0.4 mg/m ³ 15 percekben. CK Substances with European indicative limits (96/94/EC, 2000/39/EC, 2006/15/EC, 2009/161/EU), which currently has no peak limit concentration. In these cases, Annex 3.1. should be used exercised TWA: 0.1 mg/m ³ 8 órában. AK	TWA: 0.01 mg/m ³ 8 klukkustundum. dust and powder Ceiling: 0.02 mg/m ³ dust and powder
n-Butyl glycidyl ether (BGE)	TWA: 10 ppm 8 tundides. TWA: 50 mg/m ³ 8 tundides. STEL: 15 ppm 15 minutites. STEL: 80 mg/m ³ 15 minutites.		TWA: 20 ppm TWA: 135 mg/m ³		TWA: 6 ppm 8 klukkustundum. TWA: 30 mg/m ³ 8 klukkustundum. Ceiling: 12 ppm Ceiling: 60 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Silver	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ IPRD		TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ 8 ore

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

		Ag			
n-Butyl glycidyl ether (BGE)		TWA: 10 ppm IPRD TWA: 50 mg/m ³ IPRD STEL: 15 ppm STEL: 80 mg/m ³			TWA: 19 ppm 8 ore TWA: 100 mg/m ³ 8 ore STEL: 38 ppm 15 minute STEL: 200 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Silver	MAC: 1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.01 mg/m ³ 8 urah	TLV: 0.1 mg/m ³ 8 timmar. NGV	TWA: 0.1 mg/m ³ 8 saat TWA: 0.01 mg/m ³ 8 saat
n-Butyl glycidyl ether (BGE)				Indicative STEL: 15 ppm 15 minuter Indicative STEL: 80 mg/m ³ 15 minuter TLV: 10 ppm 8 timmar. NGV TLV: 50 mg/m ³ 8 timmar. NGV	

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry
MDHS 99 Metals in air by ICP-AES

Derived No Effect Level (DNEL) No information available

Route of exposure	Acute effects (local)	Acute effects (systemic)	Chronic effects (local)	Chronic effects (systemic)
Oral Dermal Inhalation				

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.
Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Disposable gloves	See manufacturers recommendations	-	EN 374	(minimum requirement)
Skin and body protection		Long sleeved clothing		

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

In case of insufficient ventilation wear suitable respiratory equipment

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Silver	
Physical State	Paste	
Odor	Mild	
Odor Threshold	No data available	
pH	Not applicable	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flash Point	341 °C / 645.8 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	No data available	
Bulk Density	No data available	
Water Solubility	Insoluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
n-Butyl glycidyl ether (BGE)	0.63	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties	Not explosive	
Oxidizing Properties	No information available	

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous Reactions

No information available.
No information available.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

Bases. Oxidizing agents.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Silver	LD50 > 5000 mg/kg (Rat)	LD50 > 2000 mg/kg (Rat)	
Bisphenol A - Epichlorohydrin polymer	LD50 = 11400 mg/kg (Rat)		
n-Butyl glycidyl ether (BGE)	LD50 = 2050 mg/kg (Rat) LD50 = 1660 mg/kg (Rat)	LD50 = 788 mg/kg (Rabbit) LD50 > 2150 mg/kg (Rat) LD50 = 2520 µL/kg (Rabbit)	LC50 = 2590 ppm (Rat) 4 h

(b) skin corrosion/irritation;

Category 2

(c) serious eye damage/irritation;

Category 2

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

Category 1

No information available

(e) germ cell mutagenicity;

Category 2

(f) carcinogenicity;

Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
n-Butyl glycidyl ether (BGE)			Cat. 3B	

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Silver	LC50: = 0.064 mg/L, 96h static (Lepomis macrochirus) LC50: = 0.0062 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: 0.00155 - 0.00293 mg/L, 96h static (Pimephales promelas)	EC50: = 0.00024 mg/L, 48h Static (Daphnia magna)		

12.2. Persistence and degradability

Persistence Degradation in sewage treatment plant

The product includes heavy metals. Prevent release into the environment. Special pretreatment required
Insoluble in water, May persist.
Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
n-Butyl glycidyl ether (BGE)	0.63	No data available

12.4. Mobility in soil

Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Other adverse effects

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors	EU - Endocrine Disruptors -	Japan - Endocrine Disruptor
-----------	---------------------------	-----------------------------	-----------------------------

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

	Candidate List	Evaluated Substances	Information
Bisphenol A - Epichlorohydrin polymer	Group III Chemical		

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC)

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.

Other Information

Do not dispose of waste into sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Do not let this chemical enter the environment.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

ADR

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

IATA

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user

No special precautions required

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

X = listed.

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

Component	EINECS	ELINCS	NLP	TSCA	DSL	NDSL	PICCS	ENCS	IECSC	AICS	KECL
Silver	231-131-3	-		X	X	-	X	-	X	X	X
Bisphenol A - Epichlorohydrin polymer	-	-	500-033-5	X	X	-	X	X	X	X	X
n-Butyl glycidyl ether (BGE)	219-376-4	-		X	X	-	X	X	X	X	X

National Regulations

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Silver	nwg - nicht wassergefährdend (non-hazardous to waters) WGK 3	
Bisphenol A - Epichlorohydrin polymer	WGK 2	
n-Butyl glycidyl ether (BGE)	WGK 2	

Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment.

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H341 - Suspected of causing genetic defects
H351 - Suspected of causing cancer
H411 - Toxic to aquatic life with long lasting effects
H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H412 - Harmful to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

PNEC - Predicted No Effect Concentration

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

SAFETY DATA SHEET

Silver two part conductive adhesive, resin

Revision Date 01-Aug-2018

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - Volatile Organic Compounds

Key literature references and sources for data

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Prepared By Health, Safety and Environmental Department

Creation Date 01-Aug-2018

Revision Date 01-Aug-2018

Revision Summary Initial Release.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet