

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihal Produk: Methylithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable AcroSeal[®] bottles

Product Description: Methylithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable AcroSeal[®] bottles

Cat No. : H36516

Molecular Formula C H3 Li

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.

Uses advised against No Information available

Company

Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

Supplier

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888
 CHEMTREC Malaysia **1-800-815-308** (Malay)
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable liquids	Category 1 (H224)
Substances/mixtures which, in contact with water, emit flammable gases	Category 1 (H260)
Pyrophoric liquids	Category 1 (H250)
Acute oral toxicity	Category 4 (H302)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Specific target organ toxicity - (single exposure)	Category 3 (H336)

Label Elements


SAFETY DATA SHEET

Methyl lithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable
AcroSeal[®] bottles

Revision Date 31-Mar-2025

Signal Word

Danger

Hazard Statements

H224 - Extremely flammable liquid and vapor
H250 - Catches fire spontaneously if exposed to air
H260 - In contact with water releases flammable gases which may ignite spontaneously
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H336 - May cause drowsiness or dizziness

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P231 + P232 - Handle and store contents under inert gas. Protect from moisture
P240 - Ground and bond container and receiving equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P330 - Rinse mouth
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P302 + P334 - IF ON SKIN: Immerse in cool water or wrap in wet bandages
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P402 + P404 - Store in a dry place. Store in a closed container

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

EUH014 - Reacts violently with water
EUH019 - May form explosive peroxides
EUH066 - Repeated exposure may cause skin dryness or cracking

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Ethyl ether	60-29-7	ca 95
Lithium, methyl-	917-54-4	4.5-5.5

SECTION 4: FIRST AID MEASURES

SAFETY DATA SHEET

Methyl lithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable AcroSeal[®] bottles

Revision Date 31-Mar-2025

Description of first aid measures

Eye Contact	Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Call a physician immediately. Clean mouth with water. If possible drink milk afterwards.
Inhalation	Remove from exposure, lie down. Remove to fresh air. If not breathing, give artificial respiration. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Dry chemical. Dike fire-control water for later disposal. This material is lighter than water and insoluble in water. The fire could easily be spread by the use of water in an area where the water cannot be contained. Water mist may be used to cool closed containers. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water. Carbon dioxide (CO₂). Foam.

Special hazards arising from the substance or mixture

Extremely flammable. Vapors may form explosive mixtures with air. Contact with water liberates toxic gas. Water reactive. Vapors may travel to source of ignition and flash back. Produce flammable gases on contact with water. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), peroxides, Methane.

Advice for fire-fighters

Vapors are heavier than air and may spread along floors. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

Methyl lithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable AcroSeal[®] bottles

Revision Date 31-Mar-2025

Personal Precautions, Protective Equipment and Emergency Procedures

Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

See Section 12 for additional Ecological Information.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Prevent product from entering drains. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Provide adequate ventilation. Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Keep combustibles (wood, paper, oil, etc) away from spilled material.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. If peroxide formation is suspected, do not open or move container. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Handle product only in closed system or provide appropriate exhaust ventilation. Keep away from open flames, hot surfaces and sources of ignition.

Conditions for Safe Storage, Including any Incompatibilities

Keep away from heat, sparks and flame. Protect from direct sunlight. Refrigerator/flammables. Containers should be dated when opened and tested periodically for the presence of peroxides. Regularly check inhibitor levels to maintain peroxide levels below 1%. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep away from water or moist air. Keep away from oxidizing agents. Purge open drums with nitrogen before resealing. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Store under an inert atmosphere. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Ethyl ether		TWA: 400 ppm STEL: 500 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 1200 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1500 mg/m ³ TWA: 400 ppm TWA: 1200 mg/m ³

Component	European Union	The United Kingdom	Germany
Ethyl ether	TWA: 100 ppm (8h) TWA: 308 mg/m ³ (8h)	STEL: 200 ppm 15 min STEL: 620 mg/m ³ 15 min	TWA: 400 ppm (8 Stunden). AGW - exposure factor 1

SAFETY DATA SHEET

Methyl lithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable AcroSeal[®] bottles

Revision Date 31-Mar-2025

	STEL: 200 ppm (15min) STEL: 616 mg/m ³ (15min)	TWA: 100 ppm 8 hr TWA: 310 mg/m ³ 8 hr	TWA: 1200 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 400 ppm (8 Stunden). MAK TWA: 1200 mg/m ³ (8 Stunden). MAK Höhepunkt: 400 ppm Höhepunkt: 1200 mg/m ³
Lithium, methyl-			TWA: 0.2 mg/m ³ (8 Stunden). MAK inorganic compounds, except Lithium and strong irritant Lithium compounds such as Lithium amide, Lithium hydride, Lithium hydroxide, Lithium nitride, Lithium oxide, Lithium tetrahydro aluminate, Lithium tetrahydroborate

Exposure Controls

Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Protective gloves

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

No information available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Yellow

Physical State

Liquid

Odor

Odorless

Odor Threshold

No data available

SAFETY DATA SHEET

Methyl lithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable
AcroSeal[®] bottles

Revision Date 31-Mar-2025

pH	No information available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flash Point	-17 °C / 1.4 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	570 mbar @ 20 °C	
Vapor Density	No information available	(Air = 1.0)
Specific Gravity / Density	0.700	
Bulk Density	Not applicable	Liquid
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethyl ether	0.82	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	
Molecular Formula	C H3 Li	
Molecular Weight	21.98	

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Yes.

Chemical Stability

May form explosive peroxides. Reacts violently with water. Moisture sensitive. Air sensitive. Reacts with air to form peroxides. Do not distill or allow to evaporate. Pyrophoric: Spontaneously flammable in air.

Possibility of Hazardous Reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	No information available.

Conditions to Avoid

SAFETY DATA SHEET

Methyl lithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable
AcroSeal[®] bottles

Revision Date 31-Mar-2025

Keep away from open flames, hot surfaces and sources of ignition. Protect from water.
Exposure to air. Exposure to light. Incompatible products. Exposure to moist air or water.

Incompatible Materials

Acids. Water. Strong acids. Alcohols. Chlorine. oxygen. Peroxides. Metals.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO₂). peroxides. Methane.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm (Rat) 4 h

(b) skin corrosion/irritation;

Category 1 B

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

No data available

(h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure;

No data available

Target Organs

No information available.

(j) aspiration hazard;

No data available

SAFETY DATA SHEET

Methylithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable AcroSeal[®] bottles

Revision Date 31-Mar-2025

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects Do not empty into drains. .

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl ether	LC50: > 10000 mg/L, 96h static (Lepomis macrochirus) LC50: = 2560 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 165 mg/L/24h		EC50 = 5600 mg/L 15 min

Persistence and degradability No information available
Persistence Persistence is unlikely.

Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl ether	0.82	No data available

Mobility in soil .

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information Waste codes should be assigned by the user based on the application for which the product was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with local regulations Do not empty into drains Large amounts will affect pH and harm aquatic organisms

SAFETY DATA SHEET

Methyl lithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable AcroSeal[®] bottles

Revision Date 31-Mar-2025

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN3394
Hazard Class 4.2
Subsidiary Hazard Class 4.3
Packing Group I
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

Road and Rail Transport

UN-No UN3394
Hazard Class 4.2
Subsidiary Hazard Class 4.3
Packing Group I
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

IATA

FORBIDDEN FOR IATA TRANSPORT
UN-No UN3394
Hazard Class 4.2
Subsidiary Hazard Class 4.3
Packing Group I
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE, FORBIDDEN FOR IATA TRANSPORT

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Ethyl ether	200-467-2	X	X	X	X	X	X	X	KE-27690
Lithium, methyl-	213-026-4	X	-	X	X	X	X	X	KE-24321

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl ether				Annex I - Y40 Annex I - Y42

National Regulations

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

SAFETY DATA SHEET

Methyl lithium, 1.6M in diethyl ether, packaged under Nitrogen in resealable AcroSeal[®] bottles

Revision Date 31-Mar-2025

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Prepared By

Revision Date

Revision Summary

Health, Safety and Environmental Department

31-Mar-2025

Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet