

Creation Date 16-Oct-2018

Revision Date 24-Feb-2023

Revision Number 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: 70% IMS with 5% Methanol
Cat No. : TS/0232/99

Unique Formula Identifier (UFI) CU7R-861S-AX02-J0UE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road, Loughborough,
Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity

Category 4 (H302)

Serious Eye Damage/Eye Irritation

Category 2 (H319)

Specific target organ toxicity - (single exposure)

Category 2 (H371)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H302 - Harmful if swallowed

H319 - Causes serious eye irritation

H371 - May cause damage to organs

Precautionary Statements

P312 - Call a POISON CENTER or doctor if you feel unwell

P264 - Wash face, hands and any exposed skin thoroughly after handling

P280 - Wear eye protection/ face protection

P337 + P313 - If eye irritation persists: Get medical advice/attention

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Ethyl alcohol	64-17-5	200-578-6	60-70	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)
Methanol	67-56-1	200-659-6	3-5	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Water	7732-18-5	231-791-2	30-35	-

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Ethyl alcohol	Eye Irrit. 2 :: C>=50%	-	-
Methanol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
--------------------	------------------------

SECTION 5: FIREFIGHTING MEASURES

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Ethyl alcohol		TWA: 1000 ppm TWA; 1920 mg/m ³ TWA WEL - STEL: 3000 ppm STEL; 5760 mg/m ³ STEL	TWA / VME: 1000 ppm (8 heures). TWA / VME: 1900 mg/m ³ (8 heures). STEL / VLCT: 5000 ppm. STEL / VLCT: 9500 mg/m ³ .	TWA: 1000 ppm 8 uren TWA: 1907 mg/m ³ 8 uren	STEL / VLA-EC: 1000 ppm (15 minutos). STEL / VLA-EC: 1910 mg/m ³ (15 minutos).
Methanol	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	WEL - TWA: 200 ppm TWA; 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL; 333 mg/m ³ STEL	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 260 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 1000 ppm. restrictive limit STEL / VLCT: 1300 mg/m ³ . restrictive limit Peau	TWA: 200 ppm 8 uren TWA: 266 mg/m ³ 8 uren STEL: 250 ppm 15 minuten STEL: 333 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 266 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
Ethyl alcohol		200 ppm TWA MAK; 380 mg/m ³ TWA MAK	STEL: 1000 ppm 15 minutos	huid STEL: 1900 mg/m ³ 15 minuten TWA: 260 mg/m ³ 8 uren	TWA: 1000 ppm 8 tunteina TWA: 1900 mg/m ³ 8 tunteina STEL: 1300 ppm 15 minuutteina STEL: 2500 mg/m ³ 15 minuutteina
Methanol	TWA: 200 ppm 8 ore. Time Weighted Average TWA: 260 mg/m ³ 8 ore. Time Weighted Average Pelle	100 ppm TWA MAK; 130 mg/m ³ TWA MAKSkin absorber	STEL: 250 ppm 15 minutos TWA: 200 ppm 8 horas TWA: 260 mg/m ³ 8 horas Pele	huid TWA: 133 mg/m ³ 8 uren	TWA: 200 ppm 8 tunteina TWA: 270 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 330 mg/m ³ 15 minuutteina Iho

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

Component	Austria	Denmark	Switzerland	Poland	Norway
Ethyl alcohol	MAK-KZGW: 2000 ppm 15 Minuten MAK-KZGW: 3800 mg/m ³ 15 Minuten MAK-TMW: 1000 ppm 8 Stunden MAK-TMW: 1900 mg/m ³ 8 Stunden	TWA: 1000 ppm 8 timer TWA: 1900 mg/m ³ 8 timer STEL: 2000 ppm 15 minutter STEL: 3800 mg/m ³ 15 minutter	STEL: 1000 ppm 15 Minuten STEL: 1920 mg/m ³ 15 Minuten TWA: 500 ppm 8 Stunden TWA: 960 mg/m ³ 8 Stunden	TWA: 1900 mg/m ³ 8 godzinach	TWA: 500 ppm 8 timer TWA: 950 mg/m ³ 8 timer STEL: 625 ppm 15 minutter. value calculated STEL: 1187.5 mg/m ³ 15 minutter. value calculated
Methanol	Haut MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 1040 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 260 mg/m ³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 260 mg/m ³ 8 timer STEL: 400 ppm 15 minutter STEL: 520 mg/m ³ 15 minutter Hud	Haut/Peau STEL: 400 ppm 15 Minuten STEL: 520 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	STEL: 300 mg/m ³ 15 minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 130 mg/m ³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 162.5 mg/m ³ 15 minutter. value calculated Hud

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Ethyl alcohol	TWA: 1000 mg/m ³	TWA-GVI: 1000 ppm 8 satima. TWA-GVI: 1900 mg/m ³ 8 satima.	STEL: 1000 ppm 15 min		TWA: 1000 mg/m ³ 8 hodinách. Ceiling: 3000 mg/m ³
Methanol	TWA: 200 ppm TWA: 260.0 mg/m ³ Skin notation	kože TWA-GVI: 200 ppm 8 satima. TWA-GVI: 260 mg/m ³ 8 satima.	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 250 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Ethyl alcohol	TWA: 500 ppm 8 tundides. TWA: 1000 mg/m ³ 8 tundides. STEL: 1000 ppm 15 minutites. STEL: 1900 mg/m ³ 15 minutites.		TWA: 1000 ppm TWA: 1900 mg/m ³	STEL: 3800 mg/m ³ 15 percekben. CK TWA: 1900 mg/m ³ 8 óraban. AK	TWA: 1000 ppm 8 klukkustundum. TWA: 1900 mg/m ³ 8 klukkustundum. Ceiling: 2000 ppm Ceiling: 3800 mg/m ³
Methanol	Nahk TWA: 200 ppm 8 tundides. TWA: 250 mg/m ³ 8 tundides. STEL: 250 ppm 15 minutites. STEL: 350 mg/m ³ 15 minutites.	Skin notation TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr	skin - potential for cutaneous absorption STEL: 250 ppm STEL: 325 mg/m ³ TWA: 200 ppm TWA: 260 mg/m ³	TWA: 260 mg/m ³ 8 óraban. AK lehetséges borön keresztüli felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 260 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 520 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Ethyl alcohol	TWA: 1000 mg/m ³	TWA: 500 ppm IPRD TWA: 1000 mg/m ³ IPRD STEL: 1000 ppm STEL: 1900 mg/m ³			TWA: 1000 ppm 8 ore TWA: 1900 mg/m ³ 8 ore STEL: 5000 ppm 15 minute STEL: 9500 mg/m ³ 15 minute
Methanol	skin - potential for cutaneous exposure TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm IPRD TWA: 260 mg/m ³ IPRD Oda	Possibility of significant uptake through the skin TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 200 ppm TWA: 260 mg/m ³	Skin notation TWA: 200 ppm 8 ore TWA: 260 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Ethyl alcohol	TWA: 1000 mg/m ³ 2391 MAC: 2000 mg/m ³	Ceiling: 1920 mg/m ³ TWA: 500 ppm TWA: 960 mg/m ³	TWA: 960 mg/m ³ 8 urah TWA: 500 ppm 8 urah STEL: 1000 ppm 15	Indicative STEL: 1000 ppm 15 minuter Indicative STEL: 1900	

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

			minutah STEL: 1920 mg/m ³ 15 minutah	mg/m ³ 15 minuter TLV: 500 ppm 8 timmar. NGV TLV: 1000 mg/m ³ 8 timmar. NGV	
Methanol	TWA: 5 mg/m ³ 1250 Skin notation MAC: 15 mg/m ³	Potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm 8 urah TWA: 260 mg/m ³ 8 urah Koža STEL: 800 ppm 15 minutah STEL: 1040 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 250 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 200 ppm 8 saat TWA: 260 mg/m ³ 8 saat

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Methanol			Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine (end of shift) Methanol: 15 mg/L urine (for long-term exposures: at the end of the shift after several shifts)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methanol					Methanol: 6 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Methanol			Methanol: 30 mg/L urine end of exposure or work shift Methanol: 30 mg/L urine after all work shifts for long-term exposure		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Ethyl alcohol 64-17-5 (60-70)		DNEL = 87 mg/kg bw/d		

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl alcohol 64-17-5 (60-70)				DNEL = 343mg/kg bw/day
Methanol 67-56-1 (3-5)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethyl alcohol 64-17-5 (60-70)	DNEL = 1900mg/m ³			DNEL = 950mg/m ³
Methanol 67-56-1 (3-5)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methanol 67-56-1 (3-5)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Methanol 67-56-1 (3-5)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Neoprene	recommendations			
Natural rubber				
PVC				

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Clear, colorless solution	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	-117 °C / -178.6 °F	
Softening Point	No data available	
Boiling Point/Range	78 °C / 172.4 °F	@ 760 mmHg
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	12 °C / 53.6 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Completely soluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethyl alcohol	-0.32	
Methanol	-0.74	
Vapor Pressure	No data available	
Density / Specific Gravity	0.88	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg OECD 401 (Rat) 3450 mg/kg (Mouse)	-	LC50 = 117-125 mg/l (4h) OECD 403 (rat) 20000 ppm/10H (rat)
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Water	-	-	-

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

Category 2

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 (60-70)	Mouse Ear Swelling Test (MEST)	mouse	non-sensitising
	OECD Test Guideline 429 Local Lymph Node Assay	mouse	non-sensitising
Methanol 67-56-1 (3-5)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity;

No data available

Component	Test method	Test species	Study result
Ethyl alcohol 64-17-5 (60-70)	AMES test OECD Test Guideline 471	in vitro Bacteria	negative
	Gene cell mutation OECD Test Guideline 476	in vitro Mammalian	negative

(f) carcinogenicity;

No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

(g) reproductive toxicity;

No data available

Component	Test method	Test species / Duration	Study result
Ethyl alcohol 64-17-5 (60-70)	OECD Test Guideline 416	Oral / mouse 2 Generation	NOAEL = 13.8 g/kg/day
	OECD Test Guideline 414	Inhalation / Rat	NOAEC = 16000 ppm
Methanol 67-56-1 (3-5)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

(h) STOT-single exposure;

Category 2

Results / Target organs

Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure;

No data available

Target Organs

No information available.

(j) aspiration hazard;

No data available

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/l (Chlorella vulgaris)
Methanol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	

Component	Microtox	M-Factor
Ethyl alcohol	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min	
Methanol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

12.2. Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Component	Degradability
Ethyl alcohol 64-17-5 (60-70)	OECD 301E = 94%

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

Methanol 67-56-1 (3-5)	DT50 ~ 17.2d >94% after 20d
Degradation in sewage treatment plant	Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl alcohol	-0.32	No data available
Methanol	-0.74	<10 dimensionless

12.4. Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1170
14.2. UN proper shipping name ETHANOL
14.3. Transport hazard class(es) 3

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

14.4. Packing group II

ADR

14.1. UN number UN1170
14.2. UN proper shipping name ETHANOL
14.3. Transport hazard class(es) 3
14.4. Packing group II

IATA

14.1. UN number UN1170
14.2. UN proper shipping name ETHANOL
14.3. Transport hazard class(es) 3
14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl alcohol	64-17-5	200-578-6	-	-	X	X	KE-13217	X	X
Methanol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl alcohol	64-17-5	X	ACTIVE	X	-	X	X	X
Methanol	67-56-1	X	ACTIVE	X	-	X	X	X
Water	7732-18-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl alcohol	64-17-5	-	-	-
Methanol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75.	-

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

			(see link for restriction details)	
Water	7732-18-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl alcohol	64-17-5	Not applicable	Not applicable
Methanol	67-56-1	500 tonne	5000 tonne
Water	7732-18-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethyl alcohol	WGK1	
Methanol	WGK 2	Class I : 20 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Methanol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5 (60-70)		Group I	
Methanol 67-56-1 (3-5)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed
H319 - Causes serious eye irritation
H371 - May cause damage to organs
H225 - Highly flammable liquid and vapor
H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled
H370 - Causes damage to organs

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Creation Date 16-Oct-2018

Revision Date 24-Feb-2023

Revision Summary Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006**

SAFETY DATA SHEET

70% IMS with 5% Methanol

Revision Date 24-Feb-2023

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet