

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml
Cat No. : 88053
Molecular Formula Be₄ O(C₂ H₃ O₂)₆ in 5% HN O₃

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
 Erlenbachweg 2, 76870 Kandel, Germany
 Tel: +49 (0) 721 84007 280
 Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
 Neuhoferstrasse 11, CH 4153 Reinach
 Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
 Tox Info Suisse Emergency Number: **145 (24hr)**
 Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
 Chemtrec (24h) Toll-Free: 0800 564 402
 Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Substances/mixtures corrosive to metal

Category 1 (H290)

Health hazards

Acute Inhalation Toxicity - Vapors

Category 4 (H332)

Skin Corrosion/Irritation

Category 1 (H314) B

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Skin Sensitization

Category 1 (H317)

Carcinogenicity

Category 1B (H350i)

Specific target organ toxicity - (repeated exposure)

Category 2 (H373)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H290 - May be corrosive to metals

H332 - Harmful if inhaled

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H350i - May cause cancer by inhalation

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

Section 3: Composition/information on ingredients

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Water	7732-18-5	231-791-2	93.87	-
Nitric acid	7697-37-2	231-714-2	5.00	Ox. Liq. 3 (H272) Met. Corr. 1 (H290) Acute Tox. 3 (H331) Skin Corr. 1A (H314) Eye Dam. 1 (H318) (EUH071)
Hexakis[.mu.-(acetato-O:O)]-.mu.4-oxotetra beryllium	19049-40-2	EEC No. 242-785-4	1.13	Acute Tox. 3 (H301) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Carc. 1B (H350i) STOT SE 3 (H335) STOT RE 1 (H372) Aquatic Chronic 2 (H411)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Nitric acid	Ox. Liq. 2 :: C>=99% Ox. Liq. 3 :: 65%<=C<99% Acute Tox. 1 (inhal) :: C>=70% Acute Tox. 3 (inhal) :: 70%>C>=26.5% Acute Tox. 4 (inhal) :: 26.5%>C>=13.25% Skin Corr. 1A :: C>=20% Skin Corr. 1B :: 5%<=C<20% Met. Corr. 1 :: C>=2% EUH071 :: C>=20%	-	-

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Nitric acid	-	-	ATE = 2.65 mg/L (vapours)

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. May cause allergic skin reaction. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Not combustible. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes.

Hazardous Combustion Products

Nitrogen oxides (NO_x), Heavy metal oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 8B

Switzerland - Storage of hazardous substances

Storage class - SC 8 (Acid)
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Nitric acid	STEL: 1 ppm (15min) STEL: 2.6 mg/m ³ (15min)	STEL: 1 ppm 15 min STEL: 2.6 mg/m ³ 15 min	STEL / VLCT: 1 ppm. indicative limit STEL / VLCT: 2.6 mg/m ³ , indicative limit	STEL: 1 ppm 15 minuten STEL: 2.6 mg/m ³ 15 minuten	STEL / VLA-EC: 1 ppm (15 minutos). STEL / VLA-EC: 2.6 mg/m ³ (15 minutos).
Hexakis[.mu.-(acetat o-o:O)]-.mu.4-oxotetr aberyllium		STEL: 0.006 mg/m ³ 15 min TWA: 0.002 mg/m ³ 8 hr Carc.	TWA / VME: 0.0006 mg/m ³ (8 heures). restrictive limit		TWA / VLA-ED: 0.0002 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Nitric acid	STEL: 1 ppm 15 minuti. Short-term STEL: 2.6 mg/m ³ 15	TWA: 1 ppm (8 Stunden). AGW - TWA: 2.6 mg/m ³ (8	STEL: 1 ppm 15 minutos STEL: 2.6 mg/m ³ 15	STEL: 0.5 ppm 15 minuten STEL: 1.3 mg/m ³ 15	TWA: 0.5 ppm 8 tunteina TWA: 1.3 mg/m ³ 8

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

	minuti. Short-term	Stunden). AGW -	minutos TWA: 2 ppm 8 horas	minuten	tunteina STEL: 1 ppm 15 minuutteina STEL: 2.6 mg/m³ 15 minuutteina
Hexakis[.mu.-(acetato-O:O)]-.mu.4-oxotetraaberyllium			STEL: 0.01 mg/m³ 15 minutos Pele		

Component	Austria	Denmark	Switzerland	Poland	Norway
Nitric acid	MAK-KZGW: 1 ppm 15 Minuten MAK-KZGW: 2.6 mg/m³ 15 Minuten	STEL: 1 ppm 15 minutter STEL: 2.6 mg/m³ 15 minutter	STEL: 2 ppm 15 Minuten STEL: 5 mg/m³ 15 Minuten TWA: 2 ppm 8 Stunden TWA: 5 mg/m³ 8 Stunden	STEL: 2.6 mg/m³ 15 minutach TWA: 1.4 mg/m³ 8 godzinach	TWA: 2 ppm 8 timer TWA: 5 mg/m³ 8 timer STEL: 4 ppm 15 minutter. value calculated STEL: 10 mg/m³ 15 minutter. value calculated
Hexakis[.mu.-(acetato-O:O)]-.mu.4-oxotetraaberyllium			TWA: 0.0006 mg/m³ 8 Stunden		

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Nitric acid	STEL : 1 ppm STEL : 2.6 mg/m³	STEL-KGVI: 1 ppm 15 minutama. STEL-KGVI: 2.6 mg/m³ 15 minutama.	STEL: 1 ppm 15 min STEL: 2.6 mg/m³ 15 min	STEL: 1 ppm STEL: 2.6 mg/m³	TWA: 1 mg/m³ 8 hodinách. Ceiling: 2.5 mg/m³
Hexakis[.mu.-(acetato-O:O)]-.mu.4-oxotetraaberyllium			Skin		

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Nitric acid	STEL: 1 ppm 15 minutes. STEL: 2.6 mg/m³ 15 minutes.	STEL: 1 ppm 15 min STEL: 2.6 mg/m³ 15 min	STEL: 1 ppm STEL: 2.6 mg/m³	STEL: 2.6 mg/m³ 15 percekben. CK STEL: 1 ppm 15 percekben. CK	STEL: 1 ppm STEL: 2.6 mg/m³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Nitric acid	STEL: 1 ppm STEL: 2.6 mg/m³ TWA: 0.78 ppm TWA: 2 mg/m³	STEL: 1 ppm STEL: 2.6 mg/m³	STEL: 1 ppm 15 Minuten STEL: 2.6 mg/m³ 15 Minuten	STEL: 1 ppm 15 minuti STEL: 2.6 mg/m³ 15 minuti	STEL: 1 ppm 15 minute STEL: 2.6 mg/m³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Nitric acid	Skin notation MAC: 2 mg/m³	Ceiling: 2.6 mg/m³	TWA: 1 ppm 8 urah TWA: 2.6 mg/m³ 8 urah STEL: 1 ppm 15 minutah STEL: 2.6 mg/m³ 15 minutah	Binding STEL: 1 ppm 15 minuter Binding STEL: 2.6 mg/m³ 15 minuter TLV: 0.5 ppm 8 timmar. NGV TLV: 1.3 mg/m³ 8 timmar. NGV	STEL: 1 ppm 15 dakika STEL: 2.6 mg/m³ 15 dakika

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry

MDHS 99 Metals in air by ICP-AES

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

No information available

Predicted No Effect Concentration (PNEC)

No information available.

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Neoprene	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use In case of insufficient ventilation, wear suitable respiratory equipment
Recommended Filter type: Acid gases filter

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance Clear

Odor No information available

Odor Threshold No data available

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	1	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Nitric acid	-2.3	
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula Be₄ O(C₂ H₃ O₂)₆ in 5% HN O₃

Section 10: Stability and reactivity

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

Strong bases.

10.6. Hazardous decomposition products

Nitrogen oxides (NO_x). Heavy metal oxides.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

ALFAA88053

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

Oral	Based on available data, the classification criteria are not met
Dermal	No data available
Inhalation	Category 4

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	-	-
Nitric acid	-	-	LC50 = 2500 ppm. (Rat) 1h

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Nitric acid	-	-	ATE = 2.65 mg/L (vapours)

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;
Respiratory No data available
Skin Category 1
 No information available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available
 There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 2

Route of exposure	Inhalation
Target Organs	Lungs.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

Ecotoxicity effects May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

12.2. Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary based on information available, May persist.
Persistence
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Nitric acid	-2.3	No data available

12.4. Mobility in soil The product is water soluble, and may spread in water systems Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Do not flush to sewer. Large amounts will affect pH and harm aquatic organisms.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

IMDG/IMO

ALFAA88053

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

14.1. UN number UN3264
14.2. UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s.
Technical Shipping Name (NITRIC ACID)
14.3. Transport hazard class(es) 8
14.4. Packing group III

ADR

14.1. UN number UN3264
14.2. UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s.
Technical Shipping Name (NITRIC ACID)
14.3. Transport hazard class(es) 8
14.4. Packing group III

IATA

14.1. UN number UN3264
14.2. UN proper shipping name Corrosive liquid, acidic, inorganic, n.o.s.
Technical Shipping Name (NITRIC ACID)
14.3. Transport hazard class(es) 8
14.4. Packing group III

14.5. Environmental hazards No hazards identified
14.6. Special precautions for user No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
Nitric acid	7697-37-2	231-714-2	-	-	X	X	KE-25911	X	X
Hexakis[.mu.-(acetato-O:O)]-.mu.4-oxotetraberyllium	19049-40-2	242-785-4	-	-	-	X	-	-	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Water	7732-18-5	X	ACTIVE	X	-	X	X	X
Nitric acid	7697-37-2	X	ACTIVE	X	-	X	X	X
Hexakis[.mu.-(acetato-O:O)]-.mu.4-oxotetraberyllium	19049-40-2	-	-	-	-	-	-	-

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances	REACH (1907/2006) - Annex XVII - Restrictions	REACH Regulation (EC 1907/2006) article 59 -
-----------	--------	--	---	--

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

		Subject to Authorization	on Certain Dangerous Substances	Candidate List of Substances of Very High Concern (SVHC)
Water	7732-18-5	-	-	-
Nitric acid	7697-37-2	-	Use restricted. See entry 75. (see link for restriction details)	-
Hexakis[.mu.-(acetato-O:O)]-.mu.4-oxotetraberyllium	19049-40-2	-	Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Water	7732-18-5	Not applicable	Not applicable
Nitric acid	7697-37-2	Not applicable	Not applicable
Hexakis[.mu.-(acetato-O:O)]-.mu.4-oxotetraberyllium	19049-40-2	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Nitric acid	WGK1	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

	substances preparation (SR 814.81)		Procedure
Nitric acid 7697-37-2 (5.00)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H290 - May be corrosive to metals
H332 - Harmful if inhaled
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H350 - May cause cancer
H350i - May cause cancer by inhalation
H373 - May cause damage to organs through prolonged or repeated exposure
H272 - May intensify fire; oxidizer
H301 - Toxic if swallowed
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H331 - Toxic if inhaled
H335 - May cause respiratory irritation
H372 - Causes damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects
EUH071 - Corrosive to the respiratory tract

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards

On basis of test data

Health Hazards

Calculation method

SAFETY DATA SHEET

Beryllium, AAS standard solution, Specpure®, Be 1000µg/ml

Revision Date 30-Nov-2024

Environmental hazards

Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Prepared By

Health, Safety and Environmental Department

Revision Date

30-Nov-2024

Revision Summary

Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, Chemo (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet