

SAFETY DATA SHEET

Revision Date 21-Jun-2024

Revision Number 6

1. Identification

Product Name Karl Fischer Coulometric AG-Oil, anolyte solution, for cells with or without diaphragm

Cat No. : 47195

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Thermo Fisher Scientific Chemicals, Inc.
30 Bond Street
Ward Hill, MA 01835-8099
Tel: 800-343-0660
Fax: 800-322-4757

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Acute oral toxicity	Category 3
Acute dermal toxicity	Category 3
Acute Inhalation Toxicity - Vapors	Category 3
Skin Corrosion/Irritation	Category 1 B
Serious Eye Damage/Eye Irritation	Category 1
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Optic nerve, Central nervous system (CNS), Respiratory system.	
Specific target organ toxicity - (repeated exposure)	Category 1
Target Organs - Liver, Blood, Kidney, Central nervous system (CNS).	

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
Causes severe skin burns and eye damage
May cause respiratory irritation
May cause cancer
May damage the unborn child
Causes damage to organs
Causes damage to organs through prolonged or repeated exposure
Toxic if swallowed, in contact with skin or if inhaled



Precautionary Statements

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Ingestion

Rinse mouth

Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. CANNOT BE MADE NON-POISONOUS.

WARNING. Cancer and Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Methyl alcohol	67-56-1	45.0
Xylenes (o-, m-, p- isomers)	1330-20-7	10.0
Sulfur dioxide	7446-09-5	10
Diethanolamine	111-42-2	10.0
Chloroform	67-66-3	10.0
1-Imidazole	288-32-4	10.0
1H-Imidazole, monohydriodide	68007-08-9	5.0

4. First-aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Most important symptoms and effects	Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Carbon dioxide (CO ₂). Powder. Water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Water mist may be used to cool closed containers. CO ₂ , dry chemical, dry sand, alcohol-resistant foam.
Unsuitable Extinguishing Media	No information available
Flash Point	9 °C / 48.2 °F
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	No information available

Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Nitrogen oxides (NO_x). Sulfur oxides. Hydrogen iodide.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health	Flammability	Instability	Physical hazards
3	3	0	-

6. Accidental release measures

Personal Precautions	Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment and Clean Up	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling	Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage.	Keep away from heat, sparks and flame. Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Materials. Acids. Reducing Agent. Acid chlorides. Acid anhydrides. Oxidizing agent.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m ³ Skin TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³	TWA: 200 ppm STEL: 250 ppm
Xylenes (o-, m-, p- isomers)	TWA: 20 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 435 mg/m ³ (Vacated) STEL: 150 ppm (Vacated) STEL: 655 mg/m ³ TWA: 100 ppm TWA: 435 mg/m ³		TWA: 100 ppm STEL: 150 ppm
Sulfur dioxide	STEL: 0.25 ppm	(Vacated) TWA: 2 ppm (Vacated) TWA: 5 mg/m ³ (Vacated) STEL: 5 ppm (Vacated) STEL: 15 mg/m ³ TWA: 5 ppm TWA: 13 mg/m ³	IDLH: 100 ppm TWA: 2 ppm TWA: 5 mg/m ³ STEL: 5 ppm STEL: 13 mg/m ³	STEL: 0.25 ppm
Diethanolamine	TWA: 1 mg/m ³ Skin	(Vacated) TWA: 3 ppm (Vacated) TWA: 15 mg/m ³	TWA: 3 ppm TWA: 15 mg/m ³	TWA: 2 mg/m ³
Chloroform	TWA: 10 ppm	(Vacated) TWA: 2 ppm (Vacated) TWA: 9.78 mg/m ³ Ceiling: 50 ppm Ceiling: 240 mg/m ³	IDLH: 500 ppm STEL: 2 ppm STEL: 9.78 mg/m ³	TWA: 10 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eyeface Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type:

SCBA. Particulates filter conforming to EN 143.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State

Liquid

Appearance

Colorless - Light yellow

Odor

No information available

Odor Threshold

No information available

pH

Not applicable

Melting Point/Range	No data available
Boiling Point/Range	59 °C / 138.2 °F
Flash Point	9 °C / 48.2 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	23 hPa @ 20 °C
Vapor Density	No information available
Specific Gravity	1.04 g/cm3
Solubility	no data available
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Acids, Reducing Agent, Acid chlorides, Acid anhydrides, Oxidizing agent
Hazardous Decomposition Products	Nitrogen oxides (NOx), Sulfur oxides, Hydrogen iodide
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Category 3.
ATE = 50 - 300 mg/kg.

Dermal LD50 Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Category 3.
ATE = 200 - 1000 mg/kg.

Vapor LC50 Based on ATE data, the classification criteria are not met. ATE > 20 mg/l. Category 3. ATE
= 2 - 10 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Xylenes (o-, m-, p- isomers)	LD50 = 3500 mg/kg (Rat)	LD50 > 4350 mg/kg (Rabbit)	29.08 mg/L [MOE Risk Assessment Vol.1, 2002]
Sulfur dioxide	Not listed	Not listed	Per CGA P-20: 2500 ppm/1hr (Rat)
Diethanolamine	LD50 = 780 mg/kg (Rat)	LD50 = 11.9 mL/kg (Rabbit)	Not listed
Chloroform	LD50 = 450 mg/kg (Rat)	LD50 > 20 g/kg (Rabbit)	47,702 mg/L (Rat) 4 h
1-Imidazole	970 mg/kg (Rat)	-	-

Toxicologically Synergistic No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation No information available

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed
Xylenes (o-, m-, p-isomers)	1330-20-7	Not listed	Not listed	Not listed	Not listed	Not listed
Sulfur dioxide	7446-09-5	Not listed	Not listed	Not listed	Not listed	Not listed
Diethanolamine	111-42-2	Group 2B	Not listed	A3	X	A3
Chloroform	67-66-3	Group 2B	Reasonably Anticipated	A3	X	A3
1-Imidazole	288-32-4	Not listed	Not listed	Not listed	Not listed	Not listed
1H-Imidazole, monohydriodide	68007-08-9	Not listed	Not listed	Not listed	Not listed	Not listed

IARC (International Agency for Research on Cancer)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

A5 - Not Suspected as a Human Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Optic nerve Central nervous system (CNS) Respiratory system
STOT - repeated exposure Liver Blood Kidney Central nervous system (CNS)

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Contains a substance which is: Toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h
Xylenes (o-, m-, p- isomers)	Not listed	LC50: 30.26 - 40.75 mg/L, 96h static (Poecilia reticulata) LC50: = 780 mg/L, 96h semi-static (Cyprinus carpio) LC50: 23.53 - 29.97 mg/L, 96h static (Pimephales promelas) LC50: > 780 mg/L, 96h (Cyprinus carpio) LC50: 7.711 - 9.591 mg/L, 96h static (Lepomis macrochirus) LC50: = 19 mg/L, 96h (Lepomis macrochirus) LC50: 13.1 - 16.5 mg/L, 96h flow-through (Lepomis macrochirus) LC50: 13.5 - 17.3 mg/L, 96h (Oncorhynchus mykiss) LC50: 2.661 - 4.093 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 13.4 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 0.0084 mg/L 24 h	LC50: = 0.6 mg/L, 48h (Gammarus lacustris) EC50: = 3.82 mg/L, 48h (water flea)
Diethanolamine	EC50: 2.1 - 2.3 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 7.8 mg/L, 72h (Desmodesmus subspicatus)	Pimephales promelas: LC50: 140 mg/L/96h	EC50 = 73 mg/L 5 min EC50 > 16 mg/L 16 h	EC50: = 55 mg/L, 48h (Daphnia magna)
Chloroform	EC50 = 560 mg/L/48h	LC50: = 300 mg/L, 96h static (Poecilia reticulata) LC50: = 18 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 18 mg/L, 96h flow-through (Lepomis macrochirus) LC50: = 71 mg/L, 96h flow-through (Pimephales promelas)	Photobacterium phosphoreum: EC50 = 520 mg/L/5 min Photobacterium phosphoreum: EC50 = 670 mg/L/15 min Photobacterium phosphoreum: EC50 = 670 mg/L/30min	EC50 = 28.9 mg/L/48h
1-Imidazole	EC50: = 82 mg/L, 96h (Desmodesmus subspicatus) EC50: = 130 mg/L, 72h (Desmodesmus subspicatus)	Not listed	= 1200 mg/L EC50 Pseudomonas putida 17 h = 231 mg/L EC50 Photobacterium phosphoreum 30 min	EC50: = 341.5 mg/L, 48h (Daphnia magna)

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Methyl alcohol	-0.74

Xylenes (o-, m-, p- isomers)	3.15
Diethanolamine	-2.46
Chloroform	2
1-Imidazole	-0.02

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-
Xylenes (o-, m-, p- isomers) - 1330-20-7	U239	-
Chloroform - 67-66-3	U044	-

14. Transport information

DOT

UN-No UN3286
 Proper Shipping Name Flammable liquid, toxic, corrosive, n.o.s.
 Technical Name (METHANOL, Imidazole)
 Hazard Class 3
 Subsidiary Hazard Class 6.1, 8
 Packing Group II

TDG

UN-No UN3286
 Proper Shipping Name Flammable liquid, toxic, corrosive, n.o.s.
 Hazard Class 3
 Subsidiary Hazard Class 6.1, 8
 Packing Group II

IATA

UN-No UN3286
 Proper Shipping Name FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S.*
 Hazard Class 3
 Subsidiary Hazard Class 6.1, 8
 Packing Group II

IMDG/IMO

UN-No UN3286
 Proper Shipping Name Flammable liquid, toxic, corrosive, n.o.s.
 Hazard Class 3
 Subsidiary Hazard Class 6.1, 8
 Packing Group II

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Methyl alcohol	67-56-1	X	ACTIVE	-
Xylenes (o-, m-, p- isomers)	1330-20-7	X	ACTIVE	-
Sulfur dioxide	7446-09-5	X	ACTIVE	-
Diethanolamine	111-42-2	X	ACTIVE	-
Chloroform	67-66-3	X	ACTIVE	-
1-Imidazole	288-32-4	X	ACTIVE	-
1H-Imidazole, monohydriodide	68007-08-9	-	-	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

'- - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Methyl alcohol	67-56-1	X	-	200-659-6	X	X	X	X	X	KE-23193
Xylenes (o-, m-, p- isomers)	1330-20-7	X	-	215-535-7	X	X	X	X	X	KE-35427
Sulfur dioxide	7446-09-5	X	-	231-195-2	X	X	X	X	X	KE-32567
Diethanolamine	111-42-2	X	-	203-868-0	X	X	X	X	X	KE-20959
Chloroform	67-66-3	X	-	200-663-8	X	X	X	X	X	KE-34076
1-Imidazole	288-32-4	X	-	206-019-2	X	X	X	X	X	KE-20937
1H-Imidazole, monohydriodide	68007-08-9	-	-	-	-	-	-	X	-	-

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting thresholds
Methyl alcohol	67-56-1	45.0	1.0 %	-
Xylenes (o-, m-, p- isomers)	1330-20-7	10.0	1.0 %	-
Diethanolamine	111-42-2	10.0	1.0 %	-
Chloroform	67-66-3	10.0	0.1 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Xylenes (o-, m-, p- isomers)	X	100 lb	-	-
Chloroform	X	10 lb	X	X

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-
Xylenes (o-, m-, p- isomers)	X		-
Diethanolamine	X		-
Chloroform	X		-

OSHA - Occupational Safety and Health Administration

Not applicable

Component	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Sulfur dioxide	-	TQ: 1000 lb

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Methyl alcohol	5000 lb	-	5000 lb 2270 kg
Xylenes (o-, m-, p- isomers)	100 lb	-	100 lb 45.4 kg
Sulfur dioxide	-	500 lb	-
Diethanolamine	100 lb	-	100 lb 45.4 kg
Chloroform	10 lb	10 lb	10 lb 4.54 kg

California Proposition 65

This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Methyl alcohol	67-56-1	Developmental	-	Developmental
Sulfur dioxide	7446-09-5	Developmental	-	Developmental
Diethanolamine	111-42-2	Carcinogen	-	Carcinogen
Chloroform	67-66-3	Carcinogen Developmental	20 µg/day 40 µg/day	Developmental Carcinogen

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Methyl alcohol	X	X	X	X	X
Xylenes (o-, m-, p- isomers)	X	X	X	X	X
Sulfur dioxide	X	X	X	-	X
Diethanolamine	X	X	X	X	X
Chloroform	X	X	X	X	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product contains the following DHS chemicals:

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard
Sulfur dioxide	Release STQs - 5000lb (anhydrous) Theft STQs - 500lb (anhydrous)
Chloroform	Release STQs - 20000lb

Other International Regulations

Mexico - Grade

No information available

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous	REACH Regulation (EC 1907/2006) article 59 - Candidate List of

			Substances	Substances of Very High Concern (SVHC)
Methyl alcohol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Xylenes (o-, m-, p- isomers)	1330-20-7	-	Use restricted. See entry 75. (see link for restriction details)	-
Sulfur dioxide	7446-09-5	-	Use restricted. See entry 75. (see link for restriction details)	-
Diethanolamine	111-42-2	-	Use restricted. See entry 75. (see link for restriction details)	-
Chloroform	67-66-3	-	Use restricted. See entry 32. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
1-Imidazole	288-32-4	-	Use restricted. See entry 30. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
1H-Imidazole, monohydriodide	68007-08-9	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable
Xylenes (o-, m-, p- isomers)	1330-20-7	Listed	Not applicable	Not applicable	Not applicable
Sulfur dioxide	7446-09-5	Listed	Not applicable	Not applicable	Not applicable
Diethanolamine	111-42-2	Listed	Not applicable	Not applicable	Not applicable
Chloroform	67-66-3	Listed	Not applicable	Not applicable	Not applicable
1-Imidazole	288-32-4	Listed	Not applicable	Not applicable	Not applicable
1H-Imidazole, monohydriodide	68007-08-9	Not applicable	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	Not applicable	Not applicable	Annex I - Y42
Sulfur dioxide	7446-09-5	Not applicable	Not applicable	Not applicable	Not applicable
Diethanolamine	111-42-2	Not applicable	Not applicable	Not applicable	Not applicable
Chloroform	67-66-3	Not applicable	Not applicable	Not applicable	Annex I - Y45
1-Imidazole	288-32-4	Not applicable	Not applicable	Not applicable	Not applicable
1H-Imidazole, monohydriodide	68007-08-9	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Health, Safety and Environmental Department
Email: chem.techinfo@thermofisher.com
www.thermofisher.com

Revision Date 21-Jun-2024
Print Date 21-Jun-2024
Revision Summary New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS