

Creation Date 24-Jul-2007

Revision Date 19-Oct-2023

Revision Number 12

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	2-n-Butoxyethanol
Cat No. :	B/4900/PB17, B/4900/08, B/4900/17, B/4900/25, B/49
Synonyms	Butyl cellosolve; Ethylene glycol monobutyl ether, Butyl glycol
Index No	603-014-00-0
CAS No	111-76-2
EC No	203-905-0
Molecular Formula	C6 H14 O2
REACH registration number	01-2119475108-36

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road, Loughborough,
Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Acute oral toxicity

Category 4 (H302)

Acute Inhalation Toxicity - Vapors

Category 3 (H331)

Skin Corrosion/Irritation

Category 2 (H315)

Serious Eye Damage/Eye Irritation

Category 2 (H319)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H302 - Harmful if swallowed

H331 - Toxic if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation

Combustible liquid

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P311 - Call a POISON CENTER or doctor/physician

2.3. Other hazards

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
2-Butoxyethanol	111-76-2	EEC No. 203-905-0	<100	Acute Tox. 4 (H302) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319)

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
2-Butoxyethanol	ATE = 1200 mg/kg bw	-	ATE = 3 mg/L (vapour)

ECHA (RAC) - Committee for Risk Assessment - European Chemicals Agency
ATE - Acute Toxicity Estimate; mg/kg bw - milligrams per kilogram of body weight

REACH registration number	01-2119475108-36
---------------------------	------------------

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Self-Protection of the First Aider	Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Symptoms may be delayed.
--------------------	---

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Combustible material. Containers may explode when heated. Vapors may accumulate in confined areas (basement, tanks, hopper/tank cars, etc.). Vapors may form explosive mixtures with air. Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), peroxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition.

Hygiene Measures

When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

7.2. Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

Keep away from heat, sparks and flame. Protect from light. Protect from moisture. Reacts with air to form peroxides. Keep containers tightly closed in a cool, well-ventilated place. Keep in properly labeled containers. Keep away from heat. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 6.1C

Switzerland - Storage of hazardous substances

Storage class - SC 6.1
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
2-Butoxyethanol	TWA: 20 ppm (8h) TWA: 98 mg/m ³ (8h) STEL: 50 ppm (15min) STEL: 246 mg/m ³ (15min) Skin	STEL: 50 ppm 15 min STEL: 246 mg/m ³ 15 min TWA: 25 ppm 8 hr TWA: 123 mg/m ³ 8 hr Skin	TWA / VME: 10 ppm (8 heures). restrictive limit TWA / VME: 49 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 50 ppm. restrictive limit STEL / VLCT: 246 mg/m ³ . restrictive limit Peau	TWA: 20 ppm 8 uren TWA: 98 mg/m ³ 8 uren STEL: 50 ppm 15 minuten STEL: 246 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 50 ppm (15 minutos). STEL / VLA-EC: 245 mg/m ³ (15 minutos). TWA / VLA-ED: 20 ppm (8 horas) TWA / VLA-ED: 98 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
2-Butoxyethanol	TWA: 20 ppm 8 ore. Time Weighted Average TWA: 98 mg/m ³ 8 ore. Time Weighted Average STEL: 50 ppm 15 minuti. Short-term STEL: 246 mg/m ³ 15 minuti. Short-term Pelle	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 49 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK applies for the sum of the concentrations of 2-Butoxyethanol and its Acetate in air TWA: 49 mg/m ³ (8 Stunden). MAK applies for the sum of the concentrations of 2-Butoxyethanol and its Acetate in air Höhepunkt: 20 ppm Höhepunkt: 98 mg/m ³ Haut	STEL: 50 ppm 15 minutos STEL: 246 mg/m ³ 15 minutos TWA: 20 ppm 8 horas TWA: 98 mg/m ³ 8 horas Pele	huid STEL: 246 mg/m ³ 15 minuten TWA: 100 mg/m ³ 8 uren	TWA: 20 ppm 8 tunteina TWA: 98 mg/m ³ 8 tunteina STEL: 50 ppm 15 minuutteina STEL: 250 mg/m ³ 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
-----------	---------	---------	-------------	--------	--------

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

2-Butoxyethanol	Haut MAK-KZGW: 40 ppm 15 Minuten MAK-KZGW: 200 mg/m ³ 15 Minuten MAK-TMW: 20 ppm 8 Stunden MAK-TMW: 98 mg/m ³ 8 Stunden	TWA: 20 ppm 8 timer TWA: 98 mg/m ³ 8 timer STEL: 246 mg/m ³ 15 minutter STEL: 50 ppm 15 minutter Hud	Haut/Peau STEL: 20 ppm 15 Minuten STEL: 98 mg/m ³ 15 Minuten TWA: 10 ppm 8 Stunden TWA: 49 mg/m ³ 8 Stunden	STEL: 200 mg/m ³ 15 minutach TWA: 98 mg/m ³ 8 godzinach	TWA: 10 ppm 8 timer TWA: 50 mg/m ³ 8 timer STEL: 20 ppm 15 minutter. value calculated STEL: 75 mg/m ³ 15 minutter. value calculated Hud
-----------------	---	--	---	--	---

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
2-Butoxyethanol	TWA: 20 ppm TWA: 98 mg/m ³ STEL : 50 ppm STEL : 246 mg/m ³ Skin notation	kože TWA-GVI: 20 ppm 8 satima. TWA-GVI: 98 mg/m ³ 8 satima. STEL-KGVI: 50 ppm 15 minutama. STEL-KGVI: 246 mg/m ³ 15 minutama.	TWA: 20 ppm 8 hr. TWA: 98 mg/m ³ 8 hr. STEL: 50 ppm 15 min STEL: 246 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption STEL: 50 ppm STEL: 246 mg/m ³ TWA: 20 ppm TWA: 98 mg/m ³	TWA: 100 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 200 mg/m ³ biological test

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
2-Butoxyethanol	Nahk TWA: 20 ppm 8 tundides. TWA: 98 mg/m ³ 8 tundides. STEL: 50 ppm 15 minutites. STEL: 246 mg/m ³ 15 minutites.	Skin notation TWA: 20 ppm 8 hr TWA: 98 mg/m ³ 8 hr STEL: 50 ppm 15 min STEL: 246 mg/m ³ 15 min	skin - potential for cutaneous absorption TWA: 25 ppm TWA: 120 mg/m ³	STEL: 246 mg/m ³ 15 percekben. CK TWA: 98 mg/m ³ 8 órában. AK lehetséges borón keresztül felszívódás	STEL: 50 ppm STEL: 246 mg/m ³ TWA: 20 ppm 8 klukkustundum. TWA: 100 mg/m ³ 8 klukkustundum. TWA: 25 ppm 8 klukkustundum. regulated under Butyl cellosolve Skin notation

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
2-Butoxyethanol	skin - potential for cutaneous exposure STEL: 50 ppm STEL: 246 mg/m ³ TWA: 20 ppm TWA: 98 mg/m ³	TWA: 10 ppm IPRD TWA: 50 mg/m ³ IPRD Oda STEL: 20 ppm STEL: 100 mg/m ³	Possibility of significant uptake through the skin TWA: 20 ppm 8 Stunden TWA: 98 mg/m ³ 8 Stunden STEL: 50 ppm 15 Minuten STEL: 246 mg/m ³ 15 Minuten	possibility of significant uptake through the skin TWA: 20 ppm TWA: 98 mg/m ³ STEL: 50 ppm 15 minuti STEL: 246 mg/m ³ 15 minuti	Skin notation TWA: 20 ppm 8 ore TWA: 98 mg/m ³ 8 ore STEL: 50 ppm 15 minute STEL: 246 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
2-Butoxyethanol	MAC: 5 mg/m ³	Ceiling: 246 mg/m ³ Potential for cutaneous absorption TWA: 20 ppm TWA: 98 mg/m ³	TWA: 20 ppm 8 urah TWA: 98 mg/m ³ 8 urah Koža STEL: 50 ppm 15 minutah STEL: 246 mg/m ³ 15 minutah	Binding STEL: 50 ppm 15 minuter Binding STEL: 246 mg/m ³ 15 minuter TLV: 10 ppm 8 timmar. NGV TLV: 50 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 20 ppm 8 saat TWA: 98 mg/m ³ 8 saat STEL: 50 ppm 15 dakika STEL: 246 mg/m ³ 15 dakika

Biological limit values

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

Component	European Union	United Kingdom	France	Spain	Germany
2-Butoxyethanol		Butoxyacetic acid: 240 mmol/mol creatinine urine post shift		Butoxyacetic acid (with hydrolysis): 200 mg/g Creatinine urine end of shift	Butoxyacetic acid (after hydrolysis): 150 mg/g Creatinine urine (for long-term exposures: at the end of the shift after several shifts)

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

					Butoxyacetic acid (after hydrolysis): 150 mg/g Creatinine urine (end of shift)
--	--	--	--	--	---

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
2-Butoxyethanol 111-76-2 (<100)		DNEL = 89mg/kg bw/day		DNEL = 125mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
2-Butoxyethanol 111-76-2 (<100)	DNEL = 246mg/m ³	DNEL = 1091mg/m ³		DNEL = 98mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
2-Butoxyethanol 111-76-2 (<100)	PNEC = 8.8mg/L	PNEC = 34.6mg/kg sediment dw	PNEC = 26.4mg/L	PNEC = 463mg/L	PNEC = 2.33mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
2-Butoxyethanol 111-76-2 (<100)	PNEC = 0.88mg/L	PNEC = 3.46mg/kg sediment dw		PNEC = 0.02g/kg food	

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	> 480 minutes	0.5 mm	EN 374	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Viton (R)	> 480 minutes	0.4 mm	Level 6	
Nitrile rubber				

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

Neoprene gloves	> 480 minutes	0.45 mm
Nitrile rubber	> 480 minutes	0.56 mm
Skin and body protection Long sleeved clothing.		

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Light yellow	
Odor	Slight	
Odor Threshold	No data available	
Melting Point/Range	-70 °C / -94 °F	
Softening Point	No data available	
Boiling Point/Range	171 °C / 339.8 °F	
Flammability (liquid)	Combustible liquid	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.1 vol% Upper 10.6 vol%	
Flash Point	62 °C / 143.6 °F	Method - Pensky Martens Closed Cup (ASTM D93, BS EN 22719, BS 2000 Part 404, IP 404, ISO 2719, AS/NZS 2106)
Autoignition Temperature	230 °C / 446 °F	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	5.31 mPa.s at 20 °C	Dynamic
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
2-Butoxyethanol	0.81	
Vapor Pressure	0.8 hPa @ 20°C	
Density / Specific Gravity	0.901	@ 20 °C
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

9.2. Other information

Molecular Formula C6 H14 O2
Molecular Weight 118.18
Explosive Properties explosive air/vapour mixtures possible
Oxidizing Properties Not oxidising

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight. Exposure to air or moisture over prolonged periods. Heating in air.

10.5. Incompatible materials

Strong oxidizing agents. Bases. Metals. Aluminium. . Zinc.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). peroxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 4
Dermal Based on available data, the classification criteria are not met
Inhalation Category 3

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
2-Butoxyethanol	1746 mg/kg (Rat)	LD50 > 2000 mg/kg (Guinea pig) OCED 402	LC50 = 450 ppm (Rat) 4 h LC50 = 486 ppm (Rat) 4 h

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
2-Butoxyethanol	ATE = 1200 mg/kg bw	-	ATE = 3 mg/L (vapour)

ECHA (RAC) - Committee for Risk Assessment - European Chemicals Agency
ATE - Acute Toxicity Estimate; mg/kg bw - milligrams per kilogram of body weight

(b) skin corrosion/irritation;

Test method Category 2
OECD 405
Test species rabbit
Observational endpoint Irritating to skin

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
2-Butoxyethanol 111-76-2 (<100)	Guinea Pig Maximisation Test (GPMT)	guinea pig	- non-sensitising

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met
The table below indicates whether each agency has listed any ingredient as a carcinogen

(g) reproductive toxicity; Based on available data, the classification criteria are not met
Reproductive Effects None known.

(h) STOT-single exposure; Based on available data, the classification criteria are not met

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs

None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Other Adverse Effects No information available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects . Do not empty into drains.

Component	Freshwater Fish	Water Flea	Freshwater Algae
2-Butoxyethanol	1490 mg/L LC50 96 h 2950 mg/L LC50 96 h	1550 mg/l EC50 48 hr >1000 mg/L EC50 48 h 1698 - 1940 mg/L EC50 24 h	1840 mg/l EC50 72 hr

12.2. Persistence and degradability

Persistence

Readily biodegradable
Persistence is unlikely.

Component	Degradability
2-Butoxyethanol	90% (28d) OECD 301B

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

111-76-2 (<100)

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
2-Butoxyethanol	0.81	No data available

12.4. Mobility in soil

The product is water soluble, and may spread in water systems. Will likely be mobile in the environment due to its water solubility. Spillage unlikely to penetrate soil: Highly mobile in soils

12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number

UN2810

14.2. UN proper shipping name

TOXIC LIQUID, ORGANIC, N.O.S.

Technical Shipping Name

2-Butoxyethanol

14.3. Transport hazard class(es)

6.1

14.4. Packing group

III

ADR

14.1. UN number

UN2810

FSUB4900

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

14.2. UN proper shipping name	TOXIC LIQUID, ORGANIC, N.O.S.
Technical Shipping Name	2-Butoxyethanol
14.3. Transport hazard class(es)	6.1
14.4. Packing group	III

IATA

14.1. UN number	UN2810
14.2. UN proper shipping name	TOXIC LIQUID, ORGANIC, N.O.S.
Technical Shipping Name	2-Butoxyethanol
14.3. Transport hazard class(es)	6.1
14.4. Packing group	III

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
2-Butoxyethanol	111-76-2	203-905-0	-	-	X	X	KE-04134	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
2-Butoxyethanol	111-76-2	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
2-Butoxyethanol	111-76-2	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
2-Butoxyethanol	111-76-2	Not applicable	Not applicable

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
2-Butoxyethanol	WGK1	

Component	France - INRS (Tables of occupational diseases)
2-Butoxyethanol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
2-Butoxyethanol 111-76-2 (<100)		Group I	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed

H331 - Toxic if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

SAFETY DATA SHEET

2-n-Butoxyethanol

Revision Date 19-Oct-2023

KECL - Korean Existing and Evaluated Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Creation Date 24-Jul-2007

Revision Date 19-Oct-2023

Revision Summary SDS sections updated.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet