

ALFAA41643

## Beryllium foil

### SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**产品说明:** 铝箔, 0.1mm (0.004in) 厚  
**Product Description:** Beryllium foil

**Cat No. :** 41643  
**CAS No** 7440-41-7  
**Molecular Formula** Be

**Supplier** Avocado Research Chemicals Ltd.  
(Part of Thermo Fisher Scientific)  
Shore Road, Heysham  
Lancashire, LA3 2XY,  
United Kingdom  
Office Tel: +44 (0) 1524 850506  
Office Fax: +44 (0) 1524 850608

**Emergency Telephone Number** For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

**E-mail address** begel.sdsdesk@thermofisher.com

**Recommended Use** Laboratory chemicals.  
**Uses advised against** No Information available

### SECTION 2. HAZARD IDENTIFICATION

**Physical State**  
Solid

**Appearance**  
Dark grey

**Odor**  
Odorless

#### Emergency Overview

Flammable solid. Toxic if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. Fatal if inhaled. May cause cancer by inhalation.

#### Classification of the substance or mixture

|                                                      |             |
|------------------------------------------------------|-------------|
| Flammable solids.                                    | Category 2  |
| Acute Oral Toxicity                                  | Category 3  |
| Acute Inhalation Toxicity - Dusts and Mists          | Category 2  |
| Skin Corrosion/Irritation                            | Category 2  |
| Serious Eye Damage/Eye Irritation                    | Category 2  |
| Skin Sensitization                                   | Category 1  |
| Carcinogenicity                                      | Category 1A |
| Specific target organ toxicity - (single exposure)   | Category 3  |
| Specific target organ toxicity - (repeated exposure) | Category 1  |

#### Label Elements

## Beryllium foil



## Signal Word

## Danger

## Hazard Statements

H228 - Flammable solid  
H301 - Toxic if swallowed  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation  
H372 - Causes damage to organs through prolonged or repeated exposure  
H330 - Fatal if inhaled  
H350i - May cause cancer by inhalation

## Precautionary Statements

## Prevention

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P264 - Wash face, hands and any exposed skin thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P272 - Contaminated work clothing should not be allowed out of the workplace  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P284 - Wear respiratory protection

## Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor  
P330 - Rinse mouth  
P362 + P364 - Take off contaminated clothing and wash it before reuse

## Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P405 - Store locked up

## Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Physical and Chemical Hazards

Combustible material.

## Health Hazards

Toxic if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. Fatal if inhaled. May cause cancer by inhalation.

## Environmental hazards

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Is not likely mobile in the environment due its low water solubility. Spillage unlikely to penetrate soil.

This product does not contain any known or suspected endocrine disruptors.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | CAS No    | Weight % |
|-----------|-----------|----------|
| Beryllium | 7440-41-7 | > 99     |

**SECTION 4. FIRST AID MEASURES****General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

**Eye Contact**

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

**Skin Contact**

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

**Inhalation**

Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.

**Ingestion**

Do NOT induce vomiting. Call a physician or poison control center immediately.

**Most important symptoms and effects**

None reasonably foreseeable. May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

**Self-Protection of the First Aider**

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**Notes to Physician**

Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Dry chemical.

**Extinguishing media which must not be used for safety reasons**

Carbon dioxide (CO<sub>2</sub>).

**Specific Hazards Arising from the Chemical**

Thermal decomposition can lead to release of irritating gases and vapors.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

**SECTION 6. ACCIDENTAL RELEASE MEASURES****Personal Precautions**

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

**Environmental Precautions**

Should not be released into the environment. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

## Beryllium foil

**Methods for Containment and Clean Up**

Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

Refer to protective measures listed in Sections 8 and 13.

**SECTION 7. HANDLING AND STORAGE****Handling**

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Avoid dust formation. Use only under a chemical fume hood. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance.

**Storage**

Keep in a dry, cool and well-ventilated place. Keep container tightly closed.

**Specific Use(s)**

Use in laboratories

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control Parameters**

| Component | China                                                                  | Taiwan                       | Thailand                                                                                          | Hong Kong                                                    |
|-----------|------------------------------------------------------------------------|------------------------------|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| Beryllium | TWA: 0.0005 mg/m <sup>3</sup><br>STEL: 0.001 mg/m <sup>3</sup><br>Skin | TWA: 0.002 mg/m <sup>3</sup> | Ceiling: 0.005 mg/m <sup>3</sup><br>STEL: 0.025 mg/m <sup>3</sup><br>TWA: 0.002 mg/m <sup>3</sup> | TWA: 0.002 mg/m <sup>3</sup><br>STEL: 0.01 mg/m <sup>3</sup> |

| Component | ACGIH TLV                      | OSHA PEL                                                                                                                                                                                                        | NIOSH                                                          | The United Kingdom                                                                 | European Union                                                                   |
|-----------|--------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------|
| Beryllium | TWA: 0.00005 mg/m <sup>3</sup> | (Vacated) TWA: 2 µg/m <sup>3</sup><br>Ceiling: 2 µg/m <sup>3</sup><br>(Vacated) STEL: 25 µg/m <sup>3</sup><br>(Vacated) Ceiling: 5 µg/m <sup>3</sup><br>TWA: 0.2 µg/m <sup>3</sup><br>STEL: 2 µg/m <sup>3</sup> | IDLH: 4 mg/m <sup>3</sup><br>Ceiling: 0.0005 mg/m <sup>3</sup> | STEL: 0.006 mg/m <sup>3</sup> 15 min<br>TWA: 0.002 mg/m <sup>3</sup> 8 hr<br>Carc. | TWA: 0.0002 mg/m <sup>3</sup> (8h)<br>TWA: 0.0006 mg/m <sup>3</sup> (8h)<br>Skin |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

**Monitoring methods**

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

**Exposure Controls****Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

**Personal protective equipment**

**Eye Protection** Goggles (European standard - EN 166)

**Hand Protection** Protective gloves

## SAFETY DATA SHEET

## Beryllium foil

| Glove material | Breakthrough time | Glove thickness | EU standard | Glove comments        |
|----------------|-------------------|-----------------|-------------|-----------------------|
| Nitrile rubber | See manufacturers | -               | EN 374      | (minimum requirement) |
| Neoprene       | recommendations   |                 |             |                       |
| PVC            |                   |                 |             |                       |
| Natural rubber |                   |                 |             |                       |

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Skin and body protection** Long sleeved clothing

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Large scale/emergency use** Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** Particulates filter conforming to EN 143

**Small scale/Laboratory use** Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Particle filtering: EN149:2001  
When RPE is used a face piece Fit Test should be conducted

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice.

**Environmental exposure controls** No information available.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                                |                          |                                          |
|------------------------------------------------|--------------------------|------------------------------------------|
| <b>Appearance</b>                              | Dark grey                |                                          |
| <b>Physical State</b>                          | Solid                    |                                          |
| <b>Odor</b>                                    | Odorless                 |                                          |
| <b>Odor Threshold</b>                          | No data available        |                                          |
| <b>pH</b>                                      | No information available |                                          |
| <b>Melting Point/Range</b>                     | 1278 °C / 2332.4 °F      |                                          |
| <b>Softening Point</b>                         | No data available        |                                          |
| <b>Boiling Point/Range</b>                     | 2970 °C / 5378 °F        | @ 5 mmHg                                 |
| <b>Flash Point</b>                             | No information available | <b>Method -</b> No information available |
| <b>Evaporation Rate</b>                        | Not applicable           | Solid                                    |
| <b>Flammability (solid,gas)</b>                | No information available |                                          |
| <b>Explosion Limits</b>                        | No data available        |                                          |
| <b>Vapor Pressure</b>                          | 1.85 mmHg                |                                          |
| <b>Vapor Density</b>                           | Not applicable           | Solid                                    |
| <b>Specific Gravity / Density</b>              | No data available        |                                          |
| <b>Bulk Density</b>                            | 1.85 @ 20°C              |                                          |
| <b>Water Solubility</b>                        | Insoluble                |                                          |
| <b>Solubility in other solvents</b>            | No information available |                                          |
| <b>Partition Coefficient (n-octanol/water)</b> |                          |                                          |
| <b>Autoignition Temperature</b>                | Not applicable           |                                          |
| <b>Decomposition Temperature</b>               | No data available        |                                          |
| <b>Viscosity</b>                               | Not applicable           | Solid                                    |
| <b>Explosive Properties</b>                    | No information available |                                          |
| <b>Oxidizing Properties</b>                    | No information available |                                          |

Molecular Formula Be  
Molecular Weight 9.01

**SECTION 10. STABILITY AND REACTIVITY**

**Stability** Stable.

**Hazardous Reactions** None under normal processing.  
**Hazardous Polymerization** Hazardous polymerization does not occur.

**Conditions to Avoid** Incompatible products.

**Materials to avoid** Acids. Bases. Halogens. Metals.

**Hazardous Decomposition Products** Beryllium oxide.

**SECTION 11. TOXICOLOGICAL INFORMATION****Product Information**

(a) acute toxicity;

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;  
Respiratory No data available  
Skin Category 1  
May cause sensitization by skin contact

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 1B  
The table below indicates whether each agency has listed any ingredient as a carcinogen

| Component | EU           | UK | Germany | IARC    |
|-----------|--------------|----|---------|---------|
| Beryllium | Carc Cat. 1B |    | Cat. 1  | Group 1 |

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3  
Results / Target organs Respiratory system

(i) STOT-repeated exposure; Category 1  
Route of exposure Inhalation  
Target Organs Lungs.

(j) aspiration hazard; Not applicable  
Solid

**Symptoms / effects, both acute and delayed** Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity effects** May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

**Persistence and Degradability** Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary  
**Persistence** Insoluble in water, May persist.  
**Degradability** Not relevant for inorganic substances.  
**Degradation in sewage treatment plant** Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**Bioaccumulative Potential** May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

**Mobility in soil** Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water solubility

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors  
**Persistent Organic Pollutant** This product does not contain any known or suspected substance  
**Ozone Depletion Potential** This product does not contain any known or suspected substance

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Waste from Residues/Unused Products** Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point.

**Other Information** Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.

**SECTION 14. TRANSPORT INFORMATION****Road and Rail Transport**

**IMDG/IMO** Not regulated

**IATA** Not regulated

**Special Precautions for User** No special precautions required

**SECTION 15. REGULATORY INFORMATION****International Inventories**

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan

## Beryllium foil

(ISHL), Australia (AICS), Korea (KECL).

| Component | The Inventory of Hazardous Chemicals (2015 Edition) | List of dangerous goods GB 12268 - 2012 | TCSI | IECSC | EINECS    | TSCA | DSL | PICCS | ENCS | ISHL | AICS | KECL     |
|-----------|-----------------------------------------------------|-----------------------------------------|------|-------|-----------|------|-----|-------|------|------|------|----------|
| Beryllium | X                                                   | X                                       | X    | X     | 231-150-7 | X    | X   | X     | X    |      | X    | KE-02829 |

## National Regulations

| Component                       | Toxic Chemical Substances Control Act |
|---------------------------------|---------------------------------------|
| Beryllium<br>7440-41-7 ( > 99 ) | Class II (95 wt%)<br>TRQ = 50 kg      |

## SECTION 16. OTHER INFORMATION

**Prepared By** Health, Safety and Environmental Department  
**Revision Date** 10-Sep-2024  
**Revision Summary** New emergency telephone response service provider.

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

**PNEC** - Predicted No Effect Concentration

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

## Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

---

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**