

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product Description: **SET 3/ DMSO ACID FAST STAIN KIT**
Cat No. : **R246303**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Oxoid Ltd
Wade Road
Basingstoke, Hants, UK
RG24 8PW
Tel: +44 (0) 1256 841144

EU entity/business name
Oxoid Deutschland GmbH
Postfach 10 07 53
D-46483
Wesel
GERMANY
Tel: + 49 (0) 281 1520
Fax: 49 (0) 281 1521

E-mail address mbd-sds@thermofisher.com

1.4. Emergency telephone number

Chemtrec EU: 001-703-527-3887
Chemtrec US: (800) 424-9300

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture****CLP Classification - Regulation (EC) No 1272/2008****Physical hazards**

Flammable liquids

Category 3 (H226)

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

Health hazards

Acute oral toxicity
Acute Inhalation Toxicity - Vapors
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Germ Cell Mutagenicity
Carcinogenicity

Category 4 (H302)
Category 4 (H332)
Category 1 B (H314)
Category 1 (H318)
Category 2 (H341)
Category 2 (H351)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H332 - Harmful if inhaled
H314 - Causes severe skin burns and eye damage
H341 - Suspected of causing genetic defects
H351 - Suspected of causing cancer

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
-----------	--------	-------	----------	---

OXDR246303

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

DMSO Basic Fuchsin Stain	NA		0	-
Dimethyl sulfoxide	67-68-5	EEC No. 200-664-3	15	-
Ethyl alcohol	64-17-5	200-578-6	15	Flam. Liq. 2 (H225)
Phenol	108-95-2	EEC No. 203-632-7	7	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Muta. 2 (H341) STOT RE 2 (H373)
Acetic acid	64-19-7	200-580-7	10	Flam. Liq. 3 (H226) Skin Corr. 1A (H314) Eye Dam. 1 (H318)
DMSO Modified Acid Fast Decolorizer	NA		0	-
Sulfuric acid	7664-93-9	231-639-5	10	Skin Corr. 1A (H314) Eye Dam. 1 (H318)
DMSO Counter Stain	NA		0	-
1,2,3-Propanetriol	56-81-5	200-289-5	16.7	-
Magenta	632-99-5	EEC No. 211-189-6	2	Carc. 2 (H351)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Phenol	Eye Irrit. 2 (H319) :: 1%<=C<3% Skin Corr. 1B (H314) :: C>=3% Skin Irrit. 2 (H315) :: 1%<=C<3%	-	-
Acetic acid	Skin Corr. 1A (H314) :: C>=90% Skin Corr. 1B (H314) :: 25%<=C<90% Eye Irrit. 2 (H319) :: 10%<=C<25% Skin Irrit. 2 (H315) :: 10%<=C<25%	-	-
Sulfuric acid	Skin Corr. 1A :: C>=15% Eye Irrit. 2 :: 5%<=C<15% Skin Irrit. 2 :: 5%<=C<15%	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3
Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Third edition. Published 2018. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Ethyl alcohol		TWA: 1000 ppm TWA; 1920 mg/m ³ TWA WEL - STEL: 3000 ppm STEL: 5760 mg/m ³ STEL	TWA / VME: 1000 ppm (8 heures). TWA / VME: 1900 mg/m ³ (8 heures). STEL / VLCT: 5000 ppm. STEL / VLCT: 9500 mg/m ³ .	TWA: 1000 ppm 8 uren TWA: 1907 mg/m ³ 8 uren	STEL / VLA-EC: 1000 ppm (15 minutos). STEL / VLA-EC: 1910 mg/m ³ (15 minutos).
Phenol	TWA: 2 ppm (8h) TWA: 8 mg/m ³ (8h) STEL: 4 ppm (15min) STEL: 16 mg/m ³ (15min) Skin	STEL: 4 ppm 15 min STEL: 16 mg/m ³ 15 min TWA: 2 ppm 8 hr TWA: 7.8 mg/m ³ 8 hr Skin	TWA / VME: 2 ppm (8 heures). restrictive limit TWA / VME: 7.8 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 4 ppm. restrictive limit STEL / VLCT: 15.6 mg/m ³ . restrictive limit Peau	TWA: 2 ppm 8 uren TWA: 8 mg/m ³ 8 uren STEL: 4 ppm 15 minuten STEL: 16 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 4 ppm (15 minutos). STEL / VLA-EC: 16 mg/m ³ (15 minutos). TWA / VLA-ED: 2 ppm (8 horas) TWA / VLA-ED: 8 mg/m ³ (8 horas) Piel
Acetic acid	TWA: 25 mg/m ³ (15min) TWA: 10 ppm (15min) STEL: 50 mg/m ³ (8h)	STEL: 37 mg/m ³ STEL: 15 ppm TWA: 10 ppm	STEL / VLCT: 10 ppm. STEL / VLCT: 25 mg/m ³ .	TWA: 10 ppm 8 uren TWA: 25 mg/m ³ 8 uren STEL: 15 ppm 15	STEL / VLA-EC: 20 ppm (15 minutos). STEL / VLA-EC: 50

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

	STEL: 20 ppm (8h)	TWA: 25 mg/m ³		minuten STEL: 38 mg/m ³ 15 minuten	mg/m ³ (15 minutos). TWA / VLA-ED: 10 ppm (8 horas) TWA / VLA-ED: 25 mg/m ³ (8 horas)
Sulfuric acid	TWA: 0.05 mg/m ³ (8h)	STEL: 0.15 mg/m ³ 15 min TWA: 0.05 mg/m ³ 8 hr	TWA / VME: 0.05 mg/m ³ (8 heures).	TWA: 0.2 mg/m ³ 8 uren	TWA / VLA-ED: 0.05 mg/m ³ (8 horas)
1,2,3-Propanetriol		TWA: 10 mg/m ³ 8 hr (mist only)	TWA / VME: 10 mg/m ³ (8 heures).	TWA: 10 mg/m ³ 8 uren	TWA / VLA-ED: 10 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Dimethyl sulfoxide		TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 160 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 50 ppm (8 Stunden). MAK TWA: 160 mg/m ³ (8 Stunden). MAK Höhepunkt: 100 ppm Höhepunkt: 320 mg/m ³ Haut			TWA: 50 ppm 8 tunteina lho
Ethyl alcohol		200 ppm TWA MAK; 380 mg/m ³ TWA MAK	TWA: 1000 ppm 8 horas	huid STEL: 1900 mg/m ³ 15 minuten TWA: 260 mg/m ³ 8 uren	TWA: 1000 ppm 8 tunteina TWA: 1900 mg/m ³ 8 tunteina STEL: 1300 ppm 15 minuutteina STEL: 2500 mg/m ³ 15 minuutteina
Phenol	TWA: 2 ppm 8 ore. Media Ponderata nel Tempo TWA: 8.0 mg/m ³ 8 ore. Media Ponderata nel Tempo STEL: 4 ppm 15 minuti. Breve termine STEL: 16 mg/m ³ 15 minuti. Breve termine Pelle	TWA: 2 ppm (8 Stunden). AGW - exposure factor 2 TWA: 8 mg/m ³ (8 Stunden). AGW - exposure factor 2 Haut	STEL: 4 ppm 15 minutos STEL: 16 mg/m ³ 15 minutos TWA: 2 ppm 8 horas TWA: 8 mg/m ³ 8 horas Pele	huid TWA: 8 mg/m ³ 8 uren	TWA: 2 ppm 8 tunteina TWA: 8 mg/m ³ 8 tunteina STEL: 4 ppm 15 minuutteina STEL: 16 mg/m ³ 15 minuutteina lho
Acetic acid	TWA: 25 ppm 8 ore. Media Ponderata nel Tempo TWA: 10 mg/m ³ 8 ore. Media Ponderata nel Tempo STEL: 50 mg/m ³ 15 minuti. Breve termine STEL: 20 ppm 15 minuti. Breve termine	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK TWA: 25 mg/m ³ (8 Stunden). MAK Höhepunkt: 20 ppm Höhepunkt: 50 mg/m ³	STEL: 20 ppm 15 minutos STEL: 50 mg/m ³ 15 minutos TWA: 10 ppm 8 horas TWA: 25 mg/m ³ 8 horas	MAC-TGG 25 mg/m ³	TWA: 5 ppm 8 tunteina TWA: 13 mg/m ³ 8 tunteina STEL: 10 ppm 15 minuutteina STEL: 25 mg/m ³ 15 minuutteina
Sulfuric acid	-	TWA: 0.1 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 0.1 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.1 mg/m ³	TWA: 0.05 mg/m ³ 8 horas	TWA: 0.05 mg/m ³ 8 uren	TWA: 0.05 mg/m ³ 8 tunteina STEL: 0.1 mg/m ³ 15 minuutteina
1,2,3-Propanetriol		TWA: 200 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 200 mg/m ³ (8 Stunden). MAK Höhepunkt: 400 mg/m ³	TWA: 10 mg/m ³ 8 horas		TWA: 20 mg/m ³ 8 tunteina

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

Component	Austria	Denmark	Switzerland	Poland	Norway
Dimethyl sulfoxide	Haut MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 160 mg/m ³ 8 Stunden	TWA: 50 ppm 8 timer TWA: 160 mg/m ³ 8 timer	Haut/Peau STEL: 100 ppm 15 Minuten STEL: 320 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 160 mg/m ³ 8 Stunden		
Ethyl alcohol	MAK-KZGW: 2000 ppm 15 Minuten MAK-KZGW: 3800 mg/m ³ 15 Minuten MAK-TMW: 1000 ppm 8 Stunden MAK-TMW: 1900 mg/m ³ 8 Stunden	TWA: 1000 ppm 8 timer TWA: 1900 mg/m ³ 8 timer	STEL: 1000 ppm 15 Minuten STEL: 1920 mg/m ³ 15 Minuten TWA: 500 ppm 8 Stunden TWA: 960 mg/m ³ 8 Stunden	TWA: 1900 mg/m ³ 8 godzinach	TWA: 500 ppm 8 timer TWA: 950 mg/m ³ 8 timer STEL: 625 ppm 15 minutter. value calculated STEL: 1187.5 mg/m ³ 15 minutter. value calculated
Phenol	Haut MAK-KZGW: 4 ppm 15 Minuten MAK-KZGW: 16 mg/m ³ 15 Minuten MAK-TMW: 2 ppm 8 Stunden MAK-TMW: 8 mg/m ³ 8 Stunden	TWA: 1 ppm 8 timer TWA: 4 mg/m ³ 8 timer Hud	Haut/Peau STEL: 5 ppm 15 Minuten STEL: 19 mg/m ³ 15 Minuten TWA: 5 ppm 8 Stunden TWA: 19 mg/m ³ 8 Stunden	STEL: 16 mg/m ³ 15 minutach TWA: 7.8 mg/m ³ 8 godzinach	TWA: 1 ppm 8 timer TWA: 4 mg/m ³ 8 timer STEL: 3 ppm 15 minutter. value from the regulation STEL: 12 mg/m ³ 15 minutter. value from the regulation Hud
Acetic acid	MAK-KZGW: 20 ppm 15 Minuten MAK-KZGW: 50 mg/m ³ 15 Minuten MAK-TMW: 10 ppm 8 Stunden MAK-TMW: 25 mg/m ³ 8 Stunden	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer	STEL: 20 ppm 15 Minuten STEL: 50 mg/m ³ 15 Minuten TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden	STEL: 50 mg/m ³ 15 minutach TWA: 25 mg/m ³ 8 godzinach	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer STEL: 20 ppm 15 minutter. value from the regulation STEL: 50 mg/m ³ 15 minutter. value from the regulation
Sulfuric acid	MAK-KZGW: 0.2 mg/m ³ 15 Minuten MAK-TMW: 0.1 mg/m ³ 8 Stunden	TWA: 0.05 mg/m ³ 8 timer	STEL: 0.2 mg/m ³ 15 Minuten TWA: 0.1 mg/m ³ 8 Stunden	TWA: 0.05 mg/m ³ 8 godzinach	TWA: 0.1 mg/m ³ 8 timer STEL: 0.3 mg/m ³ 15 minutter. value calculated thoracic fraction
1,2,3-Propanetriol			STEL: 100 mg/m ³ 15 Minuten TWA: 50 mg/m ³ 8 Stunden	TWA: 10 mg/m ³ 8 godzinach	

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Ethyl alcohol	TWA: 1000 mg/m ³	TWA-GVI: 1000 ppm 8 satima. TWA-GVI: 1900 mg/m ³ 8 satima.	STEL: 1000 ppm 15 min		TWA: 1000 mg/m ³ 8 hodinách. Ceiling: 3000 mg/m ³
Phenol	TWA: 2 ppm TWA: 8 mg/m ³ STEL : 4 ppm STEL : 16 mg/m ³ Skin notation	kože TWA-GVI: 2 ppm 8 satima. TWA-GVI: 8 mg/m ³ 8 satima. STEL-KGVI: 4 ppm 15 minutama. STEL-KGVI: 16 mg/m ³ 15 minutama.	TWA: 2 ppm 8 hr. TWA: 8 mg/m ³ 8 hr. STEL: 4 ppm 15 min STEL: 16 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption STEL: 16 mg/m ³ STEL: 4 ppm TWA: 8 mg/m ³ TWA: 2 ppm	TWA: 7.5 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 15 mg/m ³
Acetic acid	TWA: 25 mg/m ³ TWA: 10 ppm STEL : 50 mg/m ³ STEL : 20 ppm	TWA-GVI: 10 ppm 8 satima. TWA-GVI: 25 mg/m ³ 8 satima. STEL-KGVI: 20 ppm 15 minutama. STEL-KGVI: 50 mg/m ³ 15 minutama.	TWA: 20 ppm 8 hr. TWA: 50 mg/m ³ 8 hr. STEL: 20 ppm 15 min STEL: 50 mg/m ³ 15 min	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 25 mg/m ³ 8 hodinách. Ceiling: 50 mg/m ³
Sulfuric acid	TWA: 0.05 mg/m ³	TWA-GVI: 0.05 mg/m ³ 8 satima. when selecting	TWA: 0.05 ppm 8 hr. STEL: 0.15 ppm 15 min	TWA: 0.05 mg/m ³	TWA: 1 mg/m ³ 8 hodinách. SO3

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

		the appropriate exposure monitoring method the potential limitations and disturbances that may occur in the presence of other sulfur compounds should be taken into account fog, thoracic fraction			TWA: 0.05 mg/m ³ 8 hodinách. concentrated H2SO4 mist Ceiling: 2 mg/m ³ SO3
1,2,3-Propanetriol		TWA-GVI: 10 mg/m ³ 8 satima.	TWA: 10 mg/m ³ 8 hr. (mist)		TWA: 10 mg/m ³ 8 hodinách. Ceiling: 15 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Dimethyl sulfoxide	Nahk TWA: 50 ppm 8 tundides. TWA: 150 mg/m ³ 8 tundides. STEL: 150 ppm 15 minutites. STEL: 500 mg/m ³ 15 minutites.				
Ethyl alcohol	TWA: 500 ppm 8 tundides. TWA: 1000 mg/m ³ 8 tundides. STEL: 1000 ppm 15 minutites. STEL: 1900 mg/m ³ 15 minutites.		TWA: 1000 ppm TWA: 1900 mg/m ³	STEL: 3800 mg/m ³ 15 percekben. CK TWA: 1900 mg/m ³ 8 órában. AK	TWA: 1000 ppm 8 klukkustundum. TWA: 1900 mg/m ³ 8 klukkustundum. Ceiling: 2000 ppm Ceiling: 3800 mg/m ³
Phenol	Nahk TWA: 2 ppm 8 tundides. TWA: 8 mg/m ³ 8 tundides. STEL: 16 mg/m ³ 15 minutites. STEL: 4 ppm 15 minutites.	Skin notation TWA: 2 ppm 8 hr TWA: 8 mg/m ³ 8 hr STEL: 16 mg/m ³ 15 min STEL: 4 ppm 15 min	skin - potential for cutaneous absorption STEL: 4 ppm STEL: 16 mg/m ³ TWA: 2 ppm TWA: 8 mg/m ³	STEL: 16 mg/m ³ 15 percekben. CK TWA: 8 mg/m ³ 8 órában. AK lehetséges bőrön keresztüli felszívódás	TWA: 1 ppm 8 klukkustundum. TWA: 4 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 2 ppm Ceiling: 8 mg/m ³
Acetic acid	TWA: 10 ppm 8 tundides. TWA: 25 mg/m ³ 8 tundides. STEL: 10 ppm 15 minutites. STEL: 25 mg/m ³ 15 minutites.	TWA: 25 mg/m ³ 8 hr TWA: 10 ppm 8 hr STEL: 50 mg/m ³ 15 min STEL: 20 ppm 15 min	STEL: 15 ppm STEL: 37 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	STEL: 50 mg/m ³ 15 percekben. CK TWA: 25 mg/m ³ 8 órában. AK	STEL: 20 ppm STEL: 50 mg/m ³ TWA: 10 ppm 8 klukkustundum. TWA: 25 mg/m ³ 8 klukkustundum.
Sulfuric acid	TWA: 0.05 mg/m ³ 8 tundides. particles that reach the upper respiratory tract	TWA: 0.05 mg/m ³ 8 hr when selecting an appropriate exposure monitoring method, account should be taken of potential limitations and interferences that may arise in the presence of other sulphur compounds thoracic fraction	TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³ 8 órában. AK	TWA: 0.05 mg/m ³ 8 klukkustundum. thoracic fraction Ceiling: 0.1 mg/m ³ aerosol
1,2,3-Propanetriol	TWA: 10 mg/m ³ 8 tundides.		TWA: 10 mg/m ³		

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Dimethyl sulfoxide		TWA: 50 ppm IPRD TWA: 150 mg/m ³ IPRD Oda STEL: 150 ppm STEL: 500 mg/m ³			
Ethyl alcohol	TWA: 1000 mg/m ³	TWA: 500 ppm IPRD			TWA: 1000 ppm 8 ore

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

		TWA: 1000 mg/m ³ IPRD STEL: 1000 ppm STEL: 1900 mg/m ³			TWA: 1900 mg/m ³ 8 ore STEL: 5000 ppm 15 minute STEL: 9500 mg/m ³ 15 minute
Phenol	skin - potential for cutaneous exposure STEL: 4 ppm STEL: 16 mg/m ³ TWA: 2 ppm TWA: 8 mg/m ³	TWA: 2 ppm IPRD TWA: 8 mg/m ³ IPRD Oda STEL: 4 ppm STEL: 16 mg/m ³	Possibility of significant uptake through the skin TWA: 2 ppm 8 Stunden TWA: 8 mg/m ³ 8 Stunden STEL: 16 mg/m ³ 15 Minuten STEL: 4 ppm 15 Minuten	possibility of significant uptake through the skin TWA: 2 ppm TWA: 8 mg/m ³ STEL: 16 mg/m ³ 15 minuti STEL: 4 ppm 15 minuti	Skin notation TWA: 2 ppm 8 ore TWA: 8 mg/m ³ 8 ore STEL: 4 ppm 15 minute STEL: 16 mg/m ³ 15 minute
Acetic acid	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm IPRD TWA: 25 mg/m ³ IPRD STEL: 50 mg/m ³ STEL: 20 ppm	TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden STEL: 50 mg/m ³ 15 Minuten STEL: 20 ppm 15 Minuten	TWA: 10 ppm TWA: 25 mg/m ³ STEL: 20 ppm 15 minuti STEL: 50 mg/m ³ 15 minuti	TWA: 10 ppm 8 ore TWA: 25 mg/m ³ 8 ore STEL: 20 ppm 15 minute STEL: 50 mg/m ³ 15 minute
Sulfuric acid	TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³ vapor IPRD STEL: 3 mg/m ³	TWA: 0.05 mg/m ³ 8 Stunden	TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Dimethyl sulfoxide	MAC: 20 mg/m ³		TWA: 160 mg/m ³ 8 urah TWA: 50 ppm 8 urah Koža STEL: 100 ppm 15 minutah STEL: 320 mg/m ³ 15 minutah	Indicative STEL: 150 ppm 15 minuter Indicative STEL: 500 mg/m ³ 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 150 mg/m ³ 8 timmar. NGV Hud	
Ethyl alcohol	TWA: 1000 mg/m ³ 2391 MAC: 2000 mg/m ³	Ceiling: 1920 mg/m ³ TWA: 500 ppm TWA: 960 mg/m ³	TWA: 960 mg/m ³ 8 urah TWA: 500 ppm 8 urah STEL: 1000 ppm 15 minutah STEL: 1920 mg/m ³ 15 minutah	Indicative STEL: 1000 ppm 15 minuter Indicative STEL: 1900 mg/m ³ 15 minuter TLV: 500 ppm 8 timmar. NGV TLV: 1000 mg/m ³ 8 timmar. NGV	
Phenol	TWA: 0.3 mg/m ³ 0539 Skin notation MAC: 1 mg/m ³	Ceiling: 16 mg/m ³ Potential for cutaneous absorption TWA: 2 ppm TWA: 8 mg/m ³	TWA: 2 ppm 8 urah TWA: 8 mg/m ³ 8 urah Koža STEL: 4 ppm 15 minutah STEL: 16 mg/m ³ 15 minutah	Binding STEL: 4 ppm 15 minuter Binding STEL: 16 mg/m ³ 15 minuter TLV: 1 ppm 8 timmar. NGV TLV: 4 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 2 ppm 8 saat TWA: 8 mg/m ³ 8 saat STEL: 4 ppm 15 dakika STEL: 16 mg/m ³ 15 dakika
Acetic acid	Skin notation MAC: 5 mg/m ³	Ceiling: 50 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm 8 urah TWA: 25 mg/m ³ 8 urah STEL: 50 mg/m ³ 15 minutah STEL: 20 ppm 15 minutah	Binding STEL: 10 ppm 15 minuter Binding STEL: 25 mg/m ³ 15 minuter TLV: 5 ppm 8 timmar. NGV TLV: 13 mg/m ³ 8 timmar. NGV	TWA: 10 ppm 8 saat TWA: 25 mg/m ³ 8 saat
Sulfuric acid	Skin notation MAC: 1 mg/m ³	TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³ 8 urah inhalable fraction, fog STEL: 0.05 mg/m ³ 15 minutah inhalable fraction, fog	Indicative STEL: 0.2 mg/m ³ 15 minuter TLV: 0.1 mg/m ³ 8 timmar. NGV	TWA: 0.05 mg/m ³ 8 saat
1,2,3-Propanetriol		TWA: 11 mg/m ³	TWA: 200 mg/m ³ 8 urah inhalable fraction		

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

			STEL: 400 mg/m ³ 15 minutah inhalable fraction		
--	--	--	---	--	--

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Phenol			Total Phenol: 250 mg/g creatinine urine end of shift	: 120 mg/g Creatinine urine end of shift	Phenol (after hydrolysis): 120 mg/g Creatinine urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Phenol		Total phenol: 1.3 mmol/L urine after the shift.		Phenol: 200 µg/L urine at the end of exposure or end of work shift	total Phenol: 120 mg/g Creatinine urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Phenol			Phenol: 200 mg/L urine end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Dimethyl sulfoxide 67-68-5 (15)				DNEL = 200mg/kg bw/day
Ethyl alcohol 64-17-5 (15)				DNEL = 343mg/kg bw/day
Phenol 108-95-2 (7)				DNEL = 1.23mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Dimethyl sulfoxide 67-68-5 (15)			DNEL = 265mg/m ³	DNEL = 484mg/m ³
Ethyl alcohol 64-17-5 (15)	DNEL = 1900mg/m ³			DNEL = 950mg/m ³
Phenol 108-95-2 (7)	DNEL = 16mg/m ³			DNEL = 8mg/m ³
Acetic acid 64-19-7 (10)	DNEL = 25mg/m ³		DNEL = 25mg/m ³	
Sulfuric acid 7664-93-9 (10)	DNEL = 0.1mg/m ³		DNEL = 0.05mg/m ³	
1,2,3-Propanetriol 56-81-5 (16.7)			DNEL = 56mg/m ³	

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Dimethyl sulfoxide 67-68-5 (15)	PNEC = 17mg/L	PNEC = 13.4mg/kg sediment dw		PNEC = 11mg/L	PNEC = 3.02mg/kg soil dw
Ethyl alcohol 64-17-5 (15)	PNEC = 0.96mg/L	PNEC = 3.6mg/kg sediment dw	PNEC = 2.75mg/L	PNEC = 580mg/L	PNEC = 0.63mg/kg soil dw
Phenol 108-95-2 (7)	PNEC = 0.0077mg/L	PNEC = 0.0915mg/kg sediment dw	PNEC = 0.031mg/L	PNEC = 2.1mg/L	PNEC = 0.136mg/kg soil dw
Acetic acid 64-19-7 (10)	PNEC = 3.058mg/L	PNEC = 11.36mg/kg sediment dw	PNEC = 30.58mg/L	PNEC = 85mg/L	PNEC = 0.47mg/kg soil dw
Sulfuric acid 7664-93-9 (10)	PNEC = 0.0025mg/L	PNEC = 0.002mg/kg sediment dw		PNEC = 8.8mg/L	
1,2,3-Propanetriol 56-81-5 (16.7)	PNEC = 0.885mg/L	PNEC = 3.3mg/kg sediment dw	PNEC = 8.85mg/L	PNEC = 1000mg/L	PNEC = 0.141mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Dimethyl sulfoxide 67-68-5 (15)	PNEC = 1.7mg/L			PNEC = 0.7g/kg food	
Ethyl alcohol 64-17-5 (15)	PNEC = 0.79mg/L	PNEC = 2.9mg/kg sediment dw		PNEC = 0.38g/kg food PNEC = 0.72g/kg food	
Phenol 108-95-2 (7)	PNEC = 0.00077mg/L	PNEC = 0.00915mg/kg sediment dw			
Acetic acid 64-19-7 (10)	PNEC = 0.3058mg/L	PNEC = 1.136mg/kg sediment dw			
Sulfuric acid 7664-93-9 (10)	PNEC = 0.00025mg/L	PNEC = 0.002mg/kg sediment dw			
1,2,3-Propanetriol 56-81-5 (16.7)	PNEC = 0.0885mg/L	PNEC = 0.33mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Disposable gloves	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Long sleeved clothing.

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

In case of insufficient ventilation, wear suitable respiratory equipment

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	30 °C / 86 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	6.75	
Viscosity	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Dimethyl sulfoxide	-2.03	
Ethyl alcohol	-0.32	
Phenol	1.5	
Acetic acid	-0.2	
1,2,3-Propanetriol	-1.76	
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties explosive air/vapour mixtures possible

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization

No information available.

Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Category 4

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Dimethyl sulfoxide	LD50 = 28300 mg/kg (Rat)	LD50 = 40000 mg/kg (Rat)	LC50 > 5.33 mg/L (Rat) 4 h
Ethyl alcohol	LD50 = 7060 mg/kg (Rat)	-	20000 ppm/10H (Rat)
Phenol	LD50 = 340 mg/kg (Rat)	LD50 = 630 mg/kg (Rabbit)	-
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
Sulfuric acid	2140 mg/kg (Rat)	-	LC50 = 0.375 mg/L (Rat) 4 h
1,2,3-Propanetriol	12600 mg/kg (Rat)	> 10 g/kg (Rabbit)	> 2.75 mg/L/4h (Rat)(mist)

(b) skin corrosion/irritation;

Category 1 B

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

(e) germ cell mutagenicity; Category 2

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Sulfuric acid				Group 1
Magenta				Group 2B

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Dimethyl sulfoxide	40 g/L LC50 96 h 33-37 g/L LC50 96 h	EC50 24h 7000 mg/L	EC50 96h 12350 - 25500 mg/L
Ethyl alcohol	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/L/96h	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h	EC50 (72h) = 275 mg/L (Chlorella vulgaris)
Phenol	4-7 mg/L LC50 96 h 32 mg/L LC50 96 h	EC50: 10.2 - 15.5 mg/L, 48h (Daphnia magna) EC50: 4.24 - 10.7 mg/L, 48h Static (Daphnia magna)	EC50: 0.0188 - 0.1044 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: 187 - 279 mg/L, 72h static (Desmodesmus subspicatus) EC50: = 46.42 mg/L, 96h (Pseudokirchneriella subcapitata)
Acetic acid	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	EC50 = 95 mg/L/24h	-
Sulfuric acid	LC50: > 500 mg/L, 96h static	EC50: 29 mg/L/24h	-

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

	(Brachydanio rerio)		
1,2,3-Propanetriol	LC50: 51 - 57 mL/L, 96h static (Oncorhynchus mykiss)		

Component	Microtox	M-Factor
Dimethyl sulfoxide	= 16000 mg/L EC50 Pseudomonas putida 16 h = 32 g/L EC50 Tetrahymena pyriformis 24 h = 77 mg/L EC50 Photobacterium phosphoreum 5 min	
Ethyl alcohol	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min	
Phenol	EC50 21 - 36 mg/L 30 min EC50 = 23.28 mg/L 5 min EC50 = 25.61 mg/L 15 min EC50 = 28.8 mg/L 5 min EC50 = 31.6 mg/L 15 min	
Acetic acid	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	
Sulfuric acid	-	

12.2. Persistence and degradability No information available

12.3. Bioaccumulative potential No information available

Component	log Pow	Bioconcentration factor (BCF)
Dimethyl sulfoxide	-2.03	No data available
Ethyl alcohol	-0.32	No data available
Phenol	1.5	No data available
Acetic acid	-0.2	No data available
1,2,3-Propanetriol	-1.76	No data available

12.4. Mobility in soil No information available

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN2920
14.2. UN proper shipping name	Corrosive liquid, flammable, n.o.s.
14.3. Transport hazard class(es)	8
Subsidiary Hazard Class	3
14.4. Packing group	II

ADR

14.1. UN number	UN2920
14.2. UN proper shipping name	Corrosive liquid, flammable, n.o.s.
14.3. Transport hazard class(es)	8
Subsidiary Hazard Class	3
14.4. Packing group	II

IATA

14.1. UN number	UN2920
14.2. UN proper shipping name	Corrosive liquid, flammable, n.o.s.
14.3. Transport hazard class(es)	8
Subsidiary Hazard Class	3
14.4. Packing group	II

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDL), Australia

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

(AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
DMSO Basic Fuchsin Stain	NA	-	-	-	-	-	-	-	-
Dimethyl sulfoxide	67-68-5	200-664-3	-	-	X	X	KE-32367	X	X
Ethyl alcohol	64-17-5	200-578-6	-	-	X	X	KE-13217	X	X
Phenol	108-95-2	203-632-7	-	-	X	X	KE-28209	X	X
Acetic acid	64-19-7	200-580-7	-	-	X	X	X	X	X
DMSO Modified Acid Fast Decolorizer	NA	-	-	-	-	-	-	-	-
Sulfuric acid	7664-93-9	231-639-5	-	-	X	X	KE-32570	X	X
DMSO Counter Stain	NA	-	-	-	-	-	-	-	-
1,2,3-Propanetriol	56-81-5	200-289-5	-	-	X	X	KE-29297	X	X
Magenta	632-99-5	211-189-6	-	-	X	X	KE-07008	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
DMSO Basic Fuchsin Stain	NA	-	-	-	-	-	-	-
Dimethyl sulfoxide	67-68-5	X	ACTIVE	X	-	X	X	X
Ethyl alcohol	64-17-5	X	ACTIVE	X	-	X	X	X
Phenol	108-95-2	X	ACTIVE	X	-	X	X	X
Acetic acid	64-19-7	X	ACTIVE	X	-	X	X	X
DMSO Modified Acid Fast Decolorizer	NA	-	-	-	-	-	-	-
Sulfuric acid	7664-93-9	X	ACTIVE	X	-	X	X	X
DMSO Counter Stain	NA	-	-	-	-	-	-	-
1,2,3-Propanetriol	56-81-5	X	ACTIVE	X	-	X	X	X
Magenta	632-99-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Dimethyl sulfoxide	-	Use restricted. See item 75. (see link for restriction details)	-
Phenol	-	Use restricted. See item 75. (see link for restriction details)	-
Acetic acid	-	Use restricted. See item 75. (see link for restriction details)	-
Sulfuric acid	-	Use restricted. See item 75. (see link for restriction details)	-
Magenta	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
DMSO Basic Fuchsin Stain	NA	Not applicable	Not applicable
Dimethyl sulfoxide	67-68-5	Not applicable	Not applicable
Ethyl alcohol	64-17-5	Not applicable	Not applicable
Phenol	108-95-2	Not applicable	Not applicable
Acetic acid	64-19-7	Not applicable	Not applicable
DMSO Modified Acid Fast Decolorizer	NA	Not applicable	Not applicable
Sulfuric acid	7664-93-9	Not applicable	Not applicable
DMSO Counter Stain	NA	Not applicable	Not applicable
1,2,3-Propanetriol	56-81-5	Not applicable	Not applicable
Magenta	632-99-5	Not applicable	Not applicable

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals
Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Dimethyl sulfoxide	WGK1	
Ethyl alcohol	WGK1	
Phenol	WGK2	Class I : 20 mg/m ³ (Massenkonzentration)
Acetic acid	WGK1	Class II : 0.10 g/m ³ (Massenkonzentration)
Sulfuric acid	WGK1	
1,2,3-Propanetriol	WGK1	
Magenta	WGK3	

Component	France - INRS (Tables of occupational diseases)
Dimethyl sulfoxide	Tableaux des maladies professionnelles (TMP) - RG 84
Ethyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84
Phenol	Tableaux des maladies professionnelles (TMP) - RG 14

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl alcohol 64-17-5 (15)		Group I	
Phenol 108-95-2 (7)	Prohibited and Restricted Substances		
Acetic acid 64-19-7 (10)	Prohibited and Restricted Substances	Group I	
Sulfuric acid 7664-93-9 (10)	Prohibited and Restricted Substances		
Magenta 632-99-5 (2)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed

H332 - Harmful if inhaled

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H341 - Suspected of causing genetic defects
H351 - Suspected of causing cancer
H225 - Highly flammable liquid and vapor
H226 - Flammable liquid and vapor
H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Creation Date 02-Apr-2007

Revision Date 10-Dec-2021

Revision Summary Update to CLP Format.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the

SAFETY DATA SHEET

SET 3/ DMSO ACID FAST STAIN KIT

Revision Date 10-Dec-2021

date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet