

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Nickel plating solution, electroless, ammonia free
Cat No. : 44070

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Acute oral toxicity	Category 3 (H301)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Respiratory Sensitization	Category 1 (H334)
Skin Sensitization	Category 1 (H317)
Germ Cell Mutagenicity	Category 2 (H341)
Carcinogenicity	Category 1A (H350i)
Reproductive Toxicity	Category 1B (H360D)
Specific target organ toxicity - (single exposure)	Category 3 (H335)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)

Environmental hazards

Acute aquatic toxicity	Category 1 (H400)
Chronic aquatic toxicity	Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H341 - Suspected of causing genetic defects
H350i - May cause cancer by inhalation
H360D - May damage the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H410 - Very toxic to aquatic life with long lasting effects
H301 + H331 - Toxic if swallowed or if inhaled

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P311 - Call a POISON CENTER or doctor/physician
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
P337 + P313 - If eye irritation persists: Get medical advice/attention

Additional EU labelling

Restricted to professional users

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Phosphinic acid, sodium salt, monohydrate	10039-56-2		25.0	-
Nickel(II) chloride	7718-54-9	EEC No. 231-743-0	25.0	Acute Tox. 3 (H301) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Muta. 2 (H341) Carc. 1A (H350i) Repr. 1B (H360D) STOT RE 1 (H372) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Butanedioic acid, disodium salt	150-90-3	EEC No. 205-778-7	25.0	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)
Water	7732-18-5	231-791-2	24.9	-
Hydrofluoric acid	7664-39-3	EEC No. 231-634-8	0.1	Met. Corr. 1 (H290) Acute Tox. 2 (H300) Acute Tox. 1 (H310) Acute Tox. 2 (H330) Skin Corr. 1A (H314) Eye Dam. 1 (H318)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Nickel(II) chloride	Skin Irrit. 2 (H315) :: C>=20% Skin Sens. 1 (H317) :: C>=0.01% STOT RE 1 (H372) :: C>=1% STOT RE 2 (H373) :: 0.1%<C<1%	1 (acute) 1 (chronic)	-
Hydrofluoric acid	Skin Corr. 1A :: C>=7% Skin Corr. 1B :: 1%<=C<7% Eye Irrit. 2 :: 0.1%<=C<1%	-	-

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is

ALFAA44070

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

	required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Carbon dioxide (CO₂). Powder. Water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

None reasonably foreseeable. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Hydrogen chloride, Hydrogen fluoride, Oxides of phosphorus, Sodium oxides, Nickel oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 6.1D

Switzerland - Storage of hazardous substances

SC 6.1
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti> Storage class -

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Nickel(II) chloride		STEL: 0.3 mg/m ³ 15 min TWA: 0.1 mg/m ³ 8 hr			TWA / VLA-ED: 0.1 mg/m ³ (8 horas)

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

		Skin			
Hydrofluoric acid	TWA: 1.8 ppm (8h) TWA: 1.5 mg/m ³ (8h) STEL: 3 ppm (15min) STEL: 2.5 mg/m ³ (15min)	STEL: 3 ppm 15 min STEL: 2.5 mg/m ³ 15 min TWA: 1.8 ppm 8 hr TWA: 1.5 mg/m ³ 8 hr	TWA / VME: 1.8 ppm (8 heures). restrictive limit TWA / VME: 1.5 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 3 ppm. restrictive limit STEL / VLCT: 2.5 mg/m ³ . restrictive limit	TWA: 1.8 ppm 8 uren TWA: 1.5 mg/m ³ 8 uren STEL: 3 ppm 15 minuten STEL: 2.5 mg/m ³ 15 minuten	STEL / VLA-EC: 3 ppm (15 minutos). STEL / VLA-EC: 2.5 mg/m ³ (15 minutos). TWA / VLA-ED: 1.8 ppm (8 horas) TWA / VLA-ED: 1.5 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Nickel(II) chloride		TWA: 0.03 mg/m ³ (8 Stunden). AGW - exposure factor 8	TWA: 0.1 mg/m ³ 8 horas		TWA: 0.01 mg/m ³ 8 tunteina TWA: 0.05 mg/m ³ 8 tunteina
Hydrofluoric acid	TWA: 1.8 ppm 8 ore. Time Weighted Average TWA: 1.5 mg/m ³ 8 ore. Time Weighted Average STEL: 3 ppm 15 minuti. Short-term STEL: 2.5 mg/m ³ 15 minuti. Short-term	TWA: 1 ppm (8 Stunden). AGW - exposure factor 2 TWA: 0.83 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 1 mg/m ³ (8 Stunden). AGW - exposure factor 4 TWA: 1 ppm (8 Stunden). MAK TWA: 0.83 mg/m ³ (8 Stunden). MAK TWA: 1 mg/m ³ (8 Stunden). MAK Höhepunkt: 2 ppm Höhepunkt: 1.66 mg/m ³ Haut	STEL: 3 ppm 15 minutos STEL: 2.5 mg/m ³ 15 minutos Ceiling: 2 ppm TWA: 1.8 ppm 8 horas TWA: 1.5 mg/m ³ 8 horas TWA: 2.5 mg/m ³ 8 horas Pele	STEL: 1.27 ppm 15 minuten STEL: 1 mg/m ³ 15 minuten	TWA: 1.8 ppm 8 tunteina TWA: 1.5 mg/m ³ 8 tunteina STEL: 3 ppm 15 minuutteina STEL: 2.5 mg/m ³ 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Nickel(II) chloride	TRK-KZGW: 2 mg/m ³ 15 Minuten TRK-TMW: 0.5 mg/m ³				TWA: 0.05 mg/m ³ 8 timer
Hydrofluoric acid	Haut MAK-KZGW: 3 ppm 15 Minuten MAK-KZGW: 2.5 mg/m ³ 15 Minuten MAK-TMW: 1.8 ppm 8 Stunden MAK-TMW: 1.5 mg/m ³ 8 Stunden	TWA: 1.8 ppm 8 timer TWA: 1.5 mg/m ³ 8 timer STEL: 2.5 mg/m ³ 15 minutter STEL: 3 ppm 15 minutter	STEL: 2 ppm 15 Minuten STEL: 1.66 mg/m ³ 15 Minuten TWA: 1 ppm 8 Stunden TWA: 0.83 mg/m ³ 8 Stunden	STEL: 2 mg/m ³ 15 minutach TWA: 0.5 mg/m ³ 8 godzinach	TWA: 0.6 ppm 8 timer TWA: 0.5 mg/m ³ 8 timer STEL: 1.5 mg/m ³ 15 minutter. value from the regulation STEL: 1.8 ppm 15 minutter. value from the regulation Hud

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Hydrofluoric acid	TWA: 1.8 ppm TWA: 1.5 mg/m ³ STEL : 3 ppm STEL : 2.5 mg/m ³	TWA-GVI: 1.8 ppm 8 satima. TWA-GVI: 1.5 mg/m ³ 8 satima. STEL-KGVI: 3 ppm 15 minutama. STEL-KGVI: 2.5 mg/m ³ 15 minutama.	TWA: 1.5 mg/m ³ 8 hr. TWA: 1.8 ppm 8 hr. F STEL: 2.5 mg/m ³ 15 min STEL: 3 ppm 15 min Skin	STEL: 3.0 ppm STEL: 2.5 mg/m ³ TWA: 1.8 ppm TWA: 1.5 mg/m ³	TWA: 1.5 mg/m ³ 8 hodinách. Ceiling: 2.5 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Hydrofluoric acid	TWA: 1.8 ppm 8 tundides. TWA: 1.5 mg/m ³ 8 tundides. STEL: 3 ppm 15 minutites. STEL: 2.5 mg/m ³ 15 minutites.	TWA: 1.8 ppm 8 hr TWA: 1.5 mg/m ³ 8 hr STEL: 3 ppm 15 min STEL: 2.5 mg/m ³ 15 min	STEL: 3 ppm STEL: 2.5 mg/m ³ TWA: 3 ppm TWA: 2.5 mg/m ³	STEL: 2.5 mg/m ³ 15 percekben. CK STEL: 3 ppm 15 percekben. CK TWA: 1.8 ppm 8 órában. AK TWA: 1.5 mg/m ³ 8 órában. AK	STEL: 3 ppm 5 minutes STEL: 2.5 mg/m ³ 5 minutes TWA: 0.7 ppm 8 klukkustundum. TWA: 0.6 mg/m ³ 8 klukkustundum.

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

				lehetséges borön keresztüli felszívódás	
--	--	--	--	---	--

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Hydrofluoric acid	STEL: 3 ppm STEL: 2.5 mg/m ³ TWA: 1.8 ppm TWA: 1.5 mg/m ³	TWA: 1.8 ppm IPRD TWA: 1.5 mg/m ³ IPRD STEL: 3 ppm STEL: 2.5 mg/m ³	TWA: 1.8 ppm 8 Stunden TWA: 1.5 mg/m ³ 8 Stunden STEL: 3 ppm 15 Minuten STEL: 2.5 mg/m ³ 15 Minuten	TWA: 1.8 ppm TWA: 1.5 mg/m ³ STEL: 3 ppm 15 minuti STEL: 2.5 mg/m ³ 15 minuti	TWA: 1.8 ppm 8 ore TWA: 1.5 mg/m ³ 8 ore STEL: 3 ppm 15 minute STEL: 2.5 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Phosphinic acid, sodium salt, monohydrate	MAC: 10 mg/m ³				
Hydrofluoric acid	TWA: 0.1 mg/m ³ 0608 MAC: 0.5 mg/m ³	Ceiling: 2.5 mg/m ³ TWA: 1.8 ppm TWA: 1.5 mg/m ³	TWA: 1.8 ppm 8 urah TWA: 1.5 mg/m ³ 8 urah Koža STEL: 3 ppm 15 minutah STEL: 2.5 mg/m ³ 15 minutah	Binding STEL: 2 ppm 15 minuter Binding STEL: 1.7 mg/m ³ 15 minuter TLV: 1.8 ppm 8 timmar. NGV TLV: 1.5 mg/m ³ 8 timmar. NGV	TWA: 1.8 ppm 8 saat TWA: 1.5 mg/m ³ 8 saat STEL: 3 ppm 15 dakika STEL: 2.5 mg/m ³ 15 dakika

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Hydrofluoric acid			Fluorides: urine beginning of shift Fluorides: urine end of shift	Fluorides: 2 mg/L urine pre-shift Fluorides: 3 mg/L urine end of shift	Fluoride: 4.0 mg/g Creatinine urine (end of shift)

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Hydrofluoric acid			Fluoride: 7 mg/g creatinine urine end of exposure or work shift Fluoride: 4 mg/g creatinine urine prior to shift		

Monitoring methods

MDHS42/2 Nickel and inorganic compounds of nickel in air (except nickel carbonyl) Laboratory method using flame atomic absorption spectrometry or electrothermal atomic absorption spectrometry

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
Hydrofluoric acid 7664-39-3 (0.1)		0.01 mg/kg/ bw/day		0.01 mg/kg bw/day

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Butanedioic acid, disodium salt 150-90-3 (25.0)				DNEL = 11.7mg/kg bw/day

Component	Acute effects local	Acute effects	Chronic effects local	Chronic effects
-----------	---------------------	---------------	-----------------------	-----------------

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

	(Inhalation)	systemic (Inhalation)	(Inhalation)	systemic (Inhalation)
Butanedioic acid, disodium salt 150-90-3 (25.0)				DNEL = 41.1mg/m ³
Hydrofluoric acid 7664-39-3 (0.1)	DNEL = 2.5mg/m ³	DNEL = 2.5mg/m ³	DNEL = 1.5µg/m ³	DNEL = 1.5mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Nickel(II) chloride 7718-54-9 (25.0)	PNEC = 0.3136µg/L		PNEC = 3.136µg/L		
Butanedioic acid, disodium salt 150-90-3 (25.0)	PNEC = 0.1mg/L	PNEC = 0.48mg/kg sediment dw	PNEC = 1mg/L		PNEC = 37.2µg/kg soil dw
Hydrofluoric acid 7664-39-3 (0.1)	PNEC = 0.9mg/L			PNEC = 51mg/L	PNEC = 11mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Butanedioic acid, disodium salt 150-90-3 (25.0)	PNEC = 10µg/L	PNEC = 48µg/kg sediment dw	PNEC = 0.1mg/L		
Hydrofluoric acid 7664-39-3 (0.1)	PNEC = 0.9mg/L				

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Neoprene				
PVC				

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Recommended Filter type: Multi-purpose/ABEK conforming to EN14387 Particulates filter conforming to EN 143

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Butanedioic acid, disodium salt	<-0.59	
Hydrofluoric acid	-1.4	
Vapor Pressure	<=1100 hPa @ 50 °C	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Hydrogen chloride. Hydrogen fluoride. Oxides of phosphorus. Sodium oxides. Nickel oxides.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral Category 3
Dermal No data available
Inhalation Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phosphinic acid, sodium salt, monohydrate	LD50 = 7640 mg/kg (Rat)	-	-
Nickel(II) chloride	LD50 = 175 mg/kg (Rat)	-	-
Water	-	-	-
Hydrofluoric acid	-	-	LC50 = 0.79 mg/L (Rat) 1 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory Category 1
Skin Category 1
May cause sensitization by skin contact

(e) germ cell mutagenicity; Category 2

(f) carcinogenicity; Category 1A

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Nickel(II) chloride	Carc Cat. 1A		Cat. 1	Group 1

(g) reproductive toxicity; Category 1B

(h) STOT-single exposure; Category 3

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Category 1

Route of exposure Inhalation
Target Organs Lungs.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Nickel(II) chloride	LC50: = 6.9 mg/L, 96h static (Cyprinus carpio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: > 100 mg/L, 96h static (Brachydanio rerio) LC50: 2.83 - 5.99 mg/L, 96h static (Poecilia reticulata) LC50: 29.76 - 43.57 mg/L, 96h semi-static (Poecilia reticulata) LC50: = 9.65 mg/L, 96h flow-through (Poecilia reticulata) LC50: = 25 mg/L, 96h flow-through (Pimephales promelas) LC50: 2.02 - 6.88 mg/L, 96h static (Pimephales promelas) LC50: 1.9 - 4 mg/L, 96h (Pimephales promelas) LC50: 6.63 - 9.15 mg/L, 96h static (Oncorhynchus mykiss) LC50: 6.7 - 9.7 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: 2.02 - 6.88 mg/L, 96h static (Lepomis macrochirus) LC50: 18.1 - 25.5 mg/L, 96h flow-through (Lepomis macrochirus)	EC50: = 0.51 mg/L, 48h Static (Daphnia magna) EC50: = 6.68 mg/L, 48h (Daphnia magna)	EC50: 0.0063 - 0.0125 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 0.66 mg/L, 72h (Pseudokirchneriella subcapitata)
Hydrofluoric acid	LC50 = 660 mg/L, 48h (Leuciscus idus)	EC50 = 270 mg/L, 48h (Daphnia species)	

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Component	Microtox	M-Factor
Nickel(II) chloride		1 (acute) 1 (chronic)

12.2. Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary based on information available, May persist.
Persistence
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Butanedioic acid, disodium salt	<-0.59	No data available
Hydrofluoric acid	-1.4	No data available

12.4. Mobility in soil The product is water soluble, and may spread in water systems Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products Should not be released into the environment. Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Do not let this chemical enter the environment.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

IMDG/IMO

ALFAA44070

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

14.1. UN number UN3082
14.2. UN proper shipping name Environmentally hazardous substances, liquid, n.o.s.
14.3. Transport hazard class(es) 9
14.4. Packing group III

ADR

14.1. UN number UN3082
14.2. UN proper shipping name Environmentally hazardous substances, liquid, n.o.s.
14.3. Transport hazard class(es) 9
14.4. Packing group III

IATA

14.1. UN number UN3082
14.2. UN proper shipping name Environmentally hazardous substances, liquid, n.o.s.
14.3. Transport hazard class(es) 9
14.4. Packing group III

14.5. Environmental hazards Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Phosphinic acid, sodium salt, monohydrate	10039-56-2	-	-	-	X	X	-	X	X
Nickel(II) chloride	7718-54-9	231-743-0	-	-	X	X	KE-25837	X	X
Butanedioic acid, disodium salt	150-90-3	205-778-7	-	-	X	X	KE-12377	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
Hydrofluoric acid	7664-39-3	231-634-8	-	-	X	X	KE-20198	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Phosphinic acid, sodium salt, monohydrate	10039-56-2	-	-	-	-	X	X	X
Nickel(II) chloride	7718-54-9	X	ACTIVE	X	-	X	X	X
Butanedioic acid, disodium salt	150-90-3	X	ACTIVE	X	-	X	X	X
Water	7732-18-5	X	ACTIVE	X	-	X	X	X
Hydrofluoric acid	7664-39-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Phosphinic acid, sodium salt, monohydrate	10039-56-2	-	-	-
Nickel(II) chloride	7718-54-9	-	Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 30. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details) Use restricted. See entry 27. (see link for restriction details)	-
Butanedioic acid, disodium salt	150-90-3	-	-	-
Water	7732-18-5	-	-	-
Hydrofluoric acid	7664-39-3	-	Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Phosphinic acid, sodium salt, monohydrate	10039-56-2	Not applicable	Not applicable
Nickel(II) chloride	7718-54-9	Not applicable	Not applicable
Butanedioic acid, disodium salt	150-90-3	Not applicable	Not applicable
Water	7732-18-5	Not applicable	Not applicable
Hydrofluoric acid	7664-39-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Phosphinic acid, sodium salt, monohydrate	WGK2	
Nickel(II) chloride	WGK3	
Butanedioic acid, disodium salt	WGK1	
Hydrofluoric acid	WGK2	

Component	France - INRS (Tables of occupational diseases)
Nickel(II) chloride	Tableaux des maladies professionnelles (TMP) - RG 37, RG 37bis
Hydrofluoric acid	Tableaux des maladies professionnelles (TMP) - RG 32

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Hydrofluoric acid 7664-39-3 (0.1)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H290 - May be corrosive to metals
H300 - Fatal if swallowed
H301 - Toxic if swallowed
H310 - Fatal in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H331 - Toxic if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H341 - Suspected of causing genetic defects
H350 - May cause cancer
H350i - May cause cancer by inhalation
H360D - May damage the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

SAFETY DATA SHEET

Nickel plating solution, electroless, ammonia free

Revision Date 30-Nov-2024

PICCS - Philippines Inventory of Chemicals and Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit
ACGIH - American Conference of Governmental Industrial Hygienists
DNEL - Derived No Effect Level
RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%
NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
ATE - Acute Toxicity Estimate
VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Prepared By	Health, Safety and Environmental Department
Revision Date	30-Nov-2024
Revision Summary	Not applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet