

SAFETY DATA SHEET

Revision Date 01-April-2024

Revision Number 4

1. Identification

Product Name Sulfur in Diesel Fuel standard solution, Specpure®, 40,000 µg/g (4.00%)

Cat No. : 41697

Synonyms No information available

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor
Fisher Scientific
112 Colonnade Road,
Ottawa, ON K2E 7L6,
Canada
Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	

Label Elements

Signal Word

Warning

Hazard Statements

Combustible liquid

Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation
Suspected of causing cancer



Precautionary Statements

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Use only outdoors or in a well-ventilated area

Response

IF exposed or concerned: Get medical advice/attention
IF ON SKIN: Wash with plenty of soap and water
IF INHALED: Remove person to fresh air and keep comfortable for breathing
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If skin irritation occurs: Get medical advice/attention
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
Take off contaminated clothing and wash it before reuse

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Fuels, diesel, no. 2	68476-34-6	81.76
Butane, 1,1-thiobis-	544-40-1	18.24

4. First-aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water.

Most important symptoms/effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Water mist may be used to cool closed containers.

Unsuitable Extinguishing Media No information available

Flash Point 69 °C / 156.2 °F

Method - No information available

Autoignition Temperature 500 °C / 932 °F

Explosion Limits

Upper No data available

Lower No data available

Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Combustible material. Containers may explode when heated.

Hazardous Combustion Products

None known.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
2

Flammability
2

Instability
0

Physical hazards
-

6. Accidental release measures

Personal Precautions Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition.

Storage. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British	Ontario TWA/EV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
-----------	---------	---------	----------------	--------	-----------	----------	-------

		Columbia					
Fuels, diesel, no. 2	TWA: 100 mg/m ³	TWA: 100 mg/m ³ Skin	TWA: 100 mg/m ³ Skin	TWA: 100 mg/m ³	TWA: 100 mg/m ³ Skin		

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.
Ensure adequate ventilation, especially in confined areas.
Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Natural rubber	See manufacturers	-	Splash protection only
Nitrile rubber	recommendations		
Neoprene			
PVC			

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Recommended Filter type: Particulates filter conforming to EN 143

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Light brown
Odor	Petroleum distillates
Odor Threshold	No information available
pH	No information available
Melting Point/Range	No data available
Boiling Point/Range	171 - 315 °C / 339.8 - 599 °F
Flash Point	69 °C / 156.2 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable

Flammability or explosive limits

Upper

No data available

Lower

No data available

Vapor Pressure

No information available

Vapor Density

No information available

Specific Gravity

0.75 g/cm³

Solubility

No information available

Partition coefficient; n-octanol/water

No data available

Autoignition Temperature

500 °C / 932 °F

Decomposition Temperature

No information available

Viscosity

No information available

10. Stability and reactivity

Reactive Hazard

None known, based on information available

Stability

Stable under normal conditions.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Strong oxidizing agents

Hazardous Decomposition Products None under normal use conditions

Hazardous Polymerization

Hazardous polymerization does not occur.

Hazardous Reactions

None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Fuels, diesel, no. 2	Not listed	LD50 > 2000 mg/kg (Rabbit)	LC50 = 3.6 mg/L (Rat) 4 h LC50 = 5.4 mg/L (Rat) 4 h
Butane, 1,1-thiobis-	LD50 = 2220 mg/kg (Rat)	Not listed	Not listed

Toxicologically Synergistic

No information available

Products

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation

No information available

Sensitization

No information available

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Fuels, diesel, no. 2	68476-34-6	Not listed	Not listed	A3	Not listed	A3
Butane, 1,1-thiobis-	544-40-1	Not listed	Not listed	Not listed	Not listed	Not listed

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mutagenic Effects	No information available
Reproductive Effects	No information available.
Developmental Effects	No information available.
Teratogenicity	No information available.
STOT - single exposure	Respiratory system
STOT - repeated exposure	None known
Aspiration hazard	No information available
Symptoms / effects, both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Endocrine Disruptor Information	No information available
Other Adverse Effects	The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Fuels, diesel, no. 2	Not listed	LC50: = 35 mg/L, 96h flow-through (Pimephales promelas)	Not listed	Not listed
Butane, 1,1-thiobis-	Not listed	LC50: = 3.58 mg/L, 96h flow-through (Pimephales promelas)	Not listed	Not listed

Persistence and Degradability	No information available
Bioaccumulation/ Accumulation	No information available.
Mobility	No information available.

13. Disposal considerations

Waste Disposal Methods	Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.
-------------------------------	---

14. Transport information

DOT	COMBUSTIBLE LIQUID, NOT REGULATED FOR TRANSPORT IN THIS QUANTITY According to 49 CFR §173.150(f)(1), this material should be reclassified as NA1993, Combustible Liquid, NOS if it is shipped in bulk.
UN-No	NA1993
Proper Shipping Name	Combustible liquid, n.o.s.
Packing Group	III
TDG	Not regulated
IATA	Not regulated
IMDG/IMO	Not regulated

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Fuels, diesel, no. 2	68476-34-6	X	-	X	ACTIVE	270-676-1	-	-
Butane, 1,1-thiobis-	544-40-1	X	-	X	ACTIVE	208-870-5	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Fuels, diesel, no. 2	68476-34-6	X	KE-17287	-	-	X	X	X	X
Butane, 1,1-thiobis-	544-40-1	X	-	X	X	X	X	X	X

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Other International Regulations

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Fuels, diesel, no. 2	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Fuels, diesel, no. 2	68476-34-6	Listed	Not applicable	Not applicable	Not applicable
Butane, 1,1-thiobis-	544-40-1	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Fuels, diesel, no. 2	68476-34-6	Not applicable	Not applicable	Not applicable	Not applicable
Butane, 1,1-thiobis-	544-40-1	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By	Product Safety Department Email: chem.techinfo@thermofisher.com www.thermofisher.com
Revision Date	01-April-2024
Print Date	01-April-2024
Revision Summary	New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS