

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Nickel(II) octanoate, in mineral spirits**
Cat No. : **39479**
Molecular Formula **C₁₆H₃₀NiO₄**

Unique Formula Identifier (UFI) **1RFM-W6TP-6X05-8DAK**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 3 (H226)

Health hazards

Aspiration Toxicity

Category 1 (H304)

Respiratory Sensitization

Category 1 (H334)

Skin Sensitization

Category 1 (H317)

Germ Cell Mutagenicity

Category 1B (H340)

Carcinogenicity

Category 1B Category 1A (H350i)

Reproductive Toxicity

Category 1B (H360D)

Specific target organ toxicity - (repeated exposure)

Category 1 (H372)

Environmental hazards

Acute aquatic toxicity

Category 1 (H400)

Chronic aquatic toxicity

Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H317 - May cause an allergic skin reaction

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H340 - May cause genetic defects

H350i - May cause cancer by inhalation

H360D - May damage the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

H410 - Very toxic to aquatic life with long lasting effects

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331 - Do NOT induce vomiting

P284 - Wear respiratory protection

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P308 + P313 - IF exposed or concerned: Get medical advice/attention

Additional EU labelling

Restricted to professional users

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors
Toxic to terrestrial vertebrates

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
2-Ethylhexanoic acid, nickel salt	7580-31-6	EEC No. 231-480-1	48.00	Skin Sens. 1 (H317) Resp. Sens. 1 (H334) Muta. 2 (H341) Carc. 1A (H350i) Repr. 1B (H360D) STOT RE 1 (H372) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Stoddard solvent	8052-41-3	EEC No. 232-489-3	39.00	Flam. Liq. 3 (H226) Muta. 1B (H340) Carc. 1B (H350) Asp. Tox. 1 (H304) STOT RE 1 (H372) Aquatic Tox. 2 (H411) (EUH066)
2-Ethylhexanoic acid	149-57-5	EEC No. 205-743-6	13.00	Repr. 1B (H360D)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
2-Ethylhexanoic acid, nickel salt	Skin Sens. 1 (H317) :: C>=0.01% STOT RE 1 (H372) :: C>=1% STOT RE 2 (H373) :: 0.1%<=C<1%	1	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

	a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Carbon dioxide (CO₂). Powder. Foam. Water may be ineffective. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Nickel oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained. Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Stoddard solvent				TWA: 100 ppm 8 uren TWA: 533 mg/m ³ 8 uren	
2-Ethylhexanoic acid				TWA: 5 mg/m ³ 8 uren	TWA / VLA-ED: 5 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
2-Ethylhexanoic acid, nickel salt		TWA: 0.03 mg/m ³ (8 Stunden). AGW - exposure factor 8	TWA: 0.2 mg/m ³ 8 horas		
Stoddard solvent			TWA: 100 ppm 8 horas		

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

2-Ethylhexanoic acid			TWA: 5 mg/m ³ 8 horas		
----------------------	--	--	----------------------------------	--	--

Component	Austria	Denmark	Switzerland	Poland	Norway
2-Ethylhexanoic acid, nickel salt			TWA: 0.05 mg/m ³ 8 Stunden		TWA: 0.05 mg/m ³ 8 timer
Stoddard solvent		TWA: 25 ppm 8 timer TWA: 145 mg/m ³ 8 timer STEL: 50 ppm 15 minutter STEL: 290 mg/m ³ 15 minutter		STEL: 900 mg/m ³ 15 minutach TWA: 300 mg/m ³ 8 godzinach	

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Stoddard solvent			TWA: 100 ppm 8 hr. TWA: 573 mg/m ³ 8 hr.		TWA: 200 mg/m ³ 8 hodinách. Ceiling: 1000 mg/m ³
2-Ethylhexanoic acid			TWA: 4 mg/m ³ 8 hr. STEL: 12 mg/m ³ 15 min		

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Stoddard solvent	TWA: 50 ppm 8 tundides. TWA: 300 mg/m ³ 8 tundides. STEL: 100 ppm 15 minutites. STEL: 600 mg/m ³ 15 minutites.		STEL: 125 ppm STEL: 720 mg/m ³ TWA: 100 ppm TWA: 575 mg/m ³		TWA: 25 ppm 8 klukkustundum. TWA: 145 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 50 ppm Ceiling: 290 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Stoddard solvent		TWA: 50 ppm IPRD approximate value TWA: 300 mg/m ³ IPRD STEL: 600 mg/m ³ STEL: 100 ppm			

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Stoddard solvent	TWA: 300 mg/m ³ 2119 MAC: 900 mg/m ³			Indicative STEL: 100 ppm 15 minuter Indicative STEL: 600 mg/m ³ 15 minuter Indicative STEL: 60 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 300 mg/m ³ 8 timmar. NGV TLV: 50 ppm 8 timmar. NGV TLV: 175 mg/m ³ 8 timmar. NGV TLV: 30 ppm 8 timmar. NGV Hud	

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

MDHS42/2 Nickel and inorganic compounds of nickel in air (except nickel carbonyl) Laboratory method using flame atomic absorption spectrometry or electrothermal atomic absorption spectrometry

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Stoddard solvent 8052-41-3 (39.00)		DNEL = 30mg/kg bw/day	DNEL = 7.56mg/cm2	DNEL = 80mg/kg bw/day
2-Ethylhexanoic acid 149-57-5 (13.00)				DNEL = 2mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Stoddard solvent 8052-41-3 (39.00)	DNEL = 55mg/m ³	DNEL = 55mg/m ³	DNEL = 44mg/m ³	DNEL = 44mg/m ³
2-Ethylhexanoic acid 149-57-5 (13.00)				DNEL = 14mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Stoddard solvent 8052-41-3 (39.00)	PNEC = 0.14mg/L	PNEC = 1.14mg/kg sediment dw	PNEC = 0.014mg/L		
2-Ethylhexanoic acid 149-57-5 (13.00)	PNEC = 0.398mg/L	PNEC = 4.74mg/kg sediment dw	PNEC = 1mg/L	PNEC = 71.7mg/L	PNEC = 0.712mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Stoddard solvent 8052-41-3 (39.00)	PNEC = 0.35mg/L	PNEC = 0.14mg/kg sediment dw			PNEC = 10mg/m ³
2-Ethylhexanoic acid 149-57-5 (13.00)	PNEC = 0.0398mg/L	PNEC = 0.474mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Multi-purpose/ABEK conforming to EN14387 low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Green	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	40 °C / 104 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Immiscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Stoddard solvent	6.4	
2-Ethylhexanoic acid	2.7	
Vapor Pressure	<=1100 hPa @ 50 °C	
Density / Specific Gravity	0.95 g/cm3	@ 20 °C
Bulk Density	Not applicable	Liquid

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

Vapor Density No data available (Air = 1.0)
Particle characteristics Not applicable (liquid)

9.2. Other information

Molecular Formula C16 H30 NiO4
Molecular Weight 345.10
Explosive Properties explosive air/vapour mixtures possible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials Oxidizing agent.

10.6. Hazardous decomposition products Carbon monoxide (CO). Carbon dioxide (CO₂). Nickel oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Stoddard solvent	5000 mg/kg (orl, rat)	LD50 > 3000 mg/kg (Rabbit)	LC50 > 5.5 mg/L (Rat) 4 h
2-Ethylhexanoic acid	LD50 = 1600 mg/kg (Rat)	LD50 = 1140 mg/kg (Rabbit)	-

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

(d) respiratory or skin sensitization;

Respiratory

Category 1

Skin

Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity;

Category 1B

(f) carcinogenicity;

Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
2-Ethylhexanoic acid, nickel salt	Carc Cat. 1A			
Stoddard solvent	Carc Cat. 1B			

(g) reproductive toxicity;

Category 1B

(h) STOT-single exposure;

No data available

(i) STOT-repeated exposure;

Category 1

Target Organs

Central nervous system (CNS).

(j) aspiration hazard;

Category 1

Symptoms / effects, both acute and delayed

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
2-Ethylhexanoic acid	LC50: = 70 mg/L, 96h (Pimephales promelas)	EC50: = 85.4 mg/L, 48h (Daphnia magna)	EC50: = 41 mg/L, 96h (Desmodesmus subspicatus) EC50: = 61 mg/L, 72h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
2-Ethylhexanoic acid, nickel salt		1
2-Ethylhexanoic acid	EC50 = 110 mg/L 17 h EC50 = 670 mg/L 30 min	

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

12.2. Persistence and degradability	Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Persistence	Immiscible with water, May persist.
Degradation in sewage treatment plant	Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
Stoddard solvent	6.4	No data available
2-Ethylhexanoic acid	2.7	No data available

12.4. Mobility in soil Spillage unlikely to penetrate soil The product is insoluble and floats on water Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1993
14.2. UN proper shipping name Flammable liquid, n.o.s.

ALFAA39479

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

Technical Shipping Name (Mineral spirits)
14.3. Transport hazard class(es) 3
14.4. Packing group III

ADR

14.1. UN number UN1993
14.2. UN proper shipping name Flammable liquid, n.o.s.
Technical Shipping Name (Mineral spirits)
14.3. Transport hazard class(es) 3
14.4. Packing group III

IATA

14.1. UN number UN1993
14.2. UN proper shipping name Flammable liquid, n.o.s.
Technical Shipping Name (Mineral spirits)
14.3. Transport hazard class(es) 3
14.4. Packing group III

14.5. Environmental hazards Dangerous for the environment
 Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
2-Ethylhexanoic acid, nickel salt	7580-31-6	231-480-1	-	-	X	X	KE-13758	X	X
Stoddard solvent	8052-41-3	232-489-3	-	-	X	X	KE-32199	-	-
2-Ethylhexanoic acid	149-57-5	205-743-6	-	-	X	X	KE-13740	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDL	AICS	NZIoC	PICCS
2-Ethylhexanoic acid, nickel salt	7580-31-6	X	ACTIVE	X	-	X	-	-
Stoddard solvent	8052-41-3	X	ACTIVE	X	-	X	X	X
2-Ethylhexanoic acid	149-57-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
2-Ethylhexanoic acid, nickel salt	7580-31-6	-	Use restricted. See item	-

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

			28. (see link for restriction details) Use restricted. See item 30. (see link for restriction details) Use restricted. See item 75. (see link for restriction details) Use restricted. See item 27. (see link for restriction details)	
Stoddard solvent	8052-41-3	-	Use restricted. See item 28. (see link for restriction details) Use restricted. See item 29. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
2-Ethylhexanoic acid	149-57-5	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
2-Ethylhexanoic acid, nickel salt	7580-31-6	Not applicable	Not applicable
Stoddard solvent	8052-41-3	Not applicable	Not applicable
2-Ethylhexanoic acid	149-57-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Stoddard solvent	WGK2	
2-Ethylhexanoic acid	WGK1	Class I : 20 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Stoddard solvent	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
2-Ethylhexanoic acid 149-57-5 (13.00)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways
H317 - May cause an allergic skin reaction
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H340 - May cause genetic defects
H350 - May cause cancer
H350i - May cause cancer by inhalation
H360D - May damage the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
EUH066 - Repeated exposure may cause skin dryness or cracking
H226 - Flammable liquid and vapor
H341 - Suspected of causing genetic defects
H411 - Toxic to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

SAFETY DATA SHEET

Nickel(II) octanoate, in mineral spirits

Revision Date 19-Mar-2024

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared By Health, Safety and Environmental Department

Revision Date 19-Mar-2024

Revision Summary New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet