

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Acetic acid-Trimethylpentane, 60/40 (v/v) solution
Cat No. : 41895
Molecular Formula $\text{CH}_3\text{CO}_2\text{H}/(\text{CH}_3)_3\text{CCH}_2\text{CH}(\text{CH}_3)_2$

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
 Erlenbachweg 2, 76870 Kandel, Germany
 Tel: +49 (0) 721 84007 280
 Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
 Neuhofstrasse 11, CH 4153 Reinach
 Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
 Tox Info Suisse Emergency Number: **145 (24hr)**
 Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
 Chemtrec (24h) Toll-Free: 0800 564 402
 Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

Flammable liquids

Category 3 (H226)

Health hazards

Aspiration Toxicity
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Specific target organ toxicity - (single exposure)

Category 1 (H304)
Category 1 A (H314)
Category 1 (H318)
Category 3 (H336)

Environmental hazards

Acute aquatic toxicity
Chronic aquatic toxicity

Category 1 (H400)
Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H336 - May cause drowsiness or dizziness
H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Acetic acid	64-19-7	200-580-7	71.00	Flam. Liq. 3 (H226)

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

				Skin Corr. 1A (H314) Eye Dam. 1 (H318)
2,2,4-Trimethylpentane	540-84-1	EEC No. 208-759-1	29	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Acetic acid	Skin Corr. 1A (H314) :: C>=90% Skin Corr. 1B (H314) :: 25%<=C<90% Eye Irrit. 2 (H319) :: 10%<=C<25% Skin Irrit. 2 (H315) :: 10%<=C<25%	-	-
2,2,4-Trimethylpentane	-	1	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
--------------------	------------------------

SECTION 5: FIREFIGHTING MEASURES

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority.

CH - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund). **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

Component	European Union	The United Kingdom	France	Belgium	Spain
Acetic acid	TWA: 25 mg/m ³ (8h) TWA: 10 ppm (8h) STEL: 50 mg/m ³ (15min) STEL: 20 ppm (15min)	STEL: 37 mg/m ³ STEL: 15 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA / VME: 10 ppm (8 heures). TWA / VME: 25 mg/m ³ (8 heures). STEL / VLCT: 20 ppm. indicative limit STEL / VLCT: 50 mg/m ³ . indicative limit	TWA: 10 ppm 8 uren TWA: 25 mg/m ³ 8 uren STEL: 15 ppm 15 minuten STEL: 38 mg/m ³ 15 minuten	STEL / VLA-EC: 20 ppm (15 minutos). STEL / VLA-EC: 50 mg/m ³ (15 minutos). TWA / VLA-ED: 10 ppm (8 horas) TWA / VLA-ED: 25 mg/m ³ (8 horas)
2,2,4-Trimethylpentane			TWA / VME: 1000 mg/m ³ (8 heures). STEL / VLCT: 1500 mg/m ³ .		TWA / VLA-ED: 300 ppm (8 horas) TWA / VLA-ED: 1420 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Acetic acid	TWA: 25 ppm 8 ore. Time Weighted Average TWA: 10 mg/m ³ 8 ore. Time Weighted Average STEL: 50 mg/m ³ 15 minuti. Short-term STEL: 20 ppm 15 minuti. Short-term	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK TWA: 25 mg/m ³ (8 Stunden). MAK Höhepunkt: 20 ppm Höhepunkt: 50 mg/m ³	STEL: 20 ppm 15 minutos STEL: 50 mg/m ³ 15 minutos TWA: 10 ppm 8 horas TWA: 25 mg/m ³ 8 horas	MAC-TGG 25 mg/m ³	TWA: 5 ppm 8 tunteina TWA: 13 mg/m ³ 8 tunteina STEL: 10 ppm 15 minuutteina STEL: 25 mg/m ³ 15 minuutteina
2,2,4-Trimethylpentane			TWA: 300 ppm 8 horas		TWA: 300 ppm 8 tunteina TWA: 1400 mg/m ³ 8 tunteina STEL: 380 ppm 15 minuutteina STEL: 1800 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Acetic acid	MAK-KZGW: 20 ppm 15 Minuten MAK-KZGW: 50 mg/m ³ 15 Minuten	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer STEL: 50 mg/m ³ 15 minutter	STEL: 20 ppm 15 Minuten STEL: 50 mg/m ³ 15 Minuten	STEL: 50 mg/m ³ 15 minutach TWA: 25 mg/m ³ 8 godzinach	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer STEL: 20 ppm 15 minutter. value from the

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

	MAK-TMW: 10 ppm 8 Stunden MAK-TMW: 25 mg/m ³ 8 Stunden	STEL: 20 ppm 15 minutter	TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden		regulation STEL: 50 mg/m ³ 15 minutter. value from the regulation
2,2,4-Trimethylpentane	MAK-KZGW: 1200 ppm 15 Minuten MAK-KZGW: 5600 mg/m ³ 15 Minuten MAK-TMW: 300 ppm 8 Stunden MAK-TMW: 1400 mg/m ³ 8 Stunden		STEL: 200 ppm 15 Minuten STEL: 940 mg/m ³ 15 Minuten STEL: 600 ppm 15 Minuten STEL: 2800 mg/m ³ 15 Minuten TWA: 100 ppm 8 Stunden TWA: 470 mg/m ³ 8 Stunden TWA: 300 ppm 8 Stunden TWA: 1400 mg/m ³ 8 Stunden		TWA: 40 ppm 8 timer TWA: 275 mg/m ³ 8 timer

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Acetic acid	TWA: 25 mg/m ³ TWA: 10 ppm STEL : 50 mg/m ³ STEL : 20 ppm	TWA-GVI: 10 ppm 8 satima. TWA-GVI: 25 mg/m ³ 8 satima. STEL-KGVI: 20 ppm 15 minutama. STEL-KGVI: 50 mg/m ³ 15 minutama.	TWA: 20 ppm 8 hr. TWA: 50 mg/m ³ 8 hr. STEL: 20 ppm 15 min STEL: 50 mg/m ³ 15 min	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 25 mg/m ³ 8 hodinách. Ceiling: 50 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Acetic acid	TWA: 10 ppm 8 tundides. TWA: 25 mg/m ³ 8 tundides. STEL: 10 ppm 15 minutites. STEL: 25 mg/m ³ 15 minutites.	TWA: 25 mg/m ³ 8 hr TWA: 10 ppm 8 hr STEL: 50 mg/m ³ 15 min STEL: 20 ppm 15 min	STEL: 15 ppm STEL: 37 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	STEL: 50 mg/m ³ 15 percekbén. CK TWA: 25 mg/m ³ 8 órában. AK	STEL: 20 ppm STEL: 50 mg/m ³ TWA: 10 ppm 8 klukkustundum. TWA: 25 mg/m ³ 8 klukkustundum.

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Acetic acid	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm IPRD TWA: 25 mg/m ³ IPRD STEL: 50 mg/m ³ STEL: 20 ppm	TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden STEL: 50 mg/m ³ 15 Minuten STEL: 20 ppm 15 Minuten	TWA: 10 ppm TWA: 25 mg/m ³ STEL: 20 ppm 15 minuti STEL: 50 mg/m ³ 15 minuti	TWA: 10 ppm 8 ore TWA: 25 mg/m ³ 8 ore STEL: 20 ppm 15 minute STEL: 50 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Acetic acid	Skin notation MAC: 5 mg/m ³	Ceiling: 50 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm 8 urah TWA: 25 mg/m ³ 8 urah STEL: 50 mg/m ³ 15 minutah STEL: 20 ppm 15 minutah	Binding STEL: 10 ppm 15 minuter Binding STEL: 25 mg/m ³ 15 minuter TLV: 5 ppm 8 timmar. NGV TLV: 13 mg/m ³ 8 timmar. NGV	TWA: 10 ppm 8 saat TWA: 25 mg/m ³ 8 saat

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Oral)	Acute effects systemic (Oral)	Chronic effects local (Oral)	Chronic effects systemic (Oral)
2,2,4-Trimethylpentane 540-84-1 (29)				699 mg/kg bw/day

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
2,2,4-Trimethylpentane 540-84-1 (29)				DNEL = 773mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Acetic acid 64-19-7 (71.00)	DNEL = 25mg/m ³		DNEL = 25mg/m ³	
2,2,4-Trimethylpentane 540-84-1 (29)				DNEL = 2035mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Acetic acid 64-19-7 (71.00)	PNEC = 3.058mg/L	PNEC = 11.36mg/kg sediment dw	PNEC = 30.58mg/L	PNEC = 85mg/L	PNEC = 0.47mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Acetic acid 64-19-7 (71.00)	PNEC = 0.3058mg/L	PNEC = 1.136mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber Butyl rubber Nitrile rubber Neoprene PVC	See manufacturers recommendations	-	EN 374	(minimum requirement)

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

Skin and body protection	Long sleeved clothing.
Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.	
Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced Recommended Filter type: Particulates filter conforming to EN 143 or Acid gases filter Type E Yellow conforming to EN14387
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
Environmental exposure controls	Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	< 0 °C / < 32 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Acetic acid	-0.2	
Vapor Pressure	No data available	
Density / Specific Gravity	0.88 g/cm3	@ 20 °C
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	CH ₃ CO ₂ H/(CH ₃) ₃ CCH ₂ CH(CH ₃) ₂
Explosive Properties	explosive air/vapour mixtures possible

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization
Hazardous Reactions

No information available.
None under normal processing.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
2,2,4-Trimethylpentane	LD50 5000 mg/kg (Rat)	2000 mg/kg (Rabbit)	LC50 = 33.52 mg/L (Rat) 4 h

(b) skin corrosion/irritation;

Category 1 A

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

No data available

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

(h) STOT-single exposure; Category 3
Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; No data available
Target Organs No information available.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Acetic acid	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	EC50 = 95 mg/L/24h	-
2,2,4-Trimethylpentane	LC50 = 0.11 mg/l, 96h, (Rainbow trout)	EC50= 0.4 mg/l, 48h (Daphnia magna)	EC50= 2.94 mg/l, 72h

Component	Microtox	M-Factor
Acetic acid	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	
2,2,4-Trimethylpentane		1

12.2. Persistence and degradability

Persistence

Degradation in sewage treatment plant

Miscible with water, Persistence is unlikely, based on information available. Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Acetic acid	-0.2	No data available

12.4. Mobility in soil

The product is water soluble, and may spread in water systems. Will likely be mobile in the environment due to its water solubility. Highly mobile in soils.

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN2924
14.2. UN proper shipping name Flammable liquid, corrosive, n.o.s.
Technical Shipping Name (Acetic acid-Trimethylpentane, 60, 40 (v/v) solution)
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 8
14.4. Packing group II

ADR

14.1. UN number UN2924
14.2. UN proper shipping name Flammable liquid, corrosive, n.o.s.
Technical Shipping Name (Acetic acid-Trimethylpentane, 60, 40 (v/v) solution)
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 8
14.4. Packing group II

IATA

14.1. UN number UN2924
14.2. UN proper shipping name Flammable liquid, corrosive, n.o.s.

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

Technical Shipping Name	(Acetic acid-Trimethylpentane, 60, 40 (v/v) solution)
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	8
14.4. Packing group	II

14.5. Environmental hazards Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Acetic acid	64-19-7	200-580-7	-	-	X	X	X	X	X
2,2,4-Trimethylpentane	540-84-1	208-759-1	-	-	X	X	KE-34634	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Acetic acid	64-19-7	X	ACTIVE	X	-	X	X	X
2,2,4-Trimethylpentane	540-84-1	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Acetic acid	64-19-7	-	Use restricted. See item 75. (see link for restriction details)	-
2,2,4-Trimethylpentane	540-84-1	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Acetic acid	64-19-7	Not applicable	Not applicable
2,2,4-Trimethylpentane	540-84-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Acetic acid	WGK1	Class II : 0.10 g/m ³ (Massenkonzentration)
2,2,4-Trimethylpentane	WGK2	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Acetic acid 64-19-7 (71.00)	Prohibited and Restricted Substances	Group I	
2,2,4-Trimethylpentane 540-84-1 (29)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H225 - Highly flammable liquid and vapor

H226 - Flammable liquid and vapor

H315 - Causes skin irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

SAFETY DATA SHEET

Acetic acid-Trimethylpentane, 60/40 (v/v) solution

Revision Date 17-Mar-2024

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Prepared By Health, Safety and Environmental Department

Revision Date 17-Mar-2024

Revision Summary New emergency telephone response service provider.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet