

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name Styrene, stabilized

CAS No 100-42-5

Synonyms Ethenylbenzene

Product Code **O4507-1**

Address ThermoFisher Scientific Australia Pty Ltd
5 Caribbean Drive, Scoresby
VICTORIA 3179, Australia

Emergency Tel. **CHEMTREC®**
03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292
Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids

Category 3

Health hazards

Aspiration Toxicity
Acute Inhalation Toxicity - Vapors
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Reproductive Toxicity
Specific target organ toxicity - (single exposure)
Specific target organ toxicity - (repeated exposure)

Category 1
Category 4
Category 2
Category 2
Category 2
Category 3
Category 1

Environmental hazards

Chronic aquatic toxicity

Category 3

Label Elements



Flame



Exclamation Mark



Health Hazard

Signal Word**Danger****Hazard Statements**

H226 - Flammable liquid and vapor

H315 - Causes skin irritation

H304 - May be fatal if swallowed and enters airways

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H361 - Suspected of damaging fertility or the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P233 - Keep container tightly closed

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear eye protection/ face protection

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P363 - Wash contaminated clothing before reuse

P331 - Do NOT induce vomiting

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Styrene	100-42-5	>95

Section 4 - First Aid Measures

Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
General Advice	If symptoms persist, call a physician.
Self-Protection of the First Aider	Use personal protective equipment as required.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water may be ineffective.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep refrigerated. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]

updated in August, 2005. Safe Work Australia **ACGIH** - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **DE** - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Styrene	STEL: 100 ppm STEL: 426 mg/m ³ TWA: 50 ppm TWA: 213 mg/m ³	TWA: 20 ppm TWA: 85 mg/m ³ STEL: 40 ppm STEL: 170 mg/m ³	TWA: 10 ppm STEL: 20 ppm	STEL: 250 ppm 15 min STEL: 1080 mg/m ³ 15 min TWA: 100 ppm 8 hr TWA: 430 mg/m ³ 8 hr	TWA: 20 ppm (8 Stunden). AGW - exposure factor 2 TWA: 86 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 20 ppm (8 Stunden). MAK TWA: 86 mg/m ³ (8 Stunden). MAK Höhepunkt: 40 ppm Höhepunkt: 172 mg/m ³

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand	European Union	United Kingdom	Germany
Styrene		400 mg/g creatinine (urine) end of shift (Mandelic acid plus phenylglyoxylic acid) 40 µg/L (urine) end of shift (Styrene)			Mandelic acid plus Phenylglyoxylic acid: 600 mg/g Creatinine urine (end of shift) Mandelic acid plus Phenylglyoxylic acid: 600 mg/g Creatinine

					urine (for long-term exposures: at the end of the shift after several shifts)
--	--	--	--	--	--

Exposure Controls**Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber	See manufacturers	-	AS/NZS 2161	(minimum requirement)
Neoprene	recommendations			
Natural rubber				
PVC				

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Long sleeved clothing

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties**Appearance**

Colorless

Physical State

Liquid

Odor

pungent

Odor Threshold

No data available

pH

No information available

Melting Point/Range

-31 °C / -23.8 °F

Softening Point

No data available

Boiling Point/Range

145 - 146 °C / 293 - 294.8 °F @ 760 mmHg

Flash Point	31 °C / 87.8 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.1 Upper 6.1	
Vapor Pressure	7 mbar @ 20 °C	
Vapor Density	1.22	(Air = 1.0)
Specific Gravity / Density	0.906	
Bulk Density	Not applicable	Liquid
Water Solubility	0.3 mg/L (20°C)	
Solubility in other solvents	Soluble: Alcohols, Diethyl ether	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Styrene	2.96	
Autoignition Temperature	490 °C / 914 °F	
Decomposition Temperature	No data available	
Viscosity	0.695 mPa.s at 25 °C	
Explosive Properties		explosive air/vapour mixtures possible
Oxidizing Properties	No information available	
Other information		
Molecular Formula	C8 H8	
Molecular Weight	104.15	

Section 10 - Stability and Reactivity

Reactivity	Yes
Stability	Stable under normal conditions.
Conditions to Avoid	Excess heat, Incompatible products, Keep away from open flames, hot surfaces and sources of ignition, Temperatures above 40°C.
Incompatible Materials	Acids, Halogenated compounds, Copper alloys, Strong oxidizing agents.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂).
Hazardous Polymerization	Hazardous polymerization may occur. Hazardous polymerization may occur upon depletion of inhibitor.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Styrene	-	LD50 > 2000 mg/kg (Rat)	LC50 = 11.7 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;**Respiratory**

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

(f) carcinogenicity;

Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	Australia	New Zealand	New South Wales	Western Australia	IARC	EU	UK	Germany
Styrene		Suspected carcinogen			Group 2A			

**(g) reproductive toxicity;
Reproductive Effects**

Category 2

Experiments have shown reproductive toxicity effects on laboratory animals

(h) STOT-single exposure;

Category 3

Results / Target organs

Respiratory system

(i) STOT-repeated exposure;

Category 1

Target Organs

Ears, Central nervous system (CNS).

(j) aspiration hazard;

Category 1

Other Adverse Effects

The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effects

Do not empty into drains. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Styrene	LC50: 19.03 - 33.53 mg/L, 96h static (Lepomis macrochirus) LC50: 6.75 - 14.5 mg/L, 96h static (Pimephales promelas) LC50: 58.75 - 95.32 mg/L, 96h static (Poecilia reticulata) LC50: 3.24 - 4.99 mg/L, 96h flow-through (Pimephales promelas)	EC50: 3.3 - 7.4 mg/L, 48h (Daphnia magna)	EC50: 0.15 - 3.2 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: 0.46 - 4.3 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: = 0.72 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 1.4 mg/L, 72h (Pseudokirchneriella subcapitata)	= 5.4 mg/L EC50 Photobacterium phosphoreum 5 min

Persistence and Degradability**Persistence**

Insoluble in water, Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative Potential

May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
-----------	---------	-------------------------------

Styrene	2.96	13.5 dimensionless	
Mobility	Spillage unlikely to penetrate soil. The product is insoluble and floats on water. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. : Is not likely mobile in the environment due its low water solubility: Will likely be mobile in the environment due to its volatility		
Endocrine Disruptor Information			
Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Styrene	Group I Chemical	High Exposure Concern	
Persistent Organic Pollutant	This product does not contain any known or suspected substance		
Ozone Depletion Potential	This product does not contain any known or suspected substance		

Section 13 - Disposal Considerations

Waste from Residues/Unused Products	Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
Other Information	Chemical wastes should be disposed through a licensed commercial waste collection service. Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

Section 14 - Transport Information

IMDG/IMO

UN-No	UN2055
Proper Shipping Name	STYRENE MONOMER, STABILIZED
Hazard Class	3
Packing Group	III

ADG

UN-No	UN2055
Proper Shipping Name	STYRENE MONOMER, STABILIZED
Hazard Class	3
Packing Group	III

Component	Hazchem Code
Styrene 100-42-5 (>95)	3Y

IATA

UN-No	UN2055
Proper Shipping Name	STYRENE MONOMER, STABILIZED
Hazard Class	3
Packing Group	III

Environmental hazards	No hazards identified
------------------------------	-----------------------

Special Precautions	Inhibitors have been added to stabilize this product; Inhibitor levels should be maintained; Hazardous polymerization may occur upon depletion of inhibitor
----------------------------	---

Additional information

None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Styrene - 100-42-5	Schedule 5 listed - except its derivatives

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Styrene - 100-42-5	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

National pollutant inventory

Subject to reporting requirements

Component	National pollutant inventory
Styrene - 100-42-5	10 tonne/yr. Threshold category 1

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

Component	Australia	New South Wales	Western Australia	New Zealand
Styrene - 100-42-5				Suspected carcinogen

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Styrene	X	X	202-851-5	-	X	X	-	X	X	X	X	KE-35342

Legend: X - Listed. '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

International Regulations

Ozone Depletion Potential

This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their disposal
Not applicable.

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Styrene	100-42-5	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Styrene	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances	NZIoC - New Zealand Inventory of Chemicals
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List	ENCS - Japanese Existing and New Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances	KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances	CAS - Chemical Abstracts Service
TWA - Time Weighted Average	ACGIH - American Conference of Governmental Industrial Hygienists Predicted No Effect Concentration (PNEC)
IARC - International Agency for Research on Cancer	IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association	ADG Australian Code for the Transport of Dangerous Goods by Road and Rail
MARPOL - International Convention for the Prevention of Pollution from Ships	OECD - Organisation for Economic Co-operation and Development
NZS 5433:2012 - Transport of Dangerous Goods on Land	LC50 - Lethal Concentration 50%
LD50 - Lethal Dose 50%	ATE - Acute Toxicity Estimate
EC50 - Effective Concentration 50%	RPE - Respiratory Protective Equipment
WEL - Workplace Exposure Limit	NOEC - No Observed Effect Concentration
DNEL - Derived No Effect Level	BCF - Bioconcentration factor
POW - Partition coefficient Octanol:Water	PBT - Persistent, Bioaccumulative, Toxic
vPvB - very Persistent, very Bioaccumulative	
VOC - (Volatile Organic Compound)	

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and

hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Revision Date 21-Nov-2022

Revision Summary SDS sections updated, 9, 14.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet