

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihalan Produk: **Stainless Steel flake, type 316-L**
 Product Description: **Stainless Steel flake, type 316-L**
 Cat No. : 13787
 Molecular Formula Fe:Cr:Ni:Mo; 67.5:17:13:2.5 wt%

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
 Uses advised against No Information available

Company

Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

Supplier

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888
 CHEMTREC Malaysia **1-800-815-308** (Malay)
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Skin Sensitization	Category 1 (H317)
Carcinogenicity	Category 2 (H351)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)

Label Elements

Signal Word
Danger
Hazard Statements

H317 - May cause an allergic skin reaction

SAFETY DATA SHEET

Stainless Steel flake, type 316-L

Revision Date 31-Mar-2025

H351 - Suspected of causing cancer

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

Prevention

P201 - Obtain special instructions before use

P272 - Contaminated work clothing should not be allowed out of the workplace

P280 - Wear protective gloves

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 - Store in a well-ventilated place

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Iron	7439-89-6	67.5
Chromium	7440-47-3	17.0
Nickel	7440-02-0	13.0
Molybdenum	7439-98-7	2.5

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

SAFETY DATA SHEET

Stainless Steel flake, type 316-L

Revision Date 31-Mar-2025

May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

approved class D extinguishers. Do not use water or foam.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Nickel oxides, Molybdenum oxides, Iron oxides, Chromium oxide.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

Environmental precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

Methods and Material for Containment and Cleaning Up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

SAFETY DATA SHEET

Stainless Steel flake, type 316-L

Revision Date 31-Mar-2025

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Chromium		TWA: 0.5 mg/m ³	(Vacated) TWA: 1 mg/m ³ TWA: 1 mg/m ³
Nickel		TWA: 1.5 mg/m ³	(Vacated) TWA: 1 mg/m ³ TWA: 1 mg/m ³
Molybdenum		TWA: 10 mg/m ³ TWA: 3 mg/m ³	(Vacated) TWA: 10 mg/m ³

Component	European Union	The United Kingdom	Germany
Chromium	TWA: 2 mg/m ³ (8hr)	STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr	TWA: 2 mg/m ³ (8 Stunden). AGW - exposure factor 1
Nickel		STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr Skin	TWA: 0.03 mg/m ³ (8 Stunden). AGW - exposure factor 8 TWA: 0.006 mg/m ³ (8 Stunden). AGW - exposure factor 8
Molybdenum		STEL: 20 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr	

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles)

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Particulates filter conforming to EN 143

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system Local authorities should be advised if significant spillages cannot be contained

SAFETY DATA SHEET

Stainless Steel flake, type 316-L

Revision Date 31-Mar-2025

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Physical State

Solid

Odor

No information available

Odor Threshold

No data available

pH

No information available

Melting Point/Range

No data available

Softening Point

No data available

Boiling Point/Range

No information available

Flash Point

No information available

Method - No information available

Evaporation Rate

Not applicable

Solid

Flammability (solid,gas)

No information available

Explosion Limits

No data available

Vapor Pressure

23 hPa @ 20 °C

Vapor Density

Not applicable

Solid

Specific Gravity / Density

No data available

Bulk Density

No data available

Water Solubility

Insoluble in water

Solubility in other solvents

No information available

Partition Coefficient (n-octanol/water)

Autoignition Temperature

No data available

Decomposition Temperature

No data available

Viscosity

Not applicable

Solid

Explosive Properties

No information available

Oxidizing Properties

No information available

Molecular Formula

Fe:Cr:Ni:Mo; 67.5:17:13:2.5 wt%

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization

No information available.

SAFETY DATA SHEET

Stainless Steel flake, type 316-L

Revision Date 31-Mar-2025

Hazardous Reactions None under normal processing.

Conditions to Avoid

None known.

Incompatible Materials

Acids. Strong bases.

Hazardous Decomposition Products

Nickel oxides. Molybdenum oxides. Iron oxides. Chromium oxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

No data available

Inhalation

No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Iron	7500 mg/kg (Rat)	-	-
Nickel	LD50 > 9000 mg/kg (Rat)	-	LC50 > 10.2 mg/L (Rat) 1 h
Molybdenum	-	LD50 > 2000 mg/kg (Rat)	LC50 > 5.84 mg/L (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Nickel			Cat. 1	Group 2B

(g) reproductive toxicity; No data available

SAFETY DATA SHEET

Stainless Steel flake, type 316-L

Revision Date 31-Mar-2025

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 1

Route of exposure Inhalation
Target Organs Lungs.

(j) aspiration hazard; Not applicable
Solid

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Nickel	LC50: > 100 mg/L, 96h (Brachydanio rerio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 10.4 mg/L, 96h static (Cyprinus carpio)	EC50 = 510 µg/L 96h	EC50 = 0.1 mg/L 72h EC50 = 0.18 mg/L 72h	

Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Persistence Insoluble in water, May persist.
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
Chromium		1.03 - 1.22

Mobility in soil Spillage unlikely to penetrate soil. Is not likely mobile in the environment due its low water solubility.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET

Stainless Steel flake, type 316-L

Revision Date 31-Mar-2025

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Do not empty into drains

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

Not regulated

Road and Rail Transport

Not regulated

IATA

Not regulated

Special Precautions for User

No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Iron	231-096-4	X	X	X	X		X	X	KE-21059
Chromium	231-157-5	X	X	X	X		X	X	KE-05970
Nickel	231-111-4	X	X	X	X		X	X	KE-25818
Molybdenum	231-107-2	X	X	X	X		X	X	KE-25427

National Regulations

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

SAFETY DATA SHEET

Stainless Steel flake, type 316-L

Revision Date 31-Mar-2025

WEL - Workplace Exposure Limit
ACGIH - American Conference of Governmental Industrial Hygienists
RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%
POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
ATE - Acute Toxicity Estimate
VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Prepared By	Health, Safety and Environmental Department
Revision Date	31-Mar-2025
Revision Summary	Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet