

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihal Produk: **Methyl vinyl ketone, stabilized**
 Product Description: **Methyl vinyl ketone, stabilized**
 Cat No. : 128000000; 128000010; 128000025; 128000050
 Synonyms 3-Buten-2-one; MVK
 CAS No 78-94-4
 Molecular Formula C₄ H₆ O

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
 Uses advised against No Information available

Company

Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888
 CHEMTREC Malaysia **1-800-815-308** (Malay)
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Acute oral toxicity	Category 2 (H300)
Acute dermal toxicity	Category 1 (H310)
Acute Inhalation Toxicity - Vapors	Category 1 (H330)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Skin Sensitization	Category 1 (H317)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)
Acute aquatic toxicity	Category 1 (H400)
Chronic aquatic toxicity	Category 1 (H410)

Label Elements

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H373 - May cause damage to organs through prolonged or repeated exposure
H410 - Very toxic to aquatic life with long lasting effects
H300 + H310 + H330 - Fatal if swallowed, in contact with skin or if inhaled

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 - Ground and bond container and receiving equipment
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P262 - Do not get in eyes, on skin, or on clothing
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P284 - Wear respiratory protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P330 - Rinse mouth
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Methyl vinyl ketone	78-94-4	95
Acetic acid	64-19-7	0.4-1

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025

Acetonitrile	75-05-8	< 0.7
Hydroquinone	123-31-9	0.3-0.5
Water	7732-18-5	3

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Ingestion

Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation

If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025

Carbon monoxide (CO), Carbon dioxide (CO₂), Thermal decomposition can lead to release of irritating gases and vapors.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. To maintain product quality: Keep refrigerated. Keep at temperatures below 10°C.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Methyl vinyl ketone		Ceiling: 0.01 ppm	
Acetic acid		TWA: 10 ppm STEL: 15 ppm	(Vacated) TWA: 10 ppm (Vacated) TWA: 25 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³
Acetonitrile		TWA: 20 ppm Skin	(Vacated) TWA: 40 ppm (Vacated) TWA: 70 mg/m ³ (Vacated) TWA: 5 mg/m ³ (Vacated) STEL: 60 ppm

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025

			(Vacated) STEL: 105 mg/m ³ TWA: 40 ppm TWA: 70 mg/m ³
Hydroquinone		TWA: 1 mg/m ³	(Vacated) TWA: 2 mg/m ³ TWA: 2 mg/m ³

Component	European Union	The United Kingdom	Germany
Methyl vinyl ketone			Haut
Acetic acid	TWA: 25 mg/m ³ (8h) TWA: 10 ppm (8h) STEL: 50 mg/m ³ (15min) STEL: 20 ppm (15min)	STEL: 37 mg/m ³ STEL: 15 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK TWA: 25 mg/m ³ (8 Stunden). MAK Höhepunkt: 20 ppm Höhepunkt: 50 mg/m ³
Acetonitrile	TWA: 40 ppm (8hr) TWA: 70 mg/m ³ (8hr) Skin	STEL: 60 ppm 15 min STEL: 102 mg/m ³ 15 min TWA: 40 ppm 8 hr TWA: 68 mg/m ³ 8 hr	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 17 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK TWA: 17 mg/m ³ (8 Stunden). MAK TWA: 2 mg/m ³ (8 Stunden). MAK Höhepunkt: 20 ppm Höhepunkt: 34 mg/m ³ Höhepunkt: 2 mg/m ³ Haut
Hydroquinone		STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr	Haut

Exposure Controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025

Environmental exposure controls Prevent product from entering drains Do not allow material to contaminate ground water system Local authorities should be advised if significant spillages cannot be contained

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Light yellow
Physical State	Liquid
Odor	Irritating pungent
Odor Threshold	0.2 ppm
pH	Not applicable

Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	80 °C / 176 °F	@ 760 mmHg
Flash Point	-7 °C / 19.4 °F	Method - No information available

Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 2.1 vol% Upper 15.6 vol%	

Vapor Pressure	130 mbar @ 28 °C	
Vapor Density	2.4	(Air = 1.0)
Specific Gravity / Density	0.864 g/cm3 @20°C	
Bulk Density	Not applicable	Liquid
Water Solubility	Miscible	
Solubility in other solvents	No information available	

Partition Coefficient (n-octanol/water)

Component	log Pow
Acetic acid	-0.2
Acetonitrile	-0.34
Hydroquinone	0.59

Autoignition Temperature	370 °C / 698 °F	
Decomposition Temperature	No data available	
Viscosity	Dynamic 0.81 mPa.s (70 °C)	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

Molecular Formula	C4 H6 O
Molecular Weight	70.09
Surface tension	24 mN/m

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Yes. Hazardous polymerization may occur.

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025

Chemical Stability

Light sensitive. heat sensitive.

Possibility of Hazardous Reactions

Hazardous Polymerization Polymerization can occur.
Hazardous Reactions None under normal processing.

Conditions to Avoid

Excess heat. Exposure to light. Keep away from open flames, hot surfaces and sources of ignition. Incompatible products.

Incompatible Materials

Oxidizing agent. Reducing Agent. oxygen. Bases. Amines. Ammonia.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;
Oral Category 2
Dermal Category 1
Inhalation Category 1

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl vinyl ketone	LD50 = 23.1 mg/kg (Rat)	LD50 = 35 mg/kg (Rat)	LC50 = 7 mg/m ³ (Rat) 4 h
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
Acetonitrile	450-787 mg/kg (Rat) 2460 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	LC50 = 3587 ppm (6.022 mg/l) (Mouse) 4h LC50 = 16,000 ppm (26.8 mg/l) (Rat) 4h
Hydroquinone	LD50 = 298 mg/kg (Rat)	LD50 = 74800 mg/kg (Rabbit)	-
Water	-	-	-

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Acetonitrile	ATE = 617 mg/kg	-	-

ECHA (RAC) - Committee for Risk Assessment - European CHemicals Agency
ATE - Acute Toxicity Estimate; mg/kg bw - milligrams per kilogram of body weight

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025

(d) respiratory or skin sensitization;

Respiratory
Skin

Based on available data, the classification criteria are not met
Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

(f) carcinogenicity;

Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Hydroquinone			Cat. 2	

(g) reproductive toxicity;

Based on available data, the classification criteria are not met

(h) STOT-single exposure;

Based on available data, the classification criteria are not met

(i) STOT-repeated exposure;

Category 2

Target Organs

Kidney, Central nervous system (CNS), Lungs.

(j) aspiration hazard;

Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Acetic acid	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	EC50 = 95 mg/L/24h	-	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min
Acetonitrile	LC50: = 1850 mg/L, 96h static (Lepomis macrochirus) LC50: = 1000 mg/L, 96h static (Pimephales promelas)			EC50 = 28000 mg/L 48 h EC50 = 73 mg/L 24 h EC50 = 7500 mg/L 15 h

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025

	LC50: 1600 - 1690 mg/L, 96h flow-through (Pimephales promelas) LC50: = 1650 mg/L, 96h static (Poecilia reticulata)			
Hydroquinone	LC50: 0.1 - 0.18 mg/L, 96h static (Pimephales promelas) LC50: = 0.17 mg/L, 96h (Brachydanio rerio) LC50: = 0.044 mg/L, 96h flow-through (Pimephales promelas) LC50: = 0.044 mg/L, 96h flow-through (Oncorhynchus mykiss)	EC50: = 0.29 mg/L, 48h (Daphnia magna)	EC50: = 0.335 mg/L, 72h (Pseudokirchneriella subcapitata)	EC50 = 0.038 mg/L 15 min EC50 = 0.0382 mg/L 30 min EC50 = 0.042 mg/L 5 min EC50 = 23.75 mg/L 60 min

Persistence and degradability

Persistence

Degradation in sewage treatment plant

Not readily biodegradable

Persistence is unlikely, based on information available.

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Acetic acid	-0.2	No data available
Acetonitrile	-0.34	No data available
Hydroquinone	0.59	40 dimensionless

Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

Surface tension

24 mN/m

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not empty into drains Large amounts will affect pH and harm aquatic organisms Do not let this chemical enter the environment

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1251
Hazard Class 6.1
Subsidiary Hazard Class 3, 8
Packing Group I
Proper Shipping Name METHYL VINYL KETONE, STABILIZED

Road and Rail Transport

UN-No UN1251
Hazard Class 6.1
Subsidiary Hazard Class 3, 8
Packing Group I
Proper Shipping Name METHYL VINYL KETONE, STABILIZED

IATA

FORBIDDEN FOR IATA TRANSPORT
UN-No UN1251
Hazard Class 6.1
Subsidiary Hazard Class 3, 8
Packing Group I
Proper Shipping Name METHYL VINYL KETONE, STABILIZED FORBIDDEN FOR IATA TRANSPORT

Special Precautions for User

Storage conditions in Section 7 should also be met during transportation Cooled transportation <10°C is recommended to ensure shelf-life Inhibitors have been added to stabilize this product Inhibitor levels should be maintained Hazardous polymerization may occur upon depletion of inhibitor

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China X = listed Australia U.S.A. (TSCA) Canada (DSL/NDL) Europe (EINECS/ELINCS/NLP) Australia (AICS) Korea (KECL) China (IECSC) Japan (ENCS) Philippines (PICCS) Taiwan (TCSI) Japan (ISHL) New Zealand (NZIoC) Japan (ISHL)

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Methyl vinyl ketone	201-160-6	X	-	X	X	X	X	X	KE-04112
Acetic acid	200-580-7	X	X	X	X	X	X	X	X
Acetonitrile	200-835-2	X	X	X	X	X	X	X	KE-00067
Hydroquinone	204-617-8	X	X	X	X	X	X	X	KE-35112
Water	231-791-2	X	X	X	X		X	X	KE-35400

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Acetic acid				Annex I - Y34
Hydroquinone				Annex I - Y39

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SAFETY DATA SHEET

Methyl vinyl ketone, stabilized

Revision Date 21-Mar-2025

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date

21-Mar-2025

Revision Summary

SDS sections updated, 2, 11.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet