

Creation Date 21-May-2012

Revision Date 28-Mar-2024

Revision Number 15

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized
Cat No. : 257750000; 257750250; 257751000; 257755000
Synonyms Peracetic acid
Molecular Formula C2 H4 O3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
 Thermo Fisher Scientific
 Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

UK entity/business name
 Fisher Scientific UK
 Bishop Meadow Road,
 Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
 Neuhofstrasse 11, CH 4153 Reinach
 Tel: +41 (0) 56 618 41 11
 e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
 Tox Info Suisse Emergency Number: **145 (24hr)**
 Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
 Chemtrec (24h) Toll-Free: 0800 564 402
 Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Organic peroxides

Type D (H242)

Health hazards

Acute oral toxicity

Category 4 (H302)

Acute dermal toxicity

Category 4 (H312)

Acute Inhalation Toxicity - Vapors

Category 4 (H332)

Skin Corrosion/Irritation

Category 1 (H314) A

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Specific target organ toxicity - (single exposure)

Category 3 (H335)

Environmental hazards

Acute aquatic toxicity

Category 1 (H400)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H242 - Heating may cause a fire

H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

H400 - Very toxic to aquatic life

Combustible liquid

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Acetic acid	64-19-7	200-580-7	46-55	Flam. Liq. 3 (H226) Skin Corr. 1A (H314) Eye Dam. 1 (H318)
Ethaneperoxoic acid	79-21-0	EEC No. 201-186-8	34-39	Flam. Liq. 3 (H226) Org. Perox. D (H242) Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Corr. 1A (H314) Eye Dam. 1 (H318) STOT SE 3 (H335) Aquatic Acute 1 (H400)
Hydrogen peroxide	7722-84-1	231-765-0	11-15	Ox. Liq. 1 (H271) Acute Tox. 4 (H302) Acute Tox. 4 (H332) Skin Corr. 1A (H314) Eye Dam. 1 (H318) STOT SE 3 (H335) Aquatic Chronic 3 (H412)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Acetic acid	Skin Corr. 1A (H314) :: C>=90% Skin Corr. 1B (H314) :: 25%<=C<90% Eye Irrit. 2 (H319) :: 10%<=C<25% Skin Irrit. 2 (H315) :: 10%<=C<25%	-	-
Ethaneperoxoic acid	STOT SE 3 (H335) :: C>=1%	1 (acute) 10 (Chronic)	-
Hydrogen peroxide	Ox. Liq. 1 :: C>=70% Ox. Liq. 2 :: 20%<=C<70% Ox. Liq. 3 :: 8%<=C<20% Skin Corr. 1A :: C>=70% Skin Corr. 1B :: 50%<=C<70% Eye Dam. 1 :: >=8%C<50% Eye Irrit. 2 :: 5%<=C<8% Skin Irrit. 2 :: 35%<=C<50% STOT SE 3 :: C>=35% Aquatic Chronic 3 :: C>=63%	-	-

Components	Reach Registration Number
Acetic acid	01-2119475328-30
Hydrogen peroxide	01-2119485845-22
Peroxyacetic acid	01-2119531330-56

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

	required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Sulfur oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep refrigerated. Corrosives area. Organic peroxides. Keep away from heat, sparks and flame. Do not store near combustible materials. Keep container tightly closed.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 5.2

Switzerland - Storage of hazardous substances

Storage class - SC 5
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
-----------	----------------	--------------------	--------	---------	-------

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

Acetic acid	TWA: 25 mg/m ³ (8h) TWA: 10 ppm (8h) STEL: 50 mg/m ³ (15min) STEL: 20 ppm (15min)	STEL: 37 mg/m ³ STEL: 15 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA / VME: 10 ppm (8 heures). TWA / VME: 25 mg/m ³ (8 heures). STEL / VLCT: 20 ppm. indicative limit STEL / VLCT: 50 mg/m ³ . indicative limit	TWA: 10 ppm 8 uren TWA: 25 mg/m ³ 8 uren STEL: 15 ppm 15 minuten STEL: 38 mg/m ³ 15 minuten	STEL / VLA-EC: 20 ppm (15 minutos). STEL / VLA-EC: 50 mg/m ³ (15 minutos). TWA / VLA-ED: 10 ppm (8 horas) TWA / VLA-ED: 25 mg/m ³ (8 horas)
Ethaneperoxoic acid				STEL: 0.4 ppm 15 minuten STEL: 1.24 mg/m ³ 15 minuten	
Hydrogen peroxide		STEL: 2 ppm 15 min STEL: 2.8 mg/m ³ 15 min TWA: 1 ppm 8 hr TWA: 1.4 mg/m ³ 8 hr	TWA / VME: 1 ppm (8 heures). TWA / VME: 1.5 mg/m ³ (8 heures).	TWA: 1 ppm 8 uren TWA: 1.4 mg/m ³ 8 uren	TWA / VLA-ED: 1 ppm (8 horas) TWA / VLA-ED: 1.4 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Acetic acid	TWA: 25 ppm 8 ore. Time Weighted Average TWA: 10 mg/m ³ 8 ore. Time Weighted Average STEL: 50 mg/m ³ 15 minuti. Short-term STEL: 20 ppm 15 minuti. Short-term	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK TWA: 25 mg/m ³ (8 Stunden). MAK Höhepunkt: 20 ppm Höhepunkt: 50 mg/m ³	STEL: 20 ppm 15 minutos STEL: 50 mg/m ³ 15 minutos TWA: 10 ppm 8 horas TWA: 25 mg/m ³ 8 horas	MAC-TGG 25 mg/m ³	TWA: 5 ppm 8 tunteina TWA: 13 mg/m ³ 8 tunteina STEL: 10 ppm 15 minuutteina STEL: 25 mg/m ³ 15 minuutteina
Ethaneperoxoic acid		TWA: 0.1 ppm (8 Stunden). MAK TWA: 0.32 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.1 ppm Höhepunkt: 0.32 mg/m ³	STEL: 0.4 ppm 15 minutos		TWA: 0.2 ppm 8 tunteina TWA: 0.6 mg/m ³ 8 tunteina STEL: 0.5 ppm 15 minuutteina STEL: 1.5 mg/m ³ 15 minuutteina
Hydrogen peroxide		TWA: 0.5 ppm (8 Stunden). AGW - TWA: 0.71 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 0.5 ppm (8 Stunden). MAK TWA: 0.71 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.5 ppm Höhepunkt: 0.71 mg/m ³	TWA: 1 ppm 8 horas		TWA: 1 ppm 8 tunteina TWA: 1.4 mg/m ³ 8 tunteina STEL: 3 ppm 15 minuutteina STEL: 4.2 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Acetic acid	MAK-KZGW: 20 ppm 15 Minuten MAK-KZGW: 50 mg/m ³ 15 Minuten MAK-TMW: 10 ppm 8 Stunden MAK-TMW: 25 mg/m ³ 8 Stunden	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer STEL: 50 mg/m ³ 15 minutter STEL: 20 ppm 15 minutter	STEL: 20 ppm 15 Minuten STEL: 50 mg/m ³ 15 Minuten TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden	STEL: 50 mg/m ³ 15 minutach TWA: 25 mg/m ³ 8 godzinach	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer STEL: 20 ppm 15 minutter. value from the regulation STEL: 50 mg/m ³ 15 minutter. value from the regulation
Ethaneperoxoic acid				STEL: 1.6 mg/m ³ 15 minutach TWA: 0.8 mg/m ³ 8 godzinach	
Hydrogen peroxide	MAK-KZGW: 2 ppm 15 Minuten MAK-KZGW: 2.8 mg/m ³ 15 Minuten MAK-TMW: 1 ppm 8 Stunden	TWA: 1 ppm 8 timer TWA: 1.4 mg/m ³ 8 timer STEL: 2 ppm 15 minutter STEL: 2.8 mg/m ³ 15 minutter	STEL: 2 ppm 15 Minuten STEL: 2.8 mg/m ³ 15 Minuten TWA: 1 ppm 8 Stunden TWA: 1.4 mg/m ³ 8	STEL: 0.8 mg/m ³ 15 minutach TWA: 0.4 mg/m ³ 8 godzinach	TWA: 1 ppm 8 timer TWA: 1.4 mg/m ³ 8 timer STEL: 3 ppm 15 minutter. value calculated STEL: 2.8 mg/m ³ 15

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

	MAK-TMW: 1.4 mg/m ³ 8 Stunden		Stunden		minutter. value calculated
--	--	--	---------	--	----------------------------

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Acetic acid	TWA: 25 mg/m ³ TWA: 10 ppm STEL : 50 mg/m ³ STEL : 20 ppm	TWA-GVI: 10 ppm 8 satima. TWA-GVI: 25 mg/m ³ 8 satima. STEL-KGVI: 20 ppm 15 minutama. STEL-KGVI: 50 mg/m ³ 15 minutama.	TWA: 20 ppm 8 hr. TWA: 50 mg/m ³ 8 hr. STEL: 20 ppm 15 min STEL: 50 mg/m ³ 15 min	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 25 mg/m ³ 8 hodinách. Ceiling: 50 mg/m ³
Ethaneperoxoic acid			STEL: 0.4 mg/m ³ 15 min		TWA: 0.6 mg/m ³ 8 hodinách. Ceiling: 1.2 mg/m ³
Hydrogen peroxide	TWA: 1.5 mg/m ³	TWA-GVI: 1 ppm 8 satima. TWA-GVI: 1.4 mg/m ³ 8 satima. STEL-KGVI: 2 ppm 15 minutama. STEL-KGVI: 2.8 mg/m ³ 15 minutama.	TWA: 1 ppm 8 hr. TWA: 1.5 mg/m ³ 8 hr. STEL: 3 mg/m ³ 15 min STEL: 2 ppm 15 min		TWA: 1 mg/m ³ 8 hodinách. Ceiling: 2 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Acetic acid	TWA: 10 ppm 8 tundides. TWA: 25 mg/m ³ 8 tundides. STEL: 10 ppm 15 minutites. STEL: 25 mg/m ³ 15 minutites.	TWA: 25 mg/m ³ 8 hr TWA: 10 ppm 8 hr STEL: 50 mg/m ³ 15 min STEL: 20 ppm 15 min	STEL: 15 ppm STEL: 37 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	STEL: 50 mg/m ³ 15 percekben. CK TWA: 25 mg/m ³ 8 órában. AK	STEL: 20 ppm STEL: 50 mg/m ³ TWA: 10 ppm 8 klukkustundum. TWA: 25 mg/m ³ 8 klukkustundum.
Hydrogen peroxide	TWA: 1 ppm 8 tundides. TWA: 1.4 mg/m ³ 8 tundides. STEL: 2 ppm 15 minutites. STEL: 3 mg/m ³ 15 minutites.		STEL: 3 mg/m ³ TWA: 1 ppm TWA: 1.4 mg/m ³		TWA: 1 ppm 8 klukkustundum. TWA: 1.4 mg/m ³ 8 klukkustundum. Ceiling: 2 ppm Ceiling: 2.8 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Acetic acid	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm IPRD TWA: 25 mg/m ³ IPRD STEL: 50 mg/m ³ STEL: 20 ppm	TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden STEL: 50 mg/m ³ 15 Minuten STEL: 20 ppm 15 Minuten	TWA: 10 ppm TWA: 25 mg/m ³ STEL: 20 ppm 15 minuti STEL: 50 mg/m ³ 15 minuti	TWA: 10 ppm 8 ore TWA: 25 mg/m ³ 8 ore STEL: 20 ppm 15 minute STEL: 50 mg/m ³ 15 minute
Hydrogen peroxide		Ceiling: 2 ppm Ceiling: 3 mg/m ³ TWA: 1 ppm IPRD TWA: 1.4 mg/m ³ IPRD			

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Acetic acid	Skin notation MAC: 5 mg/m ³	Ceiling: 50 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm 8 urah TWA: 25 mg/m ³ 8 urah STEL: 50 mg/m ³ 15 minutah STEL: 20 ppm 15 minutah	Binding STEL: 10 ppm 15 minuter Binding STEL: 25 mg/m ³ 15 minuter TLV: 5 ppm 8 timmar. NGV TLV: 13 mg/m ³ 8 timmar. NGV	TWA: 10 ppm 8 saat TWA: 25 mg/m ³ 8 saat
Hydrogen peroxide		Ceiling: 2.8 mg/m ³ TWA: 1 ppm TWA: 1.4 mg/m ³		Binding STEL: 2 ppm 15 minuter Binding STEL: 3 mg/m ³ 15 minuter	

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

				TLV: 1 ppm 8 timmar. NGV TLV: 1.4 mg/m ³ 8 timmar. NGV	
--	--	--	--	--	--

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Acetic acid 64-19-7 (46-55)	DNEL = 25mg/m ³		DNEL = 25mg/m ³	
Ethaneperoxoic acid 79-21-0 (34-39)	DNEL = 0.56mg/m ³	DNEL = 0.56mg/m ³	DNEL = 0.56mg/m ³	DNEL = 0.56mg/m ³
Hydrogen peroxide 7722-84-1 (11-15)	DNEL = 3mg/m ³		DNEL = 1.4mg/m ³	

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Acetic acid 64-19-7 (46-55)	PNEC = 3.058mg/L	PNEC = 11.36mg/kg sediment dw	PNEC = 30.58mg/L	PNEC = 85mg/L	PNEC = 0.47mg/kg soil dw
Hydrogen peroxide 7722-84-1 (11-15)	PNEC = 0.0126mg/L	PNEC = 0.047mg/kg sediment dw	PNEC = 0.0138mg/L	PNEC = 4.66mg/L	PNEC = 0.0023mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Acetic acid 64-19-7 (46-55)	PNEC = 0.3058mg/L	PNEC = 1.136mg/kg sediment dw			
Hydrogen peroxide 7722-84-1 (11-15)	PNEC = 0.0126mg/L	PNEC = 0.047mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Particulates filter conforming to EN 143 Acid gases filter Type E Yellow conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Clear Colorless	
Odor	Strong pungent	
Odor Threshold	No data available	
Melting Point/Range	-44 °C / -47.2 °F	
Softening Point	No data available	
Boiling Point/Range	105 °C / 221 °F	@ 760 mmHg
Flammability (liquid)	Combustible liquid	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	62 °C / 143.6 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	-1.2	
Viscosity	No data available	
Water Solubility	Soluble	
Solubility in other solvents	No information available	

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

Partition Coefficient (n-octanol/water)

Component	log Pow	
Acetic acid	-0.2	
Ethaneperoxoic acid	-0.46	
Hydrogen peroxide	-1.1	
Vapor Pressure	20 hPa @ 20 °C	
Density / Specific Gravity	1.130	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C2 H4 O3
Molecular Weight	76.05
Explosive Properties	explosive air/vapour mixtures possible
Oxidizing Properties	Oxidizer

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Yes

10.2. Chemical stability

Stable under normal conditions. Oxidizer: Contact with combustible/organic material may cause fire.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition. Incompatible products. Combustible material. Excess heat.

10.5. Incompatible materials

Strong oxidizing agents. Finely powdered metals. Organic materials. Metals. Reducing Agent. Strong reducing agents. Combustible material.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Sulfur oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	No data available
Dermal	No data available
Inhalation	No data available

Toxicology data for the components

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
Ethaneperoxyoic acid	1540 µL/kg (Rat)	1410 µL/kg (Rabbit)	LC50 = 213 mg/m ³ (Rat) 4 h LC50 = 186 mg/m ³ (Rat) 4 h
Hydrogen peroxide	376 mg/kg (Rat) (90%) 910 mg/kg (Rat) (20-60%) 1518 mg/kg (Rat) (8-20% sol)	>2000 mg/kg (Rabbit)	LC50 = 2000 mg/m ³ (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available

Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms.

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

Component	Freshwater Fish	Water Flea	Freshwater Algae
Acetic acid	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	EC50 = 95 mg/L/24h	-
Ethaneperoxyoic acid	LC50: = 1.1 mg/L, 96h semi-static (Lepomis macrochirus)		
Hydrogen peroxide	LC50: 16.4 mg/L/96h (P.promelas)	EC50 7.7 mg/L/24h	EC50 2.5 mg/L/72h

Component	Microtox	M-Factor
Acetic acid	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	
Ethaneperoxyoic acid		1 (acute) 10 (Chronic)

12.2. Persistence and degradability

Persistence

Degradation in sewage treatment plant

Readily biodegradable

Soluble in water, Persistence is unlikely, based on information available.

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Acetic acid	-0.2	No data available
Ethaneperoxyoic acid	-0.46	No data available
Hydrogen peroxide	-1.1	No data available

12.4. Mobility in soil

The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant

Ozone Depletion Potential

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN3105
14.2. UN proper shipping name	ORGANIC PEROXIDE TYPE D, LIQUID (PEROXYACETIC ACID, TYPE D, STABILIZED)
14.3. Transport hazard class(es)	5.2
Subsidiary Hazard Class	8
14.4. Packing group	

ADR

14.1. UN number	UN3105
14.2. UN proper shipping name	ORGANIC PEROXIDE TYPE D, LIQUID (PEROXYACETIC ACID, TYPE D, stabilized)
14.3. Transport hazard class(es)	5.2
Subsidiary Hazard Class	8
14.4. Packing group	

IATA

FORBIDDEN FOR IATA TRANSPORT

14.1. UN number	UN3105
14.2. UN proper shipping name	ORGANIC PEROXIDE TYPE D, LIQUID (PEROXYACETIC ACID, TYPE D, STABILIZED)
14.3. Transport hazard class(es)	FORBIDDEN FOR IATA TRANSPORT
Subsidiary Hazard Class	5.2
14.4. Packing group	8

14.5. Environmental hazards	Dangerous for the environment Product is a marine pollutant according to the criteria set by IMDG/IMO
------------------------------------	--

14.6. Special precautions for user	No special precautions required.
---	----------------------------------

14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods
--	--------------------------------

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

ACR25775

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Acetic acid	64-19-7	200-580-7	-	-	X	X	X	X	X
Ethaneperoxyoic acid	79-21-0	201-186-8	-	-	X	X	2005-3-31 98	X	X
Hydrogen peroxide	7722-84-1	231-765-0	-	-	X	X	KE-20204	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Acetic acid	64-19-7	X	ACTIVE	X	-	X	X	X
Ethaneperoxyoic acid	79-21-0	X	ACTIVE	X	-	X	X	X
Hydrogen peroxide	7722-84-1	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Acetic acid	64-19-7	-	Use restricted. See item 75. (see link for restriction details)	-
Ethaneperoxyoic acid	79-21-0	-	Use restricted. See item 75. (see link for restriction details)	-
Hydrogen peroxide	7722-84-1	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Acetic acid	64-19-7	Not applicable	Not applicable
Ethaneperoxyoic acid	79-21-0	Not applicable	Not applicable
Hydrogen peroxide	7722-84-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Acetic acid	WGK1	Class II : 0.10 g/m ³ (Massenkonzentration)
Ethaneperoxyoic acid	WGK2	
Hydrogen peroxide	WGK1	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Acetic acid 64-19-7 (46-55)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H242 - Heating may cause a fire
H302 - Harmful if swallowed
H312 - Harmful in contact with skin
H332 - Harmful if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H400 - Very toxic to aquatic life

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

SAFETY DATA SHEET

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical incident response training.

Creation Date 21-May-2012

Revision Date 28-Mar-2024

Revision Summary SDS sections updated.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet