

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name tert-Butyldimethylsilyl chloride, 50 wt.% solution in toluene

Product Code	433110000; 433111000
Address	ThermoFisher Scientific Australia Pty Ltd 5 Caribbean Drive, Scoresby VICTORIA 3179, Australia
Emergency Tel.	CHEMTREC® 03 9757 4559 or +613 9757 4559
Telephone / Fax Numbers	Tel: 1300 735 292 Fax: 1800 067 639
E-mail address	ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling and storing these substances. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids Category 2

Health hazards

Aspiration Toxicity	Category 1
Skin Corrosion/Irritation	Category 1 A
Serious Eye Damage/Eye Irritation	Category 1
Reproductive Toxicity	Category 2
Specific target organ toxicity - (single exposure)	Category 3
Specific target organ toxicity - (repeated exposure)	Category 2

Environmental hazards

Chronic aquatic toxicity Category 2

Label Elements



Flame



Exclamation Mark



Health Hazard



Corrosion



Environment

Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P331 - Do NOT induce vomiting
P310 - Immediately call a POISON CENTER or doctor
P330 - Rinse mouth
P363 - Wash contaminated clothing before reuse
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Toluene	108-88-3	50
Silane, chloro(1,1-dimethylethyl)dimethyl-	18162-48-6	50

Section 4 - First Aid Measures

Inhalation

If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by

	aspiration).
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Water.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Silicon dioxide, Hydrogen chloride gas.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6 - Accidental Release Measures

Emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Handle under an inert atmosphere.

Conditions for Safe Storage, Including any Incompatibilities

Flammables area. Corrosives area. Keep away from heat, sparks and flame. Keep away from water or moist air. Store under an inert atmosphere. Keep containers tightly closed in a dry, cool and well-ventilated place.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Toluene	STEL: 150 ppm STEL: 574 mg/m ³ TWA: 50 ppm TWA: 191 mg/m ³	TWA: 20 ppm TWA: 75 mg/m ³ STEL: 100 ppm STEL: 377 mg/m ³ Skin	TWA: 20 ppm	STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m ³ 8 hr Skin	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 190 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 50 ppm (8 Stunden). MAK TWA: 190 mg/m ³ (8 Stunden). MAK Höhepunkt: 100 ppm Höhepunkt: 380 mg/m ³ Haut

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand	European Union	United Kingdom	Germany
Toluene		0.03 mg/L (urine) end of exposure or end of shift			Toluene: 600 µg/L whole blood

		(Toluene) 0.3 mg/g creatinine (urine) end of exposure or end of shift (O-Cresol)			(immediately after exposure) Toluene: 75 µg/L urine (end of shift) o-Cresol (after hydrolysis): 1.5 mg/L urine (for long-term exposures: at the end of the shift after several shifts) o-Cresol (after hydrolysis): 1.5 mg/L urine (end of shift)
--	--	--	--	--	---

Exposure Controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber	See manufacturers	-	AS/NZS 2161	(minimum requirement)
Viton (R)	recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Long sleeved clothing

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance

Physical State

Liquid

Odor	No information available	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	110 - 126 °C / 230 - 258.8 °F	
Flash Point	4 °C / 39.2 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	0.866	
Bulk Density	Not applicable	Liquid
Water Solubility	Reacts with water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Toluene	2.73	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

Other information

Section 10 - Stability and Reactivity

Reactivity	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products, Heat, flames and sparks, Exposure to moist air or water, Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Water, Strong acids, Strong bases, Amines, Aldehydes, Ketones.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂). Silicon dioxide. Hydrogen chloride gas.
Hazardous Polymerization	Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

Silane, chloro(1,1-dimethylethyl)dimethyl-	>2000 mg/kg (Rat)		
(b) skin corrosion/irritation;	Category 1 A		
(c) serious eye damage/irritation;	Category 1		
(d) respiratory or skin sensitization;			
Respiratory	No data available		
Skin	No data available		
(e) germ cell mutagenicity;	No data available		
(f) carcinogenicity;	No data available		
	There are no known carcinogenic chemicals in this product		
(g) reproductive toxicity;	Category 2		
Reproductive Effects	Experiments have shown reproductive toxicity effects on laboratory animals		
Developmental Effects	Possible risk of harm to the unborn child		
Teratogenicity	Teratogenic effects have occurred in experimental animals.		
(h) STOT-single exposure;	Category 3		
Results / Target organs	Central nervous system (CNS)		
(i) STOT-repeated exposure;	Category 2		
Target Organs	Skin, Respiratory system, Eyes, Gastrointestinal tract (GI), Liver, Kidney, Neuropsychological effects, Ears.		
(j) aspiration hazard;	Category 1		
Symptoms / effects, both acute and delayed	Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting		

Section 12 - Ecological Information

Ecotoxicity effects	The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.			
Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	EC50 = 19.7 mg/L 30 min
Persistence and Degradability	No information available			
Persistence	Persistence is unlikely, based on information available.			
Component	Degradability			
Toluene 108-88-3 (50)	86% (20d)			
Degradation in sewage treatment plant	Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. Water reactive.			
Bioaccumulative Potential	Product does not bioaccumulate due to reaction with water			

Component	log Pow	Bioconcentration factor (BCF)
Toluene	2.73	90
Mobility	No information available. Is not likely mobile in the environment	
Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors	
Persistent Organic Pollutant	This product does not contain any known or suspected substance	
Ozone Depletion Potential	This product does not contain any known or suspected substance	

Section 13 - Disposal Considerations

Waste from Residues/Unused Products	Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
Other Information	Chemical wastes should be disposed through a licensed commercial waste collection service. Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

Section 14 - Transport Information

IMDG/IMO

UN-No	UN2920
Proper Shipping Name	CORROSIVE LIQUID, FLAMMABLE, N.O.S.
Technical Shipping Name	tert-Butyldimethylsilyl chloride, toluene
Hazard Class	8
Subsidiary Hazard Class	3
Packing Group	I

ADG

UN-No	UN2920
Proper Shipping Name	CORROSIVE LIQUID, FLAMMABLE, N.O.S.
Technical Shipping Name	tert-Butyldimethylsilyl chloride, toluene
Hazard Class	8
Subsidiary Hazard Class	3
Packing Group	I

Component	Hazchem Code
Toluene 108-88-3 (50)	3YE

IATA

UN-No	UN2920
Proper Shipping Name	CORROSIVE LIQUID, FLAMMABLE, N.O.S.
Technical Shipping Name	tert-Butyldimethylsilyl chloride, toluene
Hazard Class	8
Subsidiary Hazard Class	3
Packing Group	I

Environmental hazards	Dangerous for the environment Product is a marine pollutant according to the criteria set by IMDG/IMO
------------------------------	--

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations **Australia**

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Toluene - 108-88-3	Schedule 5 listed - including Kerosene, Diesel [distillate], Mineral turpentine, White petroleum spirit, Toluene, Xylene and light mineral and paraffin oils but except their derivative;except a) Toluene and Xylene when included in Schedule 6, or b) Benzene and liquid aromatic hydrocarbons when included in Schedule 7, or c) food grade and pharmaceutical grade White mineral oil, or d) in solid or semi-solid preparations, or e) in preparations containing <=25% of designated solvents, or f) in preparations packed in pressurized spray packs, or g) in adhesives packed in containers each containing <=50 grams of adhesive, or h) in writing correction fluids and thinners for writing correction fluids packed in containers having a capacity of <=20 mL, or i) in other preparations when packed in containers with a capacity of <=2 mL Schedule 6 listed - except its derivatives;except in preparations containing <=50% of Toluene or Toluene and Xylene

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Toluene - 108-88-3	Present	-
Silane, chloro(1,1-dimethylethyl)dimethyl- - 18162-48-6	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling and storing these substances.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

Component	Australian - Illicit Drug Precursors/Reagents Substance List	Chemicals of Security Concern
Toluene - 108-88-3	Category 3	

Legend

Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted

National pollutant inventory Subject to reporting requirements

Component	National pollutant inventory
Toluene - 108-88-3	10 tonne/yr. Threshold category 1

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licensing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Toluene	X	X	203-625-9	-	X	X	-	X	X	X	X	KE-33936
Silane, chloro(1,1-dimethylethyl)dimethyl-	X	X	242-042-4	-	X	-	X	X	X	X	X	97-3-163

Legend: X - Listed. '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their disposal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories of Wastes to Be Controlled
Toluene - 108-88-3	Annex I - Y42	Y42 except Halogenated solvents

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Toluene	108-88-3	Listed	Not applicable	Not applicable	Not applicable
Silane, chloro(1,1-dimethylethyl)dimethyl-	18162-48-6	Not applicable	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	-	Use restricted. See entry 48. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances	NZIoC - New Zealand Inventory of Chemicals
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List	ENCS - Japanese Existing and New Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances	KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances	CAS - Chemical Abstracts Service
TWA - Time Weighted Average	ACGIH - American Conference of Governmental Industrial Hygienists
IARC - International Agency for Research on Cancer	Predicted No Effect Concentration (PNEC)
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association	IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
MARPOL - International Convention for the Prevention of Pollution from Ships	
NZS 5433:2020 - Transport of Dangerous Goods on Land	OECD - Organisation for Economic Co-operation and Development
LD50 - Lethal Dose 50%	LC50 - Lethal Concentration 50%
EC50 - Effective Concentration 50%	ATE - Acute Toxicity Estimate
WEL - Workplace Exposure Limit	RPE - Respiratory Protective Equipment
DNEL - Derived No Effect Level	NOEC - No Observed Effect Concentration
POW - Partition coefficient Octanol:Water	BCF - Bioconcentration factor
vPvB - very Persistent, very Bioaccumulative	PBT - Persistent, Bioaccumulative, Toxic
VOC - (Volatile Organic Compound)	

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Revision Date	17-Nov-2022
Revision Summary	Update to GHS format.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet