

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihalan Produk: **ETHYL ACETATE/ PENTANE SOLUTION**
 Product Description: **ETHYL ACETATE/ PENTANE SOLUTION**
 Cat No. : **XXETHCYC4LI**

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
 Uses advised against No Information available

Company

Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888
 CHEMTREC Malaysia **1-800-815-308** (Malay)
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Aspiration Toxicity	Category 1 (H304)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Chronic aquatic toxicity	Category 3 (H412)

Label Elements

Signal Word
Danger
Hazard Statements

H225 - Highly flammable liquid and vapor
 H304 - May be fatal if swallowed and enters airways

SAFETY DATA SHEET

ETHYL ACETATE/ PENTANE SOLUTION

Revision Date 24-Mar-2025

H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 - Ground and bond container and receiving equipment
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor if you feel unwell
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

EUH066 - Repeated exposure may cause skin dryness or cracking

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Ethyl acetate	141-78-6	50 - 90
Cyclopentane	287-92-3	10 - 50

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

SAFETY DATA SHEET

ETHYL ACETATE/ PENTANE SOLUTION

Revision Date 24-Mar-2025

Inhalation Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Thermal decomposition can lead to release of irritating gases and vapors.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage. Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SAFETY DATA SHEET

ETHYL ACETATE/ PENTANE SOLUTION

Revision Date 24-Mar-2025

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Ethyl acetate		TWA: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 1400 mg/m ³ TWA: 400 ppm TWA: 1400 mg/m ³
Cyclopentane		TWA: 1000 ppm	(Vacated) TWA: 600 ppm (Vacated) TWA: 1720 mg/m ³

Component	European Union	The United Kingdom	Germany
Ethyl acetate	TWA: 734 mg/m ³ (8h) TWA: 200 ppm (8h) STEL: 1468 mg/m ³ (15min) STEL: 400 ppm (15min)	STEL: 1468 mg/m ³ 15 min STEL: 400 ppm 15 min TWA: 734 mg/m ³ 8 hr TWA: 200 ppm 8 hr	TWA: 200 ppm (8 Stunden). AGW - exposure factor 2 TWA: 730 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 200 ppm (8 Stunden). MAK TWA: 750 mg/m ³ (8 Stunden). MAK Höhepunkt: 400 ppm Höhepunkt: 1500 mg/m ³

Exposure Controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

SAFETY DATA SHEET

ETHYL ACETATE/ PENTANE SOLUTION

Revision Date 24-Mar-2025

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls Prevent product from entering drains

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Colorless	
Physical State	Liquid	
Odor	Petroleum distillates	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flash Point	No information available	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits		
Vapor Pressure	No information available	
Vapor Density	No information available	(Air = 1.0)
Specific Gravity / Density	No data available	
Bulk Density	Not applicable	Liquid
Water Solubility	Insoluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethyl acetate	0.73	
Cyclopentane	3	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No information available	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

SAFETY DATA SHEET

ETHYL ACETATE/ PENTANE SOLUTION

Revision Date 24-Mar-2025

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

Conditions to Avoid

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Strong oxidizing agents. Strong acids. Strong bases. Amines. Peroxides.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl acetate	10,200 mg/kg (Rat)	> 20 mL/kg (Rabbit) > 18000 mg/kg (Rabbit)	58 mg/l (rat; 8 h)
Cyclopentane	LD50 = 11400 mg/kg (Rat)	-	LC50 = 106 mg/L, vapour (Rat)

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

SAFETY DATA SHEET

ETHYL ACETATE/ PENTANE SOLUTION

Revision Date 24-Mar-2025

**Respiratory
Skin**

Based on available data, the classification criteria are not met
Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Ethyl acetate 141-78-6 (50 - 90)	OECD Test Guideline 406	guinea pig	- non-sensitising

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Ethyl acetate 141-78-6 (50 - 90)	OECD Test Guideline 471 AMES test	in vitro Bacteria	negative
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative
	OECD Test Guideline 476 Gene cell mutation	in vitro Mammalian	negative
	OECD Test Guideline 474 Mouse micronucleus assay	in vivo Mammalian	negative

(f) carcinogenicity;

Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Ethyl acetate 141-78-6 (50 - 90)	OECD Test Guideline 416	Oral mouse 2 Generation	NOAEL = 26400 mg/kg bw/day
	OECD Test Guideline 414	Inhalation Rat	NOAEC = 73300 mg/m ³

(h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure;

Based on available data, the classification criteria are not met

Target Organs

None known.

(j) aspiration hazard;

Category 1

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains a substance which is: Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
-----------	-----------------	------------	------------------	----------

SAFETY DATA SHEET

ETHYL ACETATE/ PENTANE SOLUTION

Revision Date 24-Mar-2025

Ethyl acetate	Fathead minnow: LC50: 230 mg/l/ 96h Gold orfe: LC50: 270 mg/L/48h	EC50 = 717 mg/L/48h	EC50 = 3300 mg/L/48h	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h
Cyclopentane		EC50: = 10.5 mg/L, 48h (Daphnia magna)		

Persistence and degradability

Persistence Insoluble in water.

Component	Degradability
Ethyl acetate 141-78-6 (50 - 90)	79 % (20 d) (OECD 301 D)

Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Ethyl acetate	0.73	30 dimensionless
Cyclopentane	3	No data available

Mobility in soil Spillage unlikely to penetrate soil. . Is not likely mobile in the environment due its low water solubility.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not let this chemical enter the environment Do not empty into drains

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1993
Hazard Class 3
Packing Group II
Proper Shipping Name Flammable liquid, n.o.s.

SAFETY DATA SHEET

ETHYL ACETATE/ PENTANE SOLUTION

Revision Date 24-Mar-2025

Road and Rail Transport

UN-No UN1993
Hazard Class 3
Packing Group II
Proper Shipping Name Flammable liquid, n.o.s.

IATA

UN-No UN1993
Hazard Class 3
Packing Group II
Proper Shipping Name Flammable liquid, n.o.s.

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Ethyl acetate	205-500-4	X	X	X	X	X	X	X	KE-00047
Cyclopentane	206-016-6	X	X	X	X	X	X	X	KE-09297

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl acetate				Annex I - Y42

National Regulations

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

SAFETY DATA SHEET

ETHYL ACETATE/ PENTANE SOLUTION

Revision Date 24-Mar-2025

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date

24-Mar-2025

Revision Summary

Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet