

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane**
Cat No. : **41872**
Molecular Formula **C₆ H₁₈ LiNSi₂**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Aspiration Toxicity

Category 1 (H304)

Skin Corrosion/Irritation

Category 1 B (H314)

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Reproductive Toxicity

Category 2 (H361f)

Specific target organ toxicity - (single exposure)

Category 3 (H336)

Specific target organ toxicity - (repeated exposure)

Category 2 (H373)

Environmental hazards

Chronic aquatic toxicity

Category 2 (H411)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H336 - May cause drowsiness or dizziness

H361f - Suspected of damaging fertility

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

EUH014 - Reacts violently with water

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Hexane	110-54-3	EEC No. 203-777-6	73.00	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361f) STOT RE 2 (H373) Aquatic Chronic 2 (H411)
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	EEC No. 223-725-6	27.00	Flam. Sol. 1 (H228) Self Heat. 1 (H251) Skin Corr. 1B (H314) Eye Dam. 1 (H318) (EUH014)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Hexane	STOT RE 2 (H373) :: C>=5%	-	-

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Difficulty in breathing. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Dry sand. Carbon dioxide (CO₂). Powder. Do not use water or foam. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Water.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Nitrogen oxides (NO_x), Silicon dioxide, Lithium oxide.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Corrosives area. Keep away from water or moist air. Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Hexane	TWA: 20 ppm (8hr) TWA: 72 mg/m ³ (8hr)	TWA: 72 mg/m ³ TWA: 20 ppm STEL: 60 ppm STEL: 216 mg/m ³	TWA / VME: 20 ppm (8 heures). restrictive limit TWA / VME: 72 mg/m ³ (8 heures). restrictive limit TWA / VME: 1000 mg/m ³ (8 heures). STEL / VLCT: 1500 mg/m ³ .	TWA: 20 ppm 8 uren TWA: 72 mg/m ³ 8 uren	TWA / VLA-ED: 20 ppm (8 horas) TWA / VLA-ED: 72 mg/m ³ (8 horas)
Component	Italy	Germany	Portugal	The Netherlands	Finland
Hexane	TWA: 20 ppm 8 ore. Time Weighted Average TWA: 72 mg/m ³ 8 ore. Time Weighted Average	TWA: 180 mg/m ³ TWA: 50 ppm	TWA: 20 ppm 8 horas TWA: 72 mg/m ³ 8 horas Pele	STEL: 40 ppm 15 minuten STEL: 144 mg/m ³ 15 minuten TWA: 20 ppm 8 uren TWA: 72 mg/m ³ 8 uren	TWA: 20 ppm 8 tunteina TWA: 72 mg/m ³ 8 tunteina Iho
Silanamine, 1,1,1-trimethyl-N-(tri methylsilyl)-, lithium salt		TWA: 0.2 mg/m ³ (8 Stunden). MAK inorganic compounds, except Lithium and strong irritant Lithium compounds such as Lithium amide, Lithium			

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

		hydride, Lithium hydroxide, Lithium nitride, Lithium oxide, Lithium tetrahydroaluminate, Lithium tetrahydroborate			
--	--	---	--	--	--

Component	Austria	Denmark	Switzerland	Poland	Norway
Hexane	MAK-KZGW: 80 ppm 15 Minuten MAK-KZGW: 288 mg/m ³ 15 Minuten MAK-TMW: 20 ppm 8 Stunden MAK-TMW: 72 mg/m ³ 8 Stunden	TWA: 20 ppm 8 timer TWA: 72 mg/m ³ 8 timer STEL: 40 ppm 15 minutter STEL: 144 mg/m ³ 15 minutter	Haut/Peau STEL: 400 ppm 15 Minuten STEL: 1440 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 180 mg/m ³ 8 Stunden	TWA: 72 mg/m ³ 8 godzinach	TWA: 20 ppm 8 timer TWA: 72 mg/m ³ 8 timer TWA: 40 ppm 8 timer TWA: 275 mg/m ³ 8 timer STEL: 30 ppm 15 minutter. value calculated STEL: 108 mg/m ³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Hexane	TWA: 20 ppm TWA: 72.0 mg/m ³	kože TWA-GVI: 20 ppm 8 satima. TWA-GVI: 72 mg/m ³ 8 satima.	TWA: 20 ppm 8 hr. TWA: 72 mg/m ³ 8 hr. STEL: 60 ppm 15 min STEL: 216 mg/m ³ 15 min Skin	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 70 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 200 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Hexane	TWA: 20 ppm 8 tundides. TWA: 72 mg/m ³ 8 tundides.	TWA: 20 ppm 8 hr TWA: 72 mg/m ³ 8 hr	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 72 mg/m ³ 8 órában. AK TWA: 20 ppm 8 órában. AK lehetséges borón keresztüli felszívódás	TWA: 20 ppm 8 klukkustundum. TWA: 72 mg/m ³ 8 klukkustundum. Ceiling: 40 ppm Ceiling: 144 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Hexane	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 20 ppm IPRD TWA: 72 mg/m ³ IPRD	TWA: 20 ppm 8 Stunden TWA: 72 mg/m ³ 8 Stunden	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 20 ppm 8 ore TWA: 72 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Hexane	TWA: 300 mg/m ³ 0780 MAC: 900 mg/m ³	Ceiling: 140 mg/m ³ TWA: 20 mg/m ³ TWA: 72 mg/m ³	TWA: 20 ppm 8 urah TWA: 72 mg/m ³ 8 urah STEL: 576 mg/m ³ 15 minutah STEL: 160 ppm 15 minutah	Binding STEL: 50 ppm 15 minuter Binding STEL: 180 mg/m ³ 15 minuter TLV: 20 ppm 8 timmar. NGV TLV: 72 mg/m ³ 8 timmar. NGV	TWA: 20 ppm 8 saat TWA: 72 mg/m ³ 8 saat

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Hexane			2,5-Hexanedione: urine end of shift	2,5-Hexanedione: 0.2 mg/L urine end of workweek	2,5-Hexandione plus 4,5-Dihydroxy-2-hexanone (after hydrolysis): 5 mg/L urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Hexane					2,5-Hexandion: 5 mg/g Creatinine urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Hexane			2,5-Hexanedione: 5		

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

			mg/L urine end of exposure or work shift 4,5-Dihydroxy-2-hexanone: 5 mg/L urine end of exposure or work shift		
--	--	--	--	--	--

Monitoring methods

MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry

MDHS 99 Metals in air by ICP-AES

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Hexane 110-54-3 (73.00)				DNEL = 11mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Hexane 110-54-3 (73.00)				DNEL = 75mg/m ³

Predicted No Effect Concentration (PNEC)

No information available.

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)
Viton (R)				

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless - Light yellow	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	-31 °C / -23.8 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Immiscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Hexane	4.11	
Vapor Pressure	<=1100 hPa @ 50 °C	
Density / Specific Gravity	0.716 g/cm3	@ 20 °C
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C6 H18 LiNSi2
Molecular Weight	167.33

Section 10: Stability and reactivity

10.1. Reactivity

Yes

10.2. Chemical stability

Air sensitive. Moisture sensitive.

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing. Reacts violently with water.

10.4. Conditions to avoid

Exposure to moist air or water. Exposure to moisture.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Silicon dioxide.
Lithium oxide.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
 Oral No data available
 Dermal No data available
 Inhalation No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 48000 ppm (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;
 Respiratory No data available
 Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available
There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available
 Results / Target organs Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

Target Organs

Central nervous system (CNS), Peripheral Nervous System (PNS).

(j) aspiration hazard;

Category 1

Symptoms / effects, both acute and delayed

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Hexane	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	EC50: 3.87 mg/L/48h	

12.2. Persistence and degradability

Persistence Degradation in sewage treatment plant

Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary. Immiscible with water, May persist. Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
Hexane	4.11	No data available

12.4. Mobility in soil

Spillage unlikely to penetrate soil The product is insoluble and floats on water Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

IMDG/IMO

14.1. UN number

UN2924

14.2. UN proper shipping name

Flammable liquid, corrosive, n.o.s.

Technical Shipping Name

(Lithium bis(trimethylsilyl)amide, HEXANES)

14.3. Transport hazard class(es)

3

Subsidiary Hazard Class

8

14.4. Packing group

II

ADR

14.1. UN number

UN2924

14.2. UN proper shipping name

Flammable liquid, corrosive, n.o.s.

Technical Shipping Name

(Lithium bis(trimethylsilyl)amide, HEXANES)

14.3. Transport hazard class(es)

3

Subsidiary Hazard Class

8

14.4. Packing group

II

IATA

14.1. UN number

UN2924

14.2. UN proper shipping name

Flammable liquid, corrosive, n.o.s.

Technical Shipping Name

(Lithium bis(trimethylsilyl)amide, HEXANES)

14.3. Transport hazard class(es)

3

Subsidiary Hazard Class

8

14.4. Packing group

II

14.5. Environmental hazards

Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user

No special precautions required.

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Hexane	110-54-3	203-777-6	438-390-3	-	X	X	KE-18626	X	X
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	223-725-6	-	-	-	X	-	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Hexane	110-54-3	X	ACTIVE	X	-	X	X	X
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	X	ACTIVE	-	X	-	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Hexane	110-54-3	-	Use restricted. See entry 75. (see link for restriction details)	-
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Hexane	110-54-3	Not applicable	Not applicable
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Hexane	WGK3	
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	WGK2	

Component	France - INRS (Tables of occupational diseases)
Hexane	Tableaux des maladies professionnelles (TMP) - RG 59,RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Hexane 110-54-3 (73.00)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H336 - May cause drowsiness or dizziness

H361f - Suspected of damaging fertility

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

EUH014 - Reacts violently with water

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 0.9-1.1M in hexane

Revision Date 30-Nov-2024

PICCS - Philippines Inventory of Chemicals and Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit
ACGIH - American Conference of Governmental Industrial Hygienists
DNEL - Derived No Effect Level
RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%
NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
ATE - Acute Toxicity Estimate
VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Prepared By	Health, Safety and Environmental Department
Revision Date	30-Nov-2024
Revision Summary	Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet