

Creation Date 29-Jan-2021

Revision Date 26-Feb-2024

Revision Number 1

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: **Ethanol, 70% v/v**  
Cat No. : **TS/0484/25**

Unique Formula Identifier (UFI) **MWSW-J68A-3X0T-54MQ**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.  
Uses advised against No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**EU entity/business name**  
Thermo Fisher Scientific  
Janssen Pharmaceuticaaan 3a  
2440 Geel, Belgium

**UK entity/business name**  
Fisher Scientific UK  
Bishop Meadow Road, Loughborough,  
Leicestershire LE11 5RG, United Kingdom

**Swiss distributor** - Fisher Scientific AG  
Neuhofstrasse 11, CH 4153 Reinach  
Tel: +41 (0) 56 618 41 11  
e-mail - infoch@thermofisher.com

E-mail address **begel.sdsdesk@thermofisher.com**

### 1.4. Emergency telephone number

Tel: 01509 231166  
Chemtrec US: (800) 424-9300  
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:  
Tox Info Suisse Emergency Number: **145 (24hr)**  
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)  
Chemtrec (24h) Toll-Free: 0800 564 402  
Chemtrec Local: +41-43 508 20 11 (Zurich)

#### Poison Centre - Emergency information services

**Ireland** : National Poisons Information Centre (NPIC) -  
**01 809 2166** (8am-10pm, 7 days a week)  
**Malta** : +356 2395 2000

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

Cyprus : +357 2240 5611

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### CLP Classification - Regulation (EC) No 1272/2008

##### Physical hazards

Flammable liquids

Category 2 (H225)

##### Health hazards

Serious Eye Damage/Eye Irritation

Category 2 (H319)

##### Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

### 2.2. Label elements



Signal Word

Danger

#### **Hazard Statements**

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

#### **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear eye protection/ face protection

P264 - Wash face, hands and any exposed skin thoroughly after handling

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

### 2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

| Component     | CAS No    | EC No     | Weight % | CLP Classification - Regulation (EC) No 1272/2008 |
|---------------|-----------|-----------|----------|---------------------------------------------------|
| Ethyl alcohol | 64-17-5   | 200-578-6 | 60-70    | Flam. Liq. 2 (H225)<br>Eye Irrit. 2 (H319)        |
| Water         | 7732-18-5 | 231-791-2 | 30-40    | -                                                 |

| Component     | Specific concentration limits (SCL's) | M-Factor | Component notes |
|---------------|---------------------------------------|----------|-----------------|
| Ethyl alcohol | Eye Irrit. 2 :: C>=50%                | -        | -               |

| Components | Reach Registration Number |
|------------|---------------------------|
| Ethanol    | 01-2119457610-43          |

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

|                                           |                                                                                                                                                  |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General Advice</b>                     | If symptoms persist, call a physician.                                                                                                           |
| <b>Eye Contact</b>                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.                                  |
| <b>Skin Contact</b>                       | Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.                                |
| <b>Ingestion</b>                          | Clean mouth with water and drink afterwards plenty of water.                                                                                     |
| <b>Inhalation</b>                         | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.                                     |
| <b>Self-Protection of the First Aider</b> | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. |

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| <b>Notes to Physician</b> | Treat symptomatically. Symptoms may be delayed. |
|---------------------------|-------------------------------------------------|

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

## Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

#### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510  
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3  
<https://www.kvu.ch/de/themen/stoffe-und-produkte>  
<https://www.kvu.ch/fr/themes/substances-et-produits>  
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

### 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

## 8.1. Control parameters

### Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

| Component     | European Union | The United Kingdom                                                                                               | France                                                                                                                                                          | Belgium                                                       | Spain                                                                                              |
|---------------|----------------|------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| Ethyl alcohol |                | TWA: 1000 ppm TWA;<br>1920 mg/m <sup>3</sup> TWA<br>WEL - STEL: 3000 ppm<br>STEL: 5760 mg/m <sup>3</sup><br>STEL | TWA / VME: 1000 ppm<br>(8 heures).<br>TWA / VME: 1900<br>mg/m <sup>3</sup> (8 heures).<br>STEL / VLCT: 5000<br>ppm.<br>STEL / VLCT: 9500<br>mg/m <sup>3</sup> . | TWA: 1000 ppm 8 uren<br>TWA: 1907 mg/m <sup>3</sup> 8<br>uren | STEL / VLA-EC: 1000<br>ppm (15 minutos).<br>STEL / VLA-EC: 1910<br>mg/m <sup>3</sup> (15 minutos). |

| Component     | Italy | Germany                                           | Portugal                     | The Netherlands                                                                         | Finland                                                                                                                                                        |
|---------------|-------|---------------------------------------------------|------------------------------|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethyl alcohol |       | 200 ppm TWA MAK;<br>380 mg/m <sup>3</sup> TWA MAK | STEL: 1000 ppm 15<br>minutos | huid<br>STEL: 1900 mg/m <sup>3</sup> 15<br>minuten<br>TWA: 260 mg/m <sup>3</sup> 8 uren | TWA: 1000 ppm 8<br>tunteina<br>TWA: 1900 mg/m <sup>3</sup> 8<br>tunteina<br>STEL: 1300 ppm 15<br>minuutteina<br>STEL: 2500 mg/m <sup>3</sup> 15<br>minuutteina |

| Component     | Austria                                                                                                                                                              | Denmark                                                                                                                                         | Switzerland                                                                                                                                        | Poland                                     | Norway                                                                                                                                                                                |
|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethyl alcohol | MAK-KZGW: 2000 ppm<br>15 Minuten<br>MAK-KZGW: 3800<br>mg/m <sup>3</sup> 15 Minuten<br>MAK-TMW: 1000 ppm 8<br>Stunden<br>MAK-TMW: 1900 mg/m <sup>3</sup><br>8 Stunden | TWA: 1000 ppm 8 timer<br>TWA: 1900 mg/m <sup>3</sup> 8<br>timer<br>STEL: 2000 ppm 15<br>minutter<br>STEL: 3800 mg/m <sup>3</sup> 15<br>minutter | STEL: 1000 ppm 15<br>Minuten<br>STEL: 1920 mg/m <sup>3</sup> 15<br>Minuten<br>TWA: 500 ppm 8<br>Stunden<br>TWA: 960 mg/m <sup>3</sup> 8<br>Stunden | TWA: 1900 mg/m <sup>3</sup> 8<br>godzinach | TWA: 500 ppm 8 timer<br>TWA: 950 mg/m <sup>3</sup> 8 timer<br>STEL: 625 ppm 15<br>minutter. value<br>calculated<br>STEL: 1187.5 mg/m <sup>3</sup> 15<br>minutter. value<br>calculated |

| Component     | Bulgaria                    | Croatia                                                                        | Ireland               | Cyprus | Czech Republic                                                                |
|---------------|-----------------------------|--------------------------------------------------------------------------------|-----------------------|--------|-------------------------------------------------------------------------------|
| Ethyl alcohol | TWA: 1000 mg/m <sup>3</sup> | TWA-GVI: 1000 ppm 8<br>satima.<br>TWA-GVI: 1900 mg/m <sup>3</sup><br>8 satima. | STEL: 1000 ppm 15 min |        | TWA: 1000 mg/m <sup>3</sup> 8<br>hodinách.<br>Ceiling: 3000 mg/m <sup>3</sup> |

| Component     | Estonia                                                                                                                                                       | Gibraltar | Greece                                       | Hungary                                                                                         | Iceland                                                                                                                                      |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|----------------------------------------------|-------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Ethyl alcohol | TWA: 500 ppm 8<br>tundides.<br>TWA: 1000 mg/m <sup>3</sup> 8<br>tundides.<br>STEL: 1000 ppm 15<br>minutites.<br>STEL: 1900 mg/m <sup>3</sup> 15<br>minutites. |           | TWA: 1000 ppm<br>TWA: 1900 mg/m <sup>3</sup> | STEL: 3800 mg/m <sup>3</sup> 15<br>percekben. CK<br>TWA: 1900 mg/m <sup>3</sup> 8<br>óraban. AK | TWA: 1000 ppm 8<br>klukkustundum.<br>TWA: 1900 mg/m <sup>3</sup> 8<br>klukkustundum.<br>Ceiling: 2000 ppm<br>Ceiling: 3800 mg/m <sup>3</sup> |

| Component     | Latvia                      | Lithuania                                                                                                  | Luxembourg | Malta | Romania                                                                                                                              |
|---------------|-----------------------------|------------------------------------------------------------------------------------------------------------|------------|-------|--------------------------------------------------------------------------------------------------------------------------------------|
| Ethyl alcohol | TWA: 1000 mg/m <sup>3</sup> | TWA: 500 ppm IPRD<br>TWA: 1000 mg/m <sup>3</sup><br>IPRD<br>STEL: 1000 ppm<br>STEL: 1900 mg/m <sup>3</sup> |            |       | TWA: 1000 ppm 8 ore<br>TWA: 1900 mg/m <sup>3</sup> 8 ore<br>STEL: 5000 ppm 15<br>minute<br>STEL: 9500 mg/m <sup>3</sup> 15<br>minute |

| Component     | Russia                                                          | Slovak Republic                                                               | Slovenia                                                                                                                               | Sweden                                                                                                                            | Turkey |
|---------------|-----------------------------------------------------------------|-------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|--------|
| Ethyl alcohol | TWA: 1000 mg/m <sup>3</sup> 2391<br>MAC: 2000 mg/m <sup>3</sup> | Ceiling: 1920 mg/m <sup>3</sup><br>TWA: 500 ppm<br>TWA: 960 mg/m <sup>3</sup> | TWA: 960 mg/m <sup>3</sup> 8 urah<br>TWA: 500 ppm 8 urah<br>STEL: 1000 ppm 15<br>minutah<br>STEL: 1920 mg/m <sup>3</sup> 15<br>minutah | Indicative STEL: 1000<br>ppm 15 minuter<br>Indicative STEL: 1900<br>mg/m <sup>3</sup> 15 minuter<br>TLV: 500 ppm 8 timmar.<br>NGV |        |

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

|  |  |  |  |                                              |  |
|--|--|--|--|----------------------------------------------|--|
|  |  |  |  | TLV: 1000 mg/m <sup>3</sup> 8<br>timmar. NGV |  |
|--|--|--|--|----------------------------------------------|--|

## Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

## Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component                          | Acute effects local<br>(Oral) | Acute effects<br>systemic (Oral) | Chronic effects local<br>(Oral) | Chronic effects<br>systemic (Oral) |
|------------------------------------|-------------------------------|----------------------------------|---------------------------------|------------------------------------|
| Ethyl alcohol<br>64-17-5 ( 60-70 ) |                               | DNEL = 87 mg/kg bw/d             |                                 |                                    |

| Component                          | Acute effects local<br>(Dermal) | Acute effects<br>systemic (Dermal) | Chronic effects local<br>(Dermal) | Chronic effects<br>systemic (Dermal) |
|------------------------------------|---------------------------------|------------------------------------|-----------------------------------|--------------------------------------|
| Ethyl alcohol<br>64-17-5 ( 60-70 ) |                                 |                                    |                                   | DNEL = 343mg/kg<br>bw/day            |

| Component                          | Acute effects local<br>(Inhalation) | Acute effects<br>systemic (Inhalation) | Chronic effects local<br>(Inhalation) | Chronic effects<br>systemic (Inhalation) |
|------------------------------------|-------------------------------------|----------------------------------------|---------------------------------------|------------------------------------------|
| Ethyl alcohol<br>64-17-5 ( 60-70 ) | DNEL = 1900mg/m <sup>3</sup>        |                                        |                                       | DNEL = 950mg/m <sup>3</sup>              |

## Predicted No Effect Concentration (PNEC)

See values below.

## 8.2. Exposure controls

### Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

| Glove material | Breakthrough time                    | Glove thickness | EU standard | Glove comments        |
|----------------|--------------------------------------|-----------------|-------------|-----------------------|
| Viton (R)      | See manufacturers<br>recommendations | -               | EN 374      | (minimum requirement) |

#### Skin and body protection

Long sleeved clothing.

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

## Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

## Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

## Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141  
When RPE is used a face piece Fit Test should be conducted

## Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

|                                         |                             |                    |
|-----------------------------------------|-----------------------------|--------------------|
| Physical State                          | Liquid                      |                    |
| Appearance                              |                             |                    |
| Odor                                    | No information available    |                    |
| Odor Threshold                          | No data available           |                    |
| Melting Point/Range                     | No data available           |                    |
| Softening Point                         | No data available           |                    |
| Boiling Point/Range                     | 85 - 90 °C / 185 - 194 °F   | Estimated          |
| Flammability (liquid)                   | No data available           |                    |
| Flammability (solid,gas)                | Not applicable              | Liquid             |
| Explosion Limits                        | No data available           |                    |
| Flash Point                             | 21 - 22 °C / 69.8 - 71.6 °F | Method - Estimated |
| Autoignition Temperature                | No data available           |                    |
| Decomposition Temperature               | No data available           |                    |
| pH                                      | No information available    |                    |
| Viscosity                               | No data available           |                    |
| Water Solubility                        | Miscible                    |                    |
| Solubility in other solvents            | No information available    |                    |
| Partition Coefficient (n-octanol/water) |                             |                    |
| Component                               | log Pow                     |                    |
| Ethyl alcohol                           | -0.32                       |                    |
| Vapor Pressure                          | No data available           |                    |
| Density / Specific Gravity              | 0.85 - 0.88                 |                    |
| Bulk Density                            | Not applicable              | Liquid             |
| Vapor Density                           | No data available           | (Air = 1.0)        |
| Particle characteristics                | No data available           |                    |

### 9.2. Other information

|                      |                                             |
|----------------------|---------------------------------------------|
| VOC Content(%)       | 65                                          |
| Explosive Properties | Vapors may form explosive mixtures with air |

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

#### Hazardous Polymerization Hazardous Reactions

No information available.  
None under normal processing.

### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Acid anhydrides. Acid chlorides.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

#### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

#### Toxicology data for the components

| Component     | LD50 Oral                                                    | LD50 Dermal | LC50 Inhalation                                                   |
|---------------|--------------------------------------------------------------|-------------|-------------------------------------------------------------------|
| Ethyl alcohol | LD50 = 10470 mg/kg<br>OECD 401 (Rat)<br>3450 mg/kg ( Mouse ) | -           | LC50 = 117-125 mg/l (4h)<br>OECD 403 (rat)<br>20000 ppm/10H (rat) |
| Water         | -                                                            | -           | -                                                                 |

#### (b) skin corrosion/irritation;

No data available

#### (c) serious eye damage/irritation;

Category 2

#### (d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

| Component                          | Test method                                       | Test species | Study result    |
|------------------------------------|---------------------------------------------------|--------------|-----------------|
| Ethyl alcohol<br>64-17-5 ( 60-70 ) | Mouse Ear Swelling Test (MEST)                    | mouse        | non-sensitising |
|                                    | OECD Test Guideline 429<br>Local Lymph Node Assay | mouse        | non-sensitising |

#### (e) germ cell mutagenicity;

No data available

| Component | Test method | Test species | Study result |
|-----------|-------------|--------------|--------------|
|-----------|-------------|--------------|--------------|



# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

|                                    |                                               |                       |          |
|------------------------------------|-----------------------------------------------|-----------------------|----------|
| Ethyl alcohol<br>64-17-5 ( 60-70 ) | AMES test<br>OECD Test Guideline 471          | in vitro<br>Bacteria  | negative |
|                                    | Gene cell mutation<br>OECD Test Guideline 476 | in vitro<br>Mammalian | negative |

(f) carcinogenicity;

No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

No data available

| Component                          | Test method             | Test species / Duration      | Study result          |
|------------------------------------|-------------------------|------------------------------|-----------------------|
| Ethyl alcohol<br>64-17-5 ( 60-70 ) | OECD Test Guideline 416 | Oral / mouse<br>2 Generation | NOAEL = 13.8 g/kg/day |
|                                    | OECD Test Guideline 414 | Inhalation / Rat             | NOAEC =<br>16000 ppm  |

(h) STOT-single exposure;

No data available

(i) STOT-repeated exposure;

No data available

Target Organs

None known.

(j) aspiration hazard;

No data available

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecotoxicity effects

Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants. Do not empty into drains.

| Component     | Freshwater Fish                                            | Water Flea                                    | Freshwater Algae                           |
|---------------|------------------------------------------------------------|-----------------------------------------------|--------------------------------------------|
| Ethyl alcohol | Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h | EC50 = 9268 mg/L/48h<br>EC50 = 10800 mg/L/24h | EC50 (72h) = 275 mg/l (Chlorella vulgaris) |

| Component     | Microtox                                                                                                    | M-Factor |
|---------------|-------------------------------------------------------------------------------------------------------------|----------|
| Ethyl alcohol | Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min<br>Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min |          |

### 12.2. Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

| Component                          | Degradability   |
|------------------------------------|-----------------|
| Ethyl alcohol<br>64-17-5 ( 60-70 ) | OECD 301E = 94% |

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

## 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

| Component     | log Pow | Bioconcentration factor (BCF) |
|---------------|---------|-------------------------------|
| Ethyl alcohol | -0.32   | No data available             |

## 12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

## 12.5. Results of PBT and vPvB assessment

No data available for assessment.

## 12.6. Endocrine disrupting properties

### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

## 12.7. Other adverse effects

### Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance.

This product does not contain any known or suspected substance.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

#### European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

#### Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

#### Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600  
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

#### 14.1. UN number

UN1170

#### 14.2. UN proper shipping name

ETHANOL

#### 14.3. Transport hazard class(es)

3

#### 14.4. Packing group

II

### ADR

#### 14.1. UN number

UN1170

#### 14.2. UN proper shipping name

ETHANOL

#### 14.3. Transport hazard class(es)

3

#### 14.4. Packing group

II

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

## IATA

**14.1. UN number** UN1170  
**14.2. UN proper shipping name** ETHANOL  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** II

**14.5. Environmental hazards** No hazards identified

**14.6. Special precautions for user** No special precautions required.

**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component     | CAS No    | EINECS    | ELINCS | NLP | IECSC | TCSI | KECL     | ENCS | ISHL |
|---------------|-----------|-----------|--------|-----|-------|------|----------|------|------|
| Ethyl alcohol | 64-17-5   | 200-578-6 | -      | -   | X     | X    | KE-13217 | X    | X    |
| Water         | 7732-18-5 | 231-791-2 | -      | -   | X     | X    | KE-35400 | X    | -    |

| Component     | CAS No    | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|---------------|-----------|------|-----------------------------------------------|-----|------|------|-------|-------|
| Ethyl alcohol | 64-17-5   | X    | ACTIVE                                        | X   | -    | X    | X     | X     |
| Water         | 7732-18-5 | X    | ACTIVE                                        | X   | -    | X    | X     | X     |

**Legend:** X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

#### Authorisation/Restrictions according to EU REACH

Not applicable

| Component     | CAS No    | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|---------------|-----------|---------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Ethyl alcohol | 64-17-5   | -                                                                   | -                                                                             | -                                                                                                     |
| Water         | 7732-18-5 | -                                                                   | -                                                                             | -                                                                                                     |

#### Seveso III Directive (2012/18/EC)

| Component     | CAS No    | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|---------------|-----------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Ethyl alcohol | 64-17-5   | Not applicable                                                                            | Not applicable                                                                           |
| Water         | 7732-18-5 | Not applicable                                                                            | Not applicable                                                                           |

#### Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

#### Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification** Water endangering class = 1 (self classification)

| Component     | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|---------------|---------------------------------------|-------------------------|
| Ethyl alcohol | WGK1                                  |                         |

| Component     | France - INRS (Tables of occupational diseases)      |
|---------------|------------------------------------------------------|
| Ethyl alcohol | Tableaux des maladies professionnelles (TMP) - RG 84 |

## Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

| Component                          | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Ethyl alcohol<br>64-17-5 ( 60-70 ) |                                                                                                                | Group I                                                                         |                                                                                             |

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (volatile organic compound)

# SAFETY DATA SHEET

Ethanol, 70% v/v

Revision Date 26-Feb-2024

## Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

## Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

|                       |                       |
|-----------------------|-----------------------|
| Physical hazards      | On basis of test data |
| Health Hazards        | Calculation method    |
| Environmental hazards | Calculation method    |

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

|                  |                  |
|------------------|------------------|
| Creation Date    | 29-Jan-2021      |
| Revision Date    | 26-Feb-2024      |
| Revision Summary | Initial Release. |

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.  
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No  
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,  
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and  
Preparations).**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**