

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name Ethyl acetate

CAS No 141-78-6

Synonyms Acetic acid ethyl ester

Product Code E145-1; E145-4; E145-4LC; E145-20; E145-200; E1452PR; E145-500; E145FB-19; E145FB-50; E145FB-115; E145FB-200; E145POP-50; E145POPB-50; E145RB-19; E145RB-50; E145RB-115; E145RB-200; E145RS-28; E145RS-50; E145RS-115; E145RS-200; E145S-4; E145SK-4; E145SK-4LC; E145SS-28; E145SS-50; E145SS-115; E145SS-200; E145SS-1350; E145RS1250; NC1489568; E145RS200ASME; NC1852320; NC2050037

Address ThermoFisher Scientific Australia Pty Ltd
5 Caribbean Drive, Scoresby
VICTORIA 3179, Australia

Emergency Tel. **CHEMTREC®**
03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292
Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids

Category 2

Health hazards

Serious Eye Damage/Eye Irritation
Specific target organ toxicity - (single exposure)

Category 2
Category 3

Environmental hazards

No hazards identified

Label Elements



Flame



Exclamation Mark

Signal Word**Danger****Hazard Statements**

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

AUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor if you feel unwell

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

Other information**Section 3 - Composition and Information on Ingredients**

Component	CAS No	Weight %
Ethyl acetate	141-78-6	<=100

Section 4 - First Aid Measures**Inhalation**

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

General Advice	If symptoms persist, call a physician.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Difficulty in breathing. May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Ensure adequate ventilation. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Conditions for Safe Storage, Including any Incompatibilities

Flammables area. Keep away from heat, sparks and flame. Keep container tightly closed in a dry and well-ventilated place.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]

updated in August, 2005. Safe Work Australia **ACGIH** - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **DE** - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Ethyl acetate	STEL: 400 ppm STEL: 1440 mg/m ³ TWA: 200 ppm TWA: 720 mg/m ³	TWA: 200 ppm TWA: 720 mg/m ³	TWA: 400 ppm	STEL: 1468 mg/m ³ 15 min STEL: 400 ppm 15 min TWA: 734 mg/m ³ 8 hr TWA: 200 ppm 8 hr	TWA: 200 ppm (8 Stunden). AGW - exposure factor 2 TWA: 730 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 200 ppm (8 Stunden). MAK TWA: 750 mg/m ³ (8 Stunden). MAK Höhepunkt: 400 ppm Höhepunkt: 1500 mg/m ³

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Exposure Controls**Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Butyl rubber	> 120 minutes	0.5 - 0.7 mm	AS/NZS 2161	Permeation rate 8 µg/cm ² /min As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Nitrile rubber	< 200 minutes			
PVA	> 360 minutes	0.3 mm		
Nitrile rubber	< 30 minutes	0.38 mm		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Respiratory Protection Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices (or AUS/NZ equivalent)

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Colorless	
Physical State	Liquid	
Odor	sweet	
Odor Threshold	50 ppm	
pH	No information available	
Melting Point/Range	-83.5 °C / -118.3 °F	
Softening Point	No data available	
Boiling Point/Range	75 - 78 °C / 167 - 172.4 °F	
Flash Point	-4 °C / 24.8 °F	Method - CC (closed cup)
Evaporation Rate	6.2	(Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 2 Vol% Upper 12 Vol%	
Vapor Pressure	103 mbar @ 20°C	
Vapor Density	3.04	(Air = 1.0)
Specific Gravity / Density	0.902	@ 20 °C
Bulk Density	Not applicable	Liquid
Water Solubility	80 g/l	20 °C
Solubility in other solvents	Miscible Alcohol acetone	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethyl acetate	0.73	
Autoignition Temperature	427 °C / 800.6 °F	
Decomposition Temperature	No data available	
Viscosity	0.45 cP @ 20 °C	Dynamic
Explosive Properties	Not explosive	Vapors may form explosive mixtures with air
Oxidizing Properties	Not oxidising	(based on the chemical structure of the substance and oxidation states of the constituent elements)
Other information		
Molecular Formula	C4 H8 O2	
Molecular Weight	88.11	
Surface tension	24 mN/m @ 20°C	

Section 10 - Stability and Reactivity

Reactivity None known, based on information available

Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products, Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents, Strong acids, Amines, Peroxides.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂).
Hazardous Polymerization	Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;	
Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl acetate	10,200 mg/kg (Rat)	> 20 mL/kg (Rabbit) > 18000 mg/kg (Rabbit)	58 mg/l (rat; 8 h)

(b) skin corrosion/irritation;	Based on available data, the classification criteria are not met
Test method	OECD 404
Test species	rabbit
Observational endpoint	No skin irritation

(c) serious eye damage/irritation;	Category 2
Test method	OECD 405
Test species	rabbit eye
Observation end point	Irritating to eyes

(d) respiratory or skin sensitization;	
Respiratory	Based on available data, the classification criteria are not met
Skin	Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Ethyl acetate 141-78-6 (<=100)	OECD Test Guideline 406	guinea pig	- non-sensitising

(e) germ cell mutagenicity;	Based on available data, the classification criteria are not met
------------------------------------	--

Component	Test method	Test species	Study result
Ethyl acetate 141-78-6 (<=100)	OECD Test Guideline 471 AMES test	in vitro Bacteria	negative
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative
	OECD Test Guideline 476 Gene cell mutation	in vitro Mammalian	negative
	OECD Test Guideline 474 Mouse micronucleus assay	in vivo Mammalian	negative

(f) carcinogenicity;	Based on available data, the classification criteria are not met
	There are no known carcinogenic chemicals in this product

Component	Australia	New Zealand	New South Wales	Western Australia	IARC	EU	UK	Germany
Ethyl acetate			listed					

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Ethyl acetate 141-78-6 (≤100)	OECD Test Guideline 416	Oral mouse 2 Generation	NOAEL = 26400 mg/kg bw/day
	OECD Test Guideline 414	Inhalation Rat	NOAEC = 73300 mg/m ³

(h) STOT-single exposure; Category 3

Results / Target organs Central nervous system (CNS)

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Test method	EPA OTS 795.2600	EPA OTS 798.2450
Test species / Duration	Rat / 90 days	Rat / 90 days
Study result	NOAEL = 900 mg/kg bw/day LOAEL = 3600 mg/kg	NOEC = 1.28 mg/l
Route of exposure	Oral	Inhalation
Target Organs	None known.	

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed May cause central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effects Do not empty into drains.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl acetate	Fathead minnow: LC50: 230 mg/l/ 96h Gold orfe: LC50: 270 mg/L/48h	EC50 = 717 mg/L/48h	EC50 = 3300 mg/L/48h	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h

Persistence and Degradability Readily biodegradable

Persistence Persistence is unlikely, based on information available.

Component	Degradability
Ethyl acetate 141-78-6 (≤100)	79 % (20 d) (OECD 301 D)

Bioaccumulative Potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl acetate	0.73	30 dimensionless

Mobility The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Persistent Organic Pollutant This product does not contain any known or suspected substance

Ozone Depletion Potential This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure

conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

Section 14 - Transport Information

IMDG/IMO

UN-No UN1173
Proper Shipping Name ETHYL ACETATE
Hazard Class 3
Packing Group II

ADG

UN-No UN1173
Proper Shipping Name ETHYL ACETATE
Hazard Class 3
Packing Group II

Component	Hazchem Code
Ethyl acetate 141-78-6 (<=100)	3YE

IATA

UN-No UN1173
Proper Shipping Name ETHYL ACETATE
Hazard Class 3
Packing Group II

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture**National Regulations** Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

No poison schedule number allocated.

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Ethyl acetate - 141-78-6	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

National pollutant inventory Subject to reporting requirements

Component	National pollutant inventory
Ethyl acetate - 141-78-6	10 tonne/yr. Threshold category 1

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Ethyl acetate	X	X	205-500-4	-	X	X	-	X	X	X	X	KE-00047

Legend: X - Listed. '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their disposal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories of Wastes to Be Controlled
Ethyl acetate - 141-78-6	Annex I - Y42	Y42 except Halogenated solvents

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl acetate	141-78-6	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl acetate	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances	NZIoC - New Zealand Inventory of Chemicals
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List	ENCS - Japanese Existing and New Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances	KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances	CAS - Chemical Abstracts Service
TWA - Time Weighted Average	ACGIH - American Conference of Governmental Industrial Hygienists
IARC - International Agency for Research on Cancer	Predicted No Effect Concentration (PNEC)
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association	IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
MARPOL - International Convention for the Prevention of Pollution from Ships	ADG Australian Code for the Transport of Dangerous Goods by Road and Rail
NZS 5433:2012 - Transport of Dangerous Goods on Land	OECD - Organisation for Economic Co-operation and Development
LD50 - Lethal Dose 50%	LC50 - Lethal Concentration 50%
EC50 - Effective Concentration 50%	ATE - Acute Toxicity Estimate
WEL - Workplace Exposure Limit	RPE - Respiratory Protective Equipment
DNEL - Derived No Effect Level	NOEC - No Observed Effect Concentration
POW - Partition coefficient Octanol:Water	BCF - Bioconcentration factor
vPvB - very Persistent, very Bioaccumulative	PBT - Persistent, Bioaccumulative, Toxic
VOC - (Volatile Organic Compound)	

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Revision Date 21-Nov-2022
Revision Summary Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet